

libyui

3.0.10

Generated by Doxygen 1.7.6.1

Thu Aug 8 2013 10:26:36

Contents

| | | |
|----------|--|-----------|
| 1 | Class Index | 1 |
| 1.1 | Class Hierarchy | 1 |
| 2 | Class Index | 7 |
| 2.1 | Class List | 7 |
| 3 | Class Documentation | 13 |
| 3.1 | FSize Class Reference | 13 |
| 3.1.1 | Detailed Description | 14 |
| 3.1.2 | Member Enumeration Documentation | 14 |
| 3.1.2.1 | Unit | 14 |
| 3.1.3 | Constructor & Destructor Documentation | 14 |
| 3.1.3.1 | FSize | 14 |
| 3.1.3.2 | FSize | 15 |
| 3.1.3.3 | FSize | 15 |
| 3.1.4 | Member Function Documentation | 15 |
| 3.1.4.1 | asString | 15 |
| 3.1.4.2 | bestUnit | 15 |
| 3.1.4.3 | factor | 16 |
| 3.1.4.4 | fillBlock | 16 |
| 3.1.4.5 | form | 16 |
| 3.1.4.6 | form | 16 |
| 3.1.4.7 | fullBlock | 17 |

| | | |
|----------|--|----|
| 3.1.4.8 | operator long long | 17 |
| 3.1.4.9 | operator() | 17 |
| 3.1.4.10 | unit | 18 |
| 3.1.5 | Member Data Documentation | 18 |
| 3.1.5.1 | bestPrec | 18 |
| 3.2 | ImplPtr< _Impl > Class Template Reference | 18 |
| 3.2.1 | Detailed Description | 20 |
| 3.3 | noncopyable Class Reference | 21 |
| 3.4 | OptimizeChanges Class Reference | 22 |
| 3.4.1 | Detailed Description | 22 |
| 3.5 | YWidget::OptimizeChanges Class Reference | 22 |
| 3.5.1 | Detailed Description | 22 |
| 3.6 | SortedTreeltem< PAYLOAD > Class Template Reference | 23 |
| 3.6.1 | Detailed Description | 24 |
| 3.6.2 | Constructor & Destructor Documentation | 24 |
| 3.6.2.1 | SortedTreeltem | 24 |
| 3.6.2.2 | ~SortedTreeltem | 24 |
| 3.6.3 | Member Function Documentation | 25 |
| 3.6.3.1 | firstChild | 25 |
| 3.6.3.2 | insertChildSorted | 25 |
| 3.6.3.3 | next | 26 |
| 3.6.3.4 | parent | 26 |
| 3.7 | Treeltem< PAYLOAD > Class Template Reference | 26 |
| 3.7.1 | Detailed Description | 27 |
| 3.7.2 | Constructor & Destructor Documentation | 27 |
| 3.7.2.1 | Treeltem | 27 |
| 3.7.2.2 | Treeltem | 28 |
| 3.7.2.3 | ~Treeltem | 28 |
| 3.7.3 | Member Function Documentation | 28 |
| 3.7.3.1 | addChild | 28 |
| 3.7.3.2 | firstChild | 29 |

| | | |
|----------|--|----|
| 3.7.3.3 | next | 29 |
| 3.7.3.4 | parent | 29 |
| 3.7.3.5 | setFirstChild | 30 |
| 3.7.3.6 | setNext | 30 |
| 3.7.3.7 | setParent | 30 |
| 3.7.3.8 | setValue | 30 |
| 3.7.3.9 | value | 30 |
| 3.8 | YAlignment Class Reference | 31 |
| 3.8.1 | Detailed Description | 32 |
| 3.8.2 | Constructor & Destructor Documentation | 33 |
| 3.8.2.1 | YAlignment | 33 |
| 3.8.2.2 | ~YAlignment | 33 |
| 3.8.3 | Member Function Documentation | 33 |
| 3.8.3.1 | addChild | 33 |
| 3.8.3.2 | alignment | 34 |
| 3.8.3.3 | backgroundPixmap | 34 |
| 3.8.3.4 | bottomMargin | 34 |
| 3.8.3.5 | leftMargin | 34 |
| 3.8.3.6 | minHeight | 35 |
| 3.8.3.7 | minWidth | 35 |
| 3.8.3.8 | moveChild | 35 |
| 3.8.3.9 | preferredHeight | 35 |
| 3.8.3.10 | preferredWidth | 36 |
| 3.8.3.11 | rightMargin | 36 |
| 3.8.3.12 | setBackgroundPixmap | 36 |
| 3.8.3.13 | setBottomMargin | 37 |
| 3.8.3.14 | setLeftMargin | 37 |
| 3.8.3.15 | setMinHeight | 37 |
| 3.8.3.16 | setMinWidth | 37 |
| 3.8.3.17 | setRightMargin | 37 |
| 3.8.3.18 | setSize | 38 |

| | | |
|-----------|--|----|
| 3.8.3.19 | setTopMargin | 38 |
| 3.8.3.20 | stretchable | 38 |
| 3.8.3.21 | topMargin | 39 |
| 3.8.3.22 | totalMargins | 39 |
| 3.8.3.23 | widgetClass | 40 |
| 3.9 | YAlignmentPrivate Struct Reference | 41 |
| 3.9.1 | Detailed Description | 41 |
| 3.9.2 | Constructor & Destructor Documentation | 42 |
| 3.9.2.1 | YAlignmentPrivate | 42 |
| 3.10 | YApplicationPrivate Struct Reference | 42 |
| 3.10.1 | Detailed Description | 43 |
| 3.11 | YBarGraph Class Reference | 43 |
| 3.11.1 | Detailed Description | 44 |
| 3.11.2 | Constructor & Destructor Documentation | 44 |
| 3.11.2.1 | YBarGraph | 44 |
| 3.11.2.2 | ~YBarGraph | 45 |
| 3.11.3 | Member Function Documentation | 45 |
| 3.11.3.1 | addSegment | 45 |
| 3.11.3.2 | deleteAllSegments | 45 |
| 3.11.3.3 | doUpdate | 45 |
| 3.11.3.4 | getProperty | 46 |
| 3.11.3.5 | propertySet | 46 |
| 3.11.3.6 | segment | 47 |
| 3.11.3.7 | segments | 47 |
| 3.11.3.8 | setLabel | 47 |
| 3.11.3.9 | setProperty | 47 |
| 3.11.3.10 | setSegmentColor | 48 |
| 3.11.3.11 | setTextColor | 48 |
| 3.11.3.12 | setValue | 49 |
| 3.11.3.13 | widgetClass | 49 |
| 3.12 | YBarGraphMultiUpdate Class Reference | 49 |

| | |
|---|----|
| 3.12.1 Detailed Description | 50 |
| 3.12.2 Constructor & Destructor Documentation | 50 |
| 3.12.2.1 YBarGraphMultiUpdate | 50 |
| 3.12.2.2 ~YBarGraphMultiUpdate | 50 |
| 3.13 YBarGraphPrivate Struct Reference | 51 |
| 3.13.1 Detailed Description | 51 |
| 3.14 YBarGraphSegment Class Reference | 51 |
| 3.14.1 Detailed Description | 51 |
| 3.14.2 Constructor & Destructor Documentation | 52 |
| 3.14.2.1 YBarGraphSegment | 52 |
| 3.14.3 Member Function Documentation | 52 |
| 3.14.3.1 hasSegmentColor | 52 |
| 3.14.3.2 hasTextColor | 52 |
| 3.14.3.3 label | 53 |
| 3.14.3.4 segmentColor | 53 |
| 3.14.3.5 setLabel | 53 |
| 3.14.3.6 setSegmentColor | 53 |
| 3.14.3.7 setTextColor | 53 |
| 3.14.3.8 setValue | 54 |
| 3.14.3.9 textColor | 54 |
| 3.14.3.10 value | 54 |
| 3.15 YBothDim< T > Class Template Reference | 54 |
| 3.15.1 Detailed Description | 55 |
| 3.15.2 Constructor & Destructor Documentation | 56 |
| 3.15.2.1 YBothDim | 56 |
| 3.15.2.2 YBothDim | 56 |
| 3.15.3 Member Function Documentation | 56 |
| 3.15.3.1 operator[] | 56 |
| 3.15.3.2 operator[] | 56 |
| 3.16 YBuiltinCaller Class Reference | 56 |
| 3.16.1 Detailed Description | 57 |

| | | |
|-----------|--|----|
| 3.16.2 | Member Function Documentation | 57 |
| 3.16.2.1 | call | 57 |
| 3.17 | YBusyIndicator Class Reference | 58 |
| 3.17.1 | Detailed Description | 59 |
| 3.17.2 | Constructor & Destructor Documentation | 59 |
| 3.17.2.1 | YBusyIndicator | 59 |
| 3.17.2.2 | ~YBusyIndicator | 59 |
| 3.17.3 | Member Function Documentation | 60 |
| 3.17.3.1 | alive | 60 |
| 3.17.3.2 | getProperty | 60 |
| 3.17.3.3 | label | 60 |
| 3.17.3.4 | propertySet | 60 |
| 3.17.3.5 | setAlive | 61 |
| 3.17.3.6 | setLabel | 61 |
| 3.17.3.7 | setProperty | 62 |
| 3.17.3.8 | setTimeout | 63 |
| 3.17.3.9 | timeout | 63 |
| 3.17.3.10 | widgetClass | 63 |
| 3.18 | YBusyIndicatorPrivate Struct Reference | 63 |
| 3.18.1 | Detailed Description | 64 |
| 3.19 | YButtonBox Class Reference | 64 |
| 3.19.1 | Detailed Description | 66 |
| 3.19.2 | Constructor & Destructor Documentation | 66 |
| 3.19.2.1 | YButtonBox | 67 |
| 3.19.2.2 | ~YButtonBox | 67 |
| 3.19.3 | Member Function Documentation | 67 |
| 3.19.3.1 | buttonsByButtonOrder | 67 |
| 3.19.3.2 | defaultMargins | 68 |
| 3.19.3.3 | doLayout | 68 |
| 3.19.3.4 | findButton | 69 |
| 3.19.3.5 | gnomeLayoutPolicy | 69 |

| | | |
|-----------|---|----|
| 3.19.3.6 | kdeLayoutPolicy | 70 |
| 3.19.3.7 | layoutPolicy | 70 |
| 3.19.3.8 | margins | 70 |
| 3.19.3.9 | maxChildSize | 70 |
| 3.19.3.10 | moveChild | 70 |
| 3.19.3.11 | preferredHeight | 71 |
| 3.19.3.12 | preferredWidth | 71 |
| 3.19.3.13 | preferredWidth | 71 |
| 3.19.3.14 | sanityCheck | 72 |
| 3.19.3.15 | sanityCheckRelaxed | 73 |
| 3.19.3.16 | setDefaultMargins | 73 |
| 3.19.3.17 | setLayoutPolicy | 74 |
| 3.19.3.18 | setMargins | 74 |
| 3.19.3.19 | setSanityCheckRelaxed | 75 |
| 3.19.3.20 | setSize | 75 |
| 3.19.3.21 | stretchable | 76 |
| 3.19.3.22 | totalChildrenWidth | 76 |
| 3.19.3.23 | widgetClass | 77 |
| 3.20 | YButtonBoxLayoutPolicy Struct Reference | 77 |
| 3.20.1 | Detailed Description | 77 |
| 3.21 | YButtonBoxMargins Struct Reference | 77 |
| 3.21.1 | Detailed Description | 78 |
| 3.22 | YButtonBoxPrivate Struct Reference | 78 |
| 3.22.1 | Detailed Description | 79 |
| 3.22.2 | Constructor & Destructor Documentation | 79 |
| 3.22.2.1 | YButtonBoxPrivate | 79 |
| 3.23 | YCancelEvent Class Reference | 79 |
| 3.23.1 | Detailed Description | 80 |
| 3.23.2 | Constructor & Destructor Documentation | 80 |
| 3.23.2.1 | ~YCancelEvent | 80 |
| 3.24 | YCheckBox Class Reference | 81 |

| | |
|---|----|
| 3.24.1 Detailed Description | 82 |
| 3.24.2 Constructor & Destructor Documentation | 82 |
| 3.24.2.1 YCheckBox | 82 |
| 3.24.2.2 ~YCheckBox | 82 |
| 3.24.3 Member Function Documentation | 82 |
| 3.24.3.1 dontCare | 82 |
| 3.24.3.2 getProperty | 83 |
| 3.24.3.3 isChecked | 83 |
| 3.24.3.4 label | 84 |
| 3.24.3.5 propertySet | 84 |
| 3.24.3.6 setChecked | 85 |
| 3.24.3.7 setDontCare | 85 |
| 3.24.3.8 setLabel | 85 |
| 3.24.3.9 setProperty | 86 |
| 3.24.3.10 setShortcutString | 86 |
| 3.24.3.11 setUseBoldFont | 87 |
| 3.24.3.12 setValue | 87 |
| 3.24.3.13 shortcutString | 87 |
| 3.24.3.14 useBoldFont | 88 |
| 3.24.3.15 userInputProperty | 88 |
| 3.24.3.16 value | 88 |
| 3.24.3.17 widgetClass | 89 |
| 3.25 YCheckBoxFrame Class Reference | 89 |
| 3.25.1 Detailed Description | 91 |
| 3.25.2 Constructor & Destructor Documentation | 91 |
| 3.25.2.1 YCheckBoxFrame | 91 |
| 3.25.2.2 ~YCheckBoxFrame | 91 |
| 3.25.3 Member Function Documentation | 91 |
| 3.25.3.1 autoEnable | 91 |
| 3.25.3.2 getProperty | 91 |
| 3.25.3.3 handleChildrenEnablement | 92 |

| | | |
|-----------|--|-----|
| 3.25.3.4 | invertAutoEnable | 92 |
| 3.25.3.5 | label | 93 |
| 3.25.3.6 | propertySet | 93 |
| 3.25.3.7 | setAutoEnable | 93 |
| 3.25.3.8 | setInvertAutoEnable | 94 |
| 3.25.3.9 | setLabel | 94 |
| 3.25.3.10 | setProperty | 94 |
| 3.25.3.11 | setShortcutString | 95 |
| 3.25.3.12 | setValue | 96 |
| 3.25.3.13 | shortcutString | 96 |
| 3.25.3.14 | userInputProperty | 96 |
| 3.25.3.15 | value | 97 |
| 3.25.3.16 | widgetClass | 97 |
| 3.26 | YCheckBoxFramePrivate Struct Reference | 97 |
| 3.26.1 | Detailed Description | 97 |
| 3.27 | YCheckBoxPrivate Struct Reference | 98 |
| 3.27.1 | Detailed Description | 98 |
| 3.28 | YChildrenManager< T > Class Template Reference | 98 |
| 3.28.1 | Detailed Description | 99 |
| 3.28.2 | Constructor & Destructor Documentation | 99 |
| 3.28.2.1 | YChildrenManager | 99 |
| 3.28.2.2 | ~YChildrenManager | 100 |
| 3.28.3 | Member Function Documentation | 100 |
| 3.28.3.1 | add | 100 |
| 3.28.3.2 | begin | 100 |
| 3.28.3.3 | clear | 100 |
| 3.28.3.4 | container | 100 |
| 3.28.3.5 | contains | 101 |
| 3.28.3.6 | count | 101 |
| 3.28.3.7 | empty | 101 |
| 3.28.3.8 | end | 101 |

| | | |
|-----------|---|-----|
| 3.28.3.9 | firstChild | 101 |
| 3.28.3.10 | hasChildren | 101 |
| 3.28.3.11 | lastChild | 102 |
| 3.28.3.12 | rbegin | 102 |
| 3.28.3.13 | remove | 102 |
| 3.28.3.14 | rend | 102 |
| 3.29 | YChildrenRejector< T > Class Template Reference | 103 |
| 3.29.1 | Detailed Description | 104 |
| 3.29.2 | Constructor & Destructor Documentation | 104 |
| 3.29.2.1 | YChildrenRejector | 104 |
| 3.29.3 | Member Function Documentation | 104 |
| 3.29.3.1 | add | 104 |
| 3.30 | YCodeLocation Class Reference | 105 |
| 3.30.1 | Detailed Description | 105 |
| 3.30.2 | Constructor & Destructor Documentation | 105 |
| 3.30.2.1 | YCodeLocation | 105 |
| 3.30.2.2 | YCodeLocation | 105 |
| 3.30.3 | Member Function Documentation | 106 |
| 3.30.3.1 | asString | 106 |
| 3.30.3.2 | file | 106 |
| 3.30.3.3 | func | 106 |
| 3.30.3.4 | line | 106 |
| 3.30.4 | Friends And Related Function Documentation | 106 |
| 3.30.4.1 | operator<< | 106 |
| 3.31 | YColor Class Reference | 107 |
| 3.31.1 | Detailed Description | 107 |
| 3.31.2 | Constructor & Destructor Documentation | 107 |
| 3.31.2.1 | YColor | 107 |
| 3.31.2.2 | YColor | 107 |
| 3.31.3 | Member Function Documentation | 107 |
| 3.31.3.1 | blue | 107 |

| | | |
|-----------|--|-----|
| 3.31.3.2 | green | 108 |
| 3.31.3.3 | isDefined | 108 |
| 3.31.3.4 | isUndefined | 108 |
| 3.31.3.5 | red | 108 |
| 3.32 | YComboBox Class Reference | 108 |
| 3.32.1 | Detailed Description | 110 |
| 3.32.2 | Constructor & Destructor Documentation | 111 |
| 3.32.2.1 | YComboBox | 111 |
| 3.32.2.2 | ~YComboBox | 111 |
| 3.32.3 | Member Function Documentation | 111 |
| 3.32.3.1 | editable | 111 |
| 3.32.3.2 | getProperty | 111 |
| 3.32.3.3 | inputMaxLength | 112 |
| 3.32.3.4 | propertySet | 112 |
| 3.32.3.5 | selectedItem | 113 |
| 3.32.3.6 | selectedItems | 113 |
| 3.32.3.7 | selectItem | 114 |
| 3.32.3.8 | setInputMaxLength | 115 |
| 3.32.3.9 | setProperty | 115 |
| 3.32.3.10 | setText | 116 |
| 3.32.3.11 | setValidChars | 116 |
| 3.32.3.12 | setValue | 117 |
| 3.32.3.13 | text | 117 |
| 3.32.3.14 | userInputProperty | 117 |
| 3.32.3.15 | validChars | 118 |
| 3.32.3.16 | value | 118 |
| 3.32.3.17 | widgetClass | 118 |
| 3.33 | YComboBoxPrivate Struct Reference | 119 |
| 3.33.1 | Detailed Description | 119 |
| 3.34 | YCommandLine Class Reference | 119 |
| 3.34.1 | Detailed Description | 120 |

| | | |
|-----------|--|-----|
| 3.34.2 | Constructor & Destructor Documentation | 120 |
| 3.34.2.1 | YCommandLine | 120 |
| 3.34.2.2 | ~YCommandLine | 120 |
| 3.34.3 | Member Function Documentation | 120 |
| 3.34.3.1 | add | 120 |
| 3.34.3.2 | arg | 120 |
| 3.34.3.3 | argc | 121 |
| 3.34.3.4 | argv | 121 |
| 3.34.3.5 | find | 121 |
| 3.34.3.6 | operator[] | 122 |
| 3.34.3.7 | remove | 122 |
| 3.34.3.8 | replace | 123 |
| 3.34.3.9 | size | 123 |
| 3.35 | YCommandLinePrivate Struct Reference | 123 |
| 3.35.1 | Detailed Description | 123 |
| 3.36 | YContextMenu Class Reference | 124 |
| 3.36.1 | Detailed Description | 126 |
| 3.36.2 | Constructor & Destructor Documentation | 126 |
| 3.36.2.1 | YContextMenu | 126 |
| 3.36.2.2 | ~YContextMenu | 126 |
| 3.36.3 | Member Function Documentation | 126 |
| 3.36.3.1 | addItem | 126 |
| 3.36.3.2 | addItems | 127 |
| 3.36.3.3 | deleteAllItems | 128 |
| 3.36.3.4 | findMenuitem | 128 |
| 3.36.3.5 | findMenuitem | 128 |
| 3.36.3.6 | getProperty | 129 |
| 3.36.3.7 | itemAt | 130 |
| 3.36.3.8 | propertySet | 130 |
| 3.36.3.9 | rebuildMenuTree | 130 |
| 3.36.3.10 | resolveShortcutConflicts | 131 |

| | | |
|-----------|--|-----|
| 3.36.3.11 | setProperty | 131 |
| 3.36.3.12 | widgetClass | 132 |
| 3.37 | YContextMenuPrivate Struct Reference | 132 |
| 3.37.1 | Detailed Description | 132 |
| 3.38 | YDateField Class Reference | 132 |
| 3.38.1 | Detailed Description | 134 |
| 3.38.2 | Constructor & Destructor Documentation | 134 |
| 3.38.2.1 | YDateField | 134 |
| 3.38.2.2 | ~YDateField | 134 |
| 3.38.3 | Member Function Documentation | 134 |
| 3.38.3.1 | widgetClass | 134 |
| 3.39 | YDateFieldPrivate Struct Reference | 135 |
| 3.39.1 | Detailed Description | 135 |
| 3.40 | YDebugEvent Class Reference | 135 |
| 3.40.1 | Detailed Description | 136 |
| 3.40.2 | Constructor & Destructor Documentation | 136 |
| 3.40.2.1 | ~YDebugEvent | 136 |
| 3.41 | YDialog Class Reference | 137 |
| 3.41.1 | Detailed Description | 139 |
| 3.41.2 | Constructor & Destructor Documentation | 139 |
| 3.41.2.1 | YDialog | 139 |
| 3.41.2.2 | ~YDialog | 139 |
| 3.41.3 | Member Function Documentation | 140 |
| 3.41.3.1 | activate | 140 |
| 3.41.3.2 | addEventFilter | 140 |
| 3.41.3.3 | callEventFilters | 141 |
| 3.41.3.4 | checkShortcuts | 141 |
| 3.41.3.5 | colorMode | 141 |
| 3.41.3.6 | currentDialog | 142 |
| 3.41.3.7 | defaultButton | 142 |
| 3.41.3.8 | deleteAllDialogs | 142 |

| | | |
|-----------|---|-----|
| 3.41.3.9 | deleteEvent | 142 |
| 3.41.3.10 | deleteEventFilters | 143 |
| 3.41.3.11 | deleteTo | 143 |
| 3.41.3.12 | deleteTopmostDialog | 143 |
| 3.41.3.13 | destroy | 143 |
| 3.41.3.14 | dialogType | 144 |
| 3.41.3.15 | filterInvalidEvents | 144 |
| 3.41.3.16 | highlight | 145 |
| 3.41.3.17 | isMainDialog | 145 |
| 3.41.3.18 | isOpen | 145 |
| 3.41.3.19 | isTopmostDialog | 145 |
| 3.41.3.20 | open | 146 |
| 3.41.3.21 | openDialogsCount | 146 |
| 3.41.3.22 | openInternal | 146 |
| 3.41.3.23 | pollEvent | 147 |
| 3.41.3.24 | pollEventInternal | 147 |
| 3.41.3.25 | postponeShortcutCheck | 148 |
| 3.41.3.26 | recalcLayout | 148 |
| 3.41.3.27 | removeEventFilter | 148 |
| 3.41.3.28 | setDefaultButton | 149 |
| 3.41.3.29 | setInitialSize | 149 |
| 3.41.3.30 | shortcutCheckPostponed | 150 |
| 3.41.3.31 | showHelpText | 150 |
| 3.41.3.32 | showText | 150 |
| 3.41.3.33 | topmostDialog | 151 |
| 3.41.3.34 | waitForEvent | 152 |
| 3.41.3.35 | waitForEventInternal | 153 |
| 3.41.3.36 | widgetClass | 153 |
| 3.41.4 | Member Data Documentation | 153 |
| 3.41.4.1 | _dialogStack | 153 |
| 3.42 | YDialogPrivate Struct Reference | 154 |

| | |
|---|-----|
| 3.42.1 Detailed Description | 154 |
| 3.43 YDialogSpy Class Reference | 155 |
| 3.43.1 Detailed Description | 155 |
| 3.43.2 Constructor & Destructor Documentation | 155 |
| 3.43.2.1 YDialogSpy | 155 |
| 3.43.2.2 ~YDialogSpy | 156 |
| 3.43.3 Member Function Documentation | 156 |
| 3.43.3.1 exec | 157 |
| 3.43.3.2 hideProperties | 157 |
| 3.43.3.3 propertiesShown | 158 |
| 3.43.3.4 showDialogSpy | 158 |
| 3.43.3.5 showProperties | 159 |
| 3.43.3.6 showProperties | 160 |
| 3.44 YDialogSpyPrivate Struct Reference | 161 |
| 3.44.1 Detailed Description | 161 |
| 3.45 YDownloadProgress Class Reference | 162 |
| 3.45.1 Detailed Description | 163 |
| 3.45.2 Constructor & Destructor Documentation | 163 |
| 3.45.2.1 YDownloadProgress | 163 |
| 3.45.2.2 ~YDownloadProgress | 164 |
| 3.45.3 Member Function Documentation | 164 |
| 3.45.3.1 currentFileSize | 164 |
| 3.45.3.2 currentPercent | 164 |
| 3.45.3.3 expectedSize | 165 |
| 3.45.3.4 filename | 165 |
| 3.45.3.5 getProperty | 165 |
| 3.45.3.6 label | 166 |
| 3.45.3.7 propertySet | 166 |
| 3.45.3.8 setExpectedSize | 167 |
| 3.45.3.9 setFilename | 167 |
| 3.45.3.10 setLabel | 167 |

| | | |
|-----------|---|-----|
| 3.45.3.11 | setProperty | 168 |
| 3.45.3.12 | value | 169 |
| 3.45.3.13 | widgetClass | 169 |
| 3.46 | YDownloadProgressPrivate Struct Reference | 169 |
| 3.46.1 | Detailed Description | 170 |
| 3.47 | YDumbTab Class Reference | 170 |
| 3.47.1 | Detailed Description | 172 |
| 3.47.2 | Constructor & Destructor Documentation | 172 |
| 3.47.2.1 | YDumbTab | 172 |
| 3.47.2.2 | ~YDumbTab | 172 |
| 3.47.3 | Member Function Documentation | 172 |
| 3.47.3.1 | addItem | 172 |
| 3.47.3.2 | debugLabel | 173 |
| 3.47.3.3 | getProperty | 173 |
| 3.47.3.4 | propertySet | 174 |
| 3.47.3.5 | setProperty | 174 |
| 3.47.3.6 | setShortcutString | 175 |
| 3.47.3.7 | shortcutChanged | 176 |
| 3.47.3.8 | shortcutString | 176 |
| 3.47.3.9 | stretchable | 176 |
| 3.47.3.10 | widgetClass | 177 |
| 3.48 | YDumbTabPrivate Struct Reference | 177 |
| 3.48.1 | Detailed Description | 177 |
| 3.49 | YEmpty Class Reference | 178 |
| 3.49.1 | Detailed Description | 179 |
| 3.49.2 | Constructor & Destructor Documentation | 179 |
| 3.49.2.1 | YEmpty | 179 |
| 3.49.2.2 | ~YEmpty | 179 |
| 3.49.3 | Member Function Documentation | 179 |
| 3.49.3.1 | preferredHeight | 179 |
| 3.49.3.2 | preferredWidth | 179 |

| | |
|---|-----|
| 3.49.3.3 widgetClass | 180 |
| 3.50 YEmptyPrivate Struct Reference | 180 |
| 3.50.1 Detailed Description | 180 |
| 3.51 YEnvVar Class Reference | 180 |
| 3.51.1 Detailed Description | 181 |
| 3.51.2 Constructor & Destructor Documentation | 181 |
| 3.51.2.1 YEnvVar | 181 |
| 3.51.3 Member Function Documentation | 181 |
| 3.51.3.1 contains | 181 |
| 3.51.3.2 isEqual | 181 |
| 3.51.3.3 isSet | 181 |
| 3.51.3.4 name | 181 |
| 3.51.3.5 operator== | 182 |
| 3.51.3.6 value | 182 |
| 3.52 YEvent Class Reference | 182 |
| 3.52.1 Detailed Description | 183 |
| 3.52.2 Constructor & Destructor Documentation | 184 |
| 3.52.2.1 YEvent | 184 |
| 3.52.2.2 ~YEvent | 184 |
| 3.52.3 Member Function Documentation | 184 |
| 3.52.3.1 dialog | 185 |
| 3.52.3.2 eventType | 185 |
| 3.52.3.3 invalidate | 185 |
| 3.52.3.4 isValid | 185 |
| 3.52.3.5 item | 185 |
| 3.52.3.6 serial | 185 |
| 3.52.3.7 setDialog | 185 |
| 3.52.3.8 toString | 186 |
| 3.52.3.9 toString | 186 |
| 3.52.3.10 widget | 186 |
| 3.53 YEventFilter Class Reference | 186 |

| | | |
|----------|--|-----|
| 3.53.1 | Detailed Description | 187 |
| 3.53.2 | Constructor & Destructor Documentation | 188 |
| 3.53.2.1 | YEventFilter | 188 |
| 3.53.2.2 | ~YEventFilter | 188 |
| 3.53.3 | Member Function Documentation | 189 |
| 3.53.3.1 | dialog | 189 |
| 3.53.3.2 | filter | 189 |
| 3.54 | YEventFilterPrivate Struct Reference | 190 |
| 3.54.1 | Detailed Description | 191 |
| 3.55 | YFrame Class Reference | 191 |
| 3.55.1 | Detailed Description | 192 |
| 3.55.2 | Constructor & Destructor Documentation | 193 |
| 3.55.2.1 | YFrame | 193 |
| 3.55.2.2 | ~YFrame | 193 |
| 3.55.3 | Member Function Documentation | 193 |
| 3.55.3.1 | getProperty | 193 |
| 3.55.3.2 | label | 194 |
| 3.55.3.3 | propertySet | 194 |
| 3.55.3.4 | setLabel | 194 |
| 3.55.3.5 | setProperty | 195 |
| 3.55.3.6 | widgetClass | 195 |
| 3.56 | YFramePrivate Struct Reference | 196 |
| 3.56.1 | Detailed Description | 196 |
| 3.57 | YGraph Class Reference | 196 |
| 3.57.1 | Detailed Description | 198 |
| 3.57.2 | Constructor & Destructor Documentation | 198 |
| 3.57.2.1 | YGraph | 198 |
| 3.57.2.2 | YGraph | 198 |
| 3.57.2.3 | ~YGraph | 199 |
| 3.57.3 | Member Function Documentation | 199 |
| 3.57.3.1 | activatedNode | 199 |

| | | |
|-----------|--|-----|
| 3.57.3.2 | filename | 199 |
| 3.57.3.3 | getProperty | 199 |
| 3.57.3.4 | layoutAlgorithm | 200 |
| 3.57.3.5 | propertySet | 200 |
| 3.57.3.6 | renderGraph | 201 |
| 3.57.3.7 | renderGraph | 201 |
| 3.57.3.8 | setFilename | 201 |
| 3.57.3.9 | setGraph | 201 |
| 3.57.3.10 | setLayoutAlgorithm | 202 |
| 3.57.3.11 | setProperty | 202 |
| 3.57.3.12 | widgetClass | 203 |
| 3.58 | YGraphPlugin Class Reference | 203 |
| 3.58.1 | Detailed Description | 205 |
| 3.58.2 | Constructor & Destructor Documentation | 205 |
| 3.58.2.1 | YGraphPlugin | 205 |
| 3.58.2.2 | ~YGraphPlugin | 205 |
| 3.58.3 | Member Function Documentation | 205 |
| 3.58.3.1 | createGraph | 205 |
| 3.59 | YGraphPrivate Struct Reference | 205 |
| 3.59.1 | Detailed Description | 206 |
| 3.60 | YHelpButtonHandler Class Reference | 206 |
| 3.60.1 | Detailed Description | 207 |
| 3.60.2 | Member Function Documentation | 207 |
| 3.60.2.1 | filter | 207 |
| 3.61 | YIconLoader Class Reference | 208 |
| 3.61.1 | Detailed Description | 209 |
| 3.62 | YImage Class Reference | 209 |
| 3.62.1 | Detailed Description | 210 |
| 3.62.2 | Constructor & Destructor Documentation | 210 |
| 3.62.2.1 | YImage | 210 |
| 3.62.2.2 | ~YImage | 211 |

| | | |
|-----------|--|-----|
| 3.62.3 | Member Function Documentation | 211 |
| 3.62.3.1 | animated | 211 |
| 3.62.3.2 | autoScale | 211 |
| 3.62.3.3 | hasZeroSize | 211 |
| 3.62.3.4 | imageFileName | 211 |
| 3.62.3.5 | setAutoScale | 211 |
| 3.62.3.6 | setImage | 212 |
| 3.62.3.7 | setMovie | 212 |
| 3.62.3.8 | setZeroSize | 213 |
| 3.62.3.9 | widgetClass | 213 |
| 3.63 | YImagePrivate Struct Reference | 214 |
| 3.63.1 | Detailed Description | 214 |
| 3.63.2 | Constructor & Destructor Documentation | 215 |
| 3.63.2.1 | YImagePrivate | 215 |
| 3.64 | YInputField Class Reference | 215 |
| 3.64.1 | Detailed Description | 217 |
| 3.64.2 | Constructor & Destructor Documentation | 217 |
| 3.64.2.1 | YInputField | 217 |
| 3.64.2.2 | ~YInputField | 217 |
| 3.64.3 | Member Function Documentation | 218 |
| 3.64.3.1 | getProperty | 218 |
| 3.64.3.2 | inputMaxLength | 218 |
| 3.64.3.3 | label | 218 |
| 3.64.3.4 | passwordMode | 219 |
| 3.64.3.5 | propertySet | 219 |
| 3.64.3.6 | saveUserInput | 219 |
| 3.64.3.7 | setInputMaxLength | 220 |
| 3.64.3.8 | setLabel | 220 |
| 3.64.3.9 | setProperty | 221 |
| 3.64.3.10 | setShortcutString | 221 |
| 3.64.3.11 | setShrinkable | 222 |

| | | |
|-----------|--|-----|
| 3.64.3.12 | setValidChars | 222 |
| 3.64.3.13 | setValue | 223 |
| 3.64.3.14 | shortcutString | 223 |
| 3.64.3.15 | shrinkable | 223 |
| 3.64.3.16 | userInputProperty | 223 |
| 3.64.3.17 | validChars | 224 |
| 3.64.3.18 | value | 224 |
| 3.64.3.19 | widgetClass | 224 |
| 3.65 | YInputFieldPrivate Struct Reference | 224 |
| 3.65.1 | Detailed Description | 225 |
| 3.66 | YIntField Class Reference | 225 |
| 3.66.1 | Detailed Description | 227 |
| 3.66.2 | Constructor & Destructor Documentation | 227 |
| 3.66.2.1 | YIntField | 227 |
| 3.66.2.2 | ~YIntField | 227 |
| 3.66.3 | Member Function Documentation | 227 |
| 3.66.3.1 | enforceRange | 228 |
| 3.66.3.2 | getProperty | 228 |
| 3.66.3.3 | label | 229 |
| 3.66.3.4 | maxValue | 229 |
| 3.66.3.5 | minValue | 229 |
| 3.66.3.6 | propertySet | 229 |
| 3.66.3.7 | setLabel | 230 |
| 3.66.3.8 | setMaxValue | 230 |
| 3.66.3.9 | setMinValue | 231 |
| 3.66.3.10 | setProperty | 231 |
| 3.66.3.11 | setShortcutString | 232 |
| 3.66.3.12 | setValue | 232 |
| 3.66.3.13 | setValueInternal | 233 |
| 3.66.3.14 | shortcutString | 233 |
| 3.66.3.15 | userInputProperty | 234 |

| | |
|---|-----|
| 3.66.3.16 value | 234 |
| 3.66.3.17 widgetClass | 234 |
| 3.67 YIntFieldPrivate Struct Reference | 234 |
| 3.67.1 Detailed Description | 235 |
| 3.68 YItem Class Reference | 235 |
| 3.68.1 Detailed Description | 236 |
| 3.68.2 Constructor & Destructor Documentation | 236 |
| 3.68.2.1 YItem | 236 |
| 3.68.2.2 YItem | 236 |
| 3.68.2.3 ~YItem | 236 |
| 3.68.3 Member Function Documentation | 237 |
| 3.68.3.1 childrenBegin | 237 |
| 3.68.3.2 childrenEnd | 237 |
| 3.68.3.3 data | 237 |
| 3.68.3.4 hasChildren | 237 |
| 3.68.3.5 hasIconName | 237 |
| 3.68.3.6 iconName | 238 |
| 3.68.3.7 index | 238 |
| 3.68.3.8 label | 238 |
| 3.68.3.9 parent | 238 |
| 3.68.3.10 selected | 238 |
| 3.68.3.11 setData | 238 |
| 3.68.3.12 setIconName | 239 |
| 3.68.3.13 setIndex | 239 |
| 3.68.3.14 setLabel | 239 |
| 3.68.3.15 setSelected | 239 |
| 3.69 YItemShortcut Class Reference | 240 |
| 3.69.1 Detailed Description | 241 |
| 3.69.2 Constructor & Destructor Documentation | 241 |
| 3.69.2.1 YItemShortcut | 241 |
| 3.69.2.2 ~YItemShortcut | 241 |

| | |
|---|-----|
| 3.69.3 Member Function Documentation | 241 |
| 3.69.3.1 getShortcutString | 241 |
| 3.69.3.2 item | 242 |
| 3.69.3.3 setShortcut | 242 |
| 3.70 YKeyEvent Class Reference | 243 |
| 3.70.1 Detailed Description | 244 |
| 3.70.2 Constructor & Destructor Documentation | 244 |
| 3.70.2.1 YKeyEvent | 244 |
| 3.70.2.2 ~YKeyEvent | 244 |
| 3.70.3 Member Function Documentation | 244 |
| 3.70.3.1 focusWidget | 244 |
| 3.70.3.2 keySymbol | 245 |
| 3.71 YLabel Class Reference | 245 |
| 3.71.1 Detailed Description | 246 |
| 3.71.2 Constructor & Destructor Documentation | 247 |
| 3.71.2.1 YLabel | 247 |
| 3.71.2.2 ~YLabel | 247 |
| 3.71.3 Member Function Documentation | 247 |
| 3.71.3.1 debugLabel | 247 |
| 3.71.3.2 getProperty | 248 |
| 3.71.3.3 isHeading | 248 |
| 3.71.3.4 isOutputField | 248 |
| 3.71.3.5 propertySet | 249 |
| 3.71.3.6 setProperty | 249 |
| 3.71.3.7 setText | 250 |
| 3.71.3.8 setUseBoldFont | 250 |
| 3.71.3.9 setValue | 250 |
| 3.71.3.10 text | 251 |
| 3.71.3.11 useBoldFont | 251 |
| 3.71.3.12 value | 251 |
| 3.71.3.13 widgetClass | 252 |

| | |
|---|-----|
| 3.72 YLabelPrivate Struct Reference | 252 |
| 3.72.1 Detailed Description | 252 |
| 3.72.2 Constructor & Destructor Documentation | 252 |
| 3.72.2.1 YLabelPrivate | 252 |
| 3.73 YLayoutBox Class Reference | 253 |
| 3.73.1 Detailed Description | 254 |
| 3.73.2 Constructor & Destructor Documentation | 255 |
| 3.73.2.1 YLayoutBox | 255 |
| 3.73.2.2 ~YLayoutBox | 255 |
| 3.73.3 Member Function Documentation | 255 |
| 3.73.3.1 calcPrimaryGeometry | 255 |
| 3.73.3.2 calcSecondaryGeometry | 256 |
| 3.73.3.3 childrenMaxPreferredSize | 257 |
| 3.73.3.4 childrenTotalWeight | 258 |
| 3.73.3.5 countLayoutStretchChildren | 258 |
| 3.73.3.6 countNonWeightedChildren | 259 |
| 3.73.3.7 countStretchableChildren | 259 |
| 3.73.3.8 debugLayout | 259 |
| 3.73.3.9 doResize | 260 |
| 3.73.3.10 findDominatingChild | 260 |
| 3.73.3.11 isLayoutStretch | 261 |
| 3.73.3.12 moveChild | 261 |
| 3.73.3.13 preferredHeight | 262 |
| 3.73.3.14 preferredSize | 262 |
| 3.73.3.15 preferredWidth | 263 |
| 3.73.3.16 primary | 264 |
| 3.73.3.17 secondary | 264 |
| 3.73.3.18 setDebugLayout | 264 |
| 3.73.3.19 setSize | 264 |
| 3.73.3.20 stretchable | 265 |
| 3.73.3.21 totalNonWeightedChildrenPreferredSize | 266 |

| | |
|---|-----|
| 3.73.3.22 widgetClass | 266 |
| 3.74 YLayoutBoxPrivate Struct Reference | 267 |
| 3.74.1 Detailed Description | 267 |
| 3.74.2 Constructor & Destructor Documentation | 267 |
| 3.74.2.1 YLayoutBoxPrivate | 267 |
| 3.75 YLogView Class Reference | 268 |
| 3.75.1 Detailed Description | 269 |
| 3.75.2 Constructor & Destructor Documentation | 269 |
| 3.75.2.1 YLogView | 269 |
| 3.75.2.2 ~YLogView | 270 |
| 3.75.3 Member Function Documentation | 270 |
| 3.75.3.1 appendLines | 270 |
| 3.75.3.2 clearText | 270 |
| 3.75.3.3 displayLogText | 270 |
| 3.75.3.4 getProperty | 271 |
| 3.75.3.5 label | 271 |
| 3.75.3.6 lastLine | 271 |
| 3.75.3.7 lines | 272 |
| 3.75.3.8 logText | 272 |
| 3.75.3.9 maxLines | 272 |
| 3.75.3.10 propertySet | 272 |
| 3.75.3.11 setLabel | 272 |
| 3.75.3.12 setLogText | 273 |
| 3.75.3.13 setMaxLines | 273 |
| 3.75.3.14 setProperty | 274 |
| 3.75.3.15 setShortcutString | 275 |
| 3.75.3.16 setVisibleLines | 275 |
| 3.75.3.17 shortcutString | 275 |
| 3.75.3.18 visibleLines | 276 |
| 3.75.3.19 widgetClass | 276 |
| 3.76 YLogViewPrivate Struct Reference | 276 |

| | |
|---|-----|
| 3.76.1 Detailed Description | 277 |
| 3.77 YMacro Class Reference | 277 |
| 3.77.1 Detailed Description | 277 |
| 3.77.2 Member Function Documentation | 278 |
| 3.77.2.1 deletePlayer | 278 |
| 3.77.2.2 deleteRecorder | 278 |
| 3.77.2.3 endRecording | 278 |
| 3.77.2.4 play | 278 |
| 3.77.2.5 player | 279 |
| 3.77.2.6 playing | 279 |
| 3.77.2.7 playNextBlock | 279 |
| 3.77.2.8 record | 280 |
| 3.77.2.9 recorder | 280 |
| 3.77.2.10 recording | 280 |
| 3.77.2.11 setPlayer | 281 |
| 3.77.2.12 setRecorder | 281 |
| 3.78 YMacroPlayer Class Reference | 282 |
| 3.78.1 Detailed Description | 282 |
| 3.78.2 Constructor & Destructor Documentation | 283 |
| 3.78.2.1 YMacroPlayer | 283 |
| 3.78.2.2 ~YMacroPlayer | 283 |
| 3.78.3 Member Function Documentation | 283 |
| 3.78.3.1 play | 283 |
| 3.78.3.2 playing | 283 |
| 3.78.3.3 playNextBlock | 283 |
| 3.79 YMacroRecorder Class Reference | 283 |
| 3.79.1 Detailed Description | 284 |
| 3.79.2 Constructor & Destructor Documentation | 284 |
| 3.79.2.1 YMacroRecorder | 284 |
| 3.79.2.2 ~YMacroRecorder | 284 |
| 3.79.3 Member Function Documentation | 285 |

| | | |
|-----------|--|-----|
| 3.79.3.1 | endRecording | 285 |
| 3.79.3.2 | record | 285 |
| 3.79.3.3 | recording | 285 |
| 3.79.3.4 | recordMakeScreenShot | 285 |
| 3.79.3.5 | recordWidgetProperty | 285 |
| 3.80 | YMenuButton Class Reference | 285 |
| 3.80.1 | Detailed Description | 287 |
| 3.80.2 | Constructor & Destructor Documentation | 287 |
| 3.80.2.1 | YMenuButton | 287 |
| 3.80.2.2 | ~YMenuButton | 288 |
| 3.80.3 | Member Function Documentation | 288 |
| 3.80.3.1 | addItem | 288 |
| 3.80.3.2 | addItems | 289 |
| 3.80.3.3 | deleteAllItems | 289 |
| 3.80.3.4 | findMenuItem | 289 |
| 3.80.3.5 | findMenuItem | 290 |
| 3.80.3.6 | getProperty | 290 |
| 3.80.3.7 | itemAt | 291 |
| 3.80.3.8 | propertySet | 291 |
| 3.80.3.9 | rebuildMenuTree | 292 |
| 3.80.3.10 | resolveShortcutConflicts | 292 |
| 3.80.3.11 | setProperty | 292 |
| 3.80.3.12 | widgetClass | 293 |
| 3.81 | YMenuButtonPrivate Struct Reference | 293 |
| 3.81.1 | Detailed Description | 293 |
| 3.82 | YMenuEvent Class Reference | 294 |
| 3.82.1 | Detailed Description | 295 |
| 3.82.2 | Constructor & Destructor Documentation | 295 |
| 3.82.2.1 | ~YMenuEvent | 295 |
| 3.82.3 | Member Function Documentation | 295 |
| 3.82.3.1 | id | 295 |

| | | |
|-----------|--|-----|
| 3.82.3.2 | item | 296 |
| 3.83 | YMenuItem Class Reference | 296 |
| 3.83.1 | Detailed Description | 297 |
| 3.83.2 | Constructor & Destructor Documentation | 297 |
| 3.83.2.1 | YMenuItem | 297 |
| 3.83.2.2 | YMenuItem | 298 |
| 3.83.2.3 | ~YMenuItem | 298 |
| 3.83.3 | Member Function Documentation | 298 |
| 3.83.3.1 | parent | 298 |
| 3.84 | YMultiLineEdit Class Reference | 299 |
| 3.84.1 | Detailed Description | 300 |
| 3.84.2 | Constructor & Destructor Documentation | 300 |
| 3.84.2.1 | YMultiLineEdit | 300 |
| 3.84.2.2 | ~YMultiLineEdit | 301 |
| 3.84.3 | Member Function Documentation | 301 |
| 3.84.3.1 | defaultVisibleLines | 301 |
| 3.84.3.2 | getProperty | 301 |
| 3.84.3.3 | inputMaxLength | 302 |
| 3.84.3.4 | label | 302 |
| 3.84.3.5 | propertySet | 302 |
| 3.84.3.6 | setDefaultVisibleLines | 302 |
| 3.84.3.7 | setInputMaxLength | 303 |
| 3.84.3.8 | setLabel | 303 |
| 3.84.3.9 | setProperty | 303 |
| 3.84.3.10 | setShortcutString | 304 |
| 3.84.3.11 | setValue | 305 |
| 3.84.3.12 | shortcutString | 305 |
| 3.84.3.13 | userInputProperty | 305 |
| 3.84.3.14 | value | 305 |
| 3.84.3.15 | widgetClass | 306 |
| 3.85 | YMultiLineEditPrivate Struct Reference | 306 |

| | |
|--|-----|
| 3.85.1 Detailed Description | 306 |
| 3.86 YMultiProgressMeter Class Reference | 306 |
| 3.86.1 Detailed Description | 308 |
| 3.86.2 Constructor & Destructor Documentation | 308 |
| 3.86.2.1 YMultiProgressMeter | 309 |
| 3.86.2.2 ~YMultiProgressMeter | 309 |
| 3.86.3 Member Function Documentation | 309 |
| 3.86.3.1 currentValue | 309 |
| 3.86.3.2 dimension | 309 |
| 3.86.3.3 doUpdate | 309 |
| 3.86.3.4 getProperty | 310 |
| 3.86.3.5 horizontal | 310 |
| 3.86.3.6 maxValue | 310 |
| 3.86.3.7 propertySet | 310 |
| 3.86.3.8 segments | 311 |
| 3.86.3.9 setCurrentValue | 311 |
| 3.86.3.10 setCurrentValues | 311 |
| 3.86.3.11 setProperty | 312 |
| 3.86.3.12 vertical | 312 |
| 3.86.3.13 widgetClass | 313 |
| 3.87 YMultiProgressMeterPrivate Struct Reference | 313 |
| 3.87.1 Detailed Description | 313 |
| 3.88 YMultiSelectionBox Class Reference | 314 |
| 3.88.1 Detailed Description | 315 |
| 3.88.2 Constructor & Destructor Documentation | 315 |
| 3.88.2.1 YMultiSelectionBox | 315 |
| 3.88.2.2 ~YMultiSelectionBox | 316 |
| 3.88.3 Member Function Documentation | 316 |
| 3.88.3.1 currentItem | 316 |
| 3.88.3.2 getProperty | 316 |
| 3.88.3.3 propertySet | 316 |

| | | |
|-----------|--|-----|
| 3.88.3.4 | saveUserInput | 317 |
| 3.88.3.5 | setCurrentItem | 317 |
| 3.88.3.6 | setProperty | 318 |
| 3.88.3.7 | setShrinkable | 318 |
| 3.88.3.8 | shrinkable | 319 |
| 3.88.3.9 | userInputProperty | 319 |
| 3.88.3.10 | widgetClass | 319 |
| 3.89 | YMultiSelectionBoxPrivate Struct Reference | 319 |
| 3.89.1 | Detailed Description | 320 |
| 3.90 | YOptionalWidgetFactory Class Reference | 320 |
| 3.90.1 | Detailed Description | 321 |
| 3.90.2 | Constructor & Destructor Documentation | 322 |
| 3.90.2.1 | YOptionalWidgetFactory | 322 |
| 3.90.2.2 | ~YOptionalWidgetFactory | 322 |
| 3.91 | YPackageSelector Class Reference | 322 |
| 3.91.1 | Detailed Description | 323 |
| 3.91.2 | Constructor & Destructor Documentation | 324 |
| 3.91.2.1 | YPackageSelector | 324 |
| 3.91.3 | Member Function Documentation | 324 |
| 3.91.3.1 | testMode | 324 |
| 3.91.3.2 | widgetClass | 324 |
| 3.92 | YPackageSelectorPlugin Class Reference | 325 |
| 3.92.1 | Detailed Description | 326 |
| 3.92.2 | Constructor & Destructor Documentation | 326 |
| 3.92.2.1 | YPackageSelectorPlugin | 326 |
| 3.92.2.2 | ~YPackageSelectorPlugin | 326 |
| 3.92.3 | Member Function Documentation | 326 |
| 3.92.3.1 | createPackageSelector | 326 |
| 3.93 | YPartitionSplitter Class Reference | 327 |
| 3.93.1 | Detailed Description | 328 |
| 3.93.2 | Constructor & Destructor Documentation | 329 |

| | | |
|----------|--|-----|
| 3.93.2.1 | YPartitionSplitter | 329 |
| 3.93.2.2 | ~YPartitionSplitter | 330 |
| 3.93.3 | Member Function Documentation | 330 |
| 3.93.3.1 | getProperty | 330 |
| 3.93.3.2 | propertySet | 330 |
| 3.93.3.3 | setProperty | 331 |
| 3.93.3.4 | setValue | 331 |
| 3.93.3.5 | userInputProperty | 332 |
| 3.93.3.6 | value | 332 |
| 3.93.3.7 | widgetClass | 332 |
| 3.94 | YPartitionSplitterPrivate Struct Reference | 332 |
| 3.94.1 | Detailed Description | 333 |
| 3.95 | YPath Class Reference | 333 |
| 3.95.1 | Detailed Description | 333 |
| 3.95.2 | Constructor & Destructor Documentation | 333 |
| 3.95.2.1 | YPath | 333 |
| 3.95.2.2 | ~YPath | 334 |
| 3.95.3 | Member Function Documentation | 334 |
| 3.95.3.1 | dir | 334 |
| 3.95.3.2 | path | 334 |
| 3.96 | YPerThreadLogInfo Struct Reference | 335 |
| 3.96.1 | Detailed Description | 335 |
| 3.96.2 | Constructor & Destructor Documentation | 336 |
| 3.96.2.1 | YPerThreadLogInfo | 336 |
| 3.96.2.2 | ~YPerThreadLogInfo | 336 |
| 3.96.3 | Member Function Documentation | 336 |
| 3.96.3.1 | isThread | 336 |
| 3.97 | YProgressBar Class Reference | 337 |
| 3.97.1 | Detailed Description | 338 |
| 3.97.2 | Constructor & Destructor Documentation | 338 |
| 3.97.2.1 | YProgressBar | 338 |

| | | |
|-----------|--|-----|
| 3.97.2.2 | ~YProgressBar | 338 |
| 3.97.3 | Member Function Documentation | 339 |
| 3.97.3.1 | getProperty | 339 |
| 3.97.3.2 | label | 339 |
| 3.97.3.3 | maxValue | 339 |
| 3.97.3.4 | propertySet | 339 |
| 3.97.3.5 | setLabel | 340 |
| 3.97.3.6 | setProperty | 340 |
| 3.97.3.7 | setValue | 341 |
| 3.97.3.8 | value | 341 |
| 3.97.3.9 | widgetClass | 341 |
| 3.98 | YProgressBarPrivate Struct Reference | 342 |
| 3.98.1 | Detailed Description | 342 |
| 3.99 | YProperty Class Reference | 342 |
| 3.99.1 | Detailed Description | 343 |
| 3.99.2 | Constructor & Destructor Documentation | 343 |
| 3.99.2.1 | YProperty | 343 |
| 3.99.3 | Member Function Documentation | 343 |
| 3.99.3.1 | isReadOnly | 343 |
| 3.99.3.2 | name | 343 |
| 3.99.3.3 | type | 343 |
| 3.99.3.4 | typeAsStr | 343 |
| 3.99.3.5 | typeAsStr | 344 |
| 3.100 | YPropertySet Class Reference | 344 |
| 3.100.1 | Detailed Description | 344 |
| 3.100.2 | Constructor & Destructor Documentation | 345 |
| 3.100.2.1 | YPropertySet | 345 |
| 3.100.3 | Member Function Documentation | 345 |
| 3.100.3.1 | add | 345 |
| 3.100.3.2 | add | 345 |
| 3.100.3.3 | check | 346 |

| | |
|--|-----|
| 3.100.3.4 check | 346 |
| 3.100.3.5 check | 347 |
| 3.100.3.6 contains | 347 |
| 3.100.3.7 contains | 347 |
| 3.100.3.8 contains | 348 |
| 3.100.3.9 isEmpty | 348 |
| 3.100.3.10propertiesBegin | 348 |
| 3.100.3.11propertiesEnd | 348 |
| 3.100.3.12size | 348 |
| 3.101YPropertyValue Class Reference | 349 |
| 3.101.1 Detailed Description | 349 |
| 3.101.2 Constructor & Destructor Documentation | 349 |
| 3.101.2.1 YPropertyValue | 349 |
| 3.101.2.2 YPropertyValue | 350 |
| 3.101.2.3 YPropertyValue | 350 |
| 3.101.2.4 YPropertyValue | 350 |
| 3.101.2.5 YPropertyValue | 350 |
| 3.101.2.6 YPropertyValue | 350 |
| 3.101.2.7 ~YPropertyValue | 350 |
| 3.101.3 Member Function Documentation | 350 |
| 3.101.3.1 stringVal | 350 |
| 3.101.3.2 type | 351 |
| 3.101.3.3 typeAsStr | 351 |
| 3.102YPushButton Class Reference | 351 |
| 3.102.1 Detailed Description | 353 |
| 3.102.2 Constructor & Destructor Documentation | 353 |
| 3.102.2.1 YPushButton | 353 |
| 3.102.2.2 ~YPushButton | 353 |
| 3.102.3 Member Function Documentation | 353 |
| 3.102.3.1 getProperty | 354 |
| 3.102.3.2 isDefaultButton | 354 |

| | |
|--|-----|
| 3.102.3.3 isHelpButton | 354 |
| 3.102.3.4 label | 355 |
| 3.102.3.5 propertySet | 355 |
| 3.102.3.6 role | 355 |
| 3.102.3.7 setDefaultButton | 355 |
| 3.102.3.8 setFunctionKey | 356 |
| 3.102.3.9 setHelpButton | 356 |
| 3.102.3.10 setIcon | 357 |
| 3.102.3.11 setLabel | 357 |
| 3.102.3.12 setProperty | 357 |
| 3.102.3.13 setRole | 358 |
| 3.102.3.14 setShortcutString | 359 |
| 3.102.3.15 shortcutString | 359 |
| 3.102.3.16 widgetClass | 360 |
| 3.103 YPushButtonPrivate Struct Reference | 360 |
| 3.103.1 Detailed Description | 361 |
| 3.104 YRadioButton Class Reference | 361 |
| 3.104.1 Detailed Description | 362 |
| 3.104.2 Constructor & Destructor Documentation | 363 |
| 3.104.2.1 YRadioButton | 363 |
| 3.104.2.2 ~YRadioButton | 363 |
| 3.104.3 Member Function Documentation | 363 |
| 3.104.3.1 buttonGroup | 363 |
| 3.104.3.2 findRadioButtonGroup | 364 |
| 3.104.3.3 getProperty | 364 |
| 3.104.3.4 label | 365 |
| 3.104.3.5 propertySet | 365 |
| 3.104.3.6 saveUserInput | 366 |
| 3.104.3.7 setLabel | 366 |
| 3.104.3.8 setProperty | 366 |
| 3.104.3.9 setShortcutString | 367 |

| | | |
|------------|---|-----|
| 3.104.3.10 | setUseBoldFont | 368 |
| 3.104.3.11 | setValue | 368 |
| 3.104.3.12 | shortcutString | 368 |
| 3.104.3.13 | useBoldFont | 368 |
| 3.104.3.14 | userInputProperty | 369 |
| 3.104.3.15 | value | 369 |
| 3.104.3.16 | widgetClass | 369 |
| 3.105 | YRadioButtonGroup Class Reference | 370 |
| 3.105.1 | Detailed Description | 371 |
| 3.105.2 | Constructor & Destructor Documentation | 371 |
| 3.105.2.1 | YRadioButtonGroup | 371 |
| 3.105.2.2 | ~YRadioButtonGroup | 371 |
| 3.105.3 | Member Function Documentation | 372 |
| 3.105.3.1 | addRadioButton | 372 |
| 3.105.3.2 | currentButton | 372 |
| 3.105.3.3 | getProperty | 372 |
| 3.105.3.4 | propertySet | 373 |
| 3.105.3.5 | radioButtonsBegin | 373 |
| 3.105.3.6 | radioButtonsCount | 374 |
| 3.105.3.7 | radioButtonsEnd | 374 |
| 3.105.3.8 | removeRadioButton | 374 |
| 3.105.3.9 | setProperty | 374 |
| 3.105.3.10 | uncheckOtherButtons | 375 |
| 3.105.3.11 | value | 375 |
| 3.105.3.12 | widgetClass | 376 |
| 3.106 | YRadioButtonGroupPrivate Struct Reference | 376 |
| 3.106.1 | Detailed Description | 376 |
| 3.107 | YRadioButtonPrivate Struct Reference | 377 |
| 3.107.1 | Detailed Description | 377 |
| 3.107.2 | Constructor & Destructor Documentation | 378 |
| 3.107.2.1 | YRadioButtonPrivate | 378 |

| | |
|--|-----|
| 3.108YReplacePoint Class Reference | 378 |
| 3.108.1 Detailed Description | 379 |
| 3.108.2 Constructor & Destructor Documentation | 379 |
| 3.108.2.1 YReplacePoint | 379 |
| 3.108.3 Member Function Documentation | 380 |
| 3.108.3.1 showChild | 380 |
| 3.108.3.2 widgetClass | 380 |
| 3.109YRichText Class Reference | 381 |
| 3.109.1 Detailed Description | 382 |
| 3.109.2 Constructor & Destructor Documentation | 382 |
| 3.109.2.1 YRichText | 382 |
| 3.109.2.2 ~YRichText | 383 |
| 3.109.3 Member Function Documentation | 383 |
| 3.109.3.1 autoScrollDown | 383 |
| 3.109.3.2 getProperty | 383 |
| 3.109.3.3 plainTextMode | 384 |
| 3.109.3.4 propertySet | 384 |
| 3.109.3.5 setAutoScrollDown | 385 |
| 3.109.3.6 setPlainTextMode | 385 |
| 3.109.3.7 setProperty | 385 |
| 3.109.3.8 setShrinkable | 386 |
| 3.109.3.9 setText | 387 |
| 3.109.3.10setValue | 387 |
| 3.109.3.11shrinkable | 387 |
| 3.109.3.12text | 387 |
| 3.109.3.13value | 388 |
| 3.109.3.14widgetClass | 388 |
| 3.110YRichTextPrivate Struct Reference | 388 |
| 3.110.1 Detailed Description | 389 |
| 3.110.2 Constructor & Destructor Documentation | 389 |
| 3.110.2.1 YRichTextPrivate | 389 |

| | |
|--|-----|
| 3.111YRpmGroupsTree Class Reference | 389 |
| 3.111.1 Detailed Description | 390 |
| 3.111.2 Constructor & Destructor Documentation | 391 |
| 3.111.2.1 YRpmGroupsTree | 391 |
| 3.111.2.2 ~YRpmGroupsTree | 391 |
| 3.111.3 Member Function Documentation | 391 |
| 3.111.3.1 addFallbackRpmGroups | 391 |
| 3.111.3.2 addRpmGroup | 391 |
| 3.111.3.3 rpmGroup | 392 |
| 3.111.3.4 translatedRpmGroup | 392 |
| 3.112YSelectionBox Class Reference | 393 |
| 3.112.1 Detailed Description | 394 |
| 3.112.2 Constructor & Destructor Documentation | 395 |
| 3.112.2.1 YSelectionBox | 395 |
| 3.112.2.2 ~YSelectionBox | 395 |
| 3.112.3 Member Function Documentation | 395 |
| 3.112.3.1 getProperty | 396 |
| 3.112.3.2 immediateMode | 396 |
| 3.112.3.3 propertySet | 397 |
| 3.112.3.4 setImmediateMode | 397 |
| 3.112.3.5 setProperty | 397 |
| 3.112.3.6 setShrinkable | 398 |
| 3.112.3.7 shrinkable | 399 |
| 3.112.3.8 userInputProperty | 399 |
| 3.112.3.9 widgetClass | 399 |
| 3.113YSelectionBoxPrivate Struct Reference | 399 |
| 3.113.1 Detailed Description | 399 |
| 3.114YSelectionWidget Class Reference | 400 |
| 3.114.1 Detailed Description | 402 |
| 3.114.2 Constructor & Destructor Documentation | 403 |
| 3.114.2.1 YSelectionWidget | 403 |

| | |
|---|-----|
| 3.114.2.2 ~YSelectionWidget | 403 |
| 3.114.3 Member Function Documentation | 403 |
| 3.114.3.1 addItem | 403 |
| 3.114.3.2 addItem | 404 |
| 3.114.3.3 addItem | 404 |
| 3.114.3.4 addItem | 405 |
| 3.114.3.5 deleteAllItems | 405 |
| 3.114.3.6 deselectAllItems | 406 |
| 3.114.3.7 deselectAllItems | 406 |
| 3.114.3.8 enforceSingleSelection | 407 |
| 3.114.3.9 findItem | 407 |
| 3.114.3.10 findItem | 408 |
| 3.114.3.11 findSelectedItem | 408 |
| 3.114.3.12 findSelectedItems | 409 |
| 3.114.3.13 firstItem | 410 |
| 3.114.3.14 hasItems | 410 |
| 3.114.3.15 hasSelectedItem | 410 |
| 3.114.3.16 iconBasePath | 410 |
| 3.114.3.17 iconFullPath | 410 |
| 3.114.3.18 iconFullPath | 411 |
| 3.114.3.19 itemAt | 411 |
| 3.114.3.20 itemsBegin | 411 |
| 3.114.3.21 itemsContain | 412 |
| 3.114.3.22 itemsContain | 412 |
| 3.114.3.23 itemsCount | 412 |
| 3.114.3.24 itemsEnd | 413 |
| 3.114.3.25 label | 413 |
| 3.114.3.26 recursiveSelection | 413 |
| 3.114.3.27 selectedItem | 413 |
| 3.114.3.28 selectedItems | 414 |
| 3.114.3.29 selectItem | 414 |

| | | |
|------------|--|-----|
| 3.114.3.30 | setEnforceSingleSelection | 415 |
| 3.114.3.31 | setIconBasePath | 415 |
| 3.114.3.32 | setItems | 416 |
| 3.114.3.33 | setLabel | 416 |
| 3.114.3.34 | setShortcutString | 416 |
| 3.114.3.35 | shortcutString | 417 |
| 3.114.3.36 | widgetClass | 417 |
| 3.115 | YSelectionWidgetPrivate Struct Reference | 418 |
| 3.115.1 | Detailed Description | 418 |
| 3.116 | YSettings Class Reference | 418 |
| 3.116.1 | Detailed Description | 419 |
| 3.116.2 | Member Function Documentation | 419 |
| 3.116.2.1 | iconDir | 419 |
| 3.116.2.2 | localeDir | 419 |
| 3.116.2.3 | progDir | 419 |
| 3.116.2.4 | setIconDir | 419 |
| 3.116.2.5 | setLocaleDir | 419 |
| 3.116.2.6 | setProgDir | 420 |
| 3.116.2.7 | setThemeDir | 420 |
| 3.116.2.8 | themeDir | 420 |
| 3.117 | YShortcut Class Reference | 420 |
| 3.117.1 | Detailed Description | 423 |
| 3.117.2 | Member Enumeration Documentation | 423 |
| 3.117.2.1 | anonymous enum | 423 |
| 3.117.3 | Constructor & Destructor Documentation | 423 |
| 3.117.3.1 | YShortcut | 423 |
| 3.117.3.2 | ~YShortcut | 423 |
| 3.117.4 | Member Function Documentation | 423 |
| 3.117.4.1 | cleanShortcutString | 424 |
| 3.117.4.2 | cleanShortcutString | 424 |
| 3.117.4.3 | clearShortcut | 424 |

| | |
|--|-----|
| 3.117.4.4 conflict | 425 |
| 3.117.4.5 distinctShortcutChars | 425 |
| 3.117.4.6 findShortcut | 425 |
| 3.117.4.7 findShortcutPos | 426 |
| 3.117.4.8 getShortcutString | 426 |
| 3.117.4.9 getShortcutString | 427 |
| 3.117.4.10 isValidShortcutChar | 427 |
| 3.117.4.11 isButton | 428 |
| 3.117.4.12 isValid | 428 |
| 3.117.4.13 isWizardButton | 428 |
| 3.117.4.14 normalized | 428 |
| 3.117.4.15 preferred | 428 |
| 3.117.4.16 setConflict | 429 |
| 3.117.4.17 setShortcut | 429 |
| 3.117.4.18 shortcut | 429 |
| 3.117.4.19 shortcutMarker | 430 |
| 3.117.4.20 shortcutString | 430 |
| 3.117.4.21 widget | 430 |
| 3.117.4.22 widgetClass | 431 |
| 3.118 YShortcutManager Class Reference | 431 |
| 3.118.1 Detailed Description | 433 |
| 3.118.2 Constructor & Destructor Documentation | 433 |
| 3.118.2.1 YShortcutManager | 433 |
| 3.118.2.2 ~YShortcutManager | 433 |
| 3.118.3 Member Function Documentation | 434 |
| 3.118.3.1 checkShortcuts | 434 |
| 3.118.3.2 clearShortcutList | 434 |
| 3.118.3.3 conflictCount | 434 |
| 3.118.3.4 dialog | 434 |
| 3.118.3.5 findShortcutWidgets | 435 |
| 3.118.3.6 findShortestWidget | 435 |

| | |
|--|-----|
| 3.118.3.7 findShortestWizardButton | 435 |
| 3.118.3.8 resolveAllConflicts | 435 |
| 3.118.3.9 resolveConflict | 436 |
| 3.118.4 Member Data Documentation | 437 |
| 3.118.4.1 _conflictCount | 437 |
| 3.118.4.2 _dialog | 437 |
| 3.118.4.3 _shortcutList | 437 |
| 3.118.4.4 _used | 437 |
| 3.118.4.5 _wanted | 437 |
| 3.119YSimpleEventHandler Class Reference | 438 |
| 3.119.1 Detailed Description | 439 |
| 3.119.2 Constructor & Destructor Documentation | 439 |
| 3.119.2.1 YSimpleEventHandler | 439 |
| 3.119.2.2 ~YSimpleEventHandler | 439 |
| 3.119.3 Member Function Documentation | 439 |
| 3.119.3.1 blockEvents | 439 |
| 3.119.3.2 clear | 440 |
| 3.119.3.3 consumePendingEvent | 440 |
| 3.119.3.4 deleteEvent | 440 |
| 3.119.3.5 deletePendingEventsFor | 441 |
| 3.119.3.6 eventPendingFor | 441 |
| 3.119.3.7 eventsBlocked | 441 |
| 3.119.3.8 pendingEvent | 441 |
| 3.119.3.9 sendEvent | 442 |
| 3.119.3.10unblockEvents | 442 |
| 3.120YSimpleInputField Class Reference | 443 |
| 3.120.1 Detailed Description | 444 |
| 3.120.2 Constructor & Destructor Documentation | 445 |
| 3.120.2.1 YSimpleInputField | 445 |
| 3.120.2.2 ~YSimpleInputField | 445 |
| 3.120.3 Member Function Documentation | 445 |

| | | |
|------------|---|-----|
| 3.120.3.1 | getProperty | 445 |
| 3.120.3.2 | label | 446 |
| 3.120.3.3 | propertySet | 446 |
| 3.120.3.4 | setLabel | 447 |
| 3.120.3.5 | setProperty | 447 |
| 3.120.3.6 | setShortcutString | 448 |
| 3.120.3.7 | setValue | 448 |
| 3.120.3.8 | shortcutString | 449 |
| 3.120.3.9 | userInputProperty | 449 |
| 3.120.3.10 | value | 449 |
| 3.121 | YSimpleInputFieldPrivate Struct Reference | 449 |
| 3.121.1 | Detailed Description | 450 |
| 3.122 | YSingleChildContainerWidget Class Reference | 450 |
| 3.122.1 | Detailed Description | 451 |
| 3.122.2 | Constructor & Destructor Documentation | 451 |
| 3.122.2.1 | YSingleChildContainerWidget | 451 |
| 3.122.2.2 | ~YSingleChildContainerWidget | 452 |
| 3.122.3 | Member Function Documentation | 452 |
| 3.122.3.1 | preferredHeight | 452 |
| 3.122.3.2 | preferredWidth | 452 |
| 3.122.3.3 | setSize | 453 |
| 3.122.3.4 | stretchable | 454 |
| 3.123 | YSingleChildManager< T > Class Template Reference | 454 |
| 3.123.1 | Detailed Description | 455 |
| 3.123.2 | Member Function Documentation | 456 |
| 3.123.2.1 | add | 456 |
| 3.123.2.2 | replace | 456 |
| 3.124 | YSlider Class Reference | 457 |
| 3.124.1 | Detailed Description | 458 |
| 3.124.2 | Constructor & Destructor Documentation | 458 |
| 3.124.2.1 | YSlider | 459 |

| | |
|--|-----|
| 3.124.2.2 ~YSlider | 459 |
| 3.124.3 Member Function Documentation | 459 |
| 3.124.3.1 widgetClass | 459 |
| 3.125YSliderPrivate Struct Reference | 460 |
| 3.125.1 Detailed Description | 460 |
| 3.126YSpacing Class Reference | 460 |
| 3.126.1 Detailed Description | 461 |
| 3.126.2 Constructor & Destructor Documentation | 461 |
| 3.126.2.1 YSpacing | 461 |
| 3.126.2.2 ~YSpacing | 462 |
| 3.126.3 Member Function Documentation | 462 |
| 3.126.3.1 dimension | 462 |
| 3.126.3.2 preferredHeight | 462 |
| 3.126.3.3 preferredWidth | 463 |
| 3.126.3.4 size | 463 |
| 3.126.3.5 size | 463 |
| 3.126.3.6 widgetClass | 463 |
| 3.127YSpacingPrivate Struct Reference | 464 |
| 3.127.1 Detailed Description | 464 |
| 3.128YSquash Class Reference | 464 |
| 3.128.1 Detailed Description | 466 |
| 3.128.2 Constructor & Destructor Documentation | 466 |
| 3.128.2.1 YSquash | 466 |
| 3.128.2.2 ~YSquash | 466 |
| 3.128.3 Member Function Documentation | 466 |
| 3.128.3.1 horSquash | 466 |
| 3.128.3.2 stretchable | 467 |
| 3.128.3.3 vertSquash | 467 |
| 3.128.3.4 widgetClass | 467 |
| 3.129YSquashPrivate Struct Reference | 468 |
| 3.129.1 Detailed Description | 468 |

| | |
|--|-----|
| 3.129.2 Constructor & Destructor Documentation | 468 |
| 3.129.2.1 YSquashPrivate | 468 |
| 3.130 YStringTree Class Reference | 469 |
| 3.130.1 Detailed Description | 471 |
| 3.130.2 Constructor & Destructor Documentation | 471 |
| 3.130.2.1 YStringTree | 471 |
| 3.130.2.2 ~YStringTree | 472 |
| 3.130.3 Member Function Documentation | 472 |
| 3.130.3.1 addBranch | 472 |
| 3.130.3.2 completePath | 472 |
| 3.130.3.3 logBranch | 473 |
| 3.130.3.4 logTree | 474 |
| 3.130.3.5 origPath | 474 |
| 3.130.3.6 path | 475 |
| 3.130.3.7 root | 476 |
| 3.130.3.8 setTextdomain | 476 |
| 3.130.3.9 textdomain | 476 |
| 3.130.3.10 translate | 476 |
| 3.130.3.11 translatedPath | 476 |
| 3.131 YStringWidgetID Class Reference | 477 |
| 3.131.1 Detailed Description | 478 |
| 3.131.2 Constructor & Destructor Documentation | 478 |
| 3.131.2.1 YStringWidgetID | 478 |
| 3.131.2.2 ~YStringWidgetID | 478 |
| 3.131.3 Member Function Documentation | 479 |
| 3.131.3.1 isEqual | 479 |
| 3.131.3.2 toString | 479 |
| 3.131.3.3 value | 479 |
| 3.131.3.4 valueConstRef | 479 |
| 3.132 YTable Class Reference | 480 |
| 3.132.1 Detailed Description | 482 |

| | |
|--|-----|
| 3.132.2 Constructor & Destructor Documentation | 482 |
| 3.132.2.1 YTable | 482 |
| 3.132.2.2 ~YTable | 483 |
| 3.132.3 Member Function Documentation | 483 |
| 3.132.3.1 alignment | 483 |
| 3.132.3.2 cellChanged | 484 |
| 3.132.3.3 columns | 484 |
| 3.132.3.4 getProperty | 484 |
| 3.132.3.5 hasColumn | 485 |
| 3.132.3.6 hasMultiSelection | 485 |
| 3.132.3.7 header | 486 |
| 3.132.3.8 immediateMode | 486 |
| 3.132.3.9 keepSorting | 487 |
| 3.132.3.10propertySet | 487 |
| 3.132.3.11setImmediateMode | 487 |
| 3.132.3.12setKeepSorting | 488 |
| 3.132.3.13setProperty | 488 |
| 3.132.3.14setTableHeader | 489 |
| 3.132.3.15userInputProperty | 489 |
| 3.132.3.16widgetClass | 490 |
| 3.133YTableCell Class Reference | 490 |
| 3.133.1 Detailed Description | 490 |
| 3.133.2 Constructor & Destructor Documentation | 491 |
| 3.133.2.1 YTableCell | 491 |
| 3.133.2.2 YTableCell | 491 |
| 3.133.2.3 ~YTableCell | 491 |
| 3.133.3 Member Function Documentation | 491 |
| 3.133.3.1 column | 492 |
| 3.133.3.2 hasIconName | 492 |
| 3.133.3.3 iconName | 492 |
| 3.133.3.4 itemIndex | 492 |

| | |
|--|-----|
| 3.133.3.5 label | 492 |
| 3.133.3.6 parent | 493 |
| 3.133.3.7 reparent | 493 |
| 3.133.3.8 setIconName | 493 |
| 3.133.3.9 setLabel | 493 |
| 3.134YTableHeader Class Reference | 494 |
| 3.134.1 Detailed Description | 494 |
| 3.134.2 Constructor & Destructor Documentation | 495 |
| 3.134.2.1 YTableHeader | 495 |
| 3.134.2.2 ~YTableHeader | 495 |
| 3.134.3 Member Function Documentation | 495 |
| 3.134.3.1 addColumn | 495 |
| 3.134.3.2 alignment | 495 |
| 3.134.3.3 columns | 495 |
| 3.134.3.4 hasColumn | 495 |
| 3.134.3.5 header | 495 |
| 3.135YTableHeaderPrivate Struct Reference | 496 |
| 3.135.1 Detailed Description | 496 |
| 3.136YTableItem Class Reference | 496 |
| 3.136.1 Detailed Description | 498 |
| 3.136.2 Constructor & Destructor Documentation | 498 |
| 3.136.2.1 YTableItem | 498 |
| 3.136.2.2 YTableItem | 498 |
| 3.136.2.3 ~YTableItem | 499 |
| 3.136.3 Member Function Documentation | 499 |
| 3.136.3.1 addCell | 499 |
| 3.136.3.2 addCell | 500 |
| 3.136.3.3 cell | 500 |
| 3.136.3.4 cellCount | 501 |
| 3.136.3.5 cellsBegin | 501 |
| 3.136.3.6 cellsEnd | 501 |

| | |
|--|-----|
| 3.136.3.7 deleteCells | 501 |
| 3.136.3.8 hasCell | 502 |
| 3.136.3.9 hasIconName | 502 |
| 3.136.3.10 iconName | 503 |
| 3.136.3.11 label | 503 |
| 3.136.3.12 label | 504 |
| 3.137 YTablePrivate Struct Reference | 504 |
| 3.137.1 Detailed Description | 505 |
| 3.138 YTimeField Class Reference | 505 |
| 3.138.1 Detailed Description | 506 |
| 3.138.2 Constructor & Destructor Documentation | 506 |
| 3.138.2.1 YTimeField | 507 |
| 3.138.2.2 ~YTimeField | 507 |
| 3.138.3 Member Function Documentation | 507 |
| 3.138.3.1 widgetClass | 507 |
| 3.139 YTimeFieldPrivate Struct Reference | 507 |
| 3.139.1 Detailed Description | 507 |
| 3.140 YTimeoutEvent Class Reference | 508 |
| 3.140.1 Detailed Description | 509 |
| 3.140.2 Constructor & Destructor Documentation | 509 |
| 3.140.2.1 ~YTimeoutEvent | 509 |
| 3.141 YTimezoneSelector Class Reference | 509 |
| 3.141.1 Detailed Description | 510 |
| 3.141.2 Constructor & Destructor Documentation | 510 |
| 3.141.2.1 YTimezoneSelector | 511 |
| 3.141.2.2 ~YTimezoneSelector | 511 |
| 3.141.3 Member Function Documentation | 511 |
| 3.141.3.1 currentZone | 511 |
| 3.141.3.2 getProperty | 511 |
| 3.141.3.3 propertySet | 512 |
| 3.141.3.4 setCurrentZone | 512 |

| | |
|--|-----|
| 3.141.3.5 setProperty | 512 |
| 3.141.3.6 widgetClass | 513 |
| 3.142YTimezoneSelectorPrivate Class Reference | 513 |
| 3.142.1 Detailed Description | 513 |
| 3.143YTransText Class Reference | 514 |
| 3.143.1 Detailed Description | 514 |
| 3.143.2 Constructor & Destructor Documentation | 514 |
| 3.143.2.1 YTransText | 514 |
| 3.143.2.2 YTransText | 514 |
| 3.143.2.3 YTransText | 515 |
| 3.143.3 Member Function Documentation | 515 |
| 3.143.3.1 operator< | 515 |
| 3.143.3.2 operator= | 515 |
| 3.143.3.3 operator== | 516 |
| 3.143.3.4 operator> | 516 |
| 3.143.3.5 orig | 517 |
| 3.143.3.6 setOrig | 517 |
| 3.143.3.7 setTranslation | 517 |
| 3.143.3.8 trans | 517 |
| 3.143.3.9 translation | 517 |
| 3.144YTree Class Reference | 518 |
| 3.144.1 Detailed Description | 520 |
| 3.144.2 Constructor & Destructor Documentation | 520 |
| 3.144.2.1 YTree | 520 |
| 3.144.2.2 ~YTree | 520 |
| 3.144.3 Member Function Documentation | 521 |
| 3.144.3.1 addItem | 521 |
| 3.144.3.2 currentItem | 521 |
| 3.144.3.3 getProperty | 521 |
| 3.144.3.4 hasMultiSelection | 522 |
| 3.144.3.5 immediateMode | 522 |

| | |
|--|-----|
| 3.144.3.6 propertySet | 523 |
| 3.144.3.7 rebuildTree | 523 |
| 3.144.3.8 setImmediateMode | 523 |
| 3.144.3.9 setProperty | 524 |
| 3.144.3.10userInputProperty | 525 |
| 3.144.3.11widgetClass | 525 |
| 3.145YTreeltem Class Reference | 525 |
| 3.145.1 Detailed Description | 526 |
| 3.145.2 Constructor & Destructor Documentation | 527 |
| 3.145.2.1 YTreeltem | 527 |
| 3.145.2.2 YTreeltem | 527 |
| 3.145.2.3 ~YTreeltem | 527 |
| 3.145.3 Member Function Documentation | 528 |
| 3.145.3.1 addChild | 528 |
| 3.145.3.2 childrenBegin | 528 |
| 3.145.3.3 childrenEnd | 528 |
| 3.145.3.4 deleteChildren | 528 |
| 3.145.3.5 hasChildren | 529 |
| 3.145.3.6 isOpen | 529 |
| 3.145.3.7 parent | 530 |
| 3.145.3.8 setOpen | 530 |
| 3.146YTreePrivate Struct Reference | 530 |
| 3.146.1 Detailed Description | 530 |
| 3.147YUI Class Reference | 530 |
| 3.147.1 Detailed Description | 532 |
| 3.147.2 Constructor & Destructor Documentation | 533 |
| 3.147.2.1 YUI | 533 |
| 3.147.2.2 ~YUI | 533 |
| 3.147.3 Member Function Documentation | 533 |
| 3.147.3.1 app | 533 |
| 3.147.3.2 application | 534 |

| | | |
|------------|-------------------------------|-----|
| 3.147.3.3 | blockEvents | 534 |
| 3.147.3.4 | builtinCaller | 534 |
| 3.147.3.5 | createApplication | 535 |
| 3.147.3.6 | createOptionalWidgetFactory | 535 |
| 3.147.3.7 | createUIThread | 535 |
| 3.147.3.8 | createWidgetFactory | 535 |
| 3.147.3.9 | deleteNotify | 535 |
| 3.147.3.10 | ensureUICreated | 535 |
| 3.147.3.11 | eventsBlocked | 536 |
| 3.147.3.12 | idleLoop | 536 |
| 3.147.3.13 | optionalWidgetFactory | 536 |
| 3.147.3.14 | runningWithThreads | 537 |
| 3.147.3.15 | runPkgSelection | 537 |
| 3.147.3.16 | setBuiltinCaller | 537 |
| 3.147.3.17 | setButtonOrderFromEnvironment | 537 |
| 3.147.3.18 | shutdownThreads | 538 |
| 3.147.3.19 | signalUIThread | 538 |
| 3.147.3.20 | signalYCPThread | 539 |
| 3.147.3.21 | terminateUIThread | 539 |
| 3.147.3.22 | topmostConstructorHasFinished | 539 |
| 3.147.3.23 | ui | 540 |
| 3.147.3.24 | uiThreadDestructor | 540 |
| 3.147.3.25 | uiThreadMainLoop | 540 |
| 3.147.3.26 | unblockEvents | 541 |
| 3.147.3.27 | waitForUIThread | 541 |
| 3.147.3.28 | waitForYCPThread | 542 |
| 3.147.3.29 | widgetFactory | 542 |
| 3.147.4 | Member Data Documentation | 542 |
| 3.147.4.1 | _builtinCaller | 542 |
| 3.147.4.2 | _eventsBlocked | 542 |
| 3.147.4.3 | _terminate_ui_thread | 543 |

| | |
|--|-----|
| 3.147.4.4 _uiThread | 543 |
| 3.147.4.5 _withThreads | 543 |
| 3.147.4.6 pipe_from_ui | 543 |
| 3.147.4.7 pipe_to_ui | 543 |
| 3.148YUIBadPropertyArgException Class Reference | 544 |
| 3.148.1 Detailed Description | 545 |
| 3.148.2 Member Function Documentation | 545 |
| 3.148.2.1 dumpOn | 545 |
| 3.149YUIButtonRoleMismatchException Class Reference | 546 |
| 3.149.1 Detailed Description | 547 |
| 3.150YUICantLoadAnyUIException Class Reference | 547 |
| 3.150.1 Detailed Description | 548 |
| 3.151YUIDialogStackingOrderException Class Reference | 549 |
| 3.151.1 Detailed Description | 549 |
| 3.152YUIException Class Reference | 550 |
| 3.152.1 Detailed Description | 551 |
| 3.152.2 Constructor & Destructor Documentation | 551 |
| 3.152.2.1 YUIException | 551 |
| 3.152.2.2 YUIException | 552 |
| 3.152.2.3 ~YUIException | 552 |
| 3.152.3 Member Function Documentation | 552 |
| 3.152.3.1 asString | 552 |
| 3.152.3.2 dumpOn | 552 |
| 3.152.3.3 log | 553 |
| 3.152.3.4 msg | 553 |
| 3.152.3.5 relocate | 553 |
| 3.152.3.6 setMsg | 553 |
| 3.152.3.7 strErrno | 554 |
| 3.152.3.8 strErrno | 554 |
| 3.152.3.9 what | 554 |
| 3.152.3.10where | 555 |

| | |
|---|-----|
| 3.152.4 Friends And Related Function Documentation | 555 |
| 3.152.4.1 operator<< | 555 |
| 3.153YUIIndexOutOfRangeException Class Reference | 555 |
| 3.153.1 Detailed Description | 556 |
| 3.153.2 Constructor & Destructor Documentation | 556 |
| 3.153.2.1 YUIIndexOutOfRangeException | 556 |
| 3.153.3 Member Function Documentation | 557 |
| 3.153.3.1 dumpOn | 557 |
| 3.153.3.2 invalidIndex | 557 |
| 3.153.3.3 validMax | 557 |
| 3.153.3.4 validMin | 557 |
| 3.154YUIInvalidChildException< YWidget > Class Template Reference | 558 |
| 3.154.1 Detailed Description | 559 |
| 3.154.2 Member Function Documentation | 559 |
| 3.154.2.1 child | 559 |
| 3.154.2.2 container | 559 |
| 3.154.2.3 dumpOn | 560 |
| 3.155YUIInvalidDimensionException Class Reference | 560 |
| 3.155.1 Detailed Description | 561 |
| 3.156YUIInvalidWidgetException Class Reference | 562 |
| 3.156.1 Detailed Description | 562 |
| 3.157YUILoader Class Reference | 563 |
| 3.157.1 Detailed Description | 563 |
| 3.157.2 Member Function Documentation | 563 |
| 3.157.2.1 loadPlugin | 563 |
| 3.157.2.2 loadUI | 563 |
| 3.158YUILogBuffer Class Reference | 564 |
| 3.158.1 Detailed Description | 564 |
| 3.158.2 Constructor & Destructor Documentation | 565 |
| 3.158.2.1 YUILogBuffer | 565 |
| 3.158.2.2 ~YUILogBuffer | 565 |

| | |
|--|-----|
| 3.158.3 Member Function Documentation | 565 |
| 3.158.3.1 flush | 565 |
| 3.158.3.2 overflow | 566 |
| 3.158.3.3 writeBuffer | 566 |
| 3.158.3.4 xsputn | 566 |
| 3.159YUILogPrivate Struct Reference | 567 |
| 3.159.1 Detailed Description | 567 |
| 3.159.2 Constructor & Destructor Documentation | 568 |
| 3.159.2.1 YUILogPrivate | 568 |
| 3.159.2.2 ~YUILogPrivate | 568 |
| 3.159.3 Member Function Documentation | 568 |
| 3.159.3.1 findCurrentThread | 568 |
| 3.160YUINoDialogException Class Reference | 569 |
| 3.160.1 Detailed Description | 569 |
| 3.161YUINullPointerException Class Reference | 570 |
| 3.161.1 Detailed Description | 570 |
| 3.162YUIOutOfMemoryException Class Reference | 571 |
| 3.162.1 Detailed Description | 571 |
| 3.163YUIPlugin Class Reference | 572 |
| 3.163.1 Detailed Description | 573 |
| 3.163.2 Constructor & Destructor Documentation | 573 |
| 3.163.2.1 YUIPlugin | 573 |
| 3.163.2.2 ~YUIPlugin | 573 |
| 3.163.3 Member Function Documentation | 573 |
| 3.163.3.1 error | 573 |
| 3.163.3.2 errorMsg | 574 |
| 3.163.3.3 locateSymbol | 574 |
| 3.163.3.4 pluginLibBaseName | 574 |
| 3.163.3.5 pluginLibFullPath | 574 |
| 3.163.3.6 pluginLibHandle | 575 |
| 3.163.3.7 success | 575 |

| | |
|--|-----|
| 3.163.3.8 unload | 575 |
| 3.164YUIPluginException Class Reference | 575 |
| 3.164.1 Detailed Description | 576 |
| 3.165YUIPropertyException Class Reference | 577 |
| 3.165.1 Detailed Description | 578 |
| 3.165.2 Member Function Documentation | 578 |
| 3.165.2.1 dumpOn | 578 |
| 3.165.2.2 property | 578 |
| 3.165.2.3 setWidget | 578 |
| 3.165.2.4 widget | 578 |
| 3.166YUIPropertyTypeMismatchException Class Reference | 579 |
| 3.166.1 Detailed Description | 580 |
| 3.166.2 Member Function Documentation | 580 |
| 3.166.2.1 dumpOn | 581 |
| 3.166.2.2 type | 581 |
| 3.167YUISetReadOnlyPropertyException Class Reference | 581 |
| 3.167.1 Detailed Description | 583 |
| 3.167.2 Member Function Documentation | 583 |
| 3.167.2.1 dumpOn | 583 |
| 3.168YUISyntaxErrorException Class Reference | 584 |
| 3.168.1 Detailed Description | 584 |
| 3.169YUITerminator Class Reference | 585 |
| 3.169.1 Detailed Description | 585 |
| 3.169.2 Constructor & Destructor Documentation | 585 |
| 3.169.2.1 ~YUITerminator | 585 |
| 3.170YUITooManyChildrenException< YWidget > Class Template Reference | 585 |
| 3.170.1 Detailed Description | 587 |
| 3.170.2 Member Function Documentation | 587 |
| 3.170.2.1 container | 587 |
| 3.170.2.2 dumpOn | 587 |
| 3.171YUIUnknownPropertyException Class Reference | 588 |

| | |
|--|-----|
| 3.171.1 Detailed Description | 589 |
| 3.171.2 Member Function Documentation | 589 |
| 3.171.2.1 dumpOn | 590 |
| 3.172YUIUnsupportedWidgetException Class Reference | 590 |
| 3.172.1 Detailed Description | 591 |
| 3.173YUIWidgetNotFoundException Class Reference | 592 |
| 3.173.1 Detailed Description | 593 |
| 3.174YWidget Class Reference | 593 |
| 3.174.1 Detailed Description | 596 |
| 3.174.2 Constructor & Destructor Documentation | 597 |
| 3.174.2.1 YWidget | 597 |
| 3.174.2.2 ~YWidget | 597 |
| 3.174.3 Member Function Documentation | 598 |
| 3.174.3.1 addChild | 598 |
| 3.174.3.2 autoShortcut | 598 |
| 3.174.3.3 beingDestroyed | 598 |
| 3.174.3.4 childrenBegin | 598 |
| 3.174.3.5 childrenCount | 599 |
| 3.174.3.6 childrenEnd | 599 |
| 3.174.3.7 childrenManager | 600 |
| 3.174.3.8 contains | 600 |
| 3.174.3.9 debugLabel | 601 |
| 3.174.3.10deleteChildren | 601 |
| 3.174.3.11dumpDialogWidgetTree | 602 |
| 3.174.3.12dumpWidget | 602 |
| 3.174.3.13dumpWidgetTree | 602 |
| 3.174.3.14findDialog | 603 |
| 3.174.3.15findWidget | 603 |
| 3.174.3.16firstChild | 604 |
| 3.174.3.17functionKey | 604 |
| 3.174.3.18getProperty | 605 |

| | |
|---------------------------------|-----|
| 3.174.3.19hasChildren | 605 |
| 3.174.3.20hasFunctionKey | 606 |
| 3.174.3.21hasId | 606 |
| 3.174.3.22hasParent | 606 |
| 3.174.3.23hasWeight | 606 |
| 3.174.3.24helpText | 607 |
| 3.174.3.25id | 607 |
| 3.174.3.26isEnabled | 607 |
| 3.174.3.27isValid | 607 |
| 3.174.3.28lastChild | 607 |
| 3.174.3.29notify | 608 |
| 3.174.3.30notifyContextMenu | 608 |
| 3.174.3.31operator new | 608 |
| 3.174.3.32parent | 608 |
| 3.174.3.33preferredHeight | 609 |
| 3.174.3.34preferredSize | 609 |
| 3.174.3.35preferredWidth | 609 |
| 3.174.3.36propertySet | 610 |
| 3.174.3.37removeChild | 611 |
| 3.174.3.38saveUserInput | 611 |
| 3.174.3.39sendKeyEvents | 612 |
| 3.174.3.40setAutoShortcut | 612 |
| 3.174.3.41setBeingDestroyed | 612 |
| 3.174.3.42setChildrenEnabled | 612 |
| 3.174.3.43setChildrenManager | 613 |
| 3.174.3.44setDefaultStretchable | 613 |
| 3.174.3.45setDisabled | 613 |
| 3.174.3.46setEnabled | 614 |
| 3.174.3.47setFunctionKey | 614 |
| 3.174.3.48setHelpText | 614 |
| 3.174.3.49setId | 615 |

| | | |
|------------|--|-----|
| 3.174.3.50 | setKeyboardFocus | 615 |
| 3.174.3.51 | setNotify | 615 |
| 3.174.3.52 | setNotifyContextMenu | 616 |
| 3.174.3.53 | setParent | 616 |
| 3.174.3.54 | setProperty | 617 |
| 3.174.3.55 | setSendKeyEvents | 618 |
| 3.174.3.56 | setShortcutString | 618 |
| 3.174.3.57 | setSize | 619 |
| 3.174.3.58 | setStretchable | 619 |
| 3.174.3.59 | setWeight | 619 |
| 3.174.3.60 | setWidgetRep | 620 |
| 3.174.3.61 | shortcutString | 620 |
| 3.174.3.62 | startMultipleChanges | 620 |
| 3.174.3.63 | stretchable | 621 |
| 3.174.3.64 | userInputProperty | 621 |
| 3.174.3.65 | weight | 621 |
| 3.174.3.66 | widgetClass | 621 |
| 3.174.3.67 | widgetRep | 622 |
| 3.175 | YWidgetEvent Class Reference | 622 |
| 3.175.1 | Detailed Description | 623 |
| 3.175.2 | Constructor & Destructor Documentation | 623 |
| 3.175.2.1 | YWidgetEvent | 624 |
| 3.175.2.2 | ~YWidgetEvent | 624 |
| 3.175.3 | Member Function Documentation | 624 |
| 3.175.3.1 | reason | 624 |
| 3.175.3.2 | widget | 624 |
| 3.176 | YWidgetFactory Class Reference | 625 |
| 3.176.1 | Detailed Description | 627 |
| 3.176.2 | Constructor & Destructor Documentation | 627 |
| 3.176.2.1 | YWidgetFactory | 627 |
| 3.176.2.2 | ~YWidgetFactory | 628 |

| | |
|--|-----|
| 3.177YWidgetID Class Reference | 628 |
| 3.177.1 Detailed Description | 629 |
| 3.177.2 Constructor & Destructor Documentation | 629 |
| 3.177.2.1 YWidgetID | 629 |
| 3.177.2.2 ~YWidgetID | 629 |
| 3.177.3 Member Function Documentation | 629 |
| 3.177.3.1 isEqual | 629 |
| 3.177.3.2 toString | 629 |
| 3.178YWidgetPrivate Struct Reference | 630 |
| 3.178.1 Detailed Description | 630 |
| 3.178.2 Constructor & Destructor Documentation | 631 |
| 3.178.2.1 YWidgetPrivate | 631 |
| 3.179YWidgetTreeItem Class Reference | 631 |
| 3.179.1 Detailed Description | 632 |
| 3.180YWizard Class Reference | 633 |
| 3.180.1 Detailed Description | 635 |
| 3.180.2 Constructor & Destructor Documentation | 635 |
| 3.180.2.1 YWizard | 635 |
| 3.180.2.2 ~YWizard | 636 |
| 3.180.3 Member Function Documentation | 636 |
| 3.180.3.1 addMenu | 636 |
| 3.180.3.2 addMenuEntry | 636 |
| 3.180.3.3 addMenuSeparator | 636 |
| 3.180.3.4 addStep | 637 |
| 3.180.3.5 addStepHeading | 637 |
| 3.180.3.6 addSubMenu | 637 |
| 3.180.3.7 addTreeItem | 637 |
| 3.180.3.8 backButton | 637 |
| 3.180.3.9 contentsReplacePoint | 637 |
| 3.180.3.10currentTreeSelection | 637 |
| 3.180.3.11deleteMenus | 638 |

| | |
|--------------------------------------|-----|
| 3.180.3.12deleteSteps | 638 |
| 3.180.3.13deleteTreeItems | 638 |
| 3.180.3.14getProperty | 638 |
| 3.180.3.15hideReleaseNotesButton | 638 |
| 3.180.3.16nextButtonIsProtected | 639 |
| 3.180.3.17ping | 639 |
| 3.180.3.18propertySet | 639 |
| 3.180.3.19protectNextButton | 639 |
| 3.180.3.20retranslateInternalButtons | 639 |
| 3.180.3.21selectTreeItem | 640 |
| 3.180.3.22setButtonLabel | 640 |
| 3.180.3.23setCurrentStep | 640 |
| 3.180.3.24setDialogHeading | 640 |
| 3.180.3.25setDialogIcon | 641 |
| 3.180.3.26setDialogTitle | 641 |
| 3.180.3.27setHelpText | 641 |
| 3.180.3.28showReleaseNotesButton | 641 |
| 3.180.3.29updateSteps | 641 |
| 3.180.3.30widgetClass | 641 |
| 3.180.3.31wizardMode | 641 |
| 3.181YWizardPrivate Struct Reference | 642 |
| 3.181.1 Detailed Description | 642 |

Chapter 1

Class Index

1.1 Class Hierarchy

This inheritance list is sorted roughly, but not completely, alphabetically:

| | |
|-------------------------------------|-----|
| FSize | 13 |
| noncopyable | 21 |
| ImplPtr< _Impl > | 18 |
| OptimizeChanges | 22 |
| YWidget::OptimizeChanges | 22 |
| Treeltem< PAYLOAD > | 26 |
| SortedTreeltem< PAYLOAD > | 23 |
| YAlignmentPrivate | 41 |
| YApplicationPrivate | 42 |
| YBarGraphMultiUpdate | 49 |
| YBarGraphPrivate | 51 |
| YBarGraphSegment | 51 |
| YBothDim< T > | 54 |
| YBuiltinCaller | 56 |
| YBusyIndicatorPrivate | 63 |
| YButtonBoxLayoutPolicy | 77 |
| YButtonBoxMargins | 77 |
| YButtonBoxPrivate | 78 |
| YCheckBoxFramePrivate | 97 |
| YCheckBoxPrivate | 98 |
| YChildrenManager< T > | 98 |
| YChildrenRejector< T > | 103 |
| YSingleChildManager< T > | 454 |
| YCodeLocation | 105 |

| | |
|--------------------------------------|-----|
| YColor | 107 |
| YComboBoxPrivate | 119 |
| YCommandLine | 119 |
| YCommandLinePrivate | 123 |
| YContextMenuPrivate | 132 |
| YDateFieldPrivate | 135 |
| YDialogPrivate | 154 |
| YDialogSpy | 155 |
| YDialogSpyPrivate | 161 |
| YDownloadProgressPrivate | 169 |
| YDumbTabPrivate | 177 |
| YEmptyPrivate | 180 |
| YEnvVar | 180 |
| YEvent | 182 |
| YCancelEvent | 79 |
| YDebugEvent | 135 |
| YKeyEvent | 243 |
| YMenuEvent | 294 |
| YTimeoutEvent | 508 |
| YWidgetEvent | 622 |
| YEventFilter | 186 |
| YHelpButtonHandler | 206 |
| YEventFilterPrivate | 190 |
| YFramePrivate | 196 |
| YGraphPrivate | 205 |
| YIconLoader | 208 |
| YImagePrivate | 214 |
| YInputFieldPrivate | 224 |
| YIntFieldPrivate | 234 |
| YItem | 235 |
| YTableItem | 496 |
| YTreeItem | 525 |
| YMenuItem | 296 |
| YWidgetTreeItem | 631 |
| YLabelPrivate | 252 |
| YLayoutBoxPrivate | 267 |
| YLogViewPrivate | 276 |
| YMacro | 277 |
| YMacroPlayer | 282 |
| YMacroRecorder | 283 |
| YMenuButtonPrivate | 293 |
| YMultiLineEditPrivate | 306 |
| YMultiProgressMeterPrivate | 313 |
| YMultiSelectionBoxPrivate | 319 |
| YOptionalWidgetFactory | 320 |

| | |
|---|-----|
| YPartitionSplitterPrivate | 332 |
| YPath | 333 |
| YPerThreadLogInfo | 335 |
| YProgressBarPrivate | 342 |
| YProperty | 342 |
| YPropertySet | 344 |
| YPropertyValue | 349 |
| YPushButtonPrivate | 360 |
| YRadioButtonGroupPrivate | 376 |
| YRadioButtonPrivate | 377 |
| YRichTextPrivate | 388 |
| YSelectionBoxPrivate | 399 |
| YSelectionWidgetPrivate | 418 |
| YSettings | 418 |
| YShortcut | 420 |
| YItemShortcut | 240 |
| YShortcutManager | 431 |
| YSimpleEventHandler | 438 |
| YSimpleInputFieldPrivate | 449 |
| YSliderPrivate | 460 |
| YSpacingPrivate | 464 |
| YSquashPrivate | 468 |
| YStringTree | 469 |
| YRpmGroupsTree | 389 |
| YTableCell | 490 |
| YTableHeader | 494 |
| YTableHeaderPrivate | 496 |
| YTablePrivate | 504 |
| YTimeFieldPrivate | 507 |
| YTimezoneSelectorPrivate | 513 |
| YTransText | 514 |
| YTreePrivate | 530 |
| YUI | 530 |
| YUIException | 550 |
| YUIButtonRoleMismatchException | 546 |
| YUICantLoadAnyUIException | 547 |
| YUIDialogStackingOrderException | 549 |
| YUIIndexOutOfRangeException | 555 |
| YUIInvalidChildException< YWidget > | 558 |
| YUIInvalidDimensionException | 560 |
| YUIInvalidWidgetException | 562 |
| YUINoDialogException | 569 |
| YUINullPointerException | 570 |
| YUIOutOfMemoryException | 571 |
| YUIPluginException | 575 |

| | |
|--|-----|
| YUIPropertyException | 577 |
| YUIBadPropertyArgException | 544 |
| YUIPropertyTypeMismatchException | 579 |
| YUISetReadOnlyPropertyException | 581 |
| YUIUnknownPropertyException | 588 |
| YUISyntaxErrorException | 584 |
| YUITooManyChildrenException< YWidget > | 585 |
| YUIUnsupportedWidgetException | 590 |
| YUIWidgetNotFoundException | 592 |
| YUILoader | 563 |
| YUILogBuffer | 564 |
| YUILogPrivate | 567 |
| YUIPlugin | 572 |
| YGraphPlugin | 203 |
| YPackageSelectorPlugin | 325 |
| YUITerminator | 585 |
| YWidget | 593 |
| YBarGraph | 43 |
| YBusyIndicator | 58 |
| YButtonBox | 64 |
| YCheckBox | 81 |
| YDownloadProgress | 162 |
| YEmpty | 178 |
| YGraph | 196 |
| YImage | 209 |
| YInputField | 215 |
| YIntField | 225 |
| YSlider | 457 |
| YLabel | 245 |
| YLayoutBox | 253 |
| YLogView | 268 |
| YMultiLineEdit | 299 |
| YMultiProgressMeter | 306 |
| YPackageSelector | 322 |
| YPartitionSplitter | 327 |
| YProgressBar | 337 |
| YPushButton | 351 |
| YRadioButton | 361 |
| YRichText | 381 |
| YSelectionWidget | 400 |
| YComboBox | 108 |
| YContextMenu | 124 |
| YDumbTab | 170 |
| YMenuButton | 285 |
| YMultiSelectionBox | 314 |

| | |
|---------------------------------------|-----|
| YSelectionBox | 393 |
| YTable | 480 |
| YTree | 518 |
| YSimpleInputField | 443 |
| YDateField | 132 |
| YTimeField | 505 |
| YSingleChildContainerWidget | 450 |
| YAlignment | 31 |
| YCheckBoxFrame | 89 |
| YDialog | 137 |
| YFrame | 191 |
| YRadioButtonGroup | 370 |
| YReplacePoint | 378 |
| YSquash | 464 |
| YSpacing | 460 |
| YTimezoneSelector | 509 |
| YWizard | 633 |
| YWidgetFactory | 625 |
| YWidgetID | 628 |
| YStringWidgetID | 477 |
| YWidgetPrivate | 630 |
| YWizardPrivate | 642 |

Chapter 2

Class Index

2.1 Class List

Here are the classes, structs, unions and interfaces with brief descriptions:

| | |
|---------------------------|----|
| FSize | 13 |
| ImplPtr< _Impl > | 18 |
| noncopyable | 21 |
| OptimizeChanges | 22 |
| YWidget::OptimizeChanges | 22 |
| SortedTreeItem< PAYLOAD > | 23 |
| TreeItem< PAYLOAD > | 26 |
| YAlignment | 31 |
| YAlignmentPrivate | 41 |
| YApplicationPrivate | 42 |
| YBarGraph | 43 |
| YBarGraphMultiUpdate | 49 |
| YBarGraphPrivate | 51 |
| YBarGraphSegment | 51 |
| YBothDim< T > | 54 |
| YBuiltinCaller | 56 |
| YBusyIndicator | 58 |
| YBusyIndicatorPrivate | 63 |
| YButtonBox | 64 |
| YButtonBoxLayoutPolicy | 77 |
| YButtonBoxMargins | 77 |
| YButtonBoxPrivate | 78 |
| YCancelEvent | 79 |
| YCheckBox | 81 |
| YCheckBoxFrame | 89 |

| | |
|--|-----|
| YCheckBoxFramePrivate | 97 |
| YCheckBoxPrivate | 98 |
| YChildrenManager< T > | 98 |
| YChildrenRejector< T > | 103 |
| YCodeLocation | 105 |
| YColor | 107 |
| YComboBox | 108 |
| YComboBoxPrivate | 119 |
| YCommandLine | 119 |
| YCommandLinePrivate | 123 |
| YContextMenu | 124 |
| YContextMenuPrivate | 132 |
| YDateField | 132 |
| YDateFieldPrivate | 135 |
| YDebugEvent | 135 |
| YDialog | 137 |
| YDialogPrivate | 154 |
| YDialogSpy | 155 |
| YDialogSpyPrivate | 161 |
| YDownloadProgress | 162 |
| YDownloadProgressPrivate | 169 |
| YDumbTab | 170 |
| YDumbTabPrivate | 177 |
| YEmpty | 178 |
| YEmptyPrivate | 180 |
| YEnvVar | 180 |
| YEvent | 182 |
| YEventFilter | 186 |
| YEventFilterPrivate | 190 |
| YFrame | 191 |
| YFramePrivate | 196 |
| YGraph | 196 |
| YGraphPlugin | 203 |
| YGraphPrivate | 205 |
| YHelpButtonHandler | 206 |
| YIconLoader | 208 |
| YImage | 209 |
| YImagePrivate | 214 |
| YInputField | 215 |
| YInputFieldPrivate | 224 |
| YIntField | 225 |
| YIntFieldPrivate | 234 |
| YItem | 235 |
| YItemShortcut | 240 |
| YKeyEvent | 243 |
| YLabel | 245 |

| | |
|----------------------------|-----|
| YLabelPrivate | 252 |
| YLayoutBox | 253 |
| YLayoutBoxPrivate | 267 |
| YLogView | 268 |
| YLogViewPrivate | 276 |
| YMacro | 277 |
| YMacroPlayer | 282 |
| YMacroRecorder | 283 |
| YMenuButton | 285 |
| YMenuButtonPrivate | 293 |
| YMenuEvent | 294 |
| YMenuItem | 296 |
| YMultiLineEdit | 299 |
| YMultiLineEditPrivate | 306 |
| YMultiProgressMeter | 306 |
| YMultiProgressMeterPrivate | 313 |
| YMultiSelectionBox | 314 |
| YMultiSelectionBoxPrivate | 319 |
| YOptionalWidgetFactory | 320 |
| YPackageSelector | 322 |
| YPackageSelectorPlugin | 325 |
| YPartitionSplitter | 327 |
| YPartitionSplitterPrivate | 332 |
| YPath | 333 |
| YPerThreadLogInfo | 335 |
| YProgressBar | 337 |
| YProgressBarPrivate | 342 |
| YProperty | 342 |
| YPropertySet | 344 |
| YPropertyValue | 349 |
| YPushButton | 351 |
| YPushButtonPrivate | 360 |
| YRadioButton | 361 |
| YRadioButtonGroup | 370 |
| YRadioButtonGroupPrivate | 376 |
| YRadioButtonPrivate | 377 |
| YReplacePoint | 378 |
| YRichText | 381 |
| YRichTextPrivate | 388 |
| YRpmGroupsTree | 389 |
| YSelectionBox | 393 |
| YSelectionBoxPrivate | 399 |
| YSelectionWidget | 400 |
| YSelectionWidgetPrivate | 418 |
| YSettings | 418 |
| YShortcut | 420 |

| | |
|-------------------------------------|-----|
| YShortcutManager | 431 |
| YSimpleEventHandler | 438 |
| YSimpleInputField | 443 |
| YSimpleInputFieldPrivate | 449 |
| YSingleChildContainerWidget | 450 |
| YSingleChildManager< T > | 454 |
| YSlider | 457 |
| YSliderPrivate | 460 |
| YSpacing | 460 |
| YSpacingPrivate | 464 |
| YSquash | 464 |
| YSquashPrivate | 468 |
| YStringTree | 469 |
| YStringWidgetID | 477 |
| YTable | 480 |
| YTableCell | 490 |
| YTableHeader | 494 |
| YTableHeaderPrivate | 496 |
| YTableItem | 496 |
| YTablePrivate | 504 |
| YTimeField | 505 |
| YTimeFieldPrivate | 507 |
| YTimeoutEvent | 508 |
| YTimezoneSelector | 509 |
| YTimezoneSelectorPrivate | 513 |
| YTransText | 514 |
| YTree | 518 |
| YTreeItem | 525 |
| YTreePrivate | 530 |
| YUI | 530 |
| YUIBadPropertyArgException | 544 |
| YUIButtonRoleMismatchException | 546 |
| YUICantLoadAnyUIException | 547 |
| YUIDialogStackingOrderException | 549 |
| YUIException | 550 |
| YUIIndexOutOfRangeException | 555 |
| YUIInvalidChildException< YWidget > | 558 |
| YUIInvalidDimensionException | 560 |
| YUIInvalidWidgetException | 562 |
| YUILoader | 563 |
| YUILogBuffer | 564 |
| YUILogPrivate | 567 |
| YUINoDialogException | 569 |
| YUINullPointerException | 570 |
| YUIOutOfMemoryException | 571 |
| YUIPlugin | 572 |

| | |
|--|-----|
| YUIPluginException | 575 |
| YUIPropertyException | 577 |
| YUIPropertyTypeMismatchException | 579 |
| YUISetReadOnlyPropertyException | 581 |
| YUISyntaxErrorException | 584 |
| YUITerminator | 585 |
| YUITooManyChildrenException< YWidget > | 585 |
| YUIUnknownPropertyException | 588 |
| YUIUnsupportedWidgetException | 590 |
| YUIWidgetNotFoundException | 592 |
| YWidget | 593 |
| YWidgetEvent | 622 |
| YWidgetFactory | 625 |
| YWidgetID | 628 |
| YWidgetPrivate | 630 |
| YWidgetTreeItem | 631 |
| YWizard | 633 |
| YWizardPrivate | 642 |

Chapter 3

Class Documentation

3.1 FSize Class Reference

```
#include <FSize.h>
```

Public Types

- enum **Unit** { **B** = 0, **K**, **M**, **G**, **T** }

Public Member Functions

- **FSize** (const long long size_r=0)
- **FSize** (const long long size_r, const **Unit** unit_r)
- **FSize** (const std::string &sizeStr, const **Unit** unit_r=B)
- **operator long long** () const
- **FSize** & **operator+=** (const long long rhs)
- **FSize** & **operator-=** (const long long rhs)
- **FSize** & **operator*=** (const long long rhs)
- **FSize** & **operator/=** (const long long rhs)
- **FSize** & **operator++** ()
- **FSize** & **operator--** ()
- **FSize** **operator++** (int)
- **FSize** **operator--** (int)
- **FSize** & **fillBlock** (**FSize** blocksize_r=KB)
- **FSize** **fullBlock** (**FSize** blocksize_r=KB) const
- long long **operator()** (const **Unit** unit_r) const
- **Unit** **bestUnit** () const

- `std::string form (const Unit unit_r, unsigned fw=0, unsigned prec=bestPrec, const bool showunit=true) const`
- `std::string form (unsigned fw=0, unsigned prec=bestPrec, const bool showunit=true) const`
- `std::string asString () const`

Static Public Member Functions

- `static long long factor (const Unit unit_r)`
- `static const char * unit (const Unit unit_r)`

Static Public Attributes

- `static const long long KB = 1024`
- `static const long long MB = 1024 * KB`
- `static const long long GB = 1024 * MB`
- `static const long long TB = 1024 * GB`
- `static const unsigned bestPrec = (unsigned)-1`

3.1.1 Detailed Description

Store and operate on (file/package/partition) sizes (long long).

Definition at line 39 of file [FSize.h](#).

3.1.2 Member Enumeration Documentation

3.1.2.1 enum `FSize::Unit`

The Units

Definition at line 46 of file [FSize.h](#).

3.1.3 Constructor & Destructor Documentation

3.1.3.1 `FSize::FSize (const long long size_r = 0)` `[inline]`

Construct from size in Byte.

Definition at line 95 of file [FSize.h](#).

3.1.3.2 FSize::FSize (const long long *size_r*, const Unit *unit_r*) [inline]

Construct from size in certain unit. E.g. `FSize(1, FSize::K)` makes 1024 Byte.

Definition at line 103 of file [FSize.h](#).

3.1.3.3 FSize::FSize (const std::string & *sizeStr*, const Unit *unit_r* = B)

Construct from string containing a number in given unit.

Definition at line 34 of file [FSize.cc](#).


3.1.4 Member Function Documentation

3.1.4.1 std::string FSize::asString () const

Default string representation (precision 1 and unit appended).

Definition at line 122 of file [FSize.cc](#).

Here is the call graph for this function:



3.1.4.2 FSize::Unit FSize::bestUnit () const

Return the best unit for string representation.

Definition at line 66 of file [FSize.cc](#).

3.1.4.3 static long long FSize::factor (const Unit *unit_r*) [inline, static]

Return ammount of Byte in Unit.

Definition at line 65 of file [FSize.h](#).

3.1.4.4 FSize & FSize::fillBlock (FSize *blocksize_r* = KB)

Adjust size to multiple of *blocksize_r*

Definition at line 46 of file [FSize.cc](#).


3.1.4.5 std::string FSize::form (const Unit *unit_r*, unsigned *fw* = 0, unsigned *prec* = *bestPrec*, const bool *showunit* = true) const

Return string representation in given Unit. Parameter *fw* and *prec* denote field width and precision as in a "%*.*f" printf format string. Avalue of *bestPrec* automatically picks an appropriate precision depending on the unit. If *showunit* ist true, the string representaion of Unit is *appendedseparated by a single blank*.

*If Unit is **Byte**, precision is set to zero.*

Definition at line 87 of file [FSize.cc](#).

Here is the call graph for this function:




3.1.4.6 std::string FSize::form (unsigned *fw* = 0, unsigned *prec* = *bestPrec*, const bool *showunit* = true) const [inline]

Return string representation in *bestUnit*.

Definition at line 169 of file [FSize.h](#).

Here is the call graph for this function:



3.1.4.7 FSize FSize::fullBlock (FSize *blocksize_r* = KB) const [inline]

Return size adjusted to multiple of `blocksize_r`

Definition at line 136 of file [FSize.h](#).

Here is the call graph for this function:



3.1.4.8 FSize::operator long long () const [inline]

Conversion to long long

Definition at line 115 of file [FSize.h](#).

3.1.4.9 long long FSize::operator() (const Unit *unit_r*) const [inline]

Return size in Unit (not rounded)

Definition at line 141 of file [FSize.h](#).

Here is the call graph for this function:



3.1.4.10 `static const char* FSize::unit (const Unit unit_r)` `[inline, static]`

String representation of Unit.

Definition at line 79 of file [FSize.h](#).

3.1.5 Member Data Documentation

3.1.5.1 `const unsigned FSize::bestPrec = (unsigned)-1` `[static]`

Used as precision argument to [form\(\)](#), the 'best' precision according to Unist is chosen.

Definition at line 152 of file [FSize.h](#).


The documentation for this class was generated from the following files:

- `/usr/src/RPM/BUILD/libyui-3.0.10/src/FSize.h`
- `/usr/src/RPM/BUILD/libyui-3.0.10/src/FSize.cc`


3.2 ImplPtr< _Impl > Class Template Reference

```
#include <ImplPtr.h>
```

Inheritance diagram for `ImplPtr<_Impl>`:



Collaboration diagram for `ImplPtr<_Impl>`:



Public Types

- `typedef _Impl element_type`

Public Member Functions

- `ImplPtr` (`_Impl *impl_r=0`)
- `void reset` (`_Impl *impl_r=0`)
- `void swap` (`ImplPtr rhs`)

- **operator bool** () const
- const _Impl & **operator*** () const
- const _Impl * **operator->** () const
- const _Impl * **get** () const
- _Impl & **operator*** ()
- _Impl * **operator->** ()
- _Impl * **get** ()

3.2.1 Detailed Description

```
template<class _Impl>class ImplPtr< _Impl >
```

Helper template class for implementation pointers (pointers to a private class or structure that hold the member variables of a higher-level class that is part of a public API).

This pointer class maintains constness of its parent class, i.e. if it is used in a const class the class this pointer points to will also be const.

This class automatically deletes the class it points to in its destructor.


Definition at line 42 of file [ImplPtr.h](#).

The documentation for this class was generated from the following file:

- /usr/src/RPM/BUILD/libyui-3.0.10/src/ImplPtr.h

3.3 noncopyable Class Reference

Inheritance diagram for noncopyable:



The documentation for this class was generated from the following file:

- `/usr/src/RPM/BUILD/libyui-3.0.10/src/ImplPtr.h`

3.4 OptimizeChanges Class Reference

```
#include <YWidget_OptimizeChanges.h>
```

Public Member Functions

- **OptimizeChanges** ([YWidget](#) &w)

3.4.1 Detailed Description

Helper class that calls `startMultipleChanges()` in its constructor and cares about the necessary call to `doneMultipleChanges()` when it goes out of scope.

Definition at line 44 of file [YWidget_OptimizeChanges.h](#).

The documentation for this class was generated from the following file:

- `/usr/src/RPM/BUILD/libyui-3.0.10/src/YWidget_OptimizeChanges.h`

3.5 YWidget::OptimizeChanges Class Reference

```
#include <YWidget.h>
```

Public Member Functions

- **OptimizeChanges** ([YWidget](#) &w)

3.5.1 Detailed Description

Helper class that calls [startMultipleChanges\(\)](#) in its constructor and cares about the necessary call to `doneMultipleChanges()` when it goes out of scope.

Definition at line 45 of file [YWidget.h](#).


The documentation for this class was generated from the following file:

- `/usr/src/RPM/BUILD/libyui-3.0.10/src/YWidget_OptimizeChanges.h`


3.6 SortedTreeltem< PAYLOAD > Class Template Reference

```
#include <TreeItem.h>
```

Inheritance diagram for SortedTreeltem< PAYLOAD >:



Collaboration diagram for SortedTreeltem< PAYLOAD >:



Public Member Functions

- [SortedTreeltem](#) (PAYLOAD val, [SortedTreeltem](#)< PAYLOAD > *parentItem=0)
- virtual [~SortedTreeltem](#) ()
- void [insertChildSorted](#) ([SortedTreeltem](#)< PAYLOAD > *newChild)
- [SortedTreeltem](#)< PAYLOAD > * [parent](#) () const

- [SortedTreeltem](#)< PAYLOAD > * [next](#) () const
- [SortedTreeltem](#)< PAYLOAD > * [firstChild](#) () const

3.6.1 Detailed Description

`template<class PAYLOAD>class SortedTreeltem< PAYLOAD >`

Template class for tree items that maintain sort order.

Class 'PAYLOAD' to provide operator<() in addition to what template '[Treeltem](#)' requires.

Definition at line [191](#) of file [Treeltem.h](#).


3.6.2 Constructor & Destructor Documentation

3.6.2.1 `template<class PAYLOAD> SortedTreeltem< PAYLOAD >::SortedTreeltem (PAYLOAD val, SortedTreeltem< PAYLOAD > * parentItem = 0) [inline]`

Constructor. Creates a new tree item with value "val" and inserts it in ascending sort order into the children list of "parent".

Definition at line [199](#) of file [Treeltem.h](#).

Here is the call graph for this function:



3.6.2.2 `template<class PAYLOAD> virtual SortedTreeltem< PAYLOAD >::~~SortedTreeltem () [inline, virtual]`

Destructor.

Definition at line 220 of file [Treeltem.h](#).

3.6.3 Member Function Documentation

3.6.3.1 `template<class PAYLOAD> SortedTreeltem<PAYLOAD>* SortedTreeltem<PAYLOAD>::firstChild () const` `[inline]`

Returns this item's first child or 0 if there is none.

Reimplemented from [Treeltem< PAYLOAD >](#).


Definition at line 276 of file [Treeltem.h](#).

3.6.3.2 `template<class PAYLOAD> void SortedTreeltem< PAYLOAD >::insertChildSorted (SortedTreeltem< PAYLOAD > * newChild)` `[inline]`

Insert a child into the internal children list in ascending sort order. Called from the new child's constructor, thus 'public'.

Definition at line 227 of file [Treeltem.h](#).

Here is the call graph for this function:



3.6.3.3 `template<class PAYLOAD> SortedTreeltem<PAYLOAD>* SortedTreeltem<PAYLOAD>::next () const` `[inline]`

Returns this item's next sibling or 0 if there is none.

Reimplemented from [Treeltem< PAYLOAD >](#).

Definition at line 270 of file [Treeltem.h](#).

3.6.3.4 `template<class PAYLOAD> SortedTreeltem<PAYLOAD>* SortedTreeltem<PAYLOAD>::parent () const` `[inline]`

Returns this item's parent or 0 if there is none.

Reimplemented from [Treeltem< PAYLOAD >](#).

Definition at line 264 of file [Treeltem.h](#).


The documentation for this class was generated from the following file:

- `/usr/src/RPM/BUILD/libyui-3.0.10/src/Treeltem.h`

3.7 [Treeltem< PAYLOAD >](#) Class Template Reference

```
#include <TreeItem.h>
```

Inheritance diagram for [Treeltem< PAYLOAD >](#):



Public Member Functions

- [Treeltem](#) (const PAYLOAD &val, [Treeltem< PAYLOAD >](#) *parent=0)

- virtual [~Treeltem](#) ()
- const PAYLOAD & [value](#) () const
- void [setValue](#) (PAYLOAD newValue)
- [Treeltem](#)< PAYLOAD > * [parent](#) () const
- [Treeltem](#)< PAYLOAD > * [next](#) () const
- [Treeltem](#)< PAYLOAD > * [firstChild](#) () const
- void [setParent](#) ([Treeltem](#)< PAYLOAD > *newParent)
- void [setNext](#) ([Treeltem](#)< PAYLOAD > *newNext)
- void [setFirstChild](#) ([Treeltem](#)< PAYLOAD > *newFirstChild)
- void [addChild](#) ([Treeltem](#)< PAYLOAD > *newChild)

Protected Member Functions

- [Treeltem](#) (PAYLOAD val, bool autoAddChild, [Treeltem](#)< PAYLOAD > *[parent](#)=0)

Protected Attributes

- PAYLOAD [_value](#)
- [Treeltem](#)< PAYLOAD > * [_parent](#)
- [Treeltem](#)< PAYLOAD > * [_next](#)
- [Treeltem](#)< PAYLOAD > * [_firstChild](#)

3.7.1 Detailed Description

template<class PAYLOAD>class Treeltem< PAYLOAD >

Template class for tree items that can handle tree children in a generic way - [firstChild\(\)](#), [next\(\)](#) and [parent\(\)](#). Each item stores one value of type 'PAYLOAD'.

Class 'PAYLOAD' needs to provide operator=().

Definition at line 40 of file [Treeltem.h](#).

3.7.2 Constructor & Destructor Documentation

3.7.2.1 template<class PAYLOAD> [Treeltem](#)< PAYLOAD >::Treeltem (const PAYLOAD & val, [Treeltem](#)< PAYLOAD > * [parent](#) = 0) [inline]

Constructor. Creates a new tree item with value "val" and inserts it (without maintaining any meaningful sort order!) into the children list of "parent".

Definition at line 49 of file [Treeltem.h](#).

```
3.7.2.2  template<class PAYLOAD> Treeltem< PAYLOAD >::Treeltem ( PAYLOAD
        val, bool autoAddChild, Treeltem< PAYLOAD > * parent = 0 ) [inline,
        protected]
```

Constructor to be called for derived classes: Decide whether or not to automatically insert this item into the parent's children list. Useful for derived classes that want to maintain a specific sort order among children.


Definition at line 69 of file [Treeltem.h](#).

```
3.7.2.3  template<class PAYLOAD> virtual Treeltem< PAYLOAD >::~~Treeltem ( )
        [inline, virtual]
```

Destructor. Takes care of children - they will be deleted along with this item.

Definition at line 97 of file [Treeltem.h](#).

Here is the call graph for this function:



3.7.3 Member Function Documentation


```
3.7.3.1  template<class PAYLOAD> void Treeltem< PAYLOAD >::addChild ( Treeltem<
        PAYLOAD > * newChild ) [inline]
```

Add a child to the internal children list - usually called from within the child's default constructor.

This default method does not maintain any meaningful sorting order - derived classes that require this might want to use the other constructor (with 'autoAddChild' set to 'false') take care of child insertion themselves.

Definition at line 165 of file [Treeltem.h](#).

Here is the call graph for this function:



3.7.3.2 `template<class PAYLOAD> Treeltem<PAYLOAD>* Treeltem< PAYLOAD >::firstChild () const [inline]`

Returns this item's first child or 0 if there is none.

Reimplemented in [SortedTreeltem< PAYLOAD >](#).

Definition at line 137 of file [Treeltem.h](#).

3.7.3.3 `template<class PAYLOAD> Treeltem<PAYLOAD>* Treeltem< PAYLOAD >::next () const [inline]`

Returns this item's next sibling or 0 if there is none.

Reimplemented in [SortedTreeltem< PAYLOAD >](#).

Definition at line 132 of file [Treeltem.h](#).

3.7.3.4 `template<class PAYLOAD> Treeltem<PAYLOAD>* Treeltem< PAYLOAD >::parent () const [inline]`

Returns this item's parent or 0 if there is none.

Reimplemented in [SortedTreeltem< PAYLOAD >](#).

Definition at line 127 of file [Treeltem.h](#).

3.7.3.5 `template<class PAYLOAD> void Treeltem< PAYLOAD >::setFirstChild (Treeltem< PAYLOAD > * newFirstChild) [inline]`

Sets this item's first child.

Definition at line 152 of file [Treeltem.h](#).

3.7.3.6 `template<class PAYLOAD> void Treeltem< PAYLOAD >::setNext (Treeltem< PAYLOAD > * newNext) [inline]`

Sets this item's next sibling.

Definition at line 147 of file [Treeltem.h](#).

3.7.3.7 `template<class PAYLOAD> void Treeltem< PAYLOAD >::setParent (Treeltem< PAYLOAD > * newParent) [inline]`

Sets this item's parent.

Definition at line 142 of file [Treeltem.h](#).

3.7.3.8 `template<class PAYLOAD> void Treeltem< PAYLOAD >::setValue (PAYLOAD newValue) [inline]`

Set this item's value, the "payload".

If the sort order among children of one level is important, overwrite this method and change the sort order according to the new value. The template class itself never calls this.

Definition at line 122 of file [Treeltem.h](#).

3.7.3.9 `template<class PAYLOAD> const PAYLOAD& Treeltem< PAYLOAD >::value () const [inline]`

Returns this item's value, the "payload".

Definition at line 113 of file [Treeltem.h](#).


The documentation for this class was generated from the following file:

- `/usr/src/RPM/BUILD/libyui-3.0.10/src/Treeltem.h`


3.8 YAlignment Class Reference

```
#include <YAlignment.h>
```

Inheritance diagram for YAlignment:



Collaboration diagram for YAlignment:



Public Member Functions

- virtual [~YAlignment](#) ()
- virtual const char * [widgetClass](#) () const
- YAlignmentType [alignment](#) (YUIDimension dim) const
- int [leftMargin](#) () const
- int [rightMargin](#) () const
- int [topMargin](#) () const
- int [bottomMargin](#) () const
- int [totalMargins](#) (YUIDimension dim) const
- void [setLeftMargin](#) (int margin)
- void [setRightMargin](#) (int margin)
- void [setTopMargin](#) (int margin)
- void [setBottomMargin](#) (int margin)
- int [minWidth](#) () const
- int [minHeight](#) () const
- void [setMinWidth](#) (int width)
- void [setMinHeight](#) (int height)
- virtual void [setBackgroundPixmap](#) (const std::string &pixmapFileName)
- std::string [backgroundPixmap](#) () const
- virtual void [addChild](#) (YWidget *child)
- virtual void [moveChild](#) (YWidget *child, int newX, int newY)=0
- virtual bool [stretchable](#) (YUIDimension dim) const
- virtual int [preferredWidth](#) ()
- virtual int [preferredHeight](#) ()
- virtual void [setSize](#) (int newWidth, int newHeight)

Protected Member Functions

- [YAlignment](#) (YWidget *parent, YAlignmentType horAlign, YAlignmentType vertAlign)

Protected Attributes

- [ImplPtr](#)< [YAlignmentPrivate](#) > **priv**

3.8.1 Detailed Description

Implementation of all the alignment widgets:

- Left, Right, HCenter,

- Top, Bottom, VCenter,
- HVCenter
- MinSize, MinWidth, MinHeight

Definition at line 41 of file [YAlignment.h](#).

3.8.2 Constructor & Destructor Documentation

3.8.2.1 `YAlignment::YAlignment (YWidget * parent, YAlignmentType horAlign, YAlignmentType vertAlign)` `[protected]`

Constructor.

Definition at line 76 of file [YAlignment.cc](#).

3.8.2.2 `YAlignment::~~YAlignment ()` `[virtual]`

Destructor.

Definition at line 86 of file [YAlignment.cc](#).

3.8.3 Member Function Documentation

3.8.3.1 `void YAlignment::addChild (YWidget * child)` `[virtual]`


Add a child widget.

Reimplemented from [YSingleChildContainerWidget](#) to propagate stretchability down to the single child.

Reimplemented from [YWidget](#).

Definition at line 177 of file [YAlignment.cc](#).

Here is the call graph for this function:



3.8.3.2 `YAlignmentType YAlignment::alignment (YUIDimension dim) const`

Return the alignment in the specified dimension.

Definition at line 93 of file [YAlignment.cc](#).

3.8.3.3 `std::string YAlignment::backgroundPixmap () const`

Return the name of the background pixmap or an empty string, if there is none.

Definition at line 171 of file [YAlignment.cc](#).

3.8.3.4 `int YAlignment::bottomMargin () const`

Return the bottom margin in pixels, the distance between the bottom edge of this alignment and the bottom edge of the child widget.

Definition at line 117 of file [YAlignment.cc](#).

3.8.3.5 `int YAlignment::leftMargin () const`

Return the left margin in pixels, the distance between the left edge of this alignment and the left edge of the child widget.

Definition at line 99 of file [YAlignment.cc](#).

3.8.3.6 `int YAlignment::minHeight () const`

Return the minimum height of this alignment or 0 if none is set. [preferredHeight\(\)](#) will never return less than this value.

Definition at line 153 of file [YAlignment.cc](#).

3.8.3.7 `int YAlignment::minWidth () const`

Return the minimum width of this alignment or 0 if none is set. [preferredWidth\(\)](#) will never return less than this value.

Definition at line 147 of file [YAlignment.cc](#).

3.8.3.8 `virtual void YAlignment::moveChild (YWidget * child, int newx, int newy)`
[pure virtual]

Move a child widget to a new position.

3.8.3.9 `int YAlignment::preferredHeight ()` [virtual]


Preferred height of the widget.

Reimplemented from [YWidget](#).

Reimplemented from [YSingleChildContainerWidget](#).

Definition at line 207 of file [YAlignment.cc](#).

Here is the call graph for this function:



3.8.3.10 `int YAlignment::preferredWidth ()` [virtual]


Preferred width of the widget.

Reimplemented from [YWidget](#).

Reimplemented from [YSingleChildContainerWidget](#).

Definition at line 195 of file [YAlignment.cc](#).

Here is the call graph for this function:



3.8.3.11 `int YAlignment::rightMargin ()` const

Return the right margin in pixels, the distance between the right edge of this alignment and the right edge of the child widget.

Definition at line 105 of file [YAlignment.cc](#).

3.8.3.12 `void YAlignment::setBackgroundPixmap (const std::string & pixmapFileName)` [virtual]


Set a background pixmap.

Derived classes may want to overwrite this.

This parent method should be called first in the overwritten method to ensure path expansion is done as specified (prepend the theme path ("`/usr/share/libyui/theme/`") if the path doesn't start with "`/`" or "`.`").

Definition at line 334 of file [YAlignment.cc](#).

Here is the call graph for this function:



3.8.3.13 void YAlignment::setBottomMargin (int *margin*)

Set the bottom margin in pixels.

Definition at line 141 of file [YAlignment.cc](#).

3.8.3.14 void YAlignment::setLeftMargin (int *margin*)

Set the left margin in pixels.

Definition at line 123 of file [YAlignment.cc](#).

3.8.3.15 void YAlignment::setMinHeight (int *height*)

Set the minimum height to return for [preferredHeight\(\)](#).

Definition at line 165 of file [YAlignment.cc](#).

3.8.3.16 void YAlignment::setMinWidth (int *width*)

Set the minimum width to return for [preferredWidth\(\)](#).

Definition at line 159 of file [YAlignment.cc](#).

3.8.3.17 void YAlignment::setRightMargin (int *margin*)

Set the right margin in pixels.

Definition at line 129 of file [YAlignment.cc](#).

3.8.3.18 void YAlignment::setSize (int *newWidth*, int *newHeight*) [virtual]


Set the current size and move the child widget according to its alignment.

Derived classes should reimplement this, but call this base class function in their own implementation.

Reimplemented from [YSingleChildContainerWidget](#).

Definition at line 219 of file [YAlignment.cc](#).

Here is the call graph for this function:



3.8.3.19 void YAlignment::setTopMargin (int *margin*)

Set the top margin in pixels.

Definition at line 135 of file [YAlignment.cc](#).

3.8.3.20 bool YAlignment::stretchable (YUIDimension *dim*) const [virtual]


Return this widget's stretchability. Reimplemented from [YWidget](#).

In an aligned dimension the widget is always stretchable. In an unchanged dimension the widget is stretchable if the child is stretchable.

Reimplemented from [YSingleChildContainerWidget](#).

Definition at line 186 of file [YAlignment.cc](#).

Here is the call graph for this function:



3.8.3.21 `int YAlignment::topMargin () const`

Return the top margin in pixels, the distance between the top edge of this alignment and the top edge of the child widget.


Definition at line 111 of file [YAlignment.cc](#).

3.8.3.22 `int YAlignment::totalMargins (YUIDimension dim) const`

Return the sum of all margins in the specified dimension.

Definition at line 326 of file [YAlignment.cc](#).

Here is the call graph for this function:



3.8.3.23 `const char * YAlignment::widgetClass () const` [virtual]

Return a descriptive name of this widget class for logging, debugging etc.

Reimplemented from [YWidget](#).


Definition at line [353](#) of file [YAlignment.cc](#).

The documentation for this class was generated from the following files:

- `/usr/src/RPM/BUILD/libyui-3.0.10/src/YAlignment.h`
- `/usr/src/RPM/BUILD/libyui-3.0.10/src/YAlignment.cc`

3.9 YAlignmentPrivate Struct Reference

Collaboration diagram for YAlignmentPrivate:



Public Member Functions

- [YAlignmentPrivate](#) (YAlignmentType horAlign, YAlignmentType vertAlign)

Public Attributes

- int **leftMargin**
- int **rightMargin**
- int **topMargin**
- int **bottomMargin**
- int **minWidth**
- int **minHeight**
- std::string **backgroundPixmap**
- [YBothDim< YAlignmentType >](#) **alignment**

3.9.1 Detailed Description

Definition at line 38 of file [YAlignment.cc](#).

3.9.2 Constructor & Destructor Documentation

3.9.2.1 YAlignmentPrivate::YAlignmentPrivate (YAlignmentType *horAlign*, YAlignmentType *vertAlign*) [inline]

Constructor.


Definition at line 43 of file [YAlignment.cc](#).

The documentation for this struct was generated from the following file:

- [/usr/src/RPM/BUILD/libyui-3.0.10/src/YAlignment.cc](#)

3.10 YApplicationPrivate Struct Reference

Collaboration diagram for YApplicationPrivate:



Public Attributes

- std::string **productName**
- bool **reverseLayout**
- std::string **applicationTitle**
- std::string **applicationIcon**
- YFunctionKeyMap **defaultFunctionKey**
- [YIconLoader](#) * **iconLoader**

3.10.1 Detailed Description


Definition at line 44 of file [YApplication.cc](#).

The documentation for this struct was generated from the following file:


- /usr/src/RPM/BUILD/libyui-3.0.10/src/YApplication.cc

3.11 YBarGraph Class Reference

Inheritance diagram for YBarGraph:



Collaboration diagram for YBarGraph:



Public Member Functions

- virtual [~YBarGraph](#) ()
- virtual const char * [widgetClass](#) () const
- void [addSegment](#) (const [YBarGraphSegment](#) &[segment](#))
- void [deleteAllSegments](#) ()
- int [segments](#) ()
- const [YBarGraphSegment](#) & [segment](#) (int segmentIndex) const
- void [setValue](#) (int segmentIndex, int newValue)
- void [setLabel](#) (int segmentIndex, const std::string &newLabel)
- void [setSegmentColor](#) (int segmentIndex, const [YColor](#) &color)
- void [setTextColor](#) (int segmentIndex, const [YColor](#) &color)
- virtual bool [setProperty](#) (const std::string &propertyName, const [YPropertyValue](#) &val)
- virtual [YPropertyValue](#) [getProperty](#) (const std::string &propertyName)
- virtual const [YPropertySet](#) & [propertySet](#) ()

Protected Member Functions

- [YBarGraph](#) ([YWidget](#) *parent)
- virtual void [doUpdate](#) ()=0

Friends

- class [YBarGraphMultiUpdate](#)

3.11.1 Detailed Description

Definition at line [36](#) of file [YBarGraph.h](#).

3.11.2 Constructor & Destructor Documentation

3.11.2.1 [YBarGraph::YBarGraph](#) ([YWidget](#) * *parent*) [[protected](#)]

Constructor.

Definition at line [67](#) of file [YBarGraph.cc](#).

Here is the call graph for this function:



3.11.2.2 YBarGraph::~YBarGraph () [virtual]

Destructor.

Definition at line 76 of file [YBarGraph.cc](#).

3.11.3 Member Function Documentation

3.11.3.1 void YBarGraph::addSegment (const YBarGraphSegment & *segment*)

Add one segment.

If the segment's background and text colors are not explicitly specified, the [YBarGraph](#) widget will assign them from a list of (at least 5 different) color sets.

When adding multiple segments, use a [YBarGraphMultiUpdate](#) object for improved performance to hold back display updates until all segments are added.

Definition at line 96 of file [YBarGraph.cc](#).

3.11.3.2 void YBarGraph::deleteAllSegments ()

Delete all segments.

Definition at line 104 of file [YBarGraph.cc](#).

3.11.3.3 virtual void YBarGraph::doUpdate () [protected, pure virtual]

Perform a display update after any change to any of the segments.

Derived classes are required to implement this.

3.11.3.4 YPropertyValue YBarGraph::getProperty (const std::string & *propertyName*) [virtual]


Get a property. Reimplemented from [YWidget](#).

This method may throw YUIPropertyExceptions.

Reimplemented from [YWidget](#).

Definition at line 211 of file [YBarGraph.cc](#).

Here is the call graph for this function:



3.11.3.5 const YPropertySet & YBarGraph::propertySet () [virtual]

Return this class's property set. This also initializes the property upon the first call.

Reimplemented from [YWidget](#).

Reimplemented from [YWidget](#).

Definition at line 174 of file [YBarGraph.cc](#).

Here is the call graph for this function:



3.11.3.6 `const YBarGraphSegment & YBarGraph::segment (int segmentIndex) const`

Return the segment with the specified index (from 0 on).

This will throw an exception if there are not this many segments.

Definition at line 112 of file [YBarGraph.cc](#).

3.11.3.7 `int YBarGraph::segments ()`

Return the current number of segments.

Definition at line 121 of file [YBarGraph.cc](#).

3.11.3.8 `void YBarGraph::setLabel (int segmentIndex, const std::string & newLabel)`

Set the label of the segment with the specified index (from 0 on). Use %1 as a placeholder for the current value.

This will throw an exception if there are not this many segments.

Note: Use a [YBarGraphMultiUpdate](#) object for improved performance when doing multiple changes at the same time.

Definition at line 138 of file [YBarGraph.cc](#).

3.11.3.9 `bool YBarGraph::setProperty (const std::string & propertyName, const YPropertyValue & val) [virtual]`

Set a property. Reimplemented from [YWidget](#).


This function may throw YUIPropertyExceptions.

This function returns 'true' if the value was successfully set and 'false' if that value requires special handling (not in error cases: those are covered by exceptions).

Reimplemented from [YWidget](#).

Definition at line 195 of file [YBarGraph.cc](#).

Here is the call graph for this function:




3.11.3.10 void YBarGraph::setSegmentColor (int *segmentIndex*, const YColor & *color*)

Set the background color of the segment with the specified index (from 0 on).

This will throw an exception if there are not this many segments or if the color is undefined.

Definition at line 148 of file [YBarGraph.cc](#).

Here is the call graph for this function:




3.11.3.11 void YBarGraph::setTextColor (int *segmentIndex*, const YColor & *color*)

Set the text color of the segment with the specified index (from 0 on).

This will throw an exception if there are not this many segments or if the color is undefined.

Definition at line 161 of file [YBarGraph.cc](#).

Here is the call graph for this function:



3.11.3.12 void YBarGraph::setValue (int *segmentIndex*, int *newValue*)

Set the value of the segment with the specific index (from 0 on).

This will throw an exception if there are not this many segments.

Note: Use a [YBarGraphMultiUpdate](#) object for improved performance when doing multiple changes at the same time.

Definition at line 128 of file [YBarGraph.cc](#).

3.11.3.13 virtual const char* YBarGraph::widgetClass () const [inline, virtual]

Return a descriptive name of this widget class for logging, debugging etc.

Reimplemented from [YWidget](#).

Definition at line 56 of file [YBarGraph.h](#).

The documentation for this class was generated from the following files:

- [/usr/src/RPM/BUILD/libyui-3.0.10/src/YBarGraph.h](#)
- [/usr/src/RPM/BUILD/libyui-3.0.10/src/YBarGraph.cc](#)

3.12 YBarGraphMultiUpdate Class Reference

```
#include <YBarGraph.h>
```

Public Member Functions

- [YBarGraphMultiUpdate](#) ([YBarGraph](#) *barGraph)

- [~YBarGraphMultiUpdate](#) ()

3.12.1 Detailed Description

Helper class for multiple updates to a [YBarGraph](#) widget: This will hold back display updates until this object goes out of scope.

Definition at line [280](#) of file [YBarGraph.h](#).

3.12.2 Constructor & Destructor Documentation

3.12.2.1 [YBarGraphMultiUpdate::YBarGraphMultiUpdate](#) ([YBarGraph](#) * *barGraph*)

Constructor.

This will make the corresponding [YBarGraph](#) widget hold back any pending display updates (due to changed values, labels, or colors) until this object is destroyed (goes out of scope).

Create objects of this class on the stack (as local variables) and simply let them go out of scope.

Example:

```
{ YBarGraphMultiUpdate multiUpdate( myBarGraph ); myBarGraph->setValue( 0, 42 ); // No display update yet myBarGraph->setValue( 1, 84 ); // No display update yet myBarGraph->setValue( 2, 21 ); // No display update yet } // multiUpdate goes out of scope, will trigger display update now
```

Definition at line [226](#) of file [YBarGraph.cc](#).

3.12.2.2 [YBarGraphMultiUpdate::~~YBarGraphMultiUpdate](#) ()

Destructor.

This will trigger display updates of the corresponding [YBarGraph](#) widget if any are necessary.

Definition at line [235](#) of file [YBarGraph.cc](#).

The documentation for this class was generated from the following files:

- [/usr/src/RPM/BUILD/libyui-3.0.10/src/YBarGraph.h](#)
- [/usr/src/RPM/BUILD/libyui-3.0.10/src/YBarGraph.cc](#)

3.13 YBarGraphPrivate Struct Reference

Public Attributes

- `std::vector< YBarGraphSegment > segments`
- `bool updatesPending`
- `bool postponeUpdates`

3.13.1 Detailed Description

Definition at line 52 of file [YBarGraph.cc](#).

The documentation for this struct was generated from the following file:

- `/usr/src/RPM/BUILD/libyui-3.0.10/src/YBarGraph.cc`

3.14 YBarGraphSegment Class Reference

```
#include <YBarGraph.h>
```

Public Member Functions

- [YBarGraphSegment](#) (int `value`=0, const std::string &`label`=std::string(), const [YColor](#) &`segmentColor`=[YColor](#)(), const [YColor](#) &`textColor`=[YColor](#)())
- int `value` () const
- void `setValue` (int `newValue`)
- std::string `label` () const
- void `setLabel` (const std::string &`newLabel`)
- [YColor](#) `segmentColor` () const
- bool `hasSegmentColor` () const
- void `setSegmentColor` (const [YColor](#) &`color`)
- [YColor](#) `textColor` () const
- bool `hasTextColor` () const
- void `setTextColor` (const [YColor](#) &`color`)

3.14.1 Detailed Description

Helper class to describe one segment of a [YBarGraph](#).

Definition at line 181 of file [YBarGraph.h](#).

3.14.2 Constructor & Destructor Documentation

3.14.2.1 `YBarGraphSegment::YBarGraphSegment (int value = 0, const std::string & label = std::string(), const YColor & segmentColor = YColor(), const YColor & textColor = YColor()) [inline]`

Constructor.

'value' is the initial value of this segment.

'label' is the label text in the segment. Use %1 as a placeholder for the current value.

'segmentColor' is the background color of this segment.

'textColor' is the color for the label text.

The [YBarGraph](#) widget will automatically assign some default colors (one of at least 5 different ones) if none are specified.

Definition at line 199 of file [YBarGraph.h](#).

3.14.3 Member Function Documentation

3.14.3.1 `bool YBarGraphSegment::hasSegmentColor () const [inline]`

Return 'true' if this segment's background color is defined, i.e. it has a real RGB value and was not just created with the default constructor.

Definition at line 241 of file [YBarGraph.h](#).

Here is the call graph for this function:



3.14.3.2 `bool YBarGraphSegment::hasTextColor () const [inline]`

Return 'true' if this segment's text color is defined, i.e. it has a real RGB value and was not just created with the default constructor.

Definition at line 258 of file [YBarGraph.h](#).

Here is the call graph for this function:



3.14.3.3 `std::string YBarGraphSegment::label () const` `[inline]`

Return the current text label of this segment. Any %1 placeholder will be returned as %1 (not expanded).

Definition at line 223 of file [YBarGraph.h](#).

3.14.3.4 `YColor YBarGraphSegment::segmentColor () const` `[inline]`

Return the segment background color.

Definition at line 234 of file [YBarGraph.h](#).

3.14.3.5 `void YBarGraphSegment::setLabel (const std::string & newLabel)` `[inline]`

Set the text label of this segment. Use %1 as a placeholder for the current value.

Definition at line 229 of file [YBarGraph.h](#).

3.14.3.6 `void YBarGraphSegment::setSegmentColor (const YColor & color)` `[inline]`

Set this segment's background color.

Definition at line 246 of file [YBarGraph.h](#).

3.14.3.7 `void YBarGraphSegment::setTextColor (const YColor & color)` `[inline]`

Set this segment's text color.

Definition at line [263](#) of file [YBarGraph.h](#).

3.14.3.8 `void YBarGraphSegment::setValue (int newValue) [inline]`

Set the value of this segment.

Definition at line [217](#) of file [YBarGraph.h](#).

3.14.3.9 `YColor YBarGraphSegment::textColor () const [inline]`

Return this segment's text color.

Definition at line [251](#) of file [YBarGraph.h](#).

3.14.3.10 `int YBarGraphSegment::value () const [inline]`

Return the current value of this segment.

Definition at line [212](#) of file [YBarGraph.h](#).


The documentation for this class was generated from the following file:

- `/usr/src/RPM/BUILD/libyui-3.0.10/src/YBarGraph.h`

3.15 YBothDim< T > Class Template Reference

```
#include <YBothDim.h>
```


Collaboration diagram for YBothDim< T >:



Public Member Functions

- `YBothDim` (T hor, T vert)
- `YBothDim` ()
- T & `operator[]` (YUIDimension dim)
- const T & `operator[]` (YUIDimension dim) const

Public Attributes

- T `vert`
- T `hor`

3.15.1 Detailed Description

```
template<typename T>class YBothDim< T >
```

Template class for two-dimensional entities, such as

- width, height
- x_pos, y_pos
- hStretchable, vStretchable

Precondition: type T needs to have a default constructor (which all simple types like int, long, bool have).

Definition at line 41 of file [YBothDim.h](#).

3.15.2 Constructor & Destructor Documentation

3.15.2.1 `template<typename T> YBothDim< T >::YBothDim (T hor, T vert)`
`[inline]`

Constructor with explicit initialization for both values

Definition at line 52 of file [YBothDim.h](#).

3.15.2.2 `template<typename T> YBothDim< T >::YBothDim ()` `[inline]`

Default constructor (calls T default constructor for both values)

Definition at line 60 of file [YBothDim.h](#).

3.15.3 Member Function Documentation

3.15.3.1 `template<typename T> T& YBothDim< T >::operator[] (YUIDimension dim)`
`[inline]`

`operator[]` for alternative access via `myVar[YD_HORIZ]` Please note that this returns a non-const reference, so this can be used as an lvalue (e.g., in assignments)

Definition at line 68 of file [YBothDim.h](#).

3.15.3.2 `template<typename T> const T& YBothDim< T >::operator[] (YUIDimension dim) const` `[inline]`

Same as above for const objects

Definition at line 84 of file [YBothDim.h](#).

The documentation for this class was generated from the following file:

- `/usr/src/RPM/BUILD/libyui-3.0.10/src/YBothDim.h`

3.16 YBuiltinCaller Class Reference

```
#include <YBuiltinCaller.h>
```

Public Member Functions

- virtual void [call](#) ()=0

3.16.1 Detailed Description

Abstract base class for transparently calling a built-in function. Derived classes will want to add some methods to store the function to be called, arguments to that function and its result and to retrieve the result when needed.

See YCPBuiltinCaller.h for an implementation.

Definition at line [37](#) of file [YBuiltinCaller.h](#).

3.16.2 Member Function Documentation

3.16.2.1 virtual void YBuiltinCaller::call () [pure virtual]

Call the built-in. This will be called in the UI thread with appropriate syncing between the threads.

Derived classes might want to store the result of the call in a member variable in this class so it can later be queried.


Derived classes are required to implement this method.

The documentation for this class was generated from the following file:


- [/usr/src/RPM/BUILD/libyui-3.0.10/src/YBuiltinCaller.h](#)

3.17 YBusyIndicator Class Reference

Inheritance diagram for YBusyIndicator:



Collaboration diagram for YBusyIndicator:



Public Member Functions

- virtual [~YBusyIndicator](#) ()
- virtual const char * [widgetClass](#) () const
- std::string [label](#) ()
- virtual void [setLabel](#) (const std::string &[label](#))
- int [timeout](#) () const
- virtual void [setTimeout](#) (int newTimeout)

- bool [alive](#) () const
- virtual void [setAlive](#) (bool newAlive)
- virtual bool [setProperty](#) (const std::string &propertyName, const [YPropertyValue](#) &val)
- virtual [YPropertyValue](#) [getProperty](#) (const std::string &propertyName)
- virtual const [YPropertySet](#) & [propertySet](#) ()

Protected Member Functions

- [YBusyIndicator](#) ([YWidget](#) *parent, const std::string &label, int timeout=1000, bool alive=true)

3.17.1 Detailed Description

Definition at line 33 of file [YBusyIndicator.h](#).


3.17.2 Constructor & Destructor Documentation

3.17.2.1 [YBusyIndicator::YBusyIndicator](#) ([YWidget](#) * parent, const std::string & label, int timeout = 1000, bool alive = true) [protected]

Constructor.

Definition at line 52 of file [YBusyIndicator.cc](#).

Here is the call graph for this function:



3.17.2.2 [YBusyIndicator::~~YBusyIndicator](#) () [virtual]

Destructor.

Definition at line 66 of file [YBusyIndicator.cc](#).

3.17.3 Member Function Documentation

3.17.3.1 `bool YBusyIndicator::alive () const`

Return whether busy indicator is alive or in stalled stated.

Definition at line 104 of file [YBusyIndicator.cc](#).

3.17.3.2 `YPropertyValue YBusyIndicator::getProperty (const std::string & propertyName) [virtual]`


Get a property. Reimplemented from [YWidget](#).

This method may throw `YUIPropertyExceptions`.

Reimplemented from [YWidget](#).

Definition at line 149 of file [YBusyIndicator.cc](#).

Here is the call graph for this function:



3.17.3.3 `std::string YBusyIndicator::label ()`

Get the label (the caption above the progress bar).

Definition at line 72 of file [YBusyIndicator.cc](#).

3.17.3.4 `const YPropertySet & YBusyIndicator::propertySet () [virtual]`


Return this class's property set. This also initializes the property upon the first call.

Reimplemented from [YWidget](#).

Reimplemented from [YWidget](#).

Definition at line 110 of file [YBusyIndicator.cc](#).

Here is the call graph for this function:



3.17.3.5 void YBusyIndicator::setAlive (bool *newAlive*) [virtual]

Send a keep alive message to prevent BusyIndicator from changing to 'stalled' state.

Derived classes should reimplement this, but they should call this base class method at the end of the overloaded function.

Definition at line 99 of file [YBusyIndicator.cc](#).

Here is the call graph for this function:



3.17.3.6 void YBusyIndicator::setLabel (const std::string & *label*) [virtual]

Set the label (the caption above the progress bar).

Derived classes are free to reimplement this, but they should call this base class method at the end of the overloaded function.

Definition at line 78 of file [YBusyIndicator.cc](#).

Here is the call graph for this function:



3.17.3.7 `bool YBusyIndicator::setProperty (const std::string & propertyName, const YPropertyValue & val) [virtual]`

Set a property. Reimplemented from [YWidget](#).


This function may throw `YUIPropertyExceptions`.

This function returns 'true' if the value was successfully set and 'false' if that value requires special handling (not in error cases: those are covered by exceptions).

Reimplemented from [YWidget](#).

Definition at line 132 of file [YBusyIndicator.cc](#).

Here is the call graph for this function:



3.17.3.8 void YBusyIndicator::setTimeout (int *newTimeout*) [virtual]

Set the timeout in milliseconds after that the widget shows 'stalled' when no new tick is received.

Derived classes should reimplement this, but they should call this base class method at the end of the overloaded function.

Definition at line 90 of file [YBusyIndicator.cc](#).

3.17.3.9 int YBusyIndicator::timeout () const

Return the current timeout in milliseconds.

Definition at line 84 of file [YBusyIndicator.cc](#).

3.17.3.10 virtual const char* YBusyIndicator::widgetClass () const [inline, virtual]

Returns a descriptive name of this widget class for logging, debugging etc.

Reimplemented from [YWidget](#).

Definition at line 54 of file [YBusyIndicator.h](#).

The documentation for this class was generated from the following files:

- [/usr/src/RPM/BUILD/libyui-3.0.10/src/YBusyIndicator.h](#)
- [/usr/src/RPM/BUILD/libyui-3.0.10/src/YBusyIndicator.cc](#)

3.18 YBusyIndicatorPrivate Struct Reference

Public Member Functions

- **YBusyIndicatorPrivate** (const std::string &label, int timeout, bool alive)

Public Attributes

- std::string **label**
- int **timeout**
- bool **alive**

3.18.1 Detailed Description

Definition at line 33 of file [YBusyIndicator.cc](#).


The documentation for this struct was generated from the following file:

- `/usr/src/RPM/BUILD/libyui-3.0.10/src/YBusyIndicator.cc`


3.19 YButtonBox Class Reference

```
#include <YButtonBox.h>
```

Inheritance diagram for YButtonBox:



Collaboration diagram for YButtonBox:



Public Member Functions

- virtual [~YButtonBox](#) ()
- virtual const char * [widgetClass](#) () const
- virtual void [setMargins](#) (const [YButtonBoxMargins](#) &[margins](#))
- [YButtonBoxMargins](#) [margins](#) () const
- virtual void [doLayout](#) (int width, int height)
- [YPushButton](#) * [findButton](#) (YButtonRole role)
- void [sanityCheck](#) ()
- void [setSanityCheckRelaxed](#) (bool relax=true)
- bool [sanityCheckRelaxed](#) () const
- virtual int [preferredWidth](#) ()
- virtual int [preferredHeight](#) ()
- virtual void [setSize](#) (int newWidth, int newHeight)
- virtual bool [stretchable](#) (YUIDimension dimension) const

Static Public Member Functions

- static void [setLayoutPolicy](#) (const [YButtonBoxLayoutPolicy](#) &[layoutPolicy](#))
- static [YButtonBoxLayoutPolicy](#) [layoutPolicy](#) ()
- static [YButtonBoxLayoutPolicy](#) [kdeLayoutPolicy](#) ()
- static [YButtonBoxLayoutPolicy](#) [gnomeLayoutPolicy](#) ()
- static void [setDefaultMargins](#) (const [YButtonBoxMargins](#) &[margins](#))
- static [YButtonBoxMargins](#) [defaultMargins](#) ()

Protected Member Functions

- [YButtonBox](#) (YWidget *parent)
- virtual std::vector < [YPushButton](#) * > [buttonsByButtonOrder](#) ()
- int [maxChildSize](#) (YUIDimension dim) const
- int [totalChildrenWidth](#) () const
- virtual void [moveChild](#) (YWidget *child, int newX, int newY)=0
- int [preferredWidth](#) (bool equalSizeButtons)

Friends

- class **[YButtonBoxPrivate](#)**

3.19.1 Detailed Description

Container widget for dialog buttons that abstracts the button order depending on the desktop environment.

KDE and Windows arrange dialog buttons like this:

[OK] [Apply] [Cancel] [Custom1] [Custom2] ... [Help]

[Continue] [Cancel]

[Yes] [No]

GNOME and MacOS arrange them like this:

[Help] [Custom1] [Custom2] ... [Apply] [Cancel] [OK]

[Cancel] [Continue]

[No] [Yes]

This class provides the abstraction to use whatever layout is more appropriate in the current environment. The application creates the buttons as child widgets of a [YButtonBox](#) (rather than a YHBox) and leaves the button order to the [YButtonBox](#).

Each of the standard buttons ([OK], [Apply], [Cancel], [Help]) needs to have a button role properly assigned.

If set up properly (see `YApplication::setDefaultFunctionKey()`), known button labels will be assigned an appropriate role:

[OK] F10 [Continue] -> [OK] F10 [Yes] -> [OK] F10 [Accept] -> [OK] F10 [Next] -> [OK] F10

[Cancel] F9 [No] -> [Cancel] F9

[Help] F1

Buttons with nonstandard labels that act in such a role need to be explicitly assigned that role:

[Print] [Cancel] [Help] [Delete] [Cancel] [Help]

Those [Print] or [Delete] buttons act as [OK] buttons (the "yes, do it" action of that dialog). Call `YPushButton::setButtonRole(YOkButton)` explicitly for them.

[YButtonBox](#) widgets only accept [YPushButton](#) child widgets. Otherwise an exception is thrown.

If there is more than one button, one of the child buttons needs to have the [OK] role, and another needs to have the [Cancel] role. Otherwise an exception is thrown.

Definition at line 148 of file [YButtonBox.h](#).

3.19.2 Constructor & Destructor Documentation

3.19.2.1 YButtonBox::YButtonBox (YWidget * *parent*) [protected]

Constructor.

Definition at line 66 of file [YButtonBox.cc](#).

Here is the call graph for this function:



3.19.2.2 YButtonBox::~~YButtonBox () [virtual]

Destructor.

Definition at line 75 of file [YButtonBox.cc](#).

3.19.3 Member Function Documentation

3.19.3.1 std::vector< YPushButton * > YButtonBox::buttonsByButtonOrder () [protected, virtual]


Return the button children sorted (left to right) by the current button order (from the layout policy).

This default implementation handles KDE and Gnome button orders. It is used in the default [doLayout\(\)](#) method.

This may throw exceptions if there are non-button children or if there are multiple buttons with any of the standard button roles (except YCustomButton, of course).

Definition at line 410 of file [YButtonBox.cc](#).

Here is the call graph for this function:



3.19.3.2 YButtonBoxMargins YButtonBox::defaultMargins () [static]

Return the default margins for all future [YButtonBox](#) widgets.

Definition at line 132 of file [YButtonBox.cc](#).

3.19.3.3 void YButtonBox::doLayout (int width, int height) [virtual]

Lay out the button box and its children (its buttons). This is where the button order is implemented.

This method is called by the default [setSize\(\)](#) method. It uses [YButtonBox::layoutPolicy\(\)](#) and the specified margins (defaultMargins unless changed with [setMargins\(\)](#)). It moves the buttons to their position with [moveChild\(\)](#).

This all should work reasonably in all cases (Qt-UI with KDE button order, Gtk-UI with Gnome button order, NCurses-UI with KDE button order).

Still, derived classes can reimplement this. It does not make very much sense to call this default method in a new implementation.

Definition at line 161 of file [YButtonBox.cc](#).

3.19.3.6 YButtonBoxLayoutPolicy YButtonBox::kdeLayoutPolicy () [static]

Predefined layout policy for KDE-like behaviour.

Definition at line 96 of file [YButtonBox.cc](#).

3.19.3.7 YButtonBoxLayoutPolicy YButtonBox::layoutPolicy () [static]

Return the layout policy.

Definition at line 89 of file [YButtonBox.cc](#).

3.19.3.8 YButtonBoxMargins YButtonBox::margins () const

Return the margins of this [YButtonBox](#).

Notice that those are only the desired margins; if there is not enough space, margins and spacings will be reduced before buttons are cut off.


Definition at line 146 of file [YButtonBox.cc](#).

3.19.3.9 int YButtonBox::maxChildSize (YUIDimension *dim*) const [protected]

Return the (preferred) size of the biggest child widget in the specified dimension.

Definition at line 527 of file [YButtonBox.cc](#).

Here is the call graph for this function:



3.19.3.10 virtual void YButtonBox::moveChild (YWidget * *child*, int *newX*, int *newY*) [protected, pure virtual]

Move a child to a new position. This is used in [doLayout\(\)](#).

Derived classes are required to implement this.

3.19.3.11 `int YButtonBox::preferredHeight ()` `[virtual]`

Preferred height of the widget.


Reimplemented from [YWidget](#). This default method returns the height of the highest child plus the top and bottom margins.

Derived classes can reimplement this method. It does not make very much sense to call this base class method in a new implementation.

Implements [YWidget](#).

Definition at line 516 of file [YButtonBox.cc](#).

Here is the call graph for this function:



3.19.3.12 `int YButtonBox::preferredWidth ()` `[virtual]`

Preferred width of the widget.

Reimplemented from [YWidget](#). This default method returns the sum of the widths of all child widgets plus the left and right margins plus the spacings.

Derived classes can reimplement this method. It does not make very much sense to call this base class method in a new implementation.

Implements [YWidget](#).


Definition at line 509 of file [YButtonBox.cc](#).

3.19.3.13 `int YButtonBox::preferredWidth (bool equalSizeButtons)` `[protected]`

Calculate the preferred width with or without trying to enforce buttons of equal size.

Definition at line 483 of file [YButtonBox.cc](#).

Here is the call graph for this function:



3.19.3.14 void YButtonBox::sanityCheck ()

Sanity check: Check if all child widgets have the correct widget class and if the button roles are assigned correctly.

A [YButtonBox](#) with more than one button is required to have one [YOKButton](#) and one [YCancelButton](#). Neither button role may be assigned more than once.

This method may throw exceptions:


- [YUIButtonRoleMismatchException](#)
- [YUIInvalidChildException](#) (wrong widget class)

This cannot be done as child widgets are inserted since this is done from the child widgets' constructors, so virtual methods or `dynamic_cast` don't work at that point.

This is called in the default `setSize()` method (just before `doLayout()`), so any of the above errors are caught only at that time. Applications are free to call this before that time to make error handling more transparent.

Definition at line 605 of file [YButtonBox.cc](#).

Here is the call graph for this function:



3.19.3.15 `bool YButtonBox::sanityCheckRelaxed () const`

Return 'true' if sanity checks are currently relaxed, 'false' if not.


Definition at line 598 of file [YButtonBox.cc](#).

3.19.3.16 `void YButtonBox::setDefaultMargins (const YButtonBoxMargins & margins) [static]`

Set the default margins for all future [YButtonBox](#) widgets.

Definition at line 125 of file [YButtonBox.cc](#).

Here is the call graph for this function:



3.19.3.17 void YButtonBox::setLayoutPolicy (const YButtonBoxLayoutPolicy & layoutPolicy) [static]

Set the button policy for all future [YButtonBox](#) widgets: Button order, alignment if there is any excess space, whether or not to give all buttons the same size.

You might want to use one of the predefined static methods: [YButtonBox::kdeLayoutPolicy\(\)](#), [YButtonBox::gnomeLayoutPolicy\(\)](#).

The default [doLayout\(\)](#) method uses those values.

Notice that there is intentionally no way to set this differently for each individual [YButtonBox](#): This would defeat the purpose of consistency (with the desktop environment this application is running in), which is the reason for having this widget class.

Definition at line [82](#) of file [YButtonBox.cc](#).

Here is the call graph for this function:



3.19.3.18 void YButtonBox::setMargins (const YButtonBoxMargins & margins) [virtual]

Set the margins for this [YButtonBox](#).

Derived classes are free to reimplement this, but they should call this base class method in the new method.

Definition at line [139](#) of file [YButtonBox.cc](#).

Here is the call graph for this function:



3.19.3.19 void YButtonBox::setSanityCheckRelaxed (bool *relax* = true)

Relax the sanity check done in [sanityCheck\(\)](#): Do not enforce that there has to be a `YOKButton` and a `YCancelButton` if there is more than one button.

In very rare cases, it might be necessary to have a less stringent sanity check: There are some very few legitimate cases for having a `YButtonBox` with multiple buttons, yet without a `YCancelButton`.

Examples:

```
...message... <Countdown> [OK] [Stop]
```

```
...message... [OK] [Details]
```

In those cases, it makes sense to relax the sanity check.

Definition at line [591](#) of file [YButtonBox.cc](#).

3.19.3.20 void YButtonBox::setSize (int *newWidth*, int *newHeight*) [virtual]

Sets the size of the `YButtonBox`.


Derived classes can reimplement this, but this base class method should be called in the reimplemented function.

Reimplemented from `YWidget`.

Implements `YWidget`.

Definition at line [153](#) of file [YButtonBox.cc](#).

Here is the call graph for this function:



```
3.19.3.21 bool YButtonBox::stretchable ( YUIDimension dimension ) const
        [virtual]
```

Returns the stretchability of the `YButtonBox`. `YButtonBox` widgets are horizontally stretchable by default. How any excess space is used is specified in the layout policy.

Reimplemented from [YWidget](#).

Reimplemented from [YWidget](#).


Definition at line 559 of file YButtonBox.cc.

3.19.3.22 int YButtonBox::totalChildrenWidth () const [protected]

Return the sum of the (preferred) widths of all child widgets.

Definition at line 543 of file YButtonBox.cc.

Here is the call graph for this function:



3.19.3.23 `virtual const char* YButtonBox::widgetClass () const [inline, virtual]`

Return a descriptive name of this widget class for logging, debugging etc.

Reimplemented from [YWidget](#).

Definition at line 169 of file [YButtonBox.h](#).

The documentation for this class was generated from the following files:

- /usr/src/RPM/BUILD/libyui-3.0.10/src/YButtonBox.h
- /usr/src/RPM/BUILD/libyui-3.0.10/src/YButtonBox.cc

3.20 YButtonBoxLayoutPolicy Struct Reference

```
#include <YButtonBox.h>
```

Public Attributes

- YButtonOrder **buttonOrder**
- bool **equalSizeButtons**
- bool **addExcessSpaceToHelpButtonExtraMargin**
- YAlignmentType **alignment** [YUIAllDimensions]

3.20.1 Detailed Description

Helper class: Layout policy for [YButtonBox](#) widgets. This is used in the default [YButtonBox::doLayout\(\)](#) method.

Definition at line 41 of file [YButtonBox.h](#).

The documentation for this struct was generated from the following file:

- /usr/src/RPM/BUILD/libyui-3.0.10/src/YButtonBox.h

3.21 YButtonBoxMargins Struct Reference

```
#include <YButtonBox.h>
```

Public Attributes

- int **left**
- int **right**
- int **top**
- int **bottom**
- int **spacing**
- int **helpButtonExtraSpacing**

3.21.1 Detailed Description

Helper class: Margins for [YButtonBox](#) widgets. All sizes are in UI-dependent units, i.e. in pixels.


Definition at line 65 of file [YButtonBox.h](#).

The documentation for this struct was generated from the following file:

- /usr/src/RPM/BUILD/libyui-3.0.10/src/YButtonBox.h

3.22 YButtonBoxPrivate Struct Reference

Collaboration diagram for YButtonBoxPrivate:



Public Member Functions

- [YButtonBoxPrivate](#) ()

Public Attributes

- bool **sanityCheckRelaxed**
- [YButtonBoxMargins](#) **margins**

3.22.1 Detailed Description

Definition at line 45 of file [YButtonBox.cc](#).

3.22.2 Constructor & Destructor Documentation

3.22.2.1 YButtonBoxPrivate::YButtonBoxPrivate () [inline]

Constructor

Definition at line 50 of file [YButtonBox.cc](#).


The documentation for this struct was generated from the following file:

- /usr/src/RPM/BUILD/libyui-3.0.10/src/YButtonBox.cc


3.23 YCancelEvent Class Reference

```
#include <YEvent.h>
```

Inheritance diagram for YCancelEvent:



Collaboration diagram for YCancelEvent:



Protected Member Functions

- virtual [~YCancelEvent](#) ()

3.23.1 Detailed Description

Event to be returned upon closing a dialog with the window manager close button (or Alt-F4)

Definition at line 305 of file [YEvent.h](#).

3.23.2 Constructor & Destructor Documentation

3.23.2.1 virtual [YCancelEvent::~YCancelEvent](#) () [inline, protected, virtual]

Protected destructor - events can only be deleted via [YDialog::deleteEvent\(\)](#). The associated dialog will take care of this event and delete it when appropriate.


Definition at line 318 of file [YEvent.h](#).

The documentation for this class was generated from the following file:


- [/usr/src/RPM/BUILD/libyui-3.0.10/src/YEvent.h](#)

3.24 YCheckBox Class Reference

Inheritance diagram for YCheckBox:



Collaboration diagram for YCheckBox:



Public Member Functions

- virtual [~YCheckBox](#) ()
- virtual const char * [widgetClass](#) () const
- virtual YCheckBoxState [value](#) ()=0
- virtual void [setValue](#) (YCheckBoxState state)=0
- bool [isChecked](#) ()
- void [setChecked](#) (bool checked=true)

- bool [dontCare](#) ()
- void [setDontCare](#) ()
- std::string [label](#) () const
- virtual void [setLabel](#) (const std::string &[label](#))
- bool [useBoldFont](#) () const
- virtual void [setUseBoldFont](#) (bool bold=true)
- virtual bool [setProperty](#) (const std::string &propertyName, const [YPropertyValue](#) &val)
- virtual [YPropertyValue](#) [getProperty](#) (const std::string &propertyName)
- virtual const [YPropertySet](#) & [propertySet](#) ()
- virtual std::string [shortcutString](#) () const
- virtual void [setShortcutString](#) (const std::string &str)
- const char * [userInputProperty](#) ()

Protected Member Functions

- [YCheckBox](#) ([YWidget](#) *parent, const std::string &[label](#))

3.24.1 Detailed Description

Definition at line [43](#) of file [YCheckBox.h](#).

3.24.2 Constructor & Destructor Documentation

3.24.2.1 [YCheckBox::YCheckBox](#) ([YWidget](#) * *parent*, const std::string & *label*)
[protected]

Constructor.

Definition at line [45](#) of file [YCheckBox.cc](#).

3.24.2.2 [YCheckBox::~YCheckBox](#) () [virtual]

Destructor.

Definition at line [53](#) of file [YCheckBox.cc](#).

3.24.3 Member Function Documentation

3.24.3.1 bool [YCheckBox::dontCare](#) () [inline]

Simplified access to tri-state ("don't care").

Definition at line 109 of file [YCheckBox.h](#).

Here is the call graph for this function:



3.24.3.2 YPropertyValue YCheckBox::getProperty (const std::string & *propertyName*) [virtual]

Get a property. Reimplemented from [YWidget](#).


This method may throw exceptions, for example

- if there is no property with that name

Reimplemented from [YWidget](#).

Definition at line 121 of file [YCheckBox.cc](#).

Here is the call graph for this function:



3.24.3.3 bool YCheckBox::isChecked () [inline]

Simplified access to [value\(\)](#): Return 'true' if the CheckBox is checked.

Definition at line 98 of file [YCheckBox.h](#).

Here is the call graph for this function:



3.24.3.4 `std::string YCheckBox::label () const`

Get the label (the text on the CheckBox).

Definition at line 65 of file [YCheckBox.cc](#).

3.24.3.5 `const YPropertySet & YCheckBox::propertySet () [virtual]`

Return this class's property set. This also initializes the property set upon the first call.

Reimplemented from [YWidget](#).

Reimplemented from [YWidget](#).

Definition at line 84 of file [YCheckBox.cc](#).

Here is the call graph for this function:



3.24.3.6 void YCheckBox::setChecked (bool *checked* = true) [inline]

Simplified access to [setValue\(\)](#): Check or uncheck the CheckBox.

Definition at line 103 of file [YCheckBox.h](#).

Here is the call graph for this function:



3.24.3.7 void YCheckBox::setDontCare () [inline]

Simplified access to setting tri-state ("don't care").

Definition at line 114 of file [YCheckBox.h](#).

Here is the call graph for this function:



3.24.3.8 void YCheckBox::setLabel (const std::string & *label*) [virtual]

Set the label (the text on the CheckBox).

Derived classes are free to reimplement this, but they should call this base class method at the end of the overloaded function.

Definition at line 59 of file [YCheckBox.cc](#).

3.24.3.9 `bool YCheckBox::setProperty (const std::string & propertyName, const YPropertyValue & val) [virtual]`

Set a property. Reimplemented from [YWidget](#).

This method may throw exceptions, for example


- if there is no property with that name
- if the expected type and the type mismatch
- if the value is out of range

This function returns 'true' if the value was successfully set and 'false' if that value requires special handling (not in error cases: those are covered by exceptions).

Reimplemented from [YWidget](#).

Definition at line 105 of file [YCheckBox.cc](#).

Here is the call graph for this function:



3.24.3.10 `virtual void YCheckBox::setShortcutString (const std::string & str) [inline, virtual]`


Set the string of this widget that holds the keyboard shortcut.

Reimplemented from [YWidget](#).

Reimplemented from [YWidget](#).

Definition at line 187 of file [YCheckBox.h](#).

Here is the call graph for this function:



3.24.3.11 `void YCheckBox::setUseBoldFont (bool bold = true)` [virtual]

Indicate whether or not a bold font should be used.

Derived classes are free to reimplement this, but they should call this base class method at the end of the overloaded function.

Definition at line 77 of file [YCheckBox.cc](#).

3.24.3.12 `virtual void YCheckBox::setValue (YCheckBoxState state)` [pure virtual]

Set the CheckBox value (on/off/don't care).

Derived classes are required to implement this.

3.24.3.13 `virtual std::string YCheckBox::shortcutString () const` [inline, virtual]


Get the string of this widget that holds the keyboard shortcut.

Reimplemented from [YWidget](#).

Reimplemented from [YWidget](#).

Definition at line 180 of file [YCheckBox.h](#).

Here is the call graph for this function:



3.24.3.14 `bool YCheckBox::useBoldFont () const`

Returns 'true' if a bold font should be used.

Definition at line 71 of file [YCheckBox.cc](#).

3.24.3.15 `const char* YCheckBox::userInputProperty () [inline, virtual]`

The name of the widget property that will return user input. Inherited from [YWidget](#).

Reimplemented from [YWidget](#).

Definition at line 194 of file [YCheckBox.h](#).

3.24.3.16 `virtual YCheckBoxState YCheckBox::value () [pure virtual]`

Get the current value:

`YCheckBox_on` CheckBox is checked `YCheckBox_off` CheckBox is unchecked

`YCheckBox_dont_care` tri-state: CheckBox is greyed out, neither checked nor unchecked

The user cannot set `YCheckBox_dont_care` directly. This status is always only set from the outside, usually because a setting cannot be clearly determined. For example, a checkbox

[] Read only

would be set to "don't care" (by the application, not directly by the user) when it is to display the read-only state of a group of files where some are read-only and some are writeable.

Derived classes are required to implement this function. (Intentionally not const)

3.24.3.17 `virtual const char* YCheckBox::widgetClass () const` [inline, virtual]

Returns a descriptive name of this widget class for logging, debugging etc.

Reimplemented from [YWidget](#).


Definition at line 61 of file [YCheckBox.h](#).

The documentation for this class was generated from the following files:


- /usr/src/RPM/BUILD/libyui-3.0.10/src/YCheckBox.h
- /usr/src/RPM/BUILD/libyui-3.0.10/src/YCheckBox.cc

3.25 YCheckBoxFrame Class Reference

Inheritance diagram for YCheckBoxFrame:



Collaboration diagram for YCheckBoxFrame:



Public Member Functions

- [YCheckBoxFrame](#) ([YWidget](#) *parent, const std::string &label, bool checked)
- virtual [~YCheckBoxFrame](#) ()
- virtual const char * [widgetClass](#) () const
- std::string [label](#) () const
- virtual void [setLabel](#) (const std::string &label)
- virtual void [setValue](#) (bool isChecked)=0
- virtual bool [value](#) ()=0
- bool [autoEnable](#) () const
- virtual void [setAutoEnable](#) (bool autoEnable)
- bool [invertAutoEnable](#) () const
- virtual void [setInvertAutoEnable](#) (bool invertAutoEnable)
- void [handleChildrenEnablement](#) (bool isChecked)
- virtual std::string [shortcutString](#) () const
- virtual void [setShortcutString](#) (const std::string &str)
- const char * [userInputProperty](#) ()
- virtual bool [setProperty](#) (const std::string &propertyName, const [YPropertyValue](#) &val)
- virtual [YPropertyValue](#) [getProperty](#) (const std::string &propertyName)
- virtual const [YPropertySet](#) & [propertySet](#) ()

3.25.1 Detailed Description

Definition at line 35 of file [YCheckBoxFrame.h](#).

3.25.2 Constructor & Destructor Documentation

3.25.2.1 YCheckBoxFrame::YCheckBoxFrame (YWidget * *parent*, const std::string & *label*, bool *checked*)

Constructor.

Definition at line 49 of file [YCheckBoxFrame.cc](#).

3.25.2.2 YCheckBoxFrame::~YCheckBoxFrame () [virtual]

Destructor.

Definition at line 59 of file [YCheckBoxFrame.cc](#).

3.25.3 Member Function Documentation

3.25.3.1 bool YCheckBoxFrame::autoEnable () const

Handle children enabling/disabling automatically based on the CheckBoxFrame's check box?

Definition at line 75 of file [YCheckBoxFrame.cc](#).

3.25.3.2 YPropertyValue YCheckBoxFrame::getProperty (const std::string & *propertyName*) [virtual]

Get a property. Reimplemented from [YWidget](#).


This method may throw exceptions, for example

- if there is no property with that name

Reimplemented from [YWidget](#).

Definition at line 149 of file [YCheckBoxFrame.cc](#).

Here is the call graph for this function:



3.25.3.3 void YCheckBoxFrame::handleChildrenEnablement (bool isChecked)


Handle enabling/disabling of child widgets based on 'isChecked' (the current status of the check box) and [autoEnable\(\)](#) and [invertAutoEnable\(\)](#).

Derived classes should call this when the check box status changes rather than try to handle it on their level.

This method also needs to be called after new child widgets are added to establish the initial enabled or disabled state of the child widgets.

Definition at line 98 of file [YCheckBoxFrame.cc](#).

Here is the call graph for this function:



3.25.3.4 bool YCheckBoxFrame::invertAutoEnable () const

Invert the meaning of the CheckBoxFrame's check box, i.e., disable child widgets when checked?

Definition at line 86 of file [YCheckBoxFrame.cc](#).

3.25.3.5 `std::string YCheckBoxFrame::label () const`

Return the label text on the CheckBoxFrame.

Definition at line 65 of file [YCheckBoxFrame.cc](#).

3.25.3.6 `const YPropertySet & YCheckBoxFrame::propertySet () [virtual]`


Return this class's property set. This also initializes the property set upon the first call.

Reimplemented from [YWidget](#).

Reimplemented from [YWidget](#).

Definition at line 112 of file [YCheckBoxFrame.cc](#).

Here is the call graph for this function:



3.25.3.7 `void YCheckBoxFrame::setAutoEnable (bool autoEnable) [virtual]`

Change autoEnabled flag.

Derived classes are free to overload this, but they should call this base class function in the overloaded function.

Definition at line 80 of file [YCheckBoxFrame.cc](#).

Here is the call graph for this function:



3.25.3.8 void YCheckBoxFrame::setInvertAutoEnable (bool *invertAutoEnable*) [virtual]

Change invertAutoEnable flag.

Derived classes are free to overload this, but they should call this base class function in the overloaded function.

Definition at line 91 of file [YCheckBoxFrame.cc](#).

Here is the call graph for this function:



3.25.3.9 void YCheckBoxFrame::setLabel (const std::string & *label*) [virtual]

Change the label text on the CheckBoxFrame.

Derived classes should overload this, but call this base class function in the overloaded function.

Definition at line 70 of file [YCheckBoxFrame.cc](#).

Here is the call graph for this function:



3.25.3.10 bool YCheckBoxFrame::setProperty (const std::string & *propertyName*, const YPropertyValue & *val*) [virtual]

Set a property. Reimplemented from [YWidget](#).

This method may throw exceptions, for example


- if there is no property with that name
- if the expected type and the type mismatch
- if the value is out of range

This function returns 'true' if the value was successfully set and 'false' if that value requires special handling (not in error cases: those are covered by exceptions).

Reimplemented from [YWidget](#).

Definition at line 133 of file [YCheckBoxFrame.cc](#).

Here is the call graph for this function:



3.25.3.11 virtual void YCheckBoxFrame::setShortcutString (const std::string & str) [inline, virtual]


Set the string of this widget that holds the keyboard shortcut.

Reimplemented from [YWidget](#).

Reimplemented from [YWidget](#).

Definition at line 136 of file [YCheckBoxFrame.h](#).

Here is the call graph for this function:



3.25.3.12 `virtual void YCheckBoxFrame::setValue (bool isChecked)` [pure virtual]

Check or uncheck the `CheckBoxFrame`'s check box.

Derived classes are required to implement this.

3.25.3.13 `virtual std::string YCheckBoxFrame::shortcutString () const` [inline, virtual]


Get the string of this widget that holds the keyboard shortcut.

Reimplemented from [YWidget](#).

Reimplemented from [YWidget](#).

Definition at line 129 of file [YCheckBoxFrame.h](#).

Here is the call graph for this function:



3.25.3.14 `const char* YCheckBoxFrame::userInputProperty ()` [inline, virtual]

The name of the widget property that will return user input. Inherited from [YWidget](#).

Reimplemented from [YWidget](#).

Definition at line 143 of file [YCheckBoxFrame.h](#).

3.25.3.15 `virtual bool YCheckBoxFrame::value () [pure virtual]`

Get the status of the CheckBoxFrame's check box.

Derived classes are required to implement this.

3.25.3.16 `virtual const char* YCheckBoxFrame::widgetClass () const [inline, virtual]`

Returns a descriptive name of this widget class for logging, debugging etc.

Reimplemented from [YWidget](#).

Definition at line 54 of file [YCheckBoxFrame.h](#).

The documentation for this class was generated from the following files:

- `/usr/src/RPM/BUILD/libyui-3.0.10/src/YCheckBoxFrame.h`
- `/usr/src/RPM/BUILD/libyui-3.0.10/src/YCheckBoxFrame.cc`

3.26 YCheckBoxFramePrivate Struct Reference

Public Member Functions

- **YCheckBoxFramePrivate** (const std::string &label)

Public Attributes

- std::string **label**
- bool **autoEnable**
- bool **invertAutoEnable**

3.26.1 Detailed Description

Definition at line 33 of file [YCheckBoxFrame.cc](#).

The documentation for this struct was generated from the following file:

- `/usr/src/RPM/BUILD/libyui-3.0.10/src/YCheckBoxFrame.cc`

3.27 YCheckBoxPrivate Struct Reference

Public Member Functions

- **YCheckBoxPrivate** (const std::string &label)

Public Attributes

- std::string **label**
- bool **useBoldFont**

3.27.1 Detailed Description

Definition at line 33 of file [YCheckBox.cc](#).


The documentation for this struct was generated from the following file:

- /usr/src/RPM/BUILD/libyui-3.0.10/src/YCheckBox.cc

3.28 YChildrenManager< T > Class Template Reference

```
#include <YChildrenManager.h>
```

Inheritance diagram for YChildrenManager< T >:



Public Types

- typedef std::list< T * > **ChildrenList**

Public Member Functions

- [YChildrenManager](#) (T *containerParent)
- virtual [~YChildrenManager](#) ()
- bool [hasChildren](#) () const
- bool [empty](#) () const
- int [count](#) () const
- ChildrenList::const_iterator [begin](#) () const
- ChildrenList::const_iterator [end](#) () const
- ChildrenList::const_reverse_iterator [rbegin](#) () const
- ChildrenList::const_reverse_iterator [rend](#) () const
- T * [firstChild](#) ()
- T * [lastChild](#) ()
- virtual void [add](#) (T *child)
- virtual void [remove](#) (T *child)
- virtual void [clear](#) ()
- bool [contains](#) (T *child) const
- T * [container](#) () const

Protected Attributes

- T * [_container](#)
- ChildrenList [_children](#)

3.28.1 Detailed Description

```
template<class T>class YChildrenManager< T >
```

Abstract base template class for children management, such as child widgets.

Definition at line 37 of file [YChildrenManager.h](#).

3.28.2 Constructor & Destructor Documentation

3.28.2.1 `template<class T > YChildrenManager< T >::YChildrenManager (T *
containerParent) [inline]`

Constructor.

'containerParent' is the class whose children are managed.

Definition at line 46 of file [YChildrenManager.h](#).

3.28.2.2 `template<class T> virtual YChildrenManager< T>::~~YChildrenManager () [inline, virtual]`

Destructor.

Definition at line 53 of file [YChildrenManager.h](#).

3.28.3 Member Function Documentation

3.28.3.1 `template<class T> virtual void YChildrenManager< T>::add (T * child) [inline, virtual]`

Add a new child.

This may throw exceptions if more children are added than the class whose children are handled (the associated widget) can handle.

Reimplemented in [YChildrenRejector< T>](#), and [YSingleChildManager< T>](#).

Definition at line 116 of file [YChildrenManager.h](#).

3.28.3.2 `template<class T> ChildrenList::const_iterator YChildrenManager< T>::begin () const [inline]`

Return an iterator that points to the first child.

Definition at line 76 of file [YChildrenManager.h](#).

3.28.3.3 `template<class T> virtual void YChildrenManager< T>::clear () [inline, virtual]`

Remove all children. This only removes the children from the children manager's list; it does not delete them.

Definition at line 130 of file [YChildrenManager.h](#).

3.28.3.4 `template<class T> T* YChildrenManager< T>::container () const [inline]`

Returns the associated container, i.e. the object whose children are handled here.

Definition at line 148 of file [YChildrenManager.h](#).

3.28.3.5 `template<class T> bool YChildrenManager< T >::contains (T * child) const`
`[inline]`

Check if the children list contains the specified child. Returns 'true' if the children list contains the child, 'false' otherwise.

Definition at line 138 of file [YChildrenManager.h](#).

3.28.3.6 `template<class T> int YChildrenManager< T >::count () const`
`[inline]`

Returns the number of children.

Definition at line 71 of file [YChildrenManager.h](#).

3.28.3.7 `template<class T> bool YChildrenManager< T >::empty () const`
`[inline]`

Check if the children list is empty, i.e. if there are no children.

Definition at line 66 of file [YChildrenManager.h](#).

3.28.3.8 `template<class T> ChildrenList::const_iterator YChildrenManager< T >::end () const` `[inline]`

Return an iterator that points after the last child.

Definition at line 82 of file [YChildrenManager.h](#).

3.28.3.9 `template<class T> T* YChildrenManager< T >::firstChild ()` `[inline]`

Returns the first child or 0 if there is none. Useful mostly for children managers that handle only one child.


Definition at line 101 of file [YChildrenManager.h](#).

3.28.3.10 `template<class T> bool YChildrenManager< T >::hasChildren () const`
`[inline]`

Check if there are any children.

Definition at line 61 of file [YChildrenManager.h](#).

Here is the call graph for this function:



3.28.3.11 `template<class T> T* YChildrenManager<T>::lastChild () [inline]`

Returns the last child or 0 if there is none.

Definition at line 107 of file [YChildrenManager.h](#).

3.28.3.12 `template<class T> ChildrenList::const_reverse_iterator YChildrenManager<T>::rbegin () const [inline]`

Return a reverse iterator that points to the last child.

Definition at line 88 of file [YChildrenManager.h](#).

3.28.3.13 `template<class T> virtual void YChildrenManager<T>::remove (T* child) [inline, virtual]`

Remove a child. This only removes the child from the children manager's list; it does not delete it.

Definition at line 123 of file [YChildrenManager.h](#).

3.28.3.14 `template<class T> ChildrenList::const_reverse_iterator YChildrenManager<T>::rend () const [inline]`

Return a reverse iterator that points before the first child.

Definition at line 94 of file [YChildrenManager.h](#).


The documentation for this class was generated from the following file:

- `/usr/src/RPM/BUILD/libyui-3.0.10/src/YChildrenManager.h`


3.29 YChildrenRejector< T > Class Template Reference

```
#include <YChildrenManager.h>
```

Inheritance diagram for YChildrenRejector< T >:



Collaboration diagram for YChildrenRejector< T >:



Public Member Functions

- [YChildrenRejector](#) (T *containerParent)
- virtual void [add](#) (T *child)

3.29.1 Detailed Description

```
template<class T>class YChildrenRejector< T >
```

Children manager that rejects all children.

Useful for widget classes that can't handle children such as [YPushButton](#), [YSelection-Box](#) etc.

Definition at line [202](#) of file [YChildrenManager.h](#).

3.29.2 Constructor & Destructor Documentation

3.29.2.1

```
template<class T > YChildrenRejector< T >::YChildrenRejector ( T *  
containerParent ) [inline]
```

Constructor.

Definition at line [208](#) of file [YChildrenManager.h](#).

3.29.3 Member Function Documentation

3.29.3.1

```
template<class T > virtual void YChildrenRejector< T >::add ( T * child )  
[inline, virtual]
```

Add a new child.

Reimplemented from [YChildrenManager](#).

Since this class is designed to reject children, this always throws a [YUITooMany-ChildrenException](#).

Reimplemented from [YChildrenManager< T >](#).

Definition at line [220](#) of file [YChildrenManager.h](#).

Here is the call graph for this function:



The documentation for this class was generated from the following file:

- /usr/src/RPM/BUILD/libyui-3.0.10/src/YChildrenManager.h

3.30 YCodeLocation Class Reference

```
#include <YUIException.h>
```

Public Member Functions

- [YCodeLocation](#) (const std::string &file_r, const std::string &func_r, int line_r)
- [YCodeLocation](#) ()
- std::string [file](#) () const
- std::string [func](#) () const
- int [line](#) () const
- std::string [asString](#) () const

Friends

- std::ostream & [operator<<](#) (std::ostream &str, const [YCodeLocation](#) &obj)

3.30.1 Detailed Description

Helper class for UI exceptions: Store `_FILE_`, `_FUNCTION_` and `_LINE_`. Construct this using the `YUI_EXCEPTION_CODE_LOCATION` macro.

Definition at line 213 of file [YUIException.h](#).

3.30.2 Constructor & Destructor Documentation

3.30.2.1 [YCodeLocation::YCodeLocation](#) (const std::string &file_r, const std::string &func_r, int line_r) [inline]

Constructor. Commonly called using the `YUI_EXCEPTION_CODE_LOCATION` macro.

Definition at line 220 of file [YUIException.h](#).

3.30.2.2 [YCodeLocation::YCodeLocation](#) () [inline]

Default constructor.

Definition at line 231 of file [YUIException.h](#).

3.30.3 Member Function Documentation

3.30.3.1 `std::string YCodeLocation::asString () const`

Returns the location in normalized string format.

Definition at line 41 of file [YUIException.cc](#).

3.30.3.2 `std::string YCodeLocation::file () const` `[inline]`

Returns the source file name where the exception occurred.

Definition at line 238 of file [YUIException.h](#).

3.30.3.3 `std::string YCodeLocation::func () const` `[inline]`

Returns the name of the function where the exception occurred.

Definition at line 243 of file [YUIException.h](#).

3.30.3.4 `int YCodeLocation::line () const` `[inline]`

Returns the source line number where the exception occurred.

Definition at line 248 of file [YUIException.h](#).

3.30.4 Friends And Related Function Documentation

3.30.4.1 `std::ostream& operator<< (std::ostream & str, const YCodeLocation & obj)` `[friend]`

Stream output

[YCodeLocation](#) stream output

Definition at line 56 of file [YUIException.cc](#).

The documentation for this class was generated from the following files:

- `/usr/src/RPM/BUILD/libyui-3.0.10/src/YUIException.h`
- `/usr/src/RPM/BUILD/libyui-3.0.10/src/YUIException.cc`

3.31 YColor Class Reference

```
#include <YColor.h>
```

Public Member Functions

- [YColor](#) (uchar [red](#), uchar [green](#), uchar [blue](#))
- [YColor](#) ()
- uchar [red](#) () const
- uchar [green](#) () const
- uchar [blue](#) () const
- bool [isUndefined](#) () const
- bool [isDefined](#) () const

3.31.1 Detailed Description

Helper class to define an RGB color.

Definition at line [34](#) of file [YColor.h](#).

3.31.2 Constructor & Destructor Documentation

3.31.2.1 [YColor::YColor](#) (uchar *red*, uchar *green*, uchar *blue*) [[inline](#)]

Constructor.

Definition at line [40](#) of file [YColor.h](#).

3.31.2.2 [YColor::YColor](#) () [[inline](#)]

Default constructor: Create "undefined" color.

Definition at line [50](#) of file [YColor.h](#).

3.31.3 Member Function Documentation

3.31.3.1 uchar [YColor::blue](#) () const [[inline](#)]

Return the blue component (0: none, 255: bright blue).

Definition at line [68](#) of file [YColor.h](#).

3.31.3.2 uchar YColor::green () const [inline]

Return the green component (0: none, 255: bright green).

Definition at line 63 of file [YColor.h](#).

3.31.3.3 bool YColor::isDefined () const [inline]

Return 'true' if this color is defined.

Definition at line 78 of file [YColor.h](#).

3.31.3.4 bool YColor::isUndefined () const [inline]

Return 'true' if this color is undefined.

Definition at line 73 of file [YColor.h](#).

3.31.3.5 uchar YColor::red () const [inline]

Return the red component (0: none, 255: bright red).

Definition at line 58 of file [YColor.h](#).


The documentation for this class was generated from the following file:

- [/usr/src/RPM/BUILD/libyui-3.0.10/src/YColor.h](#)


3.32 YComboBox Class Reference

```
#include <YComboBox.h>
```

Inheritance diagram for YComboBox:



Collaboration diagram for YComboBox:



Public Member Functions

- virtual `~YComboBox()`
- virtual const char * `widgetClass()` const
- bool `editable()` const
- std::string `value()`
- void `setValue(const std::string &newText)`
- virtual YItem * `selectedItem()`
- virtual YItemCollection `selectedItems()`
- virtual void `selectItem(YItem *item, bool selected=true)`
- std::string `validChars()`
- virtual void `setValidChars(const std::string &validChars)`
- int `inputMaxLength()` const
- virtual void `setInputMaxLength(int numberOfChars)`
- virtual bool `setProperty(const std::string &propertyName, const YPropertyValue &val)`
- virtual YPropertyValue `getProperty(const std::string &propertyName)`
- virtual const YPropertySet & `propertySet()`
- const char * `userInputProperty()`

Protected Member Functions

- YComboBox(YWidget *parent, const std::string &label, bool editable)
- virtual std::string `text()`=0
- virtual void `setText(const std::string &newText)`=0

3.32.1 Detailed Description

ComboBox (a.k.a. "drop down box", "drop down selection"):

A widget with a drop-down list of predefined values to select from. Optionally, this widget can be created in "editable" mode which means that the user can freely enter any text.

In non-editable mode, a ComboBox works very much like a SelectionBox that uses fewer screen space. In that mode, it is recommended to use `selectedItem()` to retrieve its current value and `selectItem()` to set it.

In editable mode, a ComboBox is more like an InputField with a list to pick predefined values from (for less typing). In that mode, it is recommended to use `value()` and `setValue()`.

In either mode, it might be dangerous to use the iterators the (`itemsBegin()`, `itemsEnd()`) the base class (`YSelectionWidget`) provides to find the currently selected item: The items' "selected" flag may or may not be up to date. `YComboBox::selectedItem()` makes sure they are up to date.

Definition at line 53 of file `YComboBox.h`.

3.32.2 Constructor & Destructor Documentation

3.32.2.1 YComboBox::YComboBox (YWidget * *parent*, const std::string & *label*, bool *editable*) [protected]

Constructor.

'editable' means the user can freely enter any value without being restricted to the items of the ComboBox's list.

Definition at line 49 of file [YComboBox.cc](#).

3.32.2.2 YComboBox::~YComboBox () [virtual]

Destructor.

Definition at line 58 of file [YComboBox.cc](#).

3.32.3 Member Function Documentation

3.32.3.1 bool YComboBox::editable () const

Return 'true' if this ComboBox is editable, i.e. if the user can freely enter any value without being restricted to the items of the ComboBox's list.

Notice that this can only be set in the constructor.

Definition at line 64 of file [YComboBox.cc](#).

3.32.3.2 YPropertyValue YComboBox::getProperty (const std::string & *propertyName*) [virtual]


Get a property. Reimplemented from [YWidget](#).

This method may throw YUIPropertyExceptions.

Reimplemented from [YWidget](#).

Definition at line 220 of file [YComboBox.cc](#).

Here is the call graph for this function:



3.32.3.3 `int YComboBox::inputMaxLength () const`

The maximum input length, i.e., the maximum number of characters the user can enter. -1 means no limit.

This is only meaningful for if the ComboBox is editable.

Definition at line 82 of file [YComboBox.cc](#).

3.32.3.4 `const YPropertySet & YComboBox::propertySet () [virtual]`

Return this class's property set. This also initializes the property upon the first call.

Reimplemented from [YWidget](#).

Reimplemented from [YWidget](#).

Definition at line 172 of file [YComboBox.cc](#).

Here is the call graph for this function:



3.32.3.5 YItem * YComboBox::selectedItem () [virtual]


Return the (first) selected item or 0 if none is selected or if this ComboBox is editable and the user entered something that does not match any of the ComboBox's list items (in that case, use `value()` instead).

Reimplemented from `YSelectionWidget` for better reliability: This will compare an editable ComboBox's user input against the text labels of all items and try to return an item if there is any match.

Reimplemented from `YSelectionWidget`.

Definition at line 136 of file `YComboBox.cc`.

Here is the call graph for this function:



3.32.3.6 YItemCollection YComboBox::selectedItems () [virtual]

Return all selected items.

This is not particularly useful for ComboBoxes since there can be no more than one selected item anyway; * better use [selectedItem\(\)](#) or [value\(\)](#) instead.


This function does not transfer ownership of those items to the caller, so don't try to delete them!

Reimplemented from [YSelectionWidget](#) for better reliability.

Reimplemented from [YSelectionWidget](#).

Definition at line 157 of file [YComboBox.cc](#).

Here is the call graph for this function:



3.32.3.7 `void YComboBox::selectItem (YItem * item, bool selected = true)`
`[virtual]`


Select or deselect an item. See also [setValue\(\)](#).

Reimplemented from [YSelectionWidget](#).

Reimplemented from [YSelectionWidget](#).

Definition at line 122 of file [YComboBox.cc](#).

Here is the call graph for this function:



3.32.3.8 `void YComboBox::setInputMaxLength (int numberOfChars) [virtual]`

Set the maximum input length, i.e., the maximum number of characters the user can enter. -1 means no limit.

This is only meaningful for if the ComboBox is editable.

Derived classes are free to reimplement this, but they should call this base class method at the end of the overloaded function.

Definition at line 88 of file [YComboBox.cc](#).

3.32.3.9 `bool YComboBox::setProperty (const std::string & propertyName, const YPropertyValue & val) [virtual]`

Set a property. Reimplemented from [YWidget](#).


This function may throw `YUIPropertyExceptions`.

This function returns 'true' if the value was successfully set and 'false' if that value requires special handling (not in error cases: those are covered by exceptions).

Reimplemented from [YWidget](#).

Definition at line 200 of file [YComboBox.cc](#).

Here is the call graph for this function:



3.32.3.10 `virtual void YComboBox::setText (const std::string & newText)`
`[protected, pure virtual]`

Set this ComboBox's current value as text.

Called internally whenever the content is to change programmatically. Don't call `setValue()` or `selectItem()` from here.

Derived classes are required to implement this function.

3.32.3.11 `void YComboBox::setValidChars (const std::string & validChars)`
`[virtual]`

Set the valid input characters. No input validation is performed (i.e., the user can enter anything) if this is empty.

This is only meaningful for if the ComboBox is editable.

Derived classes are free to reimplement this, but they should call this base class method at the end of the overloaded function.

Definition at line 76 of file `YComboBox.cc`.

3.32.3.12 void YComboBox::setValue (const std::string & newText)


Set the value of this ComboBox by string: Try to find a list item with that label and select it.

If there is no matching list item, editable ComboBoxes will set their input field to that text. Non-editable ComboBoxes will throw an exception.

See also [selectItem\(\)](#).

Definition at line 100 of file [YComboBox.cc](#).

Here is the call graph for this function:



3.32.3.13 virtual std::string YComboBox::text () [protected, pure virtual]

Return this ComboBox's current value as text.

Called internally from [value\(\)](#), [selectedItem\(\)](#) and related.

Derived classes are required to implement this function.

3.32.3.14 const char* YComboBox::userInputProperty () [inline, virtual]

The name of the widget property that will return user input. Inherited from [YWidget](#).

Reimplemented from [YWidget](#).

Definition at line 211 of file [YComboBox.h](#).

3.32.3.15 `std::string YComboBox::validChars ()`

Get the valid input characters. No input validation is performed (i.e., the user can enter anything) if this is empty.

This is only meaningful for if the ComboBox is editable.

Definition at line 70 of file [YComboBox.cc](#).

3.32.3.16 `std::string YComboBox::value ()`

Return the value of this ComboBox:

The text of a list item if the user (or the application) selected a list item or the content of the ComboBox's input field if the ComboBox is editable and the user (or the application) entered text there.

See also [YComboBox::selectedItem\(\)](#).

Definition at line 94 of file [YComboBox.cc](#).

Here is the call graph for this function:



3.32.3.17 `virtual const char* YComboBox::widgetClass () const` [inline, virtual]

Returns a descriptive name of this widget class for logging, debugging etc.

Reimplemented from [YSelectionWidget](#).

Definition at line 74 of file [YComboBox.h](#).

The documentation for this class was generated from the following files:

- `/usr/src/RPM/BUILD/libyui-3.0.10/src/YComboBox.h`
- `/usr/src/RPM/BUILD/libyui-3.0.10/src/YComboBox.cc`

3.33 YComboBoxPrivate Struct Reference

Public Member Functions

- **YComboBoxPrivate** (bool editable)

Public Attributes

- bool **editable**
- std::string **validChars**
- int **inputMaxLength**

3.33.1 Detailed Description

Definition at line 34 of file [YComboBox.cc](#).

The documentation for this struct was generated from the following file:

- /usr/src/RPM/BUILD/libyui-3.0.10/src/YComboBox.cc

3.34 YCommandLine Class Reference

```
#include <YCommandLine.h>
```

Public Member Functions

- [YCommandLine](#) ()
- [~YCommandLine](#) ()
- int [argc](#) () const
- char ** [argv](#) () const
- int [size](#) () const
- std::string [arg](#) (int index) const
- std::string [operator\[\]](#) (int index) const
- void [add](#) (const std::string &[arg](#))
- void [remove](#) (int index)
- void [replace](#) (int index, const std::string &[arg](#))
- int [find](#) (const std::string &argName) const

3.34.1 Detailed Description

Utility class to access `/proc/<pid>/cmdline` to retrieve `argc` and `argv`

Definition at line 37 of file [YCommandLine.h](#).


3.34.2 Constructor & Destructor Documentation

3.34.2.1 `YCommandLine::YCommandLine ()`

Constructor. This will read `/proc/<pid>/cmdline` of this process.

Definition at line 48 of file [YCommandLine.cc](#).

Here is the call graph for this function:



3.34.2.2 `YCommandLine::~~YCommandLine ()`

Destructor.

Definition at line 71 of file [YCommandLine.cc](#).

3.34.3 Member Function Documentation

3.34.3.1 `void YCommandLine::add (const std::string & arg)`

Add a command line argument (at the end of the existing ones).

Definition at line 102 of file [YCommandLine.cc](#).

3.34.3.2 `std::string YCommandLine::arg (int index) const`

Return command line argument no. 'index' (from 0 on).

This might throw an [YUIIndexOutOfRangeException](#).

Definition at line 109 of file [YCommandLine.cc](#).

3.34.3.3 int YCommandLine::argc () const

Return the number of arguments in the command line. Remember that the command itself (the binary of the process) is included, so a value of 1 (not 0!) means "no additional arguments".

Definition at line 78 of file [YCommandLine.cc](#).

3.34.3.4 char ** YCommandLine::argv () const

Return the arguments in a C compatible fashion: An array of pointers to characters. The data are copied with `strdup()`, so they are valid beyond the life time of this object (but OTOH should be released with `free()` at some point).

Definition at line 85 of file [YCommandLine.cc](#).

Here is the call graph for this function:



3.34.3.5 int YCommandLine::find (const std::string & argName) const

Find a command line argument 'argName' ("-display" etc.). Notice that leading minus signs must be specified in 'argName'. Since `argv[0]` is the program name, the search starts from `argv[1]`.

Return the position of 'argName' (from 0 on) or -1 if not found.

Definition at line 136 of file [YCommandLine.cc](#).

Here is the call graph for this function:



3.34.3.6 `std::string YCommandLine::operator[] (int index) const` `[inline]`

Return command line argument no. 'index' (from 0 on) as operator[]:

```
for ( int i=0; i < cmdLine.argc(); i++ ) cout << cmdLine[i] << std::endl;
```

This might throw an [YUIIndexOutOfRangeException](#).

Definition at line 85 of file [YCommandLine.h](#).

Here is the call graph for this function:



3.34.3.7 `void YCommandLine::remove (int index)`

Remove command line argument no. 'index' (from 0 on).

This might throw an [YUIIndexOutOfRangeException](#).

Definition at line 118 of file [YCommandLine.cc](#).

3.34.3.8 void YCommandLine::replace (int *index*, const std::string & *arg*)

Replace command line argument no. 'index' (from 0 on) with 'arg'.

This might throw an [YUIIndexOutOfRangeException](#).

Definition at line 127 of file [YCommandLine.cc](#).

3.34.3.9 int YCommandLine::size () const [inline]

Alias for [argc\(\)](#) for those who like a more C++ -like syntax.

Definition at line 68 of file [YCommandLine.h](#).

Here is the call graph for this function:



The documentation for this class was generated from the following files:

- [/usr/src/RPM/BUILD/libyui-3.0.10/src/YCommandLine.h](#)
- [/usr/src/RPM/BUILD/libyui-3.0.10/src/YCommandLine.cc](#)

3.35 YCommandLinePrivate Struct Reference

Public Attributes

- std::vector< std::string > **args**

3.35.1 Detailed Description

Definition at line 39 of file [YCommandLine.cc](#).


The documentation for this struct was generated from the following file:

- [/usr/src/RPM/BUILD/libyui-3.0.10/src/YCommandLine.cc](#)


3.36 YContextMenu Class Reference

```
#include <YContextMenu.h>
```

Inheritance diagram for YContextMenu:



Collaboration diagram for YContextMenu:



Public Member Functions

- virtual [~YContextMenu](#) ()
- virtual const char * [widgetClass](#) () const
- virtual void [rebuildMenuTree](#) ()=0
- virtual void [addItems](#) (const YItemCollection &itemCollection)
- virtual void [addItem](#) (YItem *item_disown)
- virtual void [deleteAllItems](#) ()
- void [resolveShortcutConflicts](#) ()
- virtual bool [setProperty](#) (const std::string &propertyName, const YPropertyValue &val)
- virtual YPropertyValue [getProperty](#) (const std::string &propertyName)
- virtual const YPropertySet & [propertySet](#) ()

Protected Member Functions

- [YContextMenu](#) ()
- YMenuItem * [findMenuItem](#) (int index)
- YMenuItem * [findMenuItem](#) (int index, YItemConstIterator begin, YItemConstIterator end)
- YMenuItem * [itemAt](#) (int index)

3.36.1 Detailed Description

ContextMenu: Similar to PushButton, but with several actions: Upon clicking on a - ContextMenu (or activating it with the keyboard), a pop-up menu opens where the user can activate an action. Menu items in that pop-up menu can have submenus (that will pop up in separate pop-up menus).

Internally, this widget is more similar to the Tree widget. The difference is that it does not keep a "selected" status, but triggers an action right away, just like a PushButton. Like PushButton, ContextMenu sends an event right away when the user selects an item (clicks on a menu item or activates it with the keyboard). Items that have a submenu never send an event, they simply open their submenu when activated.

Definition at line 48 of file [YContextMenu.h](#).

3.36.2 Constructor & Destructor Documentation

3.36.2.1 YContextMenu::YContextMenu () [protected]

Constructor.

'label' is the user-visible text on the button (not above it like all other SelectionWidgets).

Definition at line 46 of file [YContextMenu.cc](#).

3.36.2.2 YContextMenu::~YContextMenu () [virtual]

Destructor.

Definition at line 55 of file [YContextMenu.cc](#).

3.36.3 Member Function Documentation

3.36.3.1 void YContextMenu::addItem (YItem * *item_disown*) [virtual]

Add one item. This widget assumes ownership of the item object and will delete it in its destructor.


This reimplementation will an index to the item that is unique for all items in this Context-Menu. That index can be used later with [findMenuItem\(\)](#) to find the item by that index.

Reimplemented from [YSelectionWidget](#).

Reimplemented from [YSelectionWidget](#).

Definition at line 71 of file [YContextMenu.cc](#).

Here is the call graph for this function:



3.36.3.2 void YContextMenu::addItem (const YItemCollection & itemCollection) [virtual]

Add multiple items. For some UIs, this can be more efficient than calling `addItem()` multiple times. This function also automatically calls `resolveShortcutConflicts()` and `rebuildMenuTree()` at the end.


Derived classes can overwrite this function, but they should call this base class function at the end of the new implementation.

Reimplemented from `YSelectionWidget`.

Reimplemented from `YSelectionWidget`.

Definition at line 62 of file `YContextMenu.cc`.

Here is the call graph for this function:



3.36.3.3 void YContextMenu::deleteAllItems () [virtual]

Delete all items.

Reimplemented from [YSelectionWidget](#).

Reimplemented from [YSelectionWidget](#).


Definition at line 97 of file [YContextMenu.cc](#).

3.36.3.4 YMenuItem * YContextMenu::findMenuItem (int index) [protected]

Recursively find the first menu item with the specified index. Returns 0 if there is no such item.

Definition at line 105 of file [YContextMenu.cc](#).

Here is the call graph for this function:




3.36.3.5 YMenuItem * YContextMenu::findMenuItem (int index, YItemConstIterator begin, YItemConstIterator end) [protected]

Recursively find the first menu item with the specified index from iterator 'begin' to iterator 'end'.

Returns 0 if there is no such item.

Definition at line 112 of file [YContextMenu.cc](#).

Here is the call graph for this function:



3.36.3.6 YPropertyValue YContextMenu::getProperty (const std::string & *propertyName*) [virtual]


Get a property. Reimplemented from [YWidget](#).

This method may throw `YUIPropertyExceptions`.

Reimplemented from [YWidget](#).

Definition at line 192 of file [YContextMenu.cc](#).

Here is the call graph for this function:



3.36.3.7 `YMenuItem* YContextMenu::itemAt (int index)` [`inline`,
`protected`]

Alias for [findMenuItem\(\)](#). Reimplemented to ensure consistent behaviour with [YSelectionWidget::itemAt\(\)](#).

Definition at line 170 of file [YContextMenu.h](#).

Here is the call graph for this function:



3.36.3.8 `const YPropertySet & YContextMenu::propertySet ()` [`virtual`]


Return this class's property set. This also initializes the property upon the first call.

Reimplemented from [YWidget](#).

Reimplemented from [YWidget](#).

Definition at line 153 of file [YContextMenu.cc](#).

Here is the call graph for this function:



3.36.3.9 `virtual void YContextMenu::rebuildMenuTree ()` [`pure virtual`]

Rebuild the displayed menu tree from the internally stored `YMenuItems`.

The application should call this (once) after all items have been added with [addItem\(\)](#). [YContextMenu::addItem\(\)](#) calls this automatically.

Derived classes are required to implement this.

3.36.3.10 void YContextMenu::resolveShortcutConflicts ()

Resolve keyboard shortcut conflicts: Change shortcuts of menu items if there are duplicates in the respective menu level.

This has to be called after all items are added, but before [rebuildMenuTree\(\)](#) (see above). [YContextMenu::addItem\(\)](#) calls this automatically.

Definition at line 138 of file [YContextMenu.cc](#).

3.36.3.11 bool YContextMenu::setProperty (const std::string & *propertyName*, const YPropertyValue & *val*) [virtual]

Set a property. Reimplemented from [YWidget](#).


This function may throw YUIPropertyExceptions.

This function returns 'true' if the value was successfully set and 'false' if that value requires special handling (not in error cases: those are covered by exceptions).

Reimplemented from [YWidget](#).

Definition at line 175 of file [YContextMenu.cc](#).

Here is the call graph for this function:



3.36.3.12 `virtual const char* YContextMenu::widgetClass () const` `[inline, virtual]`

Returns a descriptive name of this widget class for logging, debugging etc.

Reimplemented from [YSelectionWidget](#).

Definition at line 69 of file [YContextMenu.h](#).

The documentation for this class was generated from the following files:

- [/usr/src/RPM/BUILD/libyui-3.0.10/src/YContextMenu.h](#)
- [/usr/src/RPM/BUILD/libyui-3.0.10/src/YContextMenu.cc](#)

3.37 YContextMenuPrivate Struct Reference

Public Attributes

- `int nextSerialNo`

3.37.1 Detailed Description

Definition at line 34 of file [YContextMenu.cc](#).


The documentation for this struct was generated from the following file:

- [/usr/src/RPM/BUILD/libyui-3.0.10/src/YContextMenu.cc](#)


3.38 YDateField Class Reference

```
#include <YDateField.h>
```

Inheritance diagram for YDateField:



Collaboration diagram for YDateField:



Public Member Functions

- virtual [~YDateField](#) ()
- virtual const char * [widgetClass](#) () const

Protected Member Functions

- [YDateField](#) ([YWidget](#) *[parent](#), const std::string &[label](#))

3.38.1 Detailed Description

Input field for entering a date.

Derived classes are required to implement: [value\(\)](#) [setValue\(\)](#)

For both methods the date is formatted as "YYYY-MM-DD". See [YSimpleInputField.h](#) for more details.

Definition at line [42](#) of file [YDateField.h](#).

3.38.2 Constructor & Destructor Documentation

3.38.2.1 [YDateField::YDateField](#) ([YWidget](#) * *parent*, const std::string & *label*)
[protected]

Constructor.

Definition at line [43](#) of file [YDateField.cc](#).

3.38.2.2 [YDateField::~~YDateField](#) () [virtual]

Destructor.

Definition at line [51](#) of file [YDateField.cc](#).

3.38.3 Member Function Documentation

3.38.3.1 virtual const char* [YDateField::widgetClass](#) () const [inline, virtual]

Returns a descriptive name of this widget class for logging, debugging etc.

Reimplemented from [YWidget](#).

Definition at line [60](#) of file [YDateField.h](#).

The documentation for this class was generated from the following files:

- /usr/src/RPM/BUILD/libyui-3.0.10/src/YDateField.h
- /usr/src/RPM/BUILD/libyui-3.0.10/src/YDateField.cc

3.39 YDateFieldPrivate Struct Reference

Public Attributes

- bool **dummy**

3.39.1 Detailed Description

Definition at line 32 of file [YDateField.cc](#).


The documentation for this struct was generated from the following file:

- /usr/src/RPM/BUILD/libyui-3.0.10/src/YDateField.cc


3.40 YDebugEvent Class Reference

```
#include <YEvent.h>
```

Inheritance diagram for YDebugEvent:



Collaboration diagram for YDebugEvent:



Protected Member Functions

- virtual [~YDebugEvent](#) ()

3.40.1 Detailed Description

Event to be returned upon closing a dialog with the window manager close button (or Alt-F4)

Definition at line [326](#) of file [YEvent.h](#).

3.40.2 Constructor & Destructor Documentation

3.40.2.1 `virtual YDebugEvent::~~YDebugEvent () [inline, protected, virtual]`

Protected destructor - events can only be deleted via [YDialog::deleteEvent\(\)](#). The associated dialog will take care of this event and delete it when appropriate.


Definition at line [338](#) of file [YEvent.h](#).

The documentation for this class was generated from the following file:


- `/usr/src/RPM/BUILD/libyui-3.0.10/src/YEvent.h`

3.41 YDialog Class Reference

Inheritance diagram for YDialog:



Collaboration diagram for YDialog:



Public Member Functions

- virtual const char * [widgetClass](#) () const
- void [open](#) ()
- bool [isOpen](#) () const
- [YEvent](#) * [waitForEvent](#) (int timeout_millisec=0)
- [YEvent](#) * [pollEvent](#) ()
- bool [isTopmostDialog](#) () const
- bool [destroy](#) (bool doThrow=true)
- void [setInitialSize](#) ()
- void [recalcLayout](#) ()
- YDialogType [dialogType](#) () const
- bool [isMainDialog](#) ()
- YDialogColorMode [colorMode](#) () const
- void [checkShortcuts](#) (bool force=false)
- void [postponeShortcutCheck](#) ()
- bool [shortcutCheckPostponed](#) () const
- [YPushButton](#) * [defaultButton](#) () const
- void [deleteEvent](#) ([YEvent](#) *event)
- void [addEventFilter](#) ([YEventFilter](#) *eventFilter)
- void [removeEventFilter](#) ([YEventFilter](#) *eventFilter)
- virtual void [highlight](#) ([YWidget](#) *child)
- virtual void [setDefaultButton](#) ([YPushButton](#) *defaultButton)
- virtual void [activate](#) ()=0

Static Public Member Functions

- static bool [deleteTopmostDialog](#) (bool doThrow=true)
- static void [deleteAllDialogs](#) ()
- static void [deleteTo](#) ([YDialog](#) *dialog)
- static int [openDialogsCount](#) ()
- static [YDialog](#) * [currentDialog](#) (bool doThrow=true)
- static [YDialog](#) * [topmostDialog](#) (bool doThrow=true)
- static void [showText](#) (const std::string &text, bool richText=false)
- static bool [showHelpText](#) ([YWidget](#) *widget)

Protected Member Functions

- [YDialog](#) ([YDialogType](#) [dialogType](#), [YDialogColorMode](#) [colorMode](#)=YDialog-NormalColor)
- virtual [~YDialog](#) ()
- virtual void [openInternal](#) ()=0

- virtual [YEvent](#) * [waitForEventInternal](#) (int timeout_millisec)=0
- virtual [YEvent](#) * [pollEventInternal](#) ()=0
- [YEvent](#) * [filterInvalidEvents](#) ([YEvent](#) *event)
- [YEvent](#) * [callEventFilters](#) ([YEvent](#) *event)
- void [deleteEventFilters](#) ()

Static Protected Attributes

- static std::stack< [YDialog](#) * > [_dialogStack](#)

3.41.1 Detailed Description

Definition at line 41 of file [YDialog.h](#).

3.41.2 Constructor & Destructor Documentation

3.41.2.1 [YDialog::YDialog](#) ([YDialogType](#) *dialogType*, [YDialogColorMode](#) *colorMode* = [YDialogNormalColor](#)) [protected]

Constructor.

'dialogType' is one of YMainDialog or YPopupDialog.

'colorMode' can be set to [YDialogWarnColor](#) to use very bright "warning" colors or [YDialogInfoColor](#) to use more prominent, yet not quite as bright as "warning" colors. Use both only very rarely.


Definition at line 111 of file [YDialog.cc](#).

3.41.2.2 [YDialog::~~YDialog](#) () [protected, virtual]

Destructor. Don't delete a dialog directly, use [YDialog::deleteTopmostDialog\(\)](#) or [YDialog::destroy\(\)](#).

Definition at line 127 of file [YDialog.cc](#).

Here is the call graph for this function:



3.41.3 Member Function Documentation

3.41.3.1 virtual void YDialog::activate () [pure virtual]

Activate this dialog: Make sure that it is shown as the topmost dialog of this application and that it can receive input.

Derived classes are required to implement this.

3.41.3.2 void YDialog::addEventFilter (YEventFilter * *eventFilter*)

Add an event filter. This can be useful to catch certain types of events before they are delivered to the application. All event filters are called (in unspecified order) in [waitForEvent\(\)](#). Each one may consume an event, pass it through unchanged, or replace it with a newly created event.

Normally, an [YEventFilter](#) should be created on the heap with 'new'. In that case, the dialog's destructor will take care of deleting it.

In rare cases it might make sense to create an [YEventFilter](#) on the stack (as a local variable) and rely on that variable to go out of scope and be destroyed before the dialog gets destroyed. But that may be risky.


Notice that applications never need to call this function: [YEventFilter](#) does it automatically in its constructor.

Definition at line [560](#) of file [YDialog.cc](#).

Call the installed event filters.

Definition at line 594 of file YDialog.cc.

Here is the call graph for this function:




Checks the keyboard shortcuts of widgets in this dialog unless shortcut checks are postponed or 'force' is 'true'.

A forced shortcut check resets postponed checking.

Definition at line 279 of file YDialog.cc.

Here is the call graph for this function:



Return this dialog's color mode.

Definition at line 258 of file [YDialog.cc](#).

3.41.3.6 YDialog * YDialog::currentDialog (bool *doThrow* = true) [static]

Return the current (topmost) dialog.

If there is none, throw a [YUINoDialogException](#) if 'doThrow' is 'true' and return 0 if 'doThrow' is false.

Definition at line 491 of file [YDialog.cc](#).

3.41.3.7 YPushButton * YDialog::defaultButton () const

Return this dialog's default button: The button that is activated when the user hits [-Return] anywhere in this dialog. Note that this is not the same as the button that currently has the keyboard focus.

This might return 0 if there is no default button.

Definition at line 297 of file [YDialog.cc](#).

3.41.3.8 void YDialog::deleteAllDialogs () [static]

Delete all open dialogs.

Definition at line 522 of file [YDialog.cc](#).

3.41.3.9 void YDialog::deleteEvent (YEvent * *event*)

Delete an event.

Definition at line 468 of file [YDialog.cc](#).

Here is the call graph for this function:



3.41.3.10 void YDialog::deleteEventFilters () [protected]

Delete all (remaining) event filters.

Definition at line 197 of file [YDialog.cc](#).

3.41.3.11 void YDialog::deleteTo (YDialog * *dialog*) [static]

Delete all dialogs from the topmost to the one specified.

Definition at line 532 of file [YDialog.cc](#).

3.41.3.12 bool YDialog::deleteTopmostDialog (bool *doThrow* = true) [static]

Delete the topmost dialog.

Will throw a [YUINoDialogException](#) if there is no dialog and 'doThrow' is 'true'.

This is equivalent to [YDialog::currentDialog\(\)](#)->[destroy\(\)](#).

Returns 'true' if there is another open dialog after deleting, 'false' if there is none.

Definition at line 505 of file [YDialog.cc](#).

3.41.3.13 bool YDialog::destroy (bool *doThrow* = true)

Close and delete this dialog (and all its children) if it is the topmost dialog. If this is not the topmost dialog, this will throw an exception if 'doThrow' is true (default).

Remember that all pointers to the dialog and its children will be invalid after this operation.

This is intentionally not named close() since close() would not imply that the dialog and its children are deleted.

Returns 'true' upon success, 'false' upon failure.

Definition at line 212 of file [YDialog.cc](#).

Here is the call graph for this function:



3.41.3.14 YDialogType YDialog::dialogType () const

Return this dialog's type (YMainDialog / YPopupDialog / YWizardDialog).

Definition at line 233 of file [YDialog.cc](#).

3.41.3.15 YEvent * YDialog::filterInvalidEvents (YEvent * event) [protected]

Filter out invalid events: Return 0 if the event does not belong to this dialog or the unchanged event if it does. Silently discard events from widgets that have become invalid.


This may legitimately happen if some widget triggered an event yet nobody cared for that event (i.e. called `UserInput()` or `PollInput()`) and the widget has been destroyed meanwhile.

Silently discard events from all but the current (topmost) dialog.

This may happen even here even though the specific UI should have taken care about that: Events may still be in the queue. They might have been valid (i.e. belonged to the topmost dialog) when they arrived, but maybe simply nobody has evaluated them.

Definition at line 404 of file [YDialog.cc](#).

Here is the call graph for this function:



3.41.3.16 virtual void YDialog::highlight (YWidget * *child*) [inline, virtual]

Highlight a child widget of this dialog. This is meant for debugging: [YDialogSpy](#) and similar uses.

No more than one widget can be highlighted at any one time in the same dialog. - Highlighting another widget un-highlights a previously highlighted widget. 0 means 'un-highlight the last highlighted widget, but don't highlight any other'.

This default implementation does nothing.

Definition at line 306 of file [YDialog.h](#).

3.41.3.17 bool YDialog::isMainDialog ()

Return 'true' if this dialog is a dialog of main dialog size: YMainDialog or YWizardDialog.

Definition at line 240 of file [YDialog.cc](#).

3.41.3.18 bool YDialog::isOpen () const

Return 'true' if [open\(\)](#) has already been called for this dialog.

Definition at line 177 of file [YDialog.cc](#).

3.41.3.19 bool YDialog::isTopmostDialog () const

Return 'true' if this dialog is the topmost dialog.

Definition at line 184 of file [YDialog.cc](#).

3.41.3.20 void YDialog::open ()


Open a newly created dialog: Finalize it and make it visible on the screen.

Applications should call this once after all children are created. If the application doesn't do this, it will be done automatically upon the next call of [YDialog::waitForEvent\(\)](#) (or related). This is OK if [YDialog::waitForEvent\(\)](#) is called immediately after creating the dialog anyway. If it is not, the application might appear sluggish to the user.

Derived classes are free to reimplement this, but they should call this base class method in the new implementation.

Definition at line 163 of file [YDialog.cc](#).

Here is the call graph for this function:



3.41.3.21 int YDialog::openDialogsCount () [static]

Returns the number of currently open dialogs (from 1 on), i.e., the depth of the dialog stack.

Definition at line 553 of file [YDialog.cc](#).

3.41.3.22 virtual void YDialog::openInternal () [protected, pure virtual]

Internal [open\(\)](#) method. This is called (exactly once during the life time of the dialog) in [open\(\)](#).

Derived classes are required to implement this to do whatever is necessary to make this dialog visible on the screen.

3.41.3.23 YEvent * YDialog::pollEvent ()

Check if a user event is pending. If there is one, return it. If there is none, do not wait for one - return 0.


If [open\(\)](#) has not been called for this dialog until now, it is called now.

The dialog retains ownership of the event and will delete it upon the next call to [wait-ForEvent\(\)](#) or [pollEvent\(\)](#) or when the dialog is deleted. This also means that the return value of this function can safely be ignored without fear of memory leaks.

If this dialog is not the topmost dialog, an exception is thrown.

Definition at line 379 of file [YDialog.cc](#).

Here is the call graph for this function:



3.41.3.24 virtual YEvent* YDialog::pollEventInternal () [protected, pure virtual]

Check if a user event is pending. If there is one, return it. If there is none, do not wait for one - return 0.

Derived classes are required to implement this.

3.41.3.25 void YDialog::postponeShortcutCheck ()

From now on, postpone keyboard shortcut checks - i.e. normal (not forced) checkKeyboardShortcuts() will do nothing. Reset this mode by forcing a shortcut check with checkKeyboardShortcuts(true).

Definition at line 265 of file YDialog.cc.

3.41.3.26 void YDialog::recalcLayout ()


Recalculate the layout of the dialog and of all its children after children have been added or removed or if any of them changed its preferred width or height.

This is a very expensive operation. Call it only when really necessary. YDialog::open() includes a call to YDialog::setInitialSize() which does the same.

The basic idea behind this function is to call it when the dialog changed after it (and its children hierarchy) was initially created.

Definition at line 330 of file YDialog.cc.

Here is the call graph for this function:



3.41.3.27 void YDialog::removeEventFilter (YEventFilter * eventFilter)

Remove an event filter.

Notice that applications never need to call this function: YEventFilter does it automatically in its destructor.

Definition at line 582 of file YDialog.cc.

3.41.3.28 void YDialog::setDefaultButton (YPushButton * *defaultButton*) [virtual]


Set this dialog's default button (the button that is activated when the user hits [Return] anywhere in this dialog). 0 means no default button.

There should be no more than one default button in a dialog.

Derived classes are free to overwrite this method, but they should call this base class method in the new implementation.

Definition at line 304 of file [YDialog.cc](#).

Here is the call graph for this function:




3.41.3.29 void YDialog::setInitialSize ()

Set the initial dialog size, depending on dialogType: YMainDialog dialogs get the UI's "default main window" size, YPopupDialog dialogs use their content's preferred size.

Definition at line 318 of file [YDialog.cc](#).

Here is the call graph for this function:



3.41.3.30 bool YDialog::shortcutCheckPostponed () const

Return whether or not shortcut checking is currently postponed.

Definition at line 272 of file YDialog.cc.

3.41.3.31 bool YDialog::showHelpText (YWidget * *widget*) [static]


Show the help text for the specified widget. If it doesn't have one, traverse up the widget hierarchy until there is one.

If there is a help text, it is displayed in a pop-up dialog with a local event loop.

This returns 'true' on success (there was a help text) and 'false' on failure (no help text).

Definition at line 660 of file YDialog.cc.

Here is the call graph for this function:




```
3.41.3.32 void YDialog::showText ( const std::string & text, bool richText = false )
           [static]
```

Show the specified text in a pop-up dialog with a local event loop. This is useful for help texts. 'richText' indicates if **YRichText** formatting should be applied.

Definition at line 614 of file YDialog.cc.

Here is the call graph for this function:



```
3.41.3.33 static YDialog* YDialog::topmostDialog ( bool doThrow = true )
[inline, static]
```

Alias for `currentDialog()`.

Definition at line 194 of file YDialog.h.

Here is the call graph for this function:



Wait for a user event. In most cases, this means waiting until the user has clicked on a button in this dialog. If any widget has its 'notify' flag set ('opt('notify)' in YCP, setNotify(true) in C++), an action on such a widget will also make [waitForEvent\(\)](#) return.

If `open()` has not been called for this dialog until now, it is called now.

Applications can create `YEventFilters` to act upon some events before they are delivered to the application. Each event filter of this dialog is called (in undefined order) in `waitForEvent()`. An event filter can consume an event (in which case `waitForEvent()` will return to its internal event loop), pass it through unchanged, or even replace it with a new event. Refer to the [YEventFilter](#) documentation for more details.

Definition at line 339 of file YDialog.cc.

[illegible]

3.41.3.35 `virtual YEvent* YDialog::waitForEventInternal (int timeout_millisec)`
[protected, pure virtual]

Wait for a user event.

Derived classes are required to implement this.

3.41.3.36 `virtual const char* YDialog::widgetClass () const` [inline, virtual]

Return a descriptive name of this widget class for logging, debugging etc.

Reimplemented from [YWidget](#).

Definition at line 68 of file [YDialog.h](#).

3.41.4 Member Data Documentation

3.41.4.1 `std::stack< YDialog * > YDialog::_dialogStack` [static, protected]

Stack holding all currently existing dialogs.


Definition at line 393 of file [YDialog.h](#).

The documentation for this class was generated from the following files:

- [/usr/src/RPM/BUILD/libyui-3.0.10/src/YDialog.h](#)
- [/usr/src/RPM/BUILD/libyui-3.0.10/src/YDialog.cc](#)
- [/usr/src/RPM/BUILD/libyui-3.0.10/src/YUI.cc](#)

3.42 YDialogPrivate Struct Reference

Collaboration diagram for YDialogPrivate:



Public Member Functions

- **YDialogPrivate** (YDialogType dialogType, YDialogColorMode colorMode)

Public Attributes

- YDialogType **dialogType**
- YDialogColorMode **colorMode**
- bool **shortcutCheckPostponed**
- [YPushButton](#) * **defaultButton**
- bool **isOpen**
- [YEvent](#) * **lastEvent**
- YEventFilterList **eventFilterList**

3.42.1 Detailed Description

Definition at line 55 of file [YDialog.cc](#).

The documentation for this struct was generated from the following file:

- /usr/src/RPM/BUILD/libyui-3.0.10/src/YDialog.cc

3.43 YDialogSpy Class Reference

```
#include <YDialogSpy.h>
```

Public Member Functions

- void [showProperties](#) ()
- void [hideProperties](#) ()
- bool [propertiesShown](#) () const

Static Public Member Functions

- static void [showDialogSpy](#) (YDialog *dialog=0)

Protected Member Functions

- [YDialogSpy](#) (YDialog *dialog=0)
- virtual [~YDialogSpy](#) ()
- void [exec](#) ()
- void [showProperties](#) (YWidget *widget)

3.43.1 Detailed Description

An interactive dialog debugger: Show the structure and content of a dialog and its widgets.

This can be invoked by special key combinations: Ctrl-Alt-Shift-Y in the Qt UI

Definition at line 43 of file [YDialogSpy.h](#).

3.43.2 Constructor & Destructor Documentation


3.43.2.1 YDialogSpy::YDialogSpy (YDialog * dialog = 0) [protected]

Constructor: Create a [YDialogSpy](#) for the specified dialog. 0 means "use the topmost dialog".

In most cases it is more useful to use the static [showDialogSpy\(\)](#) method rather than create this dialog directly.

Definition at line 128 of file [YDialogSpy.cc](#).

Here is the call graph for this function:



3.43.2.2 YDialogSpy::~YDialogSpy () [protected, virtual]

Destructor.

Definition at line 163 of file [YDialogSpy.cc](#).


Here is the call graph for this function:



3.43.3 Member Function Documentation

Execute the event loop. This will only return when the user closes the `YDialogSpy` dialog.


Here is the call graph for this function:



Hide the "Properties" sub-window.

Generated on Thu Aug 8 2013 10:26:33 for libyui by Doxygen

Here is the call graph for this function:



3.43.3.3 bool YDialogSpy::propertiesShown () const

Return 'true' if the "Properties" sub-window is currently shown, 'false' if not.


Definition at line 170 of file [YDialogSpy.cc](#).

3.43.3.4 void YDialogSpy::showDialogSpy (YDialog * dialog = 0) [static]

Show a [YDialogSpy](#) for the specified dialog. 0 means "use the topmost dialog". This will return only when the user closes the [YDialogSpy](#) dialog.

Definition at line 336 of file [YDialogSpy.cc](#).

Here is the call graph for this function:




3.43.3.5 void YDialogSpy::showProperties ()

Show the "Properties" sub-window.

Definition at line 176 of file YDialogSpy.cc.

Here is the call graph for this function:




3.43.3.6 void YDialogSpy::showProperties (YWidget * widget) [protected]

Show the properties of the specified widget if the "Properties" sub-window is currently shown.

Definition at line 218 of file [YDialogSpy.cc](#).

Here is the call graph for this function:




The documentation for this class was generated from the following files:

- /usr/src/RPM/BUILD/libyui-3.0.10/src/YDialogSpy.h
- /usr/src/RPM/BUILD/libyui-3.0.10/src/YDialogSpy.cc

3.44 YDialogSpyPrivate Struct Reference

Collaboration diagram for YDialogSpyPrivate:



Public Attributes

- `YDialog` * **targetDialog**
- `YDialog` * **spyDialog**
- `YTree` * **widgetTree**
- `YPushButton` * **propButton**
- `YReplacePoint` * **propReplacePoint**
- `YTable` * **propTable**
- `YPushButton` * **closeButton**

3.44.1 Detailed Description

Definition at line 105 of file `YDialogSpy.cc`.


The documentation for this struct was generated from the following file:

- `/usr/src/RPM/BUILD/libyui-3.0.10/src/YDialogSpy.cc`


3.45 YDownloadProgress Class Reference

```
#include <YDownloadProgress.h>
```

Inheritance diagram for YDownloadProgress:



Collaboration diagram for YDownloadProgress:



Public Member Functions

- virtual [~YDownloadProgress](#) ()
- virtual const char * [widgetClass](#) () const
- std::string [label](#) () const
- virtual void [setLabel](#) (const std::string &[label](#))

- `std::string filename () const`
- `virtual void setFilename (const std::string &filename)`
- `YFileSize_t expectedSize () const`
- `virtual void setExpectedSize (YFileSize_t newSize)`
- `virtual YFileSize_t currentFileSize () const`
- `int currentPercent () const`
- `int value () const`
- `virtual bool setProperty (const std::string &propertyName, const YPropertyValue &val)`
- `virtual YPropertyValue getProperty (const std::string &propertyName)`
- `virtual const YPropertySet & propertySet ()`

Protected Member Functions

- `YDownloadProgress (YWidget *parent, const std::string &label, const std::string &filename, YFileSize_t expectedSize)`

3.45.1 Detailed Description

DownloadProgress: A progress bar that monitors downloading a file by repeatedly polling its size up to its expected size.

Definition at line 37 of file [YDownloadProgress.h](#).

3.45.2 Constructor & Destructor Documentation

3.45.2.1 `YDownloadProgress::YDownloadProgress (YWidget * parent, const std::string & label, const std::string & filename, YFileSize_t expectedSize)`
[protected]

Constructor.


'label' is the label above the progress bar.

'filename' is the name (with path) of the file being monitored.

'expectedSize' is the expected size of the file in bytes.

Definition at line 52 of file [YDownloadProgress.cc](#).

Here is the call graph for this function:



3.45.2.2 `YDownloadProgress::~~YDownloadProgress ()` [virtual]

Destructor.

Definition at line 66 of file [YDownloadProgress.cc](#).

3.45.3 Member Function Documentation

3.45.3.1 `YFileSize_t YDownloadProgress::currentFileSize ()` const [virtual]

Return the current size of the file that is being downloaded or 0 if this file doesn't exist (yet).

This default implementation returns the 'st_size' field of a `stat()` system call on the file. This should be useful for most implementations.

Definition at line 130 of file [YDownloadProgress.cc](#).

3.45.3.2 `int YDownloadProgress::currentPercent ()` const

Return the percentage (0..100) of the file being downloaded so far.

Definition at line 115 of file [YDownloadProgress.cc](#).

Here is the call graph for this function:



3.45.3.3 YFileSize_t YDownloadProgress::expectedSize () const

Return the expected file size.

Definition at line 101 of file [YDownloadProgress.cc](#).

3.45.3.4 std::string YDownloadProgress::filename () const

Return the name of the file that is being monitored.

Definition at line 87 of file [YDownloadProgress.cc](#).

3.45.3.5 YPropertyValue YDownloadProgress::getProperty (const std::string & *propertyName*) [virtual]


Get a property. Reimplemented from [YWidget](#).

This method may throw YUIPropertyExceptions.

Reimplemented from [YWidget](#).

Definition at line 185 of file [YDownloadProgress.cc](#).

Here is the call graph for this function:



3.45.3.6 `std::string YDownloadProgress::label () const`

Get the label (the text above the progress bar).

Definition at line 73 of file [YDownloadProgress.cc](#).

3.45.3.7 `const YPropertySet & YDownloadProgress::propertySet () [virtual]`


Return this class's property set. This also initializes the property upon the first call.

Reimplemented from [YWidget](#).

Reimplemented from [YWidget](#).

Definition at line 142 of file [YDownloadProgress.cc](#).

Here is the call graph for this function:



3.45.3.8 `void YDownloadProgress::setExpectedSize (YFileSize_t newSize)`
[virtual]

Set the expected file size.

Derived classes are free to reimplement this, but they should call this base class method at the end of the overloaded function.

Definition at line 108 of file [YDownloadProgress.cc](#).

3.45.3.9 `void YDownloadProgress::setFilename (const std::string & filename)`
[virtual]

Set the name of a new file to monitor.

Derived classes are free to reimplement this, but they should call this base class method at the end of the overloaded function.

Definition at line 94 of file [YDownloadProgress.cc](#).

Here is the call graph for this function:




3.45.3.10 `void YDownloadProgress::setLabel (const std::string & label)`
[virtual]

Set the label (the text above the progress bar).

Derived classes are free to reimplement this, but they should call this base class method at the end of the overloaded function.

Definition at line 80 of file [YDownloadProgress.cc](#).

Here is the call graph for this function:



3.45.3.11 `bool YDownloadProgress::setProperty (const std::string & propertyName,
const YPropertyValue & val)` [virtual]

Set a property. Reimplemented from [YWidget](#).


This function may throw `YUIPropertyExceptions`.

This function returns 'true' if the value was successfully set and 'false' if that value requires special handling (not in error cases: those are covered by exceptions).

Reimplemented from [YWidget](#).

Definition at line 168 of file `YDownloadProgress.cc`.

Here is the call graph for this function:




3.45.3.12 int YDownloadProgress::value () const [inline]

Alias for [currentPercent\(\)](#).

Definition at line 121 of file [YDownloadProgress.h](#).

Here is the call graph for this function:



3.45.3.13 virtual const char* YDownloadProgress::widgetClass () const [inline, virtual]

Returns a descriptive name of this widget class for logging, debugging etc.

Reimplemented from [YWidget](#).

Definition at line 63 of file [YDownloadProgress.h](#).

The documentation for this class was generated from the following files:

- `/usr/src/RPM/BUILD/libyui-3.0.10/src/YDownloadProgress.h`
- `/usr/src/RPM/BUILD/libyui-3.0.10/src/YDownloadProgress.cc`

3.46 YDownloadProgressPrivate Struct Reference

Public Member Functions

- **YDownloadProgressPrivate** (const std::string &label, const std::string &filename, YFileSize_t expectedSize)

Public Attributes

- std::string **label**
- std::string **filename**
- YFileSize_t **expectedSize**

3.46.1 Detailed Description

Definition at line 36 of file [YDownloadProgress.cc](#).


The documentation for this struct was generated from the following file:

- `/usr/src/RPM/BUILD/libyui-3.0.10/src/YDownloadProgress.cc`


3.47 YDumbTab Class Reference

```
#include <YDumbTab.h>
```

Inheritance diagram for YDumbTab:



Collaboration diagram for YDumbTab:



Public Member Functions

- virtual [~YDumbTab](#) ()
- virtual const char * [widgetClass](#) () const
- virtual void [addItem](#) (YItem *item)
- virtual void [shortcutChanged](#) ()
- virtual bool [setProperty](#) (const std::string &propertyName, const YPropertyValue &val)
- virtual YPropertyValue [getProperty](#) (const std::string &propertyName)
- virtual const YPropertySet & [propertySet](#) ()
- virtual std::string [shortcutString](#) () const
- virtual void [setShortcutString](#) (const std::string &str)
- virtual bool [stretchable](#) (YUIDimension dim) const
- virtual std::string [debugLabel](#) () const

Protected Member Functions

- [YDumbTab](#) (YWidget *parent)

3.47.1 Detailed Description

DumbTab: A very simple tab widget that can display and switch between a number of tabs, but will only deliver the "user clicked on tab " event very much like a PushButton does. Actually exchanging the content of the tab is left to the application.

DumbTab accepts a single child widget.

Definition at line 40 of file [YDumbTab.h](#).


3.47.2 Constructor & Destructor Documentation

3.47.2.1 YDumbTab::YDumbTab (YWidget * *parent*) [protected]

Constructor.

Definition at line 45 of file [YDumbTab.cc](#).

Here is the call graph for this function:



3.47.2.2 YDumbTab::~YDumbTab () [virtual]

Destructor.

Definition at line 59 of file [YDumbTab.cc](#).

3.47.3 Member Function Documentation

3.47.3.1 void YDumbTab::addItem (YItem * *item*) [virtual]

Add an item (a tab page).

Reimplemented from [YSelectionWidget](#).

Derived classes can overwrite this function, but they should call this base class function in the new implementation.

Reimplemented from [YSelectionWidget](#).

Definition at line 66 of file [YDumbTab.cc](#).


3.47.3.2 `std::string YDumbTab::debugLabel () const` `[virtual]`

Descriptive label for debugging. Derived from this widget's only child (if there is one).

Reimplemented from [YWidget](#).

Definition at line 83 of file [YDumbTab.cc](#).

Here is the call graph for this function:



3.47.3.3 `YPropertyValue YDumbTab::getProperty (const std::string & propertyName)` `[virtual]`

Get a property. Reimplemented from [YWidget](#).


This method may throw exceptions, for example

- if there is no property with that name

Reimplemented from [YWidget](#).

Definition at line 139 of file [YDumbTab.cc](#).

Here is the call graph for this function:



3.47.3.4 `const YPropertySet & YDumbTab::propertySet () [virtual]`

Return this class's property set. This also initializes the property set upon the first call.

Reimplemented from [YWidget](#).

Reimplemented from [YWidget](#).

Definition at line 100 of file [YDumbTab.cc](#).

Here is the call graph for this function:



3.47.3.5 `bool YDumbTab::setProperty (const std::string & propertyName, const YPropertyValue & val) [virtual]`

Set a property. Reimplemented from [YWidget](#).

This method may throw exceptions, for example

- if there is no property with that name
- if the expected type and the type mismatch


- if the value is out of range

This function returns 'true' if the value was successfully set and 'false' if that value requires special handling (not in error cases: those are covered by exceptions).

Reimplemented from [YWidget](#).

Definition at line 122 of file [YDumbTab.cc](#).

Here is the call graph for this function:



3.47.3.6 virtual void YDumbTab::setShortcutString (const std::string & str) [inline, virtual]

Set the string of this widget that holds the keyboard shortcut. Since [YDumbTab](#) doesn't have a shortcut for the widget itself (only for the tab pages, i.e. the items), this will simply trigger a [shortcutChanged\(\)](#) notification.

Reimplemented from [YSelectionWidget](#).

Reimplemented from [YSelectionWidget](#).

Definition at line 130 of file [YDumbTab.h](#).

Here is the call graph for this function:



3.47.3.7 `virtual void YDumbTab::shortcutChanged ()` `[inline, virtual]`

Notification that any shortcut of any item was changed by the shortcut conflict manager.

Derived classes should reimplement this.

Definition at line 76 of file [YDumbTab.h](#).

3.47.3.8 `virtual std::string YDumbTab::shortcutString () const` `[inline, virtual]`

Get the string of this widget that holds the keyboard shortcut. Notice that since [YDumbTab](#) has one shortcut for each tab page (for each item), this is not meaningful for this widget class.

Check [YItemShortcut](#) in [YShortcut.{cc,h}](#) for more details.

Reimplemented from [YSelectionWidget](#).

Reimplemented from [YSelectionWidget](#).

Definition at line 120 of file [YDumbTab.h](#).

3.47.3.9 `bool YDumbTab::stretchable (YUIDimension dim) const` `[virtual]`


Returns 'true' if this widget is stretchable in the specified dimension. In this case, the stretchability of the single child is returned.

Reimplemented from [YWidget](#).

Reimplemented from [YWidget](#).

Definition at line 73 of file [YDumbTab.cc](#).

Here is the call graph for this function:



3.47.3.10 `virtual const char* YDumbTab::widgetClass () const` `[inline, virtual]`

Returns a descriptive name of this widget class for logging, debugging etc.

Reimplemented from [YSelectionWidget](#).

Definition at line 58 of file [YDumbTab.h](#).

The documentation for this class was generated from the following files:

- `/usr/src/RPM/BUILD/libyui-3.0.10/src/YDumbTab.h`
- `/usr/src/RPM/BUILD/libyui-3.0.10/src/YDumbTab.cc`

3.48 YDumbTabPrivate Struct Reference

Public Attributes

- `bool dummy`

3.48.1 Detailed Description


Definition at line 34 of file [YDumbTab.cc](#).

The documentation for this struct was generated from the following file:


- `/usr/src/RPM/BUILD/libyui-3.0.10/src/YDumbTab.cc`

3.49 YEmpty Class Reference

Inheritance diagram for YEmpty:



Collaboration diagram for YEmpty:



Public Member Functions

- virtual [~YEmpty](#) ()
- virtual const char * [widgetClass](#) () const
- virtual int [preferredWidth](#) ()
- virtual int [preferredHeight](#) ()

Protected Member Functions

- [YEmpty](#) ([YWidget](#) *parent)

3.49.1 Detailed Description

Definition at line 35 of file [YEmpty.h](#).

3.49.2 Constructor & Destructor Documentation

3.49.2.1 [YEmpty::YEmpty](#) ([YWidget](#) * parent) [protected]

Constructor.

Definition at line 36 of file [YEmpty.cc](#).

3.49.2.2 [YEmpty::~~YEmpty](#) () [virtual]

Destructor.

Definition at line 44 of file [YEmpty.cc](#).

3.49.3 Member Function Documentation

3.49.3.1 [int YEmpty::preferredHeight](#) () [virtual]

Preferred height of the widget.

Reimplemented from [YWidget](#).

Implements [YWidget](#).

Definition at line 56 of file [YEmpty.cc](#).

3.49.3.2 [int YEmpty::preferredWidth](#) () [virtual]

Preferred width of the widget.

Reimplemented from [YWidget](#).

Implements [YWidget](#).

Definition at line 50 of file [YEmpty.cc](#).

3.49.3.3 virtual const char* YEmpty::widgetClass () const [inline, virtual]

Returns a descriptive name of this widget class for logging, debugging etc.

Reimplemented from [YWidget](#).

Definition at line 53 of file [YEmpty.h](#).

The documentation for this class was generated from the following files:

- /usr/src/RPM/BUILD/libyui-3.0.10/src/YEmpty.h
- /usr/src/RPM/BUILD/libyui-3.0.10/src/YEmpty.cc

3.50 YEmptyPrivate Struct Reference

Public Attributes

- bool **dummy**

3.50.1 Detailed Description

Definition at line 28 of file [YEmpty.cc](#).

The documentation for this struct was generated from the following file:

- /usr/src/RPM/BUILD/libyui-3.0.10/src/YEmpty.cc

3.51 YEnvVar Class Reference

```
#include <YEnvVar.h>
```

Public Member Functions

- [YEnvVar](#) (const std::string &name=std::string())
- std::string [name](#) () const
- bool [isSet](#) () const
- std::string [value](#) () const
- bool [isEqual](#) (const std::string &str, bool caseSensitive=false) const
- bool [operator==](#) (const std::string &str) const
- bool [contains](#) (const std::string &str, bool caseSensitive=false) const

3.51.1 Detailed Description

Helper class to represent an environment variable and its value.

Definition at line 36 of file [YEnvVar.h](#).

3.51.2 Constructor & Destructor Documentation

3.51.2.1 YEnvVar::YEnvVar (const std::string & name = std::string())

Constructor: Retrieve the environment variable 'name' and store the value (unless 'name' is empty).

Definition at line 36 of file [YEnvVar.cc](#).

3.51.3 Member Function Documentation

3.51.3.1 bool YEnvVar::contains (const std::string & str, bool caseSensitive = false) const

Return 'true' if the environment variable is set and the value contains 'str'.

Definition at line 66 of file [YEnvVar.cc](#).

3.51.3.2 bool YEnvVar::isEqual (const std::string & str, bool caseSensitive = false) const

Return 'true' if the environment variable is set and the value is 'str'.

Definition at line 54 of file [YEnvVar.cc](#).

3.51.3.3 bool YEnvVar::isSet () const [inline]

Return 'true' if the environment variable is set.

Definition at line 54 of file [YEnvVar.h](#).

3.51.3.4 std::string YEnvVar::name () const [inline]

Return the name of the environment variable.

Definition at line 49 of file [YEnvVar.h](#).

3.51.3.5 `bool YEnvVar::operator== (const std::string & str) const` `[inline]`

Case-insensitive comparison (shortcut for [isEqual\(\)](#)): Return 'true' if the environment variable is set and the value is 'str'.

Definition at line 72 of file [YEnvVar.h](#).

Here is the call graph for this function:



3.51.3.6 `std::string YEnvVar::value () const` `[inline]`

Return the value of the environment variable.

Definition at line 59 of file [YEnvVar.h](#).


The documentation for this class was generated from the following files:

- `/usr/src/RPM/BUILD/libyui-3.0.10/src/YEnvVar.h`
- `/usr/src/RPM/BUILD/libyui-3.0.10/src/YEnvVar.cc`

3.52 YEvent Class Reference

```
#include <YEvent.h>
```

Inheritance diagram for YEvent:



Public Types

- enum **EventType** { **NoEvent** = 0, **UnknownEvent**, **WidgetEvent**, **MenuEvent**, **KeyEvent**, **CancelEvent**, **TimeoutEvent**, **DebugEvent**, **InvalidEvent** = 0x4242 }
- enum **EventReason** { **UnknownReason** = 0, **Activated**, **SelectionChanged**, **ValueChanged**, **ContextMenuActivated** }

Public Member Functions

- **YEvent** (EventType **eventType**=UnknownEvent)
- EventType **eventType** () const
- unsigned long **serial** () const
- virtual **YWidget** * **widget** () const
- virtual **YItem** * **item** () const
- **YDialog** * **dialog** () const
- bool **isValid** () const

Static Public Member Functions

- static const char * **toString** (EventType **eventType**)
- static const char * **toString** (EventReason reason)

Protected Member Functions

- void **setDialog** (**YDialog** *dia)
- virtual **~YEvent** ()
- void **invalidate** ()

Friends

- void **YDialog::deleteEvent** (**YEvent** *event)
- void **YSimpleEventHandler::deleteEvent** (**YEvent** *event)

3.52.1 Detailed Description

Abstract base class for events to be returned upon `UI::UserInput()` and related functions.

Definition at line 43 of file [YEvent.h](#).

3.52.2 Constructor & Destructor Documentation

3.52.2.1 YEvent::YEvent (EventType *eventType* = UnknownEvent)

Constructor.

Definition at line 38 of file [YEvent.cc](#).

Here is the call graph for this function:



3.52.2.2 YEvent::~~YEvent () [protected, virtual]

Protected destructor - events can only be deleted via [YDialog::deleteEvent\(\)](#). The associated dialog will take care of this event and delete it when appropriate.

This desctructor is virtual to force a polymorph object so `dynamic_cast<>` can be used.

Definition at line 46 of file [YEvent.cc](#).

Here is the call graph for this function:



3.52.3 Member Function Documentation

3.52.3.1 YDialog* YEvent::dialog () const [inline]

Return the dialog this event belongs to or 0 if no dialog was set yet.

Definition at line 106 of file [YEvent.h](#).

3.52.3.2 EventType YEvent::eventType () const [inline]

Returns the event type.

Definition at line 79 of file [YEvent.h](#).

3.52.3.3 void YEvent::invalidate () [protected]

Mark this event as invalid. This cannot be undone.

Definition at line 60 of file [YEvent.cc](#).

3.52.3.4 bool YEvent::isValid () const

Check if this event is valid. Events become invalid in the destructor.

Definition at line 53 of file [YEvent.cc](#).

3.52.3.5 virtual YItem* YEvent::item () const [inline, virtual]

Return the [YItem](#) that corresponds to this event or 0 if there is none.

This default implementation always returns 0. Subclasses that actually return items should overwrite this method.

Reimplemented in [YMenuEvent](#).

Definition at line 101 of file [YEvent.h](#).

3.52.3.6 unsigned long YEvent::serial () const [inline]

Returns the unique serial no. of this event. This is mainly useful for debugging.

Definition at line 85 of file [YEvent.h](#).

3.52.3.7 void YEvent::setDialog (YDialog * dia) [inline, protected]

Set the dialog this event belongs to.

Definition at line 129 of file [YEvent.h](#).

3.52.3.8 `const char * YEvent::toString (EventType eventType) [static]`

Returns the character representation of an event type.

Definition at line 67 of file [YEvent.cc](#).

3.52.3.9 `const char * YEvent::toString (EventReason reason) [static]`

Returns the character representation of an event reason.

Definition at line 90 of file [YEvent.cc](#).

3.52.3.10 `virtual YWidget* YEvent::widget() const [inline, virtual]`

Returns the widget that caused this event or 0 if there is none.

This default implementation always returns 0. Subclasses that actually return widgets should overwrite this method.

Reimplemented in [YWidgetEvent](#).

Definition at line 93 of file [YEvent.h](#).


The documentation for this class was generated from the following files:

- [/usr/src/RPM/BUILD/libyui-3.0.10/src/YEvent.h](#)
- [/usr/src/RPM/BUILD/libyui-3.0.10/src/YEvent.cc](#)

3.53 YEventFilter Class Reference

```
#include <YEventFilter.h>
```

Inheritance diagram for YEventFilter:



Public Member Functions

- virtual [~YEventFilter](#) ()
- virtual [YEvent * filter](#) ([YEvent *event](#))=0
- [YDialog * dialog](#) () const

Protected Member Functions

- [YEventFilter](#) ([YDialog *dialog](#)=0)

3.53.1 Detailed Description

Abstract base class to filter events.

This class can be used to examine events just before they are delivered to the application. This is most useful for higher-level widgets or for libraries that need to react to certain events and either consume them, have them delivered unchanged to the application, or exchange an event with another one.

A [YEventFilter](#) belongs to one specific dialog. Each dialog can have any number of event filters. Each of those event filters is called (its [YEventFilter::filter\(\)](#) method) for each event inside [YDialog::waitForEvent\(\)](#). The order in which event filters are called is undefined.

[YEventFilter](#) objects should be created with 'new' (on the heap). Since an [YEventFilter](#) registers itself with its dialog, the dialog will delete it in its destructor if it still exists after all child widgets are deleted.

Thus, it is safe to store a pointer to an [YEventFilter](#) until the corresponding dialog is deleted. After that, the pointer becomes invalid.

See [YHelpButtonHandler](#) in [YDialog.cc](#) for an example.

Definition at line 62 of file [YEventFilter.h](#).

3.53.2 Constructor & Destructor Documentation

3.53.2.1 YEventFilter::YEventFilter (YDialog * dialog = 0) [protected]


Constructor.

This registers the event filter with the specified dialog. The dialog assumes ownership of this object and will delete it in its destructor (unless this object is destroyed before that time).

If 'dialog' is 0, [YDialog::currentDialog\(\)](#) is used (which can throw a [YUINoDialog-Exception](#) if there is no dialog).

Definition at line 44 of file [YEventFilter.cc](#).

Here is the call graph for this function:



3.53.2.2 YEventFilter::~YEventFilter () [virtual]

Destructor.

This will unregister this object with its dialog.

Definition at line 56 of file [YEventFilter.cc](#).

Here is the call graph for this function:



3.53.3 Member Function Documentation

3.53.3.1 YDialog * YEventFilter::dialog () const

Return the dialog this event filter belongs to.

Definition at line 63 of file [YEventFilter.cc](#).

3.53.3.2 virtual YEvent* YEventFilter::filter (YEvent * event) [pure virtual]

The heart of the matter: The event filter function. Derived classes are required to implement this.

This method can inspect the event it receives. Hint: `event->widget()` is typically the most interesting information.

This method can react on individual events and

- consume the event (i.e., return 0)
- pass the event through unchanged (simply return the event)
- create a new event (typically based on data in the received event).

If 0 or a new event (another value than 'event') is returned, the old event is deleted. If a value different from 'event' or 0 is returned, that value is assumed to be a pointer to a newly created event. The dialog will assume ownership of that event and delete it when appropriate.

Note: Never delete 'event' in this method! Return 0 or a new event instead; the caller will take care of deleting the old event.


Implemented in [YHelpButtonHandler](#).

The documentation for this class was generated from the following files:

- /usr/src/RPM/BUILD/libyui-3.0.10/src/YEventFilter.h
- /usr/src/RPM/BUILD/libyui-3.0.10/src/YEventFilter.cc

3.54 YEventFilterPrivate Struct Reference

Collaboration diagram for YEventFilterPrivate:



Public Member Functions

- **YEventFilterPrivate** ([YDialog](#) *dialog)

Public Attributes

- [YDialog](#) * **dialog**

3.54.1 Detailed Description


Definition at line 32 of file [YEventFilter.cc](#).

The documentation for this struct was generated from the following file:


- `/usr/src/RPM/BUILD/libyui-3.0.10/src/YEventFilter.cc`

3.55 YFrame Class Reference

Inheritance diagram for YFrame:



Collaboration diagram for YFrame:



Public Member Functions

- virtual [~YFrame](#) ()
- virtual const char * [widgetClass](#) () const
- virtual void [setLabel](#) (const std::string &newLabel)
- std::string [label](#) () const
- virtual bool [setProperty](#) (const std::string &propertyName, const [YPropertyValue](#) &val)
- virtual [YPropertyValue](#) [getProperty](#) (const std::string &propertyName)
- virtual const [YPropertySet](#) & [propertySet](#) ()

Protected Member Functions

- [YFrame](#) ([YWidget](#) *parent, const std::string &label)

3.55.1 Detailed Description

Definition at line 35 of file [YFrame.h](#).

3.55.2 Constructor & Destructor Documentation

3.55.2.1 YFrame::YFrame (YWidget * *parent*, const std::string & *label*) [protected]

Constructor.

Definition at line 45 of file [YFrame.cc](#).

3.55.2.2 YFrame::~YFrame () [virtual]

Destructor.

Definition at line 53 of file [YFrame.cc](#).

3.55.3 Member Function Documentation

3.55.3.1 YPropertyValue YFrame::getProperty (const std::string & *propertyName*) [virtual]

Get a property. Reimplemented from [YWidget](#).


This method may throw exceptions, for example

- if there is no property with that name

Reimplemented from [YWidget](#).

Definition at line 106 of file [YFrame.cc](#).

Here is the call graph for this function:



3.55.3.2 `std::string YFrame::label () const`

Get the current frame label.

Definition at line 65 of file [YFrame.cc](#).

3.55.3.3 `const YPropertySet & YFrame::propertySet () [virtual]`

Return this class's property set. This also initializes the property set upon the first call.

Reimplemented from [YWidget](#).

Reimplemented from [YWidget](#).

Definition at line 72 of file [YFrame.cc](#).

Here is the call graph for this function:



3.55.3.4 `void YFrame::setLabel (const std::string & newLabel) [virtual]`

Change the frame label.

Derived classes should overwrite this, but call this base class function in the overwritten function.

Definition at line 59 of file [YFrame.cc](#).

Here is the call graph for this function:



3.55.3.5 `bool YFrame::setProperty (const std::string & propertyName, const YPropertyValue & val) [virtual]`

Set a property. Reimplemented from [YWidget](#).

This method may throw exceptions, for example


- if there is no property with that name
- if the expected type and the type mismatch
- if the value is out of range

This function returns 'true' if the value was successfully set and 'false' if that value requires special handling (not in error cases: those are covered by exceptions).

Reimplemented from [YWidget](#).

Definition at line 91 of file [YFrame.cc](#).

Here is the call graph for this function:



3.55.3.6 `virtual const char* YFrame::widgetClass () const [inline, virtual]`

Returns a descriptive name of this widget class for logging, debugging etc.

Reimplemented from [YWidget](#).

Definition at line 53 of file [YFrame.h](#).

The documentation for this class was generated from the following files:

- /usr/src/RPM/BUILD/libyui-3.0.10/src/YFrame.h
- /usr/src/RPM/BUILD/libyui-3.0.10/src/YFrame.cc

3.56 YFramePrivate Struct Reference

Public Member Functions

- **YFramePrivate** (const std::string &frameLabel)

Public Attributes

- std::string **label**

3.56.1 Detailed Description


Definition at line 33 of file [YFrame.cc](#).

The documentation for this struct was generated from the following file:


- /usr/src/RPM/BUILD/libyui-3.0.10/src/YFrame.cc

3.57 YGraph Class Reference

Inheritance diagram for YGraph:



Collaboration diagram for YGraph:



Public Member Functions

- virtual `~YGraph ()`
- virtual const char * `widgetClass ()` const
- virtual bool `setProperty` (const std::string &propertyName, const `YPropertyValue` &val)
- virtual `YPropertyValue` `getProperty` (const std::string &propertyName)
- virtual const `YPropertySet` & `propertySet ()`
- std::string `filename ()` const
- virtual void `setFilename` (const std::string &filename)
- std::string `layoutAlgorithm ()` const
- virtual void `setLayoutAlgorithm` (const std::string &filename)
- virtual void `setGraph` (void *graph)
- virtual std::string `activatedNode ()` const

Protected Member Functions

- `YGraph` (`YWidget` *parent, const std::string &filename, const std::string &layoutAlgorithm)
- `YGraph` (`YWidget` *parent, void *graph)
- virtual void `renderGraph` (const std::string &filename, const std::string &layoutAlgorithm)=0
- virtual void `renderGraph` (void *graph)=0

3.57.1 Detailed Description

Definition at line 43 of file [YGraph.h](#).

3.57.2 Constructor & Destructor Documentation


3.57.2.1 `YGraph::YGraph (YWidget * parent, const std::string & filename, const std::string & layoutAlgorithm)` [protected]

Constructor.

Loads a graph in DOT format from filename and uses the layout algorithm layout-Algorithm to layout and then render the graph. The layout algorithm can be any string accepted by the function gvLayout from graphviz, e.g. "dot" or "neato".

Definition at line 44 of file [YGraph.cc](#).

Here is the call graph for this function:




3.57.2.2 `YGraph::YGraph (YWidget * parent, void * graph)` [protected]

Constructor.

Renders the graph. The graph must already contain layout information.

Definition at line 53 of file [YGraph.cc](#).

Here is the call graph for this function:



3.57.2.3 YGraph::~YGraph () [virtual]

Destructor.

Definition at line 62 of file [YGraph.cc](#).

3.57.3 Member Function Documentation

3.57.3.1 std::string YGraph::activatedNode () const [virtual]

Return name of activated node. Activation can happen due to e.g. single right mouse click (context menu) or double left mouse click.

Definition at line 106 of file [YGraph.cc](#).

3.57.3.2 std::string YGraph::filename () const

Return the filename that describes the graph.

Definition at line 69 of file [YGraph.cc](#).

3.57.3.3 YPropertyValue YGraph::getProperty (const std::string & *propertyName*) [virtual]


Get a property. Reimplemented from [YWidget](#).

This method may throw YUIPropertyExceptions.

Reimplemented from [YWidget](#).

Definition at line 151 of file [YGraph.cc](#).

Here is the call graph for this function:



3.57.3.4 `std::string YGraph::layoutAlgorithm () const`

Return the layout-algorithm used for the graph.

Definition at line 84 of file [YGraph.cc](#).

3.57.3.5 `const YPropertySet & YGraph::propertySet () [virtual]`

Return this class's property set. This also initializes the property upon the first call.

Reimplemented from [YWidget](#).

Reimplemented from [YWidget](#).

Definition at line 113 of file [YGraph.cc](#).

Here is the call graph for this function:



3.57.3.6 `virtual void YGraph::renderGraph (const std::string & filename, const std::string & layoutAlgorithm)` [protected, pure virtual]

Render the graph from the filename. Derived classes are required to implement this.

3.57.3.7 `virtual void YGraph::renderGraph (void * graph)` [protected, pure virtual]


Render the graph. Derived classes are required to implement this.

3.57.3.8 `void YGraph::setFilename (const std::string & filename)` [virtual]

Set the filename that describes the graph and render the graph. Derived classes can reimplement this, but they should call this base class method in the new implementation. Most derived classes only need to implement [renderGraph\(\)](#).

Definition at line 76 of file [YGraph.cc](#).

Here is the call graph for this function:



3.57.3.9 `void YGraph::setGraph (void * graph)` [virtual]

Render the graph. Derived classes can reimplement this, but they should call this base class method in the new implementation. Most derived classes only need to implement [renderGraph\(\)](#).

Definition at line 91 of file [YGraph.cc](#).

Here is the call graph for this function:



3.57.3.10 `void YGraph::setLayoutAlgorithm (const std::string & filename)`
[virtual]

Set the layout-algorithm used for the graph. Derived classes can reimplement this, but they should call this base class method in the new implementation.

Definition at line 99 of file [YGraph.cc](#).

Here is the call graph for this function:



3.57.3.11 `bool YGraph::setProperty (const std::string & propertyName, const YPropertyValue & val)` [virtual]

Set a property. Reimplemented from [YWidget](#).


This function may throw `YUIPropertyExceptions`.

This function returns 'true' if the value was successfully set and 'false' if that value requires special handling (not in error cases: those are covered by exceptions).

Reimplemented from [YWidget](#).

Definition at line 135 of file [YGraph.cc](#).

Here is the call graph for this function:



3.57.3.12 `virtual const char* YGraph::widgetClass () const` `[inline, virtual]`

Returns a descriptive name of this widget class for logging, debugging etc.

Reimplemented from [YWidget](#).

Definition at line 75 of file [YGraph.h](#).


The documentation for this class was generated from the following files:

- `/usr/src/RPM/BUILD/libyui-3.0.10/src/YGraph.h`
- `/usr/src/RPM/BUILD/libyui-3.0.10/src/YGraph.cc`


3.58 YGraphPlugin Class Reference

```
#include <YGraphPlugin.h>
```

Inheritance diagram for YGraphPlugin:



Collaboration diagram for YGraphPlugin:



Public Member Functions

- virtual [YGraph](#) * [createGraph](#) ([YWidget](#) *parent, const std::string &filename, const std::string &layoutAlgorithm)=0

Protected Member Functions

- [YGraphPlugin](#) (const char *pluginLibBaseName)
- virtual [~YGraphPlugin](#) ()

3.58.1 Detailed Description

Abstract base class for simplified access to UI plugins for graph widget.

Definition at line 37 of file [YGraphPlugin.h](#).

3.58.2 Constructor & Destructor Documentation

3.58.2.1 `YGraphPlugin::YGraphPlugin (const char * pluginLibBaseName)`
[inline, protected]

Constructor: Load the specified plugin library from the standard UI plugin directory (/usr/lib/yui/).

Definition at line 44 of file [YGraphPlugin.h](#).

3.58.2.2 `virtual YGraphPlugin::~YGraphPlugin ()` [inline, protected, virtual]

Destructor. Calls dlclose() which will unload the plugin library if it is no longer used, i.e. if the reference count dlopen() uses reaches 0.

Definition at line 51 of file [YGraphPlugin.h](#).

3.58.3 Member Function Documentation

3.58.3.1 `virtual YGraph* YGraphPlugin::createGraph (YWidget * parent, const std::string & filename, const std::string & layoutAlgorithm)` [pure virtual]

Create a graph widget. Derived classes need to implement this.

This might return 0 if the plugin lib could not be loaded or if the appropriate symbol could not be located in the plugin lib.

The documentation for this class was generated from the following file:

- /usr/src/RPM/BUILD/libyui-3.0.10/src/YGraphPlugin.h

3.59 YGraphPrivate Struct Reference

Public Member Functions

- **YGraphPrivate** (std::string filename, std::string layoutAlgorithm)

Public Attributes

- `std::string filename`
- `std::string layoutAlgorithm`

3.59.1 Detailed Description


Definition at line 32 of file [YGraph.cc](#).

The documentation for this struct was generated from the following file:


- `/usr/src/RPM/BUILD/libyui-3.0.10/src/YGraph.cc`

3.60 YHelpButtonHandler Class Reference

Inheritance diagram for YHelpButtonHandler:



Collaboration diagram for YHelpButtonHandler:



Public Member Functions

- **YHelpButtonHandler** ([YDialog](#) *dialog)
- [YEvent](#) * filter ([YEvent](#) *event)

3.60.1 Detailed Description

Helper class: Event filter that handles "Help" buttons.

Definition at line 80 of file [YDialog.cc](#).

3.60.2 Member Function Documentation

3.60.2.1 `YEvent* YHelpButtonHandler::filter (YEvent * event)` [inline, virtual]

The heart of the matter: The event filter function. Derived classes are required to implement this.

This method can inspect the event it receives. Hint: `event->widget()` is typically the most interesting information.


This method can react on individual events and

- consume the event (i.e., return 0)
- pass the event through unchanged (simply return the event)

- If 0 or a new event (another value than 'event') is returned, the old event is deleted. If a value different from 'event' or 0 is returned, that value is assumed to be a pointer to a newly created event. The dialog will assume ownership of that event and delete it when appropriate.

Implements [YEventFilter](#).

Here is the call graph for this function:



- /usr/src/RPM/BUILD/libyui-3.0.10/src/YDialog.cc

Public Member Functions

- `std::string findIcon` (`std::string` name)
- `void setIconBasePath` (`std::string` path)

- `std::string iconBasePath () const`
- `void addIconSearchPath (std::string path)`

3.61.1 Detailed Description


Definition at line 32 of file [YIconLoader.h](#).

The documentation for this class was generated from the following files:


- `/usr/src/RPM/BUILD/libyui-3.0.10/src/YIconLoader.h`
- `/usr/src/RPM/BUILD/libyui-3.0.10/src/YIconLoader.cc`

3.62 YImage Class Reference

Inheritance diagram for YImage:



Collaboration diagram for YImage:



Public Member Functions

- [YImage](#) ([YWidget](#) *[parent](#), const std::string &[imageFileName](#), bool [animated](#)=false)
- virtual [~YImage](#) ()
- virtual const char * [widgetClass](#) () const
- std::string [imageFileName](#) () const
- bool [animated](#) () const
- virtual void [setImage](#) (const std::string &[imageFileName](#), bool [animated](#)=false)
- void [setMovie](#) (const std::string &[movieFileName](#))
- bool [hasZeroSize](#) (YUIDimension dim) const
- void [setZeroSize](#) (YUIDimension dim, bool [zeroSize](#)=true)
- bool [autoScale](#) () const
- virtual void [setAutoScale](#) (bool [autoScale](#)=true)

3.62.1 Detailed Description

Definition at line 35 of file [YImage.h](#).

3.62.2 Constructor & Destructor Documentation

3.62.2.1 [YImage::YImage](#) ([YWidget](#) * [parent](#), const std::string & [imageFileName](#), bool [animated](#) = false)

Constructor.

'animated' indicates if 'imageFileName' is an animated image format (e.g., MNG).

Definition at line 54 of file [YImage.cc](#).

3.62.2.2 YImage::~YImage () [virtual]

Destructor.

Definition at line 64 of file [YImage.cc](#).

3.62.3 Member Function Documentation

3.62.3.1 bool YImage::animated () const

Returns 'true' if the current image is an animated image format (e.g., MNG).

Definition at line 76 of file [YImage.cc](#).

3.62.3.2 bool YImage::autoScale () const

Return 'true' if the image should be scaled to fit into the available space.

Definition at line 102 of file [YImage.cc](#).

3.62.3.3 bool YImage::hasZeroSize (YUIDimension *dim*) const

Return 'true' if the image widget should be stretchable with a default width of 0 in the specified dimension. This is useful if the widget width is determined by outside constraints, like the width of a neighbouring widget.

Definition at line 89 of file [YImage.cc](#).

3.62.3.4 std::string YImage::imageFileName () const

Return the file name of this widget's image.

Definition at line 70 of file [YImage.cc](#).

3.62.3.5 void YImage::setAutoScale (bool *autoScale* = true) [virtual]

Make the image fit into the available space.

Derived classes should overwrite this, but call this base class function in the new function.

Definition at line 108 of file [YImage.cc](#).

Here is the call graph for this function:




3.62.3.6 `void YImage::setImage (const std::string & imageFileName, bool animated = false) [virtual]`

Set and display a new image (or movie if animated is 'true').

Derived classes should overwrite this, but call this base class function in the new function.

Definition at line 82 of file [YImage.cc](#).

Here is the call graph for this function:



3.62.3.7 `void YImage::setMovie (const std::string & movieFileName) [inline]`

Set and display a movie (an animated image).

Definition at line 81 of file [YImage.h](#).

Here is the call graph for this function:



3.62.3.8 void YImage::setZeroSize (YUIDimension dim, bool zeroSize = true)

Make the image widget stretchable with a default size of 0 in the specified dimension. This is useful if the widget width is determined by outside constraints, like the width of a neighbouring widget.

This function is intentionally not virtual because it is only relevant during the next geometry update, in which case the derived class has to check this value anyway.

Definition at line 95 of file [YImage.cc](#).

Here is the call graph for this function:



3.62.3.9 virtual const char* YImage::widgetClass () const [inline, virtual]

Returns a descriptive name of this widget class for logging, debugging etc.

Reimplemented from [YWidget](#).


Definition at line 57 of file [YImage.h](#).

The documentation for this class was generated from the following files:

- `/usr/src/RPM/BUILD/libyui-3.0.10/src/YImage.h`
- `/usr/src/RPM/BUILD/libyui-3.0.10/src/YImage.cc`

3.63 YImagePrivate Struct Reference

Collaboration diagram for YImagePrivate:



Public Member Functions

- [YImagePrivate](#) (const std::string &imageFileName, bool animated)

Public Attributes

- std::string **imageFileName**
- bool **animated**
- [YBothDim](#)< bool > **zeroSize**
- bool **autoScale**

3.63.1 Detailed Description

Definition at line 30 of file [YImage.cc](#).

3.63.2 Constructor & Destructor Documentation

3.63.2.1 YImagePrivate::YImagePrivate (const std::string & *imageFileName*, bool *animated*) [inline]

Constructor.

Definition at line 35 of file [YImage.cc](#).


The documentation for this struct was generated from the following file:

- /usr/src/RPM/BUILD/libyui-3.0.10/src/YImage.cc


3.64 YInputField Class Reference

```
#include <YInputField.h>
```

Inheritance diagram for YInputField:



Collaboration diagram for YInputField:



Public Member Functions

- virtual `~YInputField ()`
- virtual `const char * widgetClass () const`
- virtual `std::string value ()=0`
- virtual `void setValue (const std::string &text)=0`
- `std::string label () const`
- virtual `void setLabel (const std::string &label)`
- `bool passwordMode () const`
- `std::string validChars ()`
- virtual `void setValidChars (const std::string &validChars)`
- `int inputMaxLength () const`
- virtual `void setInputMaxLength (int numberOfChars)`
- `bool shrinkable () const`
- virtual `void setShrinkable (bool shrinkable=true)`
- virtual `bool setProperty (const std::string &propertyName, const YPropertyValue &val)`
- virtual `YPropertyValue getProperty (const std::string &propertyName)`
- virtual `const YPropertySet & propertySet ()`
- virtual `std::string shortcutString () const`
- virtual `void setShortcutString (const std::string &str)`
- `const char * userInputProperty ()`
- virtual `void saveUserInput (YMacroRecorder *macroRecorder)`

Protected Member Functions

- [YInputField](#) ([YWidget](#) *parent, const std::string &label, bool passwordMode=false)

3.64.1 Detailed Description

InputField: General purpose one line input field for entering text and other data. Can be used for entering passwords with a "*" echoed for every character typed.

Like most widgets, the InputField has a label (a caption) above the input field itself. The label can and should get a keyboard shortcut (specified with '&') that will make the input field receive the keyboard focus with a special key combination ("&Name" -> Alt-N or Ctrl-N will make the keyboard focus jump to the corresponding input field).

Definition at line 46 of file [YInputField.h](#).

3.64.2 Constructor & Destructor Documentation

3.64.2.1 **YInputField::YInputField** ([YWidget](#) * parent, const std::string & label, bool passwordMode = false) [protected]

Constructor.

Create an input field with 'label' as the caption. If 'passwordMode' is set, the input will be not be echoed as clear text.

Definition at line 53 of file [YInputField.cc](#).

Here is the call graph for this function:



3.64.2.2 **YInputField::~YInputField** () [virtual]

Destructor.

Definition at line 64 of file [YInputField.cc](#).

3.64.3 Member Function Documentation

3.64.3.1 YPropertyValue YInputField::getProperty (const std::string & *propertyName*) [virtual]


Get a property. Reimplemented from [YWidget](#).

This method may throw YUIPropertyExceptions.

Reimplemented from [YWidget](#).

Definition at line 168 of file [YInputField.cc](#).

Here is the call graph for this function:



3.64.3.2 int YInputField::inputMaxLength () const

The maximum input length, i.e., the maximum number of characters the user can enter.
-1 means no limit.

Definition at line 113 of file [YInputField.cc](#).

3.64.3.3 std::string YInputField::label () const

Get the label (the caption above the input field).

Definition at line 70 of file [YInputField.cc](#).

3.64.3.4 bool YInputField::passwordMode () const

Returns 'true' if this input field is in password mode, i.e. if there should be no on-screen echo or only a '*' for each character typed.

Notice that this can only be set in the constructor.

Definition at line 82 of file [YInputField.cc](#).

3.64.3.5 const YPropertySet & YInputField::propertySet () [virtual]

Return this class's property set. This also initializes the property upon the first call.

Reimplemented from [YWidget](#).

Reimplemented from [YWidget](#).

Definition at line 126 of file [YInputField.cc](#).

Here is the call graph for this function:



3.64.3.6 void YInputField::saveUserInput (YMacroRecorder * macroRecorder) [virtual]


Save the widget's user input to a macro recorder.

Reimplemented from [YWidget](#) to avoid recording passwords.

Reimplemented from [YWidget](#).

Definition at line 184 of file [YInputField.cc](#).

Here is the call graph for this function:



3.64.3.7 `void YInputField::setInputMaxLength (int numberOfChars)` [virtual]

Set the maximum input length, i.e., the maximum number of characters the user can enter. -1 means no limit.

Derived classes are free to reimplement this, but they should call this base class method at the end of the overloaded function.

Definition at line 119 of file [YInputField.cc](#).

3.64.3.8 `void YInputField::setLabel (const std::string & label)` [virtual]

Set the label (the caption above the input field).

Derived classes are free to reimplement this, but they should call this base class method at the end of the overloaded function.

Definition at line 76 of file [YInputField.cc](#).

Here is the call graph for this function:



3.64.3.9 `bool YInputField::setProperty (const std::string & propertyName, const YPropertyValue & val) [virtual]`

Set a property. Reimplemented from [YWidget](#).


This function may throw YUIPropertyExceptions.

This function returns 'true' if the value was successfully set and 'false' if that value requires special handling (not in error cases: those are covered by exceptions).

Reimplemented from [YWidget](#).

Definition at line 150 of file [YInputField.cc](#).

Here is the call graph for this function:



3.64.3.10 `virtual void YInputField::setShortcutString (const std::string & str) [inline, virtual]`


Set the string of this widget that holds the keyboard shortcut.

Reimplemented from [YWidget](#).

Reimplemented from [YWidget](#).

Definition at line 193 of file [YInputField.h](#).

Here is the call graph for this function:



3.64.3.11 `void YInputField::setShrinkable (bool shrinkable = true) [virtual]`

Make this InputField very small. This will take effect only upon the next geometry management run.

Derived classes can overwrite this, but should call this base class function in the new function.

Definition at line 94 of file [YInputField.cc](#).

Here is the call graph for this function:



3.64.3.12 `void YInputField::setValidChars (const std::string & validChars) [virtual]`

Set the valid input characters. No input validation is performed (i.e., the user can enter anything) if this is empty.

Derived classes are free to reimplement this, but they should call this base class method at the end of the overloaded function.

Definition at line 107 of file [YInputField.cc](#).

3.64.3.13 `virtual void YInputField::setValue (const std::string & text)` [pure virtual]

Set the current value (the text entered by the user or set from the outside) of this input field.

Derived classes are required to implement this.

3.64.3.14 `virtual std::string YInputField::shortcutString () const` [inline, virtual]


Get the string of this widget that holds the keyboard shortcut.

Reimplemented from [YWidget](#).

Reimplemented from [YWidget](#).

Definition at line 186 of file [YInputField.h](#).

Here is the call graph for this function:



3.64.3.15 `bool YInputField::shrinkable () const`

Return 'true' if this InputField should be very small.

Definition at line 88 of file [YInputField.cc](#).

3.64.3.16 `const char* YInputField::userInputProperty ()` [inline, virtual]

The name of the widget property that will return user input. Inherited from [YWidget](#).

Reimplemented from [YWidget](#).

Definition at line 200 of file [YInputField.h](#).

3.64.3.17 `std::string YInputField::validChars ()`

Get the valid input characters. No input validation is performed (i.e., the user can enter anything) if this is empty.

Definition at line 101 of file [YInputField.cc](#).

3.64.3.18 `virtual std::string YInputField::value ()` [pure virtual]

Get the current value (the text entered by the user or set from the outside) of this input field.

Derived classes are required to implement this.

3.64.3.19 `const char * YInputField::widgetClass () const` [virtual]

Return a descriptive name of this widget class for logging, debugging etc.

Reimplemented from [YWidget](#).

Definition at line 194 of file [YInputField.cc](#).

The documentation for this class was generated from the following files:

- `/usr/src/RPM/BUILD/libyui-3.0.10/src/YInputField.h`
- `/usr/src/RPM/BUILD/libyui-3.0.10/src/YInputField.cc`

3.65 YInputFieldPrivate Struct Reference

Public Member Functions

- **YInputFieldPrivate** (std::string label, bool passwordMode)

Public Attributes

- std::string **label**
- bool **passwordMode**
- bool **shrinkable**
- std::string **validChars**
- int **inputMaxLength**

3.65.1 Detailed Description

Definition at line 35 of file [YInputField.cc](#).


The documentation for this struct was generated from the following file:

- `/usr/src/RPM/BUILD/libyui-3.0.10/src/YInputField.cc`


3.66 YIntField Class Reference

```
#include <YIntField.h>
```

Inheritance diagram for YIntField:



Collaboration diagram for YIntField:



Public Member Functions

- virtual [~YIntField](#) ()
- virtual const char * [widgetClass](#) () const
- virtual int [value](#) ()=0
- void [setValue](#) (int val)
- int [minValue](#) () const
- void [setMinValue](#) (int val)
- int [maxValue](#) () const
- void [setMaxValue](#) (int val)
- std::string [label](#) () const
- virtual void [setLabel](#) (const std::string &label)
- virtual bool [setProperty](#) (const std::string &propertyName, const [YPropertyValue](#) &val)
- virtual [YPropertyValue](#) [getProperty](#) (const std::string &propertyName)
- virtual const [YPropertySet](#) & [propertySet](#) ()
- virtual std::string [shortcutString](#) () const
- virtual void [setShortcutString](#) (const std::string &str)
- const char * [userInputProperty](#) ()

Protected Member Functions

- [YIntField](#) ([YWidget](#) *parent, const std::string &label, int minValue, int maxValue)
- virtual void [setValueInternal](#) (int val)=0
- int [enforceRange](#) (int val) const

3.66.1 Detailed Description

IntField: Input field for integer values. Enforces input range between a specified minimum and maximum value.

Definition at line 38 of file [YIntField.h](#).

3.66.2 Constructor & Destructor Documentation

3.66.2.1 `YIntField::YIntField (YWidget * parent, const std::string & label, int minValue, int maxValue)` [protected]


Constructor.

Create an IntField with 'label' as the caption, and the specified minimum and maximum values.

Note that YWidgetFactory::createIntField() also has an 'initialValue' parameter that is not used here (because the current value is not stored in this base class, but in the derived class).

Definition at line 50 of file [YIntField.cc](#).

Here is the call graph for this function:



3.66.2.2 `YIntField::~YIntField ()` [virtual]

Destructor.

Definition at line 64 of file [YIntField.cc](#).

3.66.3 Member Function Documentation

3.66.3.1 `int YIntField::enforceRange (int val) const` [protected]

Enforce 'val' to be between `minValue` and `maxValue`. Return a value that is in range. This does not change the internally stored value of this `IntField` in any way.

Definition at line 71 of file [YIntField.cc](#).

Here is the call graph for this function:



3.66.3.2 `YPropertyValue YIntField::getProperty (const std::string & propertyName)` [virtual]


Get a property. Reimplemented from [YWidget](#).

This method may throw `YUIPropertyExceptions`.

Reimplemented from [YWidget](#).

Definition at line 181 of file [YIntField.cc](#).

Here is the call graph for this function:



3.66.3.3 `std::string YIntField::label () const`

Get the label (the caption above the input field).

Definition at line 124 of file [YIntField.cc](#).

3.66.3.4 `int YIntField::maxValue () const`

Return the maximum value.

Definition at line 104 of file [YIntField.cc](#).

3.66.3.5 `int YIntField::minValue () const`

Return the minimum value.

Definition at line 84 of file [YIntField.cc](#).

3.66.3.6 `const YPropertySet & YIntField::propertySet () [virtual]`


Return this class's property set. This also initializes the property upon the first call.

Reimplemented from [YWidget](#).

Reimplemented from [YWidget](#).

Definition at line 139 of file [YIntField.cc](#).

Here is the call graph for this function:



3.66.3.7 void YIntField::setLabel (const std::string & label) [virtual]

Set the label (the caption above the input field).

Derived classes are free to reimplement this, but they should call this base class method at the end of the overloaded function.

Definition at line 131 of file [YIntField.cc](#).

Here is the call graph for this function:




3.66.3.8 void YIntField::setMaxValue (int val)

Set a new maximum value. If the current value is greater than that, it will be set to the new maximum.

Definition at line 111 of file [YIntField.cc](#).

Here is the call graph for this function:




3.66.3.9 void YIntField::setMinValue (int val)

Set a new minimum value. If the current value is less than that, it will be set to the new minimum.

Definition at line 91 of file YIntField.cc.

Here is the call graph for this function:



```
3.66.3.10 bool YIntField::setProperty ( const std::string & propertyName, const
        YPropertyValue & val ) [virtual]
```

Set a property. Reimplemented from [YWidget](#).


This function may throw `YUIPropertyExceptions`.

This function returns 'true' if the value was successfully set and 'false' if that value requires special handling (not in error cases: those are covered by exceptions).

Reimplemented from [YWidget](#).

Definition at line 163 of file YIntField.cc.

Here is the call graph for this function:



3.66.3.11 virtual void YIntField::setShortcutString (const std::string & str) [inline, virtual]


Set the string of this widget that holds the keyboard shortcut.

Reimplemented from [YWidget](#).

Reimplemented from [YWidget](#).

Definition at line 179 of file [YIntField.h](#).

Here is the call graph for this function:




3.66.3.12 void YIntField::setValue (int val) [inline]

Set the current value (the number entered by the user or set from the outside) of this IntField. This method enforces 'val' to be between minValue and maxValue.

Definition at line 81 of file [YIntField.h](#).

Here is the call graph for this function:



3.66.3.13 `virtual void YIntField::setValueInternal (int val)` `[protected, pure virtual]`

Set the current value (the number entered by the user or set from the outside) of this IntField. 'val' is guaranteed to be between `minValue` and `maxValue`; no further checks are required.

Derived classes are required to implement this method.

3.66.3.14 `virtual std::string YIntField::shortcutString () const` `[inline, virtual]`


Get the string of this widget that holds the keyboard shortcut.

Reimplemented from [YWidget](#).

Reimplemented from [YWidget](#).

Definition at line 172 of file [YIntField.h](#).

Here is the call graph for this function:



3.66.3.15 `const char* YIntField::userInputProperty () [inline, virtual]`

The name of the widget property that will return user input. Inherited from [YWidget](#).

Reimplemented from [YWidget](#).

Definition at line 186 of file [YIntField.h](#).

3.66.3.16 `virtual int YIntField::value () [pure virtual]`

Get the current value (the number entered by the user or set from the outside) of this IntField.

Derived classes are required to implement this.

3.66.3.17 `virtual const char* YIntField::widgetClass () const [inline, virtual]`

Return a descriptive name of this widget class for logging, debugging etc.

Reimplemented from [YWidget](#).

Reimplemented in [YSlider](#).

Definition at line 66 of file [YIntField.h](#).

The documentation for this class was generated from the following files:

- `/usr/src/RPM/BUILD/libyui-3.0.10/src/YIntField.h`
- `/usr/src/RPM/BUILD/libyui-3.0.10/src/YIntField.cc`

3.67 YIntFieldPrivate Struct Reference

Public Member Functions

- **YIntFieldPrivate** (const std::string &label, int minValue, int maxValue)

Public Attributes

- std::string **label**
- int **minValue**
- int **maxValue**

3.67.1 Detailed Description

Definition at line 32 of file [YIntField.cc](#).


The documentation for this struct was generated from the following file:

- [/usr/src/RPM/BUILD/libyui-3.0.10/src/YIntField.cc](#)

3.68 YItem Class Reference

```
#include <YItem.h>
```

Inheritance diagram for YItem:



Public Member Functions

- [YItem](#) (const std::string &[label](#), bool [selected](#)=false)
- [YItem](#) (const std::string &[label](#), const std::string &[iconName](#), bool [selected](#)=false)
- virtual [~YItem](#) ()
- std::string [label](#) () const
- void [setLabel](#) (const std::string &newLabel)
- std::string [iconName](#) () const
- bool [hasIconName](#) () const
- void [setIconName](#) (const std::string &newIconName)

- bool [selected](#) () const
- void [setSelected](#) (bool sel=true)
- void [setIndex](#) (int [index](#))
- int [index](#) () const
- void [setData](#) (void *newData)
- void * [data](#) () const
- virtual bool [hasChildren](#) () const
- virtual YItemIterator [childrenBegin](#) ()
- virtual YItemConstIterator **childrenBegin** () const
- virtual YItemIterator [childrenEnd](#) ()
- virtual YItemConstIterator **childrenEnd** () const
- virtual YItem * [parent](#) () const

3.68.1 Detailed Description

Simple item class for SelectionBox, ComboBox, MultiSelectionBox etc. items. This class provides stubs for children management.

Definition at line [43](#) of file [YItem.h](#).

3.68.2 Constructor & Destructor Documentation

3.68.2.1 `YItem::YItem (const std::string & label, bool selected = false) [inline]`

Constructor with just the label and optionally the selected state.

Definition at line [49](#) of file [YItem.h](#).

3.68.2.2 `YItem::YItem (const std::string & label, const std::string & iconName, bool selected = false) [inline]`

Constructor with label and icon name and optionally the selected state.

Definition at line [59](#) of file [YItem.h](#).

3.68.2.3 `virtual YItem::~YItem () [inline, virtual]`

Destructor.

Definition at line [70](#) of file [YItem.h](#).

3.68.3 Member Function Documentation

3.68.3.1 virtual YItemIterator YItem::childrenBegin () [inline, virtual]

Return an iterator that points to the first child item of this item.

This default implementation returns the 'end' iterator of the class-static always empty `_noChildren YItemCollection`. It is safe to use this iterator in classic iterator loops:

```
for ( YItemIterator it = myItem->childrenBegin(); it != myItem->childrenEnd(); ++it ) { ...
}
```

The loop body will only ever be executed if this item is a derived class that actually manages child items.

Reimplemented in [YTreeItem](#).

Definition at line 166 of file [YItem.h](#).

3.68.3.2 virtual YItemIterator YItem::childrenEnd () [inline, virtual]

Return an iterator that points after the last child item of this item.

This default implementation returns the 'end' iterator of the class-static always empty `_noChildren YItemCollection`.

Reimplemented in [YTreeItem](#).

Definition at line 175 of file [YItem.h](#).

3.68.3.3 void* YItem::data () const [inline]

Return the opaque data pointer.

Definition at line 133 of file [YItem.h](#).

3.68.3.4 virtual bool YItem::hasChildren () const [inline, virtual]

Return 'true' if this item has any child items.

Reimplemented in [YTreeItem](#).

Definition at line 147 of file [YItem.h](#).

3.68.3.5 bool YItem::hasIconName () const [inline]

Return 'true' if this item has an icon name.

Definition at line 91 of file [YItem.h](#).

3.68.3.6 `std::string YItem::iconName () const` `[inline]`

Return this item's icon name.

Definition at line 86 of file [YItem.h](#).

3.68.3.7 `int YItem::index () const` `[inline]`

Return the index of this item (as set with [setIndex\(\)](#)).

Definition at line 118 of file [YItem.h](#).

3.68.3.8 `std::string YItem::label () const` `[inline]`

Return this item's label. This is what the user sees in a dialog, so this will usually be a translated text.

Reimplemented in [YTableItem](#).

Definition at line 76 of file [YItem.h](#).

3.68.3.9 `virtual YItem* YItem::parent () const` `[inline, virtual]`

Returns this item's parent item or 0 if it is a toplevel item. This default implementation always returns 0. Derived classes that handle children should reimplement this.

Reimplemented in [YTreeItem](#), and [YMenuItem](#).

Definition at line 183 of file [YItem.h](#).

3.68.3.10 `bool YItem::selected () const` `[inline]`

Return 'true' if this item is currently selected.

Definition at line 101 of file [YItem.h](#).

3.68.3.11 `void YItem::setData (void * newData)` `[inline]`

Set the opaque data pointer for application use.

Applications can use this to store the pointer to a counterpart of this tree item. It is the application's responsibility to watch for dangling pointers and possibly deleting the data. All this class ever does with this pointer is to store it.

Definition at line 128 of file [YItem.h](#).

3.68.3.12 void YItem::setIconName (const std::string & newIconName) [inline]

Set this item's icon name.

Definition at line 96 of file [YItem.h](#).

3.68.3.13 void YItem::setIndex (int index) [inline]

Set this item's index.

Definition at line 113 of file [YItem.h](#).

Here is the call graph for this function:

**3.68.3.14** void YItem::setLabel (const std::string & newLabel) [inline]

Set this item's label.

Definition at line 81 of file [YItem.h](#).

3.68.3.15 void YItem::setSelected (bool sel = true) [inline]

Select or unselect this item. This does not have any effect on any other item; if it is desired that only one item is selected at any time, the caller has to take care of that.

Definition at line 108 of file [YItem.h](#).


The documentation for this class was generated from the following files:

- /usr/src/RPM/BUILD/libyui-3.0.10/src/YItem.h
- /usr/src/RPM/BUILD/libyui-3.0.10/src/YItem.cc


3.69 YItemShortcut Class Reference

```
#include <YShortcut.h>
```

Inheritance diagram for YItemShortcut:



Collaboration diagram for YItemShortcut:



Public Member Functions

- [YItemShortcut](#) ([YWidget](#) **widget*, [YItem](#) **item*)
- virtual [~YItemShortcut](#) ()
- [YItem](#) * *item* () const
- virtual void [setShortcut](#) (char newShortcut)

Protected Member Functions

- virtual std::string [getShortcutString](#) ()

3.69.1 Detailed Description

Special case for widgets that can have multiple shortcuts based on items (like [YDumb-Tab](#))

Definition at line 225 of file [YShortcut.h](#).

3.69.2 Constructor & Destructor Documentation

3.69.2.1 [YItemShortcut::YItemShortcut](#) ([YWidget](#) * *widget*, [YItem](#) * *item*)
[inline]

Constructor.

Definition at line 231 of file [YShortcut.h](#).

3.69.2.2 virtual [YItemShortcut::~YItemShortcut](#) () [inline, virtual]

Destructor.

Definition at line 239 of file [YShortcut.h](#).

3.69.3 Member Function Documentation


3.69.3.1 std::string [YItemShortcut::getShortcutString](#) () [protected, virtual]

Obtain the the shortcut property of this shortcut's widget - the string that contains "&" to designate a shortcut.

Reimplemented from [YShortcut](#).

Definition at line 310 of file [YShortcut.cc](#).

Here is the call graph for this function:



3.69.3.2 `YItem* YItemShortcut::item () const` [inline]

Return the associated item.

Definition at line 244 of file [YShortcut.h](#).


3.69.3.3 `void YItemShortcut::setShortcut (char newShortcut)` [virtual]

Set (override) the shortcut character. In this subclass, it will change the internally stored item.

Reimplemented from [YShortcut](#).

Definition at line 320 of file [YShortcut.cc](#).

Here is the call graph for this function:




The documentation for this class was generated from the following files:

- `/usr/src/RPM/BUILD/libyui-3.0.10/src/YShortcut.h`


- /usr/src/RPM/BUILD/libyui-3.0.10/src/YShortcut.cc

3.70 YKeyEvent Class Reference

Inheritance diagram for YKeyEvent:



Collaboration diagram for YKeyEvent:



Public Member Functions

- [YKeyEvent](#) (const std::string &[keySymbol](#), [YWidget](#) *[focusWidget](#)=0)
- std::string [keySymbol](#) () const

- [YWidget](#) * [focusWidget](#) () const

Protected Member Functions

- virtual [~YKeyEvent](#) ()

Protected Attributes

- std::string [_keySymbol](#)
- [YWidget](#) * [_focusWidget](#)

3.70.1 Detailed Description

Definition at line 206 of file [YEvent.h](#).

3.70.2 Constructor & Destructor Documentation

3.70.2.1 [YKeyEvent::YKeyEvent](#) (const std::string & *keySymbol*, [YWidget](#) * *focusWidget* = 0)

Constructor.

Create a key event with a specified key symbol (a text describing the key, such as "-CursorLeft", "F1", etc.) and optionally the widget that currently has the keyboard focus.

Definition at line 123 of file [YEvent.cc](#).

3.70.2.2 virtual [YKeyEvent::~YKeyEvent](#) () [inline, protected, virtual]

Protected destructor - events can only be deleted via [YDialog::deleteEvent\(\)](#). The associated dialog will take care of this event and delete it when appropriate.

Definition at line 241 of file [YEvent.h](#).

3.70.3 Member Function Documentation

3.70.3.1 [YWidget](#)* [YKeyEvent::focusWidget](#) () const [inline]

Returns the widget that currently has the keyboard focus.

This might be 0 if no widget has the focus or if the creator of this event could not obtain that information.

Definition at line 232 of file [YEvent.h](#).

3.70.3.2 `std::string YKeyEvent::keySymbol () const` `[inline]`

Returns the key symbol - a text describing the key, such as "CursorLeft", "F1", "a", "A", etc.

Definition at line 224 of file [YEvent.h](#).


The documentation for this class was generated from the following files:

- `/usr/src/RPM/BUILD/libyui-3.0.10/src/YEvent.h`
- `/usr/src/RPM/BUILD/libyui-3.0.10/src/YEvent.cc`


3.71 YLabel Class Reference

```
#include <YLabel.h>
```

Inheritance diagram for YLabel:



Collaboration diagram for YLabel:



Public Member Functions

- [YLabel](#) ([YWidget](#) *parent, const std::string &text, bool isHeading=false, bool isOutputField=false)
- virtual [~YLabel](#) ()
- virtual const char * [widgetClass](#) () const
- std::string [text](#) () const
- std::string [value](#) () const
- std::string [label](#) () const
- virtual void [setText](#) (const std::string &newText)
- void [setValue](#) (const std::string &newValue)
- void [setLabel](#) (const std::string &newLabel)
- bool [isHeading](#) () const
- bool [isOutputField](#) () const
- bool [useBoldFont](#) () const
- virtual void [setUseBoldFont](#) (bool bold=true)
- virtual bool [setProperty](#) (const std::string &propertyName, const [YPropertyValue](#) &val)
- virtual [YPropertyValue](#) [getProperty](#) (const std::string &propertyName)
- virtual const [YPropertySet](#) & [propertySet](#) ()
- virtual std::string [debugLabel](#) () const

3.71.1 Detailed Description

Implementation of the Label, Heading and OutputField widgets

Definition at line 38 of file [YLabel.h](#).

3.71.2 Constructor & Destructor Documentation

3.71.2.1 `YLabel::YLabel (YWidget * parent, const std::string & text, bool isHeading = false, bool isOutputField = false)`

Constructor.

'isHeading' indicates if this should be displayed as a Heading widget, i.e. with a bold and/or larger font. This cannot be changed after creating the widget.

'isOutputField' indicates if this should be displayed as an OutputField widget, i.e. similar to an InputField the user can't change. This cannot be changed after creating the widget.

Definition at line 56 of file [YLabel.cc](#).

3.71.2.2 `YLabel::~YLabel ()` [virtual]

Destructor.

Definition at line 67 of file [YLabel.cc](#).

3.71.3 Member Function Documentation

3.71.3.1 `std::string YLabel::debugLabel () const` [virtual]


Returns a descriptive label of this widget instance for debugging.

Reimplemented from [YWidget](#) since a [YLabel](#) doesn't have a shortcut property.

Reimplemented from [YWidget](#).

Definition at line 164 of file [YLabel.cc](#).

Here is the call graph for this function:



3.71.3.2 YPropertyValue YLabel::getProperty (const std::string & *propertyName*) [virtual]

Get a property. Reimplemented from [YWidget](#).


This method may throw exceptions, for example

- if there is no property with that name

Reimplemented from [YWidget](#).

Definition at line 150 of file [YLabel.cc](#).

Here is the call graph for this function:



3.71.3.3 bool YLabel::isHeading () const

Return 'true' if this is a Heading widget, i.e., it should display its text in a bold and/or larger font.

This cannot be changed after creating the widget.

Definition at line 85 of file [YLabel.cc](#).

3.71.3.4 bool YLabel::isOutputField () const

Return 'true' if this is an OutputField widget, i.e., it should display its text similar to an InputField the user can't change.

This cannot be changed after creating the widget.

Definition at line 91 of file [YLabel.cc](#).

3.71.3.5 `const YPropertySet & YLabel::propertySet ()` [virtual]

Return this class's property set. This also initializes the property set upon the first call.

Reimplemented from [YWidget](#).

Reimplemented from [YWidget](#).

Definition at line 110 of file [YLabel.cc](#).

Here is the call graph for this function:



3.71.3.6 `bool YLabel::setProperty (const std::string & propertyName, const YPropertyValue & val)` [virtual]

Set a property. Reimplemented from [YWidget](#).

This method may throw exceptions, for example


- if there is no property with that name
- if the expected type and the type mismatch
- if the value is out of range

This function returns 'true' if the value was successfully set and 'false' if that value requires special handling (not in error cases: those are covered by exceptions).

Reimplemented from [YWidget](#).

Definition at line 133 of file [YLabel.cc](#).

Here is the call graph for this function:



3.71.3.7 void YLabel::setText (const std::string & newText) [virtual]

Set the text the widget displays.

Derived classes should overwrite this, but call this base class function in the overwritten function.

Definition at line 79 of file [YLabel.cc](#).

3.71.3.8 void YLabel::setUseBoldFont (bool bold = true) [virtual]

Switch bold font on or off.

Derived classes should overwrite this, but call this base class function in the overwritten function.

Definition at line 103 of file [YLabel.cc](#).

3.71.3.9 void YLabel::setValue (const std::string & newValue) [inline]

Aliases for [setText\(\)](#).

Definition at line 93 of file [YLabel.h](#).

Here is the call graph for this function:



3.71.3.10 `std::string YLabel::text () const`

Return the text the widget displays.

Definition at line 73 of file [YLabel.cc](#).

3.71.3.11 `bool YLabel::useBoldFont () const`

Return 'true' if a bold font should be used.

Definition at line 97 of file [YLabel.cc](#).

3.71.3.12 `std::string YLabel::value () const` `[inline]`

Aliases for [text\(\)](#).

Definition at line 79 of file [YLabel.h](#).

Here is the call graph for this function:



3.71.3.13 `const char * YLabel::widgetClass () const` `[virtual]`

Returns a descriptive name of this widget class for logging, debugging etc.

Reimplemented from [YWidget](#).

Reimplemented from [YWidget](#).

Definition at line 186 of file [YLabel.cc](#).

The documentation for this class was generated from the following files:

- [/usr/src/RPM/BUILD/libyui-3.0.10/src/YLabel.h](#)
- [/usr/src/RPM/BUILD/libyui-3.0.10/src/YLabel.cc](#)

3.72 YLabelPrivate Struct Reference

Public Member Functions

- [YLabelPrivate](#) (const std::string &text, bool isHeading, bool isOutputField)

Public Attributes

- std::string **text**
- bool **isHeading**
- bool **isOutputField**
- bool **useBoldFont**

3.72.1 Detailed Description

Definition at line 35 of file [YLabel.cc](#).

3.72.2 Constructor & Destructor Documentation

3.72.2.1 `YLabelPrivate::YLabelPrivate (const std::string & text, bool isHeading, bool isOutputField)` `[inline]`

Constructor


Definition at line 40 of file [YLabel.cc](#).

The documentation for this struct was generated from the following file:


- [/usr/src/RPM/BUILD/libyui-3.0.10/src/YLabel.cc](#)

3.73 YLayoutBox Class Reference

Inheritance diagram for YLayoutBox:



Collaboration diagram for YLayoutBox:



Public Types

- typedef std::vector< int > **sizeVector**
- typedef std::vector< int > **posVector**

Public Member Functions

- virtual [~YLayoutBox](#) ()

- virtual const char * [widgetClass](#) () const
- YUIDimension [primary](#) () const
- YUIDimension [secondary](#) () const
- bool [debugLayout](#) () const
- void [setDebugLayout](#) (bool deb=true)
- virtual int [preferredSize](#) (YUIDimension dim)
- virtual int [preferredWidth](#) ()
- virtual int [preferredHeight](#) ()
- virtual void [setSize](#) (int newWidth, int newHeight)
- virtual bool [stretchable](#) (YUIDimension dimension) const
- virtual void [moveChild](#) (YWidget *child, int newX, int newY)=0

Static Public Member Functions

- static bool [isLayoutStretch](#) (YWidget *child, YUIDimension dimension)

Protected Member Functions

- [YLayoutBox](#) (YWidget *parent, YUIDimension dim)
- int [childrenTotalWeight](#) (YUIDimension dimension)
- int [childrenMaxPreferredSize](#) (YUIDimension dimension)
- int [totalNonWeightedChildrenPreferredSize](#) (YUIDimension dimension)
- int [countNonWeightedChildren](#) (YUIDimension dimension)
- int [countStretchableChildren](#) (YUIDimension dimension)
- int [countLayoutStretchChildren](#) (YUIDimension dimension)
- YWidget * [findDominatingChild](#) ()
- void [calcPrimaryGeometry](#) (int newSize, sizeVector &childSize, posVector &childPos)
- void [calcSecondaryGeometry](#) (int newSize, sizeVector &childSize, posVector &childPos)
- void [doResize](#) (sizeVector &width, sizeVector &height, posVector &x_pos, posVector &y_pos)

3.73.1 Detailed Description

Definition at line 35 of file [YLayoutBox.h](#).

3.73.2 Constructor & Destructor Documentation

3.73.2.1 YLayoutBox::YLayoutBox (YWidget * *parent*, YUIDimension *dim*) [protected]

Constructor.

Creates a VBox for `dim == YD_VERT` or a HBox for `YD_HORIZ`.

Definition at line 66 of file [YLayoutBox.cc](#).

Here is the call graph for this function:



3.73.2.2 YLayoutBox::~~YLayoutBox () [virtual]

Destructor.

Definition at line 75 of file [YLayoutBox.cc](#).


3.73.3 Member Function Documentation

3.73.3.1 void YLayoutBox::calcPrimaryGeometry (int *newSize*, sizeVector & *childSize*, posVector & *childPos*) [protected]

Calculate the sizes and positions of all children in the primary dimension and store them in "childSize" and "childPos".

Definition at line 398 of file [YLayoutBox.cc](#).

Here is the call graph for this function:




3.73.3.2 void YLayoutBox::calcSecondaryGeometry (int *newSize*, sizeVector & *childSize*, posVector & *childPos*) [protected]

Calculate the sizes and positions of all children in the secondary dimension and store them in "childSize" and "childPos".

Definition at line 694 of file [YLayoutBox.cc](#).

Here is the call graph for this function:




3.73.3.3 `int YLayoutBox::childrenMaxPreferredSize (YUIDimension dimension)` [protected]

Return the maximum preferred size of all children in the specified dimension.

Definition at line 231 of file [YLayoutBox.cc](#).

Here is the call graph for this function:




3.73.3.4 `int YLayoutBox::childrenTotalWeight (YUIDimension dimension)` `[protected]`

Add up all the children's weights.

Definition at line 247 of file [YLayoutBox.cc](#).

Here is the call graph for this function:




3.73.3.5 `int YLayoutBox::countLayoutStretchChildren (YUIDimension dimension)` `[protected]`

Count the number of "rubber bands", i.e. the number of stretchable layout spacings (e.g. `{H|V}Weight`, `{H|V}Spacing`). Only those without a weight are counted.

Definition at line 315 of file [YLayoutBox.cc](#).

Here is the call graph for this function:




3.73.3.6 int YLayoutBox::countNonWeightedChildren (YUIDimension *dimension*) [protected]

Count the number of non-weighted children.

Definition at line 280 of file [YLayoutBox.cc](#).

Here is the call graph for this function:




3.73.3.7 int YLayoutBox::countStretchableChildren (YUIDimension *dimension*) [protected]

Count the number of stretchable (non-weighted) children. Note: Weighted children are `_always_` considered stretchable.

Definition at line 297 of file [YLayoutBox.cc](#).

Here is the call graph for this function:



3.73.3.8 bool YLayoutBox::debugLayout () const

Returns 'true' if layout debugging (verbose logging during layout) is on.

Definition at line 96 of file [YLayoutBox.cc](#).


3.73.3.9 `void YLayoutBox::doResize (sizeVector & width, sizeVector & height, posVector & x_pos, posVector & y_pos)` [protected]

Actually perform resizing and moving the child widgets to the appropriate position.

The vectors passed are the sizes previously calculated by [calcPrimaryGeometry\(\)](#) and [calcSecondaryGeometry\(\)](#).

Definition at line 746 of file [YLayoutBox.cc](#).

Here is the call graph for this function:




3.73.3.10 `YWidget * YLayoutBox::findDominatingChild ()` [protected]

Determine the number of the "dominating child" - the child widget that determines the overall size with respect to its weight.

Return 0 if there is no dominating child, i.e. none of the children has a weight specified.

Definition at line 185 of file [YLayoutBox.cc](#).

Here is the call graph for this function:




3.73.3.11 `bool YLayoutBox::isLayoutStretch (YWidget * child, YUIDimension dimension) [static]`

Check if this is a layout stretch widget in the specified dimension, i.e. an empty widget that is stretchable.

Definition at line 333 of file [YLayoutBox.cc](#).

Here is the call graph for this function:



3.73.3.12 `virtual void YLayoutBox::moveChild (YWidget * child, int newX, int newY) [pure virtual]`

Move a child to a new position.

Derived classes are required to implement this.

3.73.3.13 `int YLayoutBox::preferredHeight ()` [virtual]


Preferred height of the widget.

Reimplemented from [YWidget](#).

Implements [YWidget](#).

Definition at line 165 of file [YLayoutBox.cc](#).

Here is the call graph for this function:



3.73.3.14 `int YLayoutBox::preferredSize (YUIDimension dim)` [virtual]


Preferred size of the widget in the specified dimension.

Reimplemented from [YWidget](#).

Reimplemented from [YWidget](#).

Definition at line 111 of file [YLayoutBox.cc](#).

Here is the call graph for this function:



3.73.3.15 int YLayoutBox::preferredWidth () [virtual]


Preferred width of the widget.

Reimplemented from [YWidget](#).

Implements [YWidget](#).

Definition at line 159 of file [YLayoutBox.cc](#).

Here is the call graph for this function:



3.73.3.16 YUIDimension YLayoutBox::primary () const

Return the primary dimension, i.e., the dimension this LayoutBox lays out its children in: YD_VERT for a VBox, YD_HORIZ for a HBox.

Definition at line 82 of file [YLayoutBox.cc](#).

3.73.3.17 YUIDimension YLayoutBox::secondary () const

Return the secondary dimension.

Definition at line 89 of file [YLayoutBox.cc](#).

3.73.3.18 void YLayoutBox::setDebugLayout (bool *deb* = true)

Enable or disable layout debugging.

Definition at line 102 of file [YLayoutBox.cc](#).

3.73.3.19 void YLayoutBox::setSize (int *newWidth*, int *newHeight*) [virtual]

Sets the size of the layout box. This is where the layout policy is implemented.


Derived classes can reimplement this, but this base class method should be called in the reimplemented function.

Reimplemented from [YWidget](#).

Implements [YWidget](#).

Definition at line 365 of file [YLayoutBox.cc](#).

Here is the call graph for this function:



```
3.73.3.20 bool YLayoutBox::stretchable ( YUIDimension dimension ) const
           [virtual]
```


Returns the stretchability of the layout box: The layout box is stretchable if one of the children is stretchable in this dimension or if one of the child widgets has a layout weight in this dimension.

Reimplemented from [YWidget](#).

Reimplemented from [YWidget](#).

Definition at line 349 of file YLayoutBox.cc.

Here is the call graph for this function:




3.73.3.21 `int YLayoutBox::totalNonWeightedChildrenPreferredSize (YUIDimension dimension)` [protected]

Add up all the non-weighted children's preferred sizes in the specified dimension.

Definition at line 263 of file [YLayoutBox.cc](#).

Here is the call graph for this function:



3.73.3.22 `const char * YLayoutBox::widgetClass () const` [virtual]

Returns a descriptive name of this widget class for logging, debugging etc.

Reimplemented from [YWidget](#).

Definition at line 775 of file [YLayoutBox.cc](#).

Here is the call graph for this function:



The documentation for this class was generated from the following files:

- /usr/src/RPM/BUILD/libyui-3.0.10/src/YLayoutBox.h
- /usr/src/RPM/BUILD/libyui-3.0.10/src/YLayoutBox.cc

3.74 YLayoutBoxPrivate Struct Reference

Public Member Functions

- [YLayoutBoxPrivate](#) (YUIDimension prim)

Public Attributes

- YUIDimension **primary**
- YUIDimension **secondary**
- bool **debugLayout**

3.74.1 Detailed Description

Definition at line 43 of file [YLayoutBox.cc](#).

3.74.2 Constructor & Destructor Documentation

3.74.2.1 YLayoutBoxPrivate::YLayoutBoxPrivate (YUIDimension *prim*) `[inline]`

Constructor

Definition at line 48 of file [YLayoutBox.cc](#).


The documentation for this struct was generated from the following file:

- /usr/src/RPM/BUILD/libyui-3.0.10/src/YLayoutBox.cc


3.75 YLogView Class Reference

```
#include <YLogView.h>
```

Inheritance diagram for YLogView:



Collaboration diagram for YLogView:



Public Member Functions

- virtual [~YLogView](#) ()

- virtual const char * [widgetClass](#) () const
- std::string [label](#) () const
- virtual void [setLabel](#) (const std::string &[label](#))
- int [visibleLines](#) () const
- void [setVisibleLines](#) (int newVisibleLines)
- int [maxLines](#) () const
- void [setMaxLines](#) (int newMaxLines)
- std::string [logText](#) () const
- void [setLogText](#) (const std::string &text)
- std::string [lastLine](#) () const
- void [appendLines](#) (const std::string &text)
- void [clearText](#) ()
- int [lines](#) () const
- virtual bool [setProperty](#) (const std::string &propertyName, const [YPropertyValue](#) &val)
- virtual [YPropertyValue](#) [getProperty](#) (const std::string &propertyName)
- virtual const [YPropertySet](#) & [propertySet](#) ()
- virtual std::string [shortcutString](#) () const
- virtual void [setShortcutString](#) (const std::string &str)

Protected Member Functions

- [YLogView](#) ([YWidget](#) *[parent](#), const std::string &[label](#), int [visibleLines](#), int [maxLines](#))
- virtual void [displayLogText](#) (const std::string &text)=0

3.75.1 Detailed Description

LogView: A scrollable (output-only) text to display a growing log, very much like the "tail -f" shell command.

Definition at line 37 of file [YLogView.h](#).

3.75.2 Constructor & Destructor Documentation

3.75.2.1 [YLogView::YLogView](#) ([YWidget](#) * *parent*, const std::string & *label*, int *visibleLines*, int *maxLines*) [protected]

Constructor.

'label' is the caption above the log. 'visibleLines' indicates how many lines should be visible by default (unless changed by other layout constraints), 'maxLines' specifies how

many lines (always the last ones) to keep in the log. 0 for 'maxLines' means "keep all lines".

Definition at line 58 of file [YLogView.cc](#).

Here is the call graph for this function:



3.75.2.2 YLogView::~YLogView () [virtual]

Destructor.

Definition at line 69 of file [YLogView.cc](#).

3.75.3 Member Function Documentation

3.75.3.1 void YLogView::appendLines (const std::string & text)

Append one or more lines to the log text and trigger a display update.

Definition at line 161 of file [YLogView.cc](#).

3.75.3.2 void YLogView::clearText ()

Clear the log text and trigger a display update.

Definition at line 206 of file [YLogView.cc](#).

3.75.3.3 virtual void YLogView::displayLogText (const std::string & text) [protected, pure virtual]

Display the part of the log text that should be displayed. 'text' contains the last '[visibleLines\(\)](#)' lines. This is called whenever the log text changes. Note that the text might also be empty, in which case the displayed log text should be cleared.

Derived classes are required to implement this.

3.75.3.4 YPropertyValue YLogView::getProperty (const std::string & *propertyName*) [virtual]


Get a property. Reimplemented from [YWidget](#).

This method may throw YUIPropertyExceptions.

Reimplemented from [YWidget](#).

Definition at line 273 of file [YLogView.cc](#).

Here is the call graph for this function:



3.75.3.5 std::string YLogView::label () const

Return the label (the caption above the log text).

Definition at line 76 of file [YLogView.cc](#).

3.75.3.6 std::string YLogView::lastLine () const

Return the last log line.

Definition at line 151 of file [YLogView.cc](#).

3.75.3.7 int YLogView::lines () const

Return the current number of lines.

Definition at line 213 of file YLogView.cc.

3.75.3.8 std::string YLogView::logText () const

Return the entire log text as one large string of concatenated lines delimited with new-lines.

Definition at line 125 of file YLogView.cc.

3.75.3.9 int YLogView::maxLines () const

Return the maximum number of lines to store. The last `maxLines()` lines of the log text will be kept.

Definition at line 104 of file YLogView.cc.

3.75.3.10 const YPropertySet & YLogView::propertySet () [virtual]

Return this class's property set. This also initializes the property upon the first call.

Reimplemented from YWidget.

Reimplemented from YWidget.

Definition at line 228 of file YLogView.cc.

Here is the call graph for this function:



3.75.3.11 void YLogView::setLabel (const std::string & label) [virtual]

Set the label (the caption above the log text).

Derived classes are free to reimplement this, but they should call this base class method at the end of the overloaded function.

Definition at line 83 of file [YLogView.cc](#).

Here is the call graph for this function:




3.75.3.12 `void YLogView::setLogText (const std::string & text) [inline]`

Set (replace) the entire log text and trigger a display update.

Definition at line 122 of file [YLogView.h](#).

Here is the call graph for this function:



3.75.3.13 `void YLogView::setMaxLines (int newMaxLines)`

Set the maximum number of lines to store. "0" means "keep all lines" (beware of memory overflow!).

If the new value is lower than the old value, any (now) excess lines before the last 'newMaxLines' lines of the log text is cut off and a display update is triggered.

This method is intentionally not virtual since a display update is triggered when appropriate.

Definition at line 111 of file [YLogView.cc](#).

3.75.3.14 `bool YLogView::setProperty (const std::string & propertyName, const YPropertyValue & val) [virtual]`

Set a property. Reimplemented from [YWidget](#).


This function may throw YUIPropertyExceptions.

This function returns 'true' if the value was successfully set and 'false' if that value requires special handling (not in error cases: those are covered by exceptions).

Reimplemented from [YWidget](#).

Definition at line 254 of file [YLogView.cc](#).

Here is the call graph for this function:



3.75.3.15 `virtual void YLogView::setShortcutString (const std::string & str)`
[inline, virtual]


Set the string of this widget that holds the keyboard shortcut.

Reimplemented from [YWidget](#).

Reimplemented from [YWidget](#).

Definition at line 186 of file [YLogView.h](#).

Here is the call graph for this function:



3.75.3.16 `void YLogView::setVisibleLines (int newVisibleLines)`

Set the number of visible lines. Changing this has only effect upon the next geometry call, so applications calling this function might want to trigger a re-layout afterwards.

This method is intentionally not virtual: `visibleLines()` should be queried in the [preferred-Height\(\)](#) implementation.

Definition at line 97 of file [YLogView.cc](#).

3.75.3.17 `virtual std::string YLogView::shortcutString () const` [inline, virtual]


Get the string of this widget that holds the keyboard shortcut.

Reimplemented from [YWidget](#).

Reimplemented from [YWidget](#).

Definition at line 179 of file [YLogView.h](#).

Here is the call graph for this function:



3.75.3.18 int YLogView::visibleLines () const

Return the number of visible lines.

Definition at line 90 of file [YLogView.cc](#).

3.75.3.19 virtual const char* YLogView::widgetClass () const [inline, virtual]

Returns a descriptive name of this widget class for logging, debugging etc.

Reimplemented from [YWidget](#).

Definition at line 64 of file [YLogView.h](#).

The documentation for this class was generated from the following files:

- [/usr/src/RPM/BUILD/libyui-3.0.10/src/YLogView.h](#)
- [/usr/src/RPM/BUILD/libyui-3.0.10/src/YLogView.cc](#)

3.76 YLogViewPrivate Struct Reference

Public Member Functions

- **YLogViewPrivate** (const std::string &label, int visibleLines, int maxLines)

Public Attributes

- std::string **label**
- int **visibleLines**

- int **maxLines**
- StringDeque **logText**

3.76.1 Detailed Description

Definition at line 40 of file [YLogView.cc](#).

The documentation for this struct was generated from the following file:

- /usr/src/RPM/BUILD/libyui-3.0.10/src/YLogView.cc

3.77 YMacro Class Reference

```
#include <YMacro.h>
```

Static Public Member Functions

- static void [setRecorder](#) ([YMacroRecorder](#) *recorder)
- static void [setPlayer](#) ([YMacroPlayer](#) *player)
- static void [record](#) (const std::string ¯oFile)
- static void [endRecording](#) ()
- static bool [recording](#) ()
- static void [play](#) (const std::string ¯oFile)
- static void [playNextBlock](#) ()
- static bool [playing](#) ()
- static [YMacroRecorder](#) * [recorder](#) ()
- static [YMacroPlayer](#) * [player](#) ()
- static void [deleteRecorder](#) ()
- static void [deletePlayer](#) ()

3.77.1 Detailed Description

Simple access to macro recording and playing.

This class stores an instance of a macro recorder and a macro player. Since both - [YMacroRecorder](#) and [YMacroPlayer](#) are abstract base classes, derived classes from either of them have to be instantiated and set ([setRecorder\(\)](#), [setPlayer\(\)](#)) from the outside for anything to happen. Until that point, none of the macro operations here do anything (but also don't throw any error or exception).

Definition at line 44 of file [YMacro.h](#).

3.77.2 Member Function Documentation

3.77.2.1 void YMacro::deletePlayer () [static]

Delete the current macro player if there is one.

Definition at line 105 of file [YMacro.cc](#).

3.77.2.2 void YMacro::deleteRecorder () [static]

Delete the current macro recorder if there is one.

Definition at line 98 of file [YMacro.cc](#).

3.77.2.3 void YMacro::endRecording () [static]

End macro recording.

Definition at line 59 of file [YMacro.cc](#).

Here is the call graph for this function:



3.77.2.4 void YMacro::play (const std::string & macroFile) [static]

Play a macro from the specified macro file.

Definition at line 75 of file [YMacro.cc](#).

Here is the call graph for this function:



3.77.2.5 `static YMacroPlayer* YMacro::player () [inline, static]`

Return the current macro player or 0 if there is none.

Definition at line 106 of file [YMacro.h](#).

3.77.2.6 `bool YMacro::playing () [static]`

Return 'true' if a macro is currently being played.

Definition at line 89 of file [YMacro.cc](#).

Here is the call graph for this function:




3.77.2.7 `void YMacro::playNextBlock () [static]`

Play the next block from the current macro, if there is one playing.

Definition at line 82 of file [YMacro.cc](#).

Here is the call graph for this function:




3.77.2.8 void YMacro::record (const std::string & macroFile) [static]

Record a macro to the specified macro file.

Definition at line 52 of file [YMacro.cc](#).

Here is the call graph for this function:



3.77.2.9 static YMacroRecorder* YMacro::recorder () [inline, static]

Return the current macro recorder or 0 if there is none.

Definition at line 101 of file [YMacro.h](#).

3.77.2.10 bool YMacro::recording () [static]

Return 'true' if a macro is currently being recorded.

Definition at line 66 of file [YMacro.cc](#).

Here is the call graph for this function:



3.77.2.11 void YMacro::setPlayer (YMacroPlayer * *player*) [static]

Set a macro player.

This needs to be done from the outside since [YMacroRecorder](#) is an abstract base class, i.e., it needs to be derived to be instantiated.

Definition at line 43 of file [YMacro.cc](#).

Here is the call graph for this function:



3.77.2.12 void YMacro::setRecorder (YMacroRecorder * *recorder*) [static]

Set a macro recorder.

This needs to be done from the outside since [YMacroRecorder](#) is an abstract base class, i.e., it needs to be derived to be instantiated.

Definition at line 34 of file [YMacro.cc](#).

Here is the call graph for this function:



The documentation for this class was generated from the following files:

- `/usr/src/RPM/BUILD/libyui-3.0.10/src/YMacro.h`
- `/usr/src/RPM/BUILD/libyui-3.0.10/src/YMacro.cc`

3.78 YMacroPlayer Class Reference

```
#include <YMacroPlayer.h>
```

Public Member Functions

- virtual `~YMacroPlayer` ()
- virtual void `play` (const std::string ¯oFile)=0
- virtual void `playNextBlock` ()=0
- virtual bool `playing` () const =0

Protected Member Functions

- `YMacroPlayer` ()

Friends

- class `YMacro`

3.78.1 Detailed Description

Abstract base class for macro player.

Applications should not use this directly, but the static methods in [YMacro](#).

Definition at line 35 of file [YMacroPlayer.h](#).

3.78.2 Constructor & Destructor Documentation

3.78.2.1 YMacroPlayer::YMacroPlayer () [inline, protected]

Constructor

Definition at line 43 of file [YMacroPlayer.h](#).

3.78.2.2 virtual YMacroPlayer::~YMacroPlayer () [inline, virtual]

Destructor

Definition at line 49 of file [YMacroPlayer.h](#).

3.78.3 Member Function Documentation

3.78.3.1 virtual void YMacroPlayer::play (const std::string & *macroFile*) [pure virtual]

Play a macro from the specified macro file.

3.78.3.2 virtual bool YMacroPlayer::playing () const [pure virtual]

Return 'true' if a macro is currently being played.

3.78.3.3 virtual void YMacroPlayer::playNextBlock () [pure virtual]

Play the next block from the current macro, if there is one playing.

The documentation for this class was generated from the following file:

- /usr/src/RPM/BUILD/libyui-3.0.10/src/YMacroPlayer.h

3.79 YMacroRecorder Class Reference

```
#include <YMacroRecorder.h>
```

Public Member Functions

- virtual [~YMacroRecorder](#) ()
- virtual void [record](#) (const std::string ¯oFileName)=0
- virtual void [endRecording](#) ()=0
- virtual bool [recording](#) () const =0
- virtual void [recordWidgetProperty](#) (YWidget *widget, const char *propertyName)=0
- virtual void [recordMakeScreenShot](#) (bool enabled=false, const std::string &filename=std::string())=0

Protected Member Functions

- [YMacroRecorder](#) ()

Friends

- class **YMacro**

3.79.1 Detailed Description

Abstract base class for macro recorders.

Applications should not use this directly, but the static methods in [YMacro](#).

Definition at line 38 of file [YMacroRecorder.h](#).

3.79.2 Constructor & Destructor Documentation

3.79.2.1 YMacroRecorder::YMacroRecorder () [inline, protected]

Constructor

Definition at line 47 of file [YMacroRecorder.h](#).

3.79.2.2 virtual YMacroRecorder::~YMacroRecorder () [inline, virtual]

Destructor

Definition at line 53 of file [YMacroRecorder.h](#).

3.79.3 Member Function Documentation

3.79.3.1 `virtual void YMacroRecorder::endRecording () [pure virtual]`

End recording and close the current macro file (if there is any).

3.79.3.2 `virtual void YMacroRecorder::record (const std::string & macroFileName)
[pure virtual]`

Start recording a macro to the specified file.

3.79.3.3 `virtual bool YMacroRecorder::recording () const [pure virtual]`

Return 'true' if a macro is currently being recorded.

3.79.3.4 `virtual void YMacroRecorder::recordMakeScreenShot (bool enabled
= false, const std::string & filename = std::string()) [pure
virtual]`

Record a "UI::MakeScreenShot()" statement.

If 'enabled' is 'false', this statement will be commented out. If no file name is given, a default file name (with auto-increment) will be used.

3.79.3.5 `virtual void YMacroRecorder::recordWidgetProperty (YWidget * widget,
const char * propertyName) [pure virtual]`

Record one widget property.


The documentation for this class was generated from the following file:

- /usr/src/RPM/BUILD/libyui-3.0.10/src/YMacroRecorder.h


3.80 YMenuButton Class Reference

```
#include <YMenuButton.h>
```

Inheritance diagram for YMenuButton:



Collaboration diagram for YMenuButton:



Public Member Functions

- virtual `~YMenuButton()`
- virtual const char * `widgetClass()` const
- virtual void `rebuildMenuTree()`=0
- virtual void `addItems` (const YItemCollection &itemCollection)
- virtual void `addItem` (YItem *item_disown)
- virtual void `deleteAllItems()`
- void `resolveShortcutConflicts()`
- virtual bool `setProperty` (const std::string &propertyName, const YPropertyValue &val)
- virtual YPropertyValue `getProperty` (const std::string &propertyName)
- virtual const YPropertySet & `propertySet()`

Protected Member Functions

- YMenuButton (YWidget *parent, const std::string &label)
- YMenuItem * `findMenuItem` (int index)
- YMenuItem * `findMenuItem` (int index, YItemConstIterator begin, YItemConstIterator end)
- YMenuItem * `itemAt` (int index)

3.80.1 Detailed Description

MenuButton: Similar to PushButton, but with several actions: Upon clicking on a MenuButton (or activating it with the keyboard), a pop-up menu opens where the user can activate an action. Menu items in that pop-up menu can have submenus (that will pop up in separate pop-up menus).

Internally, this widget is more similar to the Tree widget. The difference is that it does not keep a "selected" status, but triggers an action right away, just like a PushButton. Like PushButton, MenuButton sends an event right away when the user selects an item (clicks on a menu item or activates it with the keyboard). Items that have a submenu never send an event, they simply open their submenu when activated.

Definition at line 48 of file [YMenuButton.h](#).

3.80.2 Constructor & Destructor Documentation

3.80.2.1 YMenuButton::YMenuButton (YWidget * parent, const std::string & label) [protected]

Constructor.

'label' is the user-visible text on the button (not above it like all other SelectionWidgets).

Definition at line 46 of file [YMenuButton.cc](#).

3.80.2.2 YMenuButton::~YMenuButton () [virtual]

Destructor.

Definition at line 55 of file [YMenuButton.cc](#).

3.80.3 Member Function Documentation

3.80.3.1 void YMenuButton::addItem (YItem * *item_disown*) [virtual]

Add one item. This widget assumes ownership of the item object and will delete it in its destructor.


This reimplementation will an index to the item that is unique for all items in this Menu-Button. That index can be used later with [findMenuitem\(\)](#) to find the item by that index.

Reimplemented from [YSelectionWidget](#).

Reimplemented from [YSelectionWidget](#).

Definition at line 71 of file [YMenuButton.cc](#).

Here is the call graph for this function:



3.80.3.2 void YMenuButton::addItems (const YItemCollection & *itemCollection*) [virtual]

Add multiple items. For some UIs, this can be more efficient than calling [addItem\(\)](#) multiple times. This function also automatically calls [resolveShortcutConflicts\(\)](#) and [rebuildMenuTree\(\)](#) at the end.


Derived classes can overwrite this function, but they should call this base class function at the end of the new implementation.

Reimplemented from [YSelectionWidget](#).

Reimplemented from [YSelectionWidget](#).

Definition at line 62 of file [YMenuButton.cc](#).

Here is the call graph for this function:



3.80.3.3 void YMenuButton::deleteAllItems () [virtual]

Delete all items.

Reimplemented from [YSelectionWidget](#).

Reimplemented from [YSelectionWidget](#).


Definition at line 97 of file [YMenuButton.cc](#).

3.80.3.4 YMenuItem * YMenuButton::findMenuItem (int *index*) [protected]

Recursively find the first menu item with the specified index. Returns 0 if there is no such item.

Definition at line 105 of file [YMenuButton.cc](#).

Here is the call graph for this function:




3.80.3.5 `YMenuItem * YMenuButton::findMenuItem (int index, YItemConstIterator begin, YItemConstIterator end)` [protected]

Recursively find the first menu item with the specified index from iterator 'begin' to iterator 'end'.

Returns 0 if there is no such item.

Definition at line 112 of file [YMenuButton.cc](#).

Here is the call graph for this function:



3.80.3.6 `YPropertyValue YMenuButton::getProperty (const std::string & propertyName)` [virtual]


Get a property. Reimplemented from [YWidget](#).

This method may throw `YUIPropertyExceptions`.

Reimplemented from [YWidget](#).

Definition at line 192 of file [YMenuButton.cc](#).

Here is the call graph for this function:




3.80.3.7 YMenuItem* YMenuButton::itemAt (int index) [inline, protected]

Alias for [findMenuItem\(\)](#). Reimplemented to ensure consistent behaviour with [YSelectionWidget::itemAt\(\)](#).

Definition at line 170 of file [YMenuButton.h](#).

Here is the call graph for this function:



3.80.3.8 const YPropertySet & YMenuButton::propertySet () [virtual]

Return this class's property set. This also initializes the property upon the first call.

Reimplemented from [YWidget](#).

Reimplemented from [YWidget](#).

Definition at line 153 of file [YMenuButton.cc](#).

Here is the call graph for this function:



3.80.3.9 virtual void YMenuButton::rebuildMenuTree () [pure virtual]

Rebuild the displayed menu tree from the internally stored YMenuItems.

The application should call this (once) after all items have been added with [addItem\(\)](#). [YMenuButton::addItem\(\)](#) calls this automatically.

Derived classes are required to implement this.

3.80.3.10 void YMenuButton::resolveShortcutConflicts ()

Resolve keyboard shortcut conflicts: Change shortcuts of menu items if there are duplicates in the respective menu level.

This has to be called after all items are added, but before [rebuildMenuTree\(\)](#) (see above). [YMenuButton::addItem\(\)](#) calls this automatically.

Definition at line 138 of file [YMenuButton.cc](#).

3.80.3.11 bool YMenuButton::setProperty (const std::string & propertyName, const YPropertyValue & val) [virtual]

Set a property. Reimplemented from [YWidget](#).


This function may throw YUIPropertyExceptions.

This function returns 'true' if the value was successfully set and 'false' if that value requires special handling (not in error cases: those are covered by exceptions).

Reimplemented from [YWidget](#).

Definition at line 175 of file [YMenuButton.cc](#).

Here is the call graph for this function:



3.80.3.12 `virtual const char* YMenuButton::widgetClass () const` [`inline`, `virtual`]

Returns a descriptive name of this widget class for logging, debugging etc.

Reimplemented from [YSelectionWidget](#).

Definition at line 69 of file [YMenuButton.h](#).

The documentation for this class was generated from the following files:

- `/usr/src/RPM/BUILD/libyui-3.0.10/src/YMenuButton.h`
- `/usr/src/RPM/BUILD/libyui-3.0.10/src/YMenuButton.cc`

3.81 YMenuButtonPrivate Struct Reference

Public Attributes

- `int nextSerialNo`

3.81.1 Detailed Description

Definition at line 34 of file [YMenuButton.cc](#).


The documentation for this struct was generated from the following file:

- /usr/src/RPM/BUILD/libyui-3.0.10/src/YMenuButton.cc


3.82 YMenuEvent Class Reference

```
#include <YEvent.h>
```

Inheritance diagram for YMenuEvent:



Collaboration diagram for YMenuEvent:



Public Member Functions

- **YMenuEvent** ([YItem](#) **item*)
- **YMenuEvent** (const char **id*)
- **YMenuEvent** (const std::string &*id*)
- virtual [YItem](#) * *item* () const
- std::string *id* () const

Protected Member Functions

- virtual [~YMenuEvent](#) ()

Protected Attributes

- [YItem](#) * *_item*
- std::string *_id*

3.82.1 Detailed Description

Event to be returned upon menu selection.

Definition at line 256 of file [YEvent.h](#).

3.82.2 Constructor & Destructor Documentation

3.82.2.1 virtual **YMenuEvent::~YMenuEvent** () [inline, protected, virtual]

Protected destructor - events can only be deleted via [YDialog::deleteEvent\(\)](#). The associated dialog will take care of this event and delete it when appropriate.

Definition at line 289 of file [YEvent.h](#).

3.82.3 Member Function Documentation

3.82.3.1 std::string **YMenuEvent::id** () const [inline]

Return the string ID of this event. This will be an empty string if the event was constructed with a [YItem](#).

Definition at line 280 of file [YEvent.h](#).

3.82.3.2 virtual YItem* YMenuEvent::item () const [inline, virtual]

Return the [YItem](#) that corresponds to this event or 0 if the event was constructed with a string ID.

Reimplemented from [YEvent](#).

Reimplemented from [YEvent](#).

Definition at line 274 of file [YEvent.h](#).


The documentation for this class was generated from the following file:

- /usr/src/RPM/BUILD/libyui-3.0.10/src/YEvent.h


3.83 YMenuItem Class Reference

```
#include <YMenuItem.h>
```

Inheritance diagram for YMenuItem:



Collaboration diagram for YMenuItem:



Public Member Functions

- [YMenuItem](#) (const std::string &[label](#))
- **YMenuItem** (const std::string &[label](#), const std::string &[iconName](#))
- [YMenuItem](#) ([YMenuItem](#) *[parent](#), const std::string &[label](#))
- **YMenuItem** ([YMenuItem](#) *[parent](#), const std::string &[label](#), const std::string &[iconName](#))
- virtual [~YMenuItem](#) ()
- [YMenuItem](#) * [parent](#) () const

3.83.1 Detailed Description

Item class for menu items.

Definition at line 35 of file [YMenuItem.h](#).

3.83.2 Constructor & Destructor Documentation

3.83.2.1 YMenuItem::YMenuItem (const std::string & *label*) [\[inline\]](#)

Constructors for toplevel items.

Definition at line 41 of file [YMenuItem.h](#).

3.83.2.2 YMenuItem::YMenuItem (YMenuItem * *parent*, const std::string & *label*)
[inline]

Constructors for items that have a parent item.

They will automatically register this item with the parent item. The parent assumes ownership of this item and will delete it in its (the parent's) destructor.

Definition at line 57 of file [YMenuItem.h](#).

3.83.2.3 virtual YMenuItem::~YMenuItem () [inline, virtual]

Destructor.

This will delete all children.

Definition at line 73 of file [YMenuItem.h](#).

3.83.3 Member Function Documentation

3.83.3.1 YMenuItem* YMenuItem::parent () const [inline, virtual]

Returns this item's parent item or 0 if it is a toplevel item.

Reimplemented from [YTreeItem](#).


Definition at line 79 of file [YMenuItem.h](#).

The documentation for this class was generated from the following file:


- /usr/src/RPM/BUILD/libyui-3.0.10/src/YMenuItem.h

3.84 YMultiLineEdit Class Reference

Inheritance diagram for YMultiLineEdit:



Collaboration diagram for YMultiLineEdit:



Public Member Functions

- virtual [~YMultiLineEdit](#) ()
- virtual const char * [widgetClass](#) () const
- virtual std::string [value](#) ()=0
- virtual void [setValue](#) (const std::string &text)=0
- std::string [label](#) () const
- virtual void [setLabel](#) (const std::string &label)

- int [inputMaxLength](#) () const
- virtual void [setInputMaxLength](#) (int numberOfChars)
- int [defaultVisibleLines](#) () const
- virtual void [setDefaultVisibleLines](#) (int newVisibleLines)
- virtual bool [setProperty](#) (const std::string &propertyName, const [YPropertyValue](#) &val)
- virtual [YPropertyValue](#) [getProperty](#) (const std::string &propertyName)
- virtual const [YPropertySet](#) & [propertySet](#) ()
- virtual std::string [shortcutString](#) () const
- virtual void [setShortcutString](#) (const std::string &str)
- const char * [userInputProperty](#) ()

Protected Member Functions

- [YMultiLineEdit](#) (YWidget *parent, const std::string &label)

3.84.1 Detailed Description

Definition at line 33 of file [YMultiLineEdit.h](#).

3.84.2 Constructor & Destructor Documentation

3.84.2.1 [YMultiLineEdit::YMultiLineEdit](#) (YWidget * parent, const std::string & label)
[protected]

Constructor.

Definition at line 52 of file [YMultiLineEdit.cc](#).

Here is the call graph for this function:



3.84.2.2 YMultiLineEdit::~YMultiLineEdit () [virtual]

Destructor.

Definition at line 63 of file [YMultiLineEdit.cc](#).

3.84.3 Member Function Documentation

3.84.3.1 int YMultiLineEdit::defaultVisibleLines () const

Return the number of input lines that are visible by default.

This is what the widget would like to get (which will be reflected by [preferredHeight\(\)](#)), not what it currently actually has due to layout constraints.

Definition at line 93 of file [YMultiLineEdit.cc](#).

3.84.3.2 YPropertyValue YMultiLineEdit::getProperty (const std::string & *propertyName*) [virtual]


Get a property. Reimplemented from [YWidget](#).

This method may throw YUIPropertyExceptions.

Reimplemented from [YWidget](#).

Definition at line 145 of file [YMultiLineEdit.cc](#).

Here is the call graph for this function:



3.84.3.3 `int YMultiLineEdit::inputMaxLength () const`

The maximum input length, i.e., the maximum number of characters the user can enter. -1 means no limit.

Definition at line 81 of file [YMultiLineEdit.cc](#).

3.84.3.4 `std::string YMultiLineEdit::label () const`

Get the label (the caption above the MultiLineEdit).

Definition at line 69 of file [YMultiLineEdit.cc](#).

3.84.3.5 `const YPropertySet & YMultiLineEdit::propertySet () [virtual]`


Return this class's property set. This also initializes the property upon the first call.

Reimplemented from [YWidget](#).

Reimplemented from [YWidget](#).

Definition at line 106 of file [YMultiLineEdit.cc](#).

Here is the call graph for this function:



3.84.3.6 `void YMultiLineEdit::setDefaultVisibleLines (int newVisibleLines) [virtual]`

Set the number of input lines that are visible by default.

This is what the widget would like to get (which will be reflected by [preferredHeight\(\)](#)), not what it currently actually has due to layout constraints.

Notice that since a MultiLineEdit is stretchable in both dimensions, it might get more or less screen space, depending on the layout. This value is only meaningful if there are no other layout constraints.

Changing this value will not trigger a re-layout.

Derived classes can overwrite this function (but should call this base class function in the new function implementation), but it will normally be sufficient to query [defaultVisibleLines\(\)](#) in [preferredHeight\(\)](#).

Definition at line 99 of file [YMultiLineEdit.cc](#).

3.84.3.7 void **YMultiLineEdit::setInputMaxLength** (int *numberOfChars*)
[virtual]

Set the maximum input length, i.e., the maximum number of characters the user can enter. -1 means no limit.

Derived classes are free to reimplement this, but they should call this base class method at the end of the overloaded function.

Definition at line 87 of file [YMultiLineEdit.cc](#).

3.84.3.8 void **YMultiLineEdit::setLabel** (const std::string & *label*) [virtual]

Set the label (the caption above the MultiLineEdit).

Derived classes are free to reimplement this, but they should call this base class method at the end of the overloaded function.

Definition at line 75 of file [YMultiLineEdit.cc](#).

Here is the call graph for this function:



3.84.3.9 bool **YMultiLineEdit::setProperty** (const std::string & *propertyName*, const YPropertyValue & *val*) [virtual]

Set a property. Reimplemented from [YWidget](#).


This function may throw YUIPropertyExceptions.

This function returns 'true' if the value was successfully set and 'false' if that value requires special handling (not in error cases: those are covered by exceptions).

Reimplemented from [YWidget](#).

Definition at line 128 of file [YMultiLineEdit.cc](#).

Here is the call graph for this function:



3.84.3.10 `virtual void YMultiLineEdit::setShortcutString (const std::string & str)`
`[inline, virtual]`

Set the string of this widget that holds the keyboard shortcut.

Reimplemented from [YWidget](#).

Reimplemented from [YWidget](#).

Definition at line 166 of file [YMultiLineEdit.h](#).

Here is the call graph for this function:



3.84.3.11 `virtual void YMultiLineEdit::setValue (const std::string & text)` [pure virtual]

Set the current value (the text entered by the user or set from the outside) of this MultiLineEdit.

Derived classes are required to implement this.

3.84.3.12 `virtual std::string YMultiLineEdit::shortcutString () const` [inline, virtual]


Get the string of this widget that holds the keyboard shortcut.

Reimplemented from [YWidget](#).

Reimplemented from [YWidget](#).

Definition at line 159 of file [YMultiLineEdit.h](#).

Here is the call graph for this function:



3.84.3.13 `const char* YMultiLineEdit::userInputProperty ()` [inline, virtual]

The name of the widget property that will return user input. Inherited from [YWidget](#).

Reimplemented from [YWidget](#).

Definition at line 173 of file [YMultiLineEdit.h](#).

3.84.3.14 `virtual std::string YMultiLineEdit::value ()` [pure virtual]

Get the current value (the text entered by the user or set from the outside) of this MultiLineEdit.

Derived classes are required to implement this.

3.84.3.15 `virtual const char* YMultiLineEdit::widgetClass () const` `[inline, virtual]`

Returns a descriptive name of this widget class for logging, debugging etc.

Reimplemented from [YWidget](#).

Definition at line 51 of file [YMultiLineEdit.h](#).

The documentation for this class was generated from the following files:

- `/usr/src/RPM/BUILD/libyui-3.0.10/src/YMultiLineEdit.h`
- `/usr/src/RPM/BUILD/libyui-3.0.10/src/YMultiLineEdit.cc`

3.85 YMultiLineEditPrivate Struct Reference

Public Member Functions

- **YMultiLineEditPrivate** (const std::string &label)

Public Attributes

- std::string **label**
- int **inputMaxLength**
- int **defaultVisibleLines**

3.85.1 Detailed Description

Definition at line 36 of file [YMultiLineEdit.cc](#).


The documentation for this struct was generated from the following file:

- `/usr/src/RPM/BUILD/libyui-3.0.10/src/YMultiLineEdit.cc`


3.86 YMultiProgressMeter Class Reference

```
#include <YMultiProgressMeter.h>
```

Inheritance diagram for YMultiProgressMeter:



Collaboration diagram for YMultiProgressMeter:



Public Member Functions

- virtual [~YMultiProgressMeter](#) ()
- virtual const char * [widgetClass](#) () const
- YUIDimension [dimension](#) () const
- bool [horizontal](#) () const
- bool [vertical](#) () const
- int [segments](#) () const
- float [maxValue](#) (int segment) const
- float [currentValue](#) (int segment) const

- void [setCurrentValue](#) (int segment, float value)
- void [setCurrentValues](#) (const std::vector< float > &values)
- virtual bool [setProperty](#) (const std::string &propertyName, const [YPropertyValue](#) &val)
- virtual [YPropertyValue](#) [getProperty](#) (const std::string &propertyName)
- virtual const [YPropertySet](#) & [propertySet](#) ()
- virtual void [doUpdate](#) ()=0

Protected Member Functions

- [YMultiProgressMeter](#) ([YWidget](#) *parent, YUIDimension dim, const std::vector< float > &maxValues)

3.86.1 Detailed Description

MultiProgressMeter: Progress bar with several segments that can indicate progress individually. This is useful to display progress of several activities that might not necessarily all be done in sequence.

A common example is installing packages from several CDs: Each CD would get a separate segment. Each segment's size would be proportional to the amount of data to be installed from that CD. This visualizes at the same time (a) how many CDs are involved (b) how much in proportion is to be expected from each CD (c) whether or not a specific CD is finished.

Visual example (horizontal **MultiProgressMeter**):

```
[=====...] [==] [.....] [.]
```

This corresponds to 4 CDs:

CD #1: A lot of packages are to be installed from this CD, and a fair amount of those are already installed, but some are still missing. CD #2: Some packages were installed from this, but this CD is finished. CD #3: Quite some packages are to be installed from this CD. CD #4: Very few packages are to be installed from this CD.

As can be seen from this simple example, this widget can visualize a lot of complex information at the same time in a very natural way.

This is an optional widget, i.e. not all UIs support it.

Definition at line 64 of file [YMultiProgressMeter.h](#).


3.86.2 Constructor & Destructor Documentation

**3.86.2.1 YMultiProgressMeter::YMultiProgressMeter (YWidget * *parent*,
YUIDimension *dim*, const std::vector< float > & *maxValues*)** [protected]

Constructor

Definition at line 54 of file [YMultiProgressMeter.cc](#).

Here is the call graph for this function:



3.86.2.2 YMultiProgressMeter::~~YMultiProgressMeter () [virtual]

Destructor.

Definition at line 67 of file [YMultiProgressMeter.cc](#).

3.86.3 Member Function Documentation

3.86.3.1 float YMultiProgressMeter::currentValue (int *segment*) const

Return the current value for the specified segment (counting from 0). If no value has been set yet, -1 is returned.

Definition at line 106 of file [YMultiProgressMeter.cc](#).

3.86.3.2 YUIDimension YMultiProgressMeter::dimension () const

Return the orientation of the MultiProgressBar.

Definition at line 74 of file [YMultiProgressMeter.cc](#).

3.86.3.3 virtual void YMultiProgressMeter::doUpdate () [pure virtual]

Notification that values have been updated and the widget needs to be redisplayed. Derived classes need to reimplement this.

3.86.3.4 YPropertyValue YMultiProgressMeter::getProperty (const std::string & *propertyName*) [virtual]


Get a property. Reimplemented from [YWidget](#).

This method may throw YUIPropertyExceptions.

Reimplemented from [YWidget](#).

Definition at line 173 of file [YMultiProgressMeter.cc](#).

Here is the call graph for this function:



3.86.3.5 bool YMultiProgressMeter::horizontal () const

Return 'true' if the orientation is horizontal.

Definition at line 80 of file [YMultiProgressMeter.cc](#).

3.86.3.6 float YMultiProgressMeter::maxValue (int *segment*) const

Return the maximum value for the specified segment (counting from 0).

Definition at line 98 of file [YMultiProgressMeter.cc](#).

3.86.3.7 const YPropertySet & YMultiProgressMeter::propertySet () [virtual]


Return this class's property set. This also initializes the property upon the first call.

Reimplemented from [YWidget](#).

Reimplemented from [YWidget](#).

Definition at line 140 of file [YMultiProgressMeter.cc](#).

Here is the call graph for this function:



3.86.3.8 `int YMultiProgressMeter::segments () const`

Return the number of segments.

Definition at line 92 of file [YMultiProgressMeter.cc](#).


3.86.3.9 `void YMultiProgressMeter::setCurrentValue (int segment, float value)`

Set the current value for the specified segment. This must be in the range 0..maxValue(segment).

Remember to call [doUpdate\(\)](#) after all changed values are set!

Definition at line 114 of file [YMultiProgressMeter.cc](#).

Here is the call graph for this function:




3.86.3.10 `void YMultiProgressMeter::setCurrentValues (const std::vector< float > & values)`

Set all current values and call [doUpdate\(\)](#).

Definition at line 128 of file [YMultiProgressMeter.cc](#).

Here is the call graph for this function:



3.86.3.11 `bool YMultiProgressMeter::setProperty (const std::string & propertyName,
const YPropertyValue & val)` [virtual]

Set a property. Reimplemented from [YWidget](#).


This function may throw YUIPropertyExceptions.

This function returns 'true' if the value was successfully set and 'false' if that value requires special handling (not in error cases: those are covered by exceptions).

Reimplemented from [YWidget](#).

Definition at line 158 of file [YMultiProgressMeter.cc](#).

Here is the call graph for this function:



3.86.3.12 `bool YMultiProgressMeter::vertical ()` const

Return 'true' if the orientation is vertical.

Definition at line 86 of file [YMultiProgressMeter.cc](#).

3.86.3.13 `virtual const char* YMultiProgressMeter::widgetClass () const`
`[inline, virtual]`

Return a descriptive name of this widget class for logging, debugging etc.

Reimplemented from [YWidget](#).

Definition at line 84 of file [YMultiProgressMeter.h](#).

The documentation for this class was generated from the following files:

- `/usr/src/RPM/BUILD/libyui-3.0.10/src/YMultiProgressMeter.h`
- `/usr/src/RPM/BUILD/libyui-3.0.10/src/YMultiProgressMeter.cc`

3.87 YMultiProgressMeterPrivate Struct Reference

Public Member Functions

- **YMultiProgressMeterPrivate** (YUIDimension dim, const std::vector< float > &maxValues)

Public Attributes

- YUIDimension **dim**
- std::vector< float > **maxValues**
- std::vector< float > **currentValues**

3.87.1 Detailed Description


Definition at line 33 of file [YMultiProgressMeter.cc](#).

The documentation for this struct was generated from the following file:


- `/usr/src/RPM/BUILD/libyui-3.0.10/src/YMultiProgressMeter.cc`

3.88 YMultiSelectionBox Class Reference

Inheritance diagram for YMultiSelectionBox:



Collaboration diagram for YMultiSelectionBox:



Public Member Functions

- virtual [~YMultiSelectionBox](#) ()
- virtual const char * [widgetClass](#) () const
- bool [shrinkable](#) () const
- virtual void [setShrinkable](#) (bool [shrinkable](#)=true)
- virtual bool [setProperty](#) (const std::string &propertyName, const [YPropertyValue](#) &val)
- virtual [YPropertyValue](#) [getProperty](#) (const std::string &propertyName)
- virtual const [YPropertySet](#) & [propertySet](#) ()
- const char * [userInputProperty](#) ()
- virtual [YItem](#) * [currentItem](#) ()=0
- virtual void [setCurrentItem](#) ([YItem](#) *item)=0
- virtual void [saveUserInput](#) ([YMacroRecorder](#) *macroRecorder)

Protected Member Functions

- [YMultiSelectionBox](#) ([YWidget](#) *parent, const std::string &label)

3.88.1 Detailed Description

Definition at line 33 of file [YMultiSelectionBox.h](#).


3.88.2 Constructor & Destructor Documentation

3.88.2.1 [YMultiSelectionBox::YMultiSelectionBox](#) ([YWidget](#) * *parent*, const std::string & *label*) [protected]

Constructor.

Definition at line 46 of file [YMultiSelectionBox.cc](#).

Here is the call graph for this function:



3.88.2.2 YMultiSelectionBox::~~YMultiSelectionBox () [virtual]

Destructor.

Definition at line 59 of file [YMultiSelectionBox.cc](#).

3.88.3 Member Function Documentation

3.88.3.1 virtual YItem* YMultiSelectionBox::currentItem () [pure virtual]

Return the the item that currently has the keyboard focus or 0 if no item currently has the keyboard focus.

Notice that for a MultiSelectionBox the current item is not necessarily selected, i.e., its check box may or may not be checked.

Derived classes are required to implement this function.

3.88.3.2 YPropertyValue YMultiSelectionBox::getProperty (const std::string & *propertyName*) [virtual]


Get a property. Reimplemented from [YWidget](#).

This method may throw YUIPropertyExceptions.

Reimplemented from [YWidget](#).

Definition at line 122 of file [YMultiSelectionBox.cc](#).

Here is the call graph for this function:



3.88.3.3 const YPropertySet & YMultiSelectionBox::propertySet () [virtual]


Return this class's property set. This also initializes the property upon the first call.

Reimplemented from [YWidget](#).

Reimplemented from [YWidget](#).

Definition at line 78 of file [YMultiSelectionBox.cc](#).

Here is the call graph for this function:



3.88.3.4 `void YMultiSelectionBox::saveUserInput (YMacroRecorder * macroRecorder)` [virtual]

Save the widget's user input to a macro recorder.

Reimplemented from [YWidget](#) because two properties need to be recorded.

Reimplemented from [YWidget](#).

Definition at line 139 of file [YMultiSelectionBox.cc](#).

Here is the call graph for this function:



3.88.3.5 `virtual void YMultiSelectionBox::setCurrentItem (YItem * item)` [pure virtual]

Set the keyboard focus to the specified item. 0 means clear the keyboard focus.

Notice that for a MultiSelectionBox the current item is not necessarily selected, i.e., its check box may or may not be checked. Use [selectItem\(\)](#) for that.

Also notice that [selectItem\(\)](#) does not make that newly selected item the current item. Derived classes are required to implement this function.

3.88.3.6 `bool YMultiSelectionBox::setProperty (const std::string & propertyName, const YPropertyValue & val)` `[virtual]`

Set a property. Reimplemented from [YWidget](#).


This function may throw YUIPropertyExceptions.

This function returns 'true' if the value was successfully set and 'false' if that value requires special handling (not in error cases: those are covered by exceptions).

Reimplemented from [YWidget](#).

Definition at line 103 of file [YMultiSelectionBox.cc](#).

Here is the call graph for this function:



3.88.3.7 `void YMultiSelectionBox::setShrinkable (bool shrinkable = true)` `[virtual]`

Make this MultiSelectionBox very small. This will take effect only upon the next geometry management run.

Derived classes can overwrite this, but should call this base class function in the new function.

Definition at line 71 of file [YMultiSelectionBox.cc](#).

Here is the call graph for this function:



3.88.3.8 bool YMultiSelectionBox::shrinkable () const

Return 'true' if this MultiSelectionBox should be very small.

Definition at line 65 of file [YMultiSelectionBox.cc](#).

3.88.3.9 const char* YMultiSelectionBox::userInputProperty () [inline, virtual]

The name of the widget property that will return user input. Inherited from [YWidget](#).

Reimplemented from [YWidget](#).

Definition at line 100 of file [YMultiSelectionBox.h](#).

3.88.3.10 virtual const char* YMultiSelectionBox::widgetClass () const [inline, virtual]

Returns a descriptive name of this widget class for logging, debugging etc.

Reimplemented from [YSelectionWidget](#).

Definition at line 51 of file [YMultiSelectionBox.h](#).

The documentation for this class was generated from the following files:

- [/usr/src/RPM/BUILD/libyui-3.0.10/src/YMultiSelectionBox.h](#)
- [/usr/src/RPM/BUILD/libyui-3.0.10/src/YMultiSelectionBox.cc](#)

3.89 YMultiSelectionBoxPrivate Struct Reference

Public Attributes

- bool **shrinkable**

3.89.1 Detailed Description

Definition at line 35 of file [YMultiSelectionBox.cc](#).

The documentation for this struct was generated from the following file:

- [/usr/src/RPM/BUILD/libyui-3.0.10/src/YMultiSelectionBox.cc](#)

3.90 YOptionalWidgetFactory Class Reference

```
#include <YOptionalWidgetFactory.h>
```

Public Member Functions

- virtual bool **hasWizard** ()
- virtual [YWizard](#) * **createWizard** ([YWidget](#) *parent, const std::string &backButtonLabel, const std::string &abortButtonLabel, const std::string &nextButtonLabel, YWizardMode wizardMode=YWizardMode_Standard)
- virtual bool **hasDumbTab** ()
- virtual [YDumbTab](#) * **createDumbTab** ([YWidget](#) *parent)
- virtual bool **hasSlider** ()
- virtual [YSlider](#) * **createSlider** ([YWidget](#) *parent, const std::string &label, int minVal, int maxVal, int initialVal)
- virtual bool **hasDateField** ()
- virtual [YDateField](#) * **createDateField** ([YWidget](#) *parent, const std::string &label)
- virtual bool **hasTimeField** ()
- virtual [YTimeField](#) * **createTimeField** ([YWidget](#) *parent, const std::string &label)
- virtual bool **hasBarGraph** ()
- virtual [YBarGraph](#) * **createBarGraph** ([YWidget](#) *parent)
- virtual bool **hasPatternSelector** ()
- virtual [YWidget](#) * **createPatternSelector** ([YWidget](#) *parent, long modeFlags=0)
- virtual bool **hasSimplePatchSelector** ()
- virtual [YWidget](#) * **createSimplePatchSelector** ([YWidget](#) *parent, long modeFlags=0)
- virtual bool **hasMultiProgressMeter** ()
- [YMultiProgressMeter](#) * **createHMultiProgressMeter** ([YWidget](#) *parent, const std::vector< float > &maxValues)

- [YMultiProgressMeter](#) * **createVMultiProgressMeter** ([YWidget](#) *parent, const std::vector< float > &maxValues)
- virtual [YMultiProgressMeter](#) * **createMultiProgressMeter** ([YWidget](#) *parent, YUIDimension dim, const std::vector< float > &maxValues)
- virtual bool **hasPartitionSplitter** ()
- virtual [YPartitionSplitter](#) * **createPartitionSplitter** ([YWidget](#) *parent, int usedSize, int totalFreeSize, int newPartSize, int minNewPartSize, int minFreeSize, const std::string &usedLabel, const std::string &freeLabel, const std::string &newPartLabel, const std::string &freeFieldLabel, const std::string &newPartFieldLabel)
- virtual bool **hasDownloadProgress** ()
- virtual [YDownloadProgress](#) * **createDownloadProgress** ([YWidget](#) *parent, const std::string &label, const std::string &filename, YFileSize_t expectedFileSize)
- bool **hasDummySpecialWidget** ()
- [YWidget](#) * **createDummySpecialWidget** ([YWidget](#) *parent)
- virtual bool **hasTimezoneSelector** ()
- virtual [YTimezoneSelector](#) * **createTimezoneSelector** ([YWidget](#) *parent, const std::string &ixmap, const std::map< std::string, std::string > &timezones)
- virtual bool **hasGraph** ()
- virtual [YGraph](#) * **createGraph** ([YWidget](#) *parent, const std::string &filename, const std::string &layoutAlgorithm)
- virtual [YGraph](#) * **createGraph** ([YWidget](#) *parent, void *graph)
- virtual bool **hasContextMenu** ()

Protected Member Functions

- [YOptionalWidgetFactory](#) ()
- virtual [~YOptionalWidgetFactory](#) ()

Friends

- class **YUI**

3.90.1 Detailed Description

Abstract widget factory for optional ("special") widgets.

Remember to always check with the corresponding "has..()" method if the current UI actually provides the requested widget. Otherwise the "create..." method will throw an exception.

Definition at line 56 of file [YOptionalWidgetFactory.h](#).

3.90.2 Constructor & Destructor Documentation

3.90.2.1 YOptionalWidgetFactory::YOptionalWidgetFactory () [protected]

Constructor.

Use [YUI::optionalWidgetFactory\(\)](#) to get the singleton for this class.

Definition at line 38 of file [YOptionalWidgetFactory.cc](#).

3.90.2.2 YOptionalWidgetFactory::~YOptionalWidgetFactory () [protected, virtual]

Destructor.


Definition at line 43 of file [YOptionalWidgetFactory.cc](#).

The documentation for this class was generated from the following files:


- [/usr/src/RPM/BUILD/libyui-3.0.10/src/YOptionalWidgetFactory.h](#)
- [/usr/src/RPM/BUILD/libyui-3.0.10/src/YOptionalWidgetFactory.cc](#)

3.91 YPackageSelector Class Reference

Inheritance diagram for YPackageSelector:



Collaboration diagram for YPackageSelector:



Public Member Functions

- virtual const char * [widgetClass](#) () const
- bool [testMode](#) () const
- bool **onlineUpdateMode** () const
- bool **updateMode** () const
- bool **searchMode** () const
- bool **summaryMode** () const
- bool **repoMode** () const
- bool **repoMgrEnabled** () const
- bool **confirmUnsupported** () const

Protected Member Functions

- [YPackageSelector](#) ([YWidget](#) *parent, long modeFlags=0)

Protected Attributes

- long **_modeFlags**

3.91.1 Detailed Description

Definition at line 40 of file [YPackageSelector.h](#).

3.91.2 Constructor & Destructor Documentation

3.91.2.1 YPackageSelector::YPackageSelector (YWidget * *parent*, long *modeFlags* = 0) [protected]

Constructor.

'modeFlags' are flags determining which modes to use, ORed together: YPkg_Online-UpdateMode | YPkg_TestMode

Definition at line 32 of file [YPackageSelector.cc](#).

Here is the call graph for this function:



3.91.3 Member Function Documentation

3.91.3.1 bool YPackageSelector::testMode () const [inline]

Check for the various modes.

Definition at line 61 of file [YPackageSelector.h](#).

3.91.3.2 virtual const char* YPackageSelector::widgetClass () const [inline, virtual]

Returns a descriptive name of this widget class for logging, debugging etc.

Reimplemented from [YWidget](#).

Definition at line 56 of file [YPackageSelector.h](#).


The documentation for this class was generated from the following files:

- /usr/src/RPM/BUILD/libyui-3.0.10/src/YPackageSelector.h
- /usr/src/RPM/BUILD/libyui-3.0.10/src/YPackageSelector.cc


3.92 YPackageSelectorPlugin Class Reference

```
#include <YPackageSelectorPlugin.h>
```

Inheritance diagram for YPackageSelectorPlugin:



Collaboration diagram for YPackageSelectorPlugin:



Public Member Functions

- virtual [YPackageSelector](#) * [createPackageSelector](#) ([YWidget](#) *parent, long modeFlags=0)=0

Protected Member Functions

- [YPackageSelectorPlugin](#) (const char *[pluginLibBaseName](#))
- virtual [~YPackageSelectorPlugin](#) ()

3.92.1 Detailed Description

Abstract base class for simplified access to UI plugins for package selection.

Definition at line 38 of file [YPackageSelectorPlugin.h](#).

3.92.2 Constructor & Destructor Documentation

3.92.2.1 [YPackageSelectorPlugin::YPackageSelectorPlugin](#) (const char * *pluginLibBaseName*) [inline, protected]

Constructor: Load the specified plugin library from the standard UI plugin directory (/usr/lib/yui/).

Definition at line 45 of file [YPackageSelectorPlugin.h](#).

3.92.2.2 virtual [YPackageSelectorPlugin::~YPackageSelectorPlugin](#) () [inline, protected, virtual]

Destructor. Calls dlclose() which will unload the plugin library if it is no longer used, i.e. if the reference count dlopen() uses reaches 0.

Definition at line 52 of file [YPackageSelectorPlugin.h](#).

3.92.3 Member Function Documentation

3.92.3.1 virtual [YPackageSelector*](#) [YPackageSelectorPlugin::create-](#) [PackageSelector](#) ([YWidget](#) **parent*, long *modeFlags* = 0) [pure virtual]

Create a package selector. Derived classes need to implement this.

This might return 0 if the plugin lib could not be loaded or if the appropriate symbol could not be located in the plugin lib.


The documentation for this class was generated from the following file:

- /usr/src/RPM/BUILD/libyui-3.0.10/src/YPackageSelectorPlugin.h


3.93 YPartitionSplitter Class Reference

```
#include <YPartitionSplitter.h>
```

Inheritance diagram for YPartitionSplitter:



Collaboration diagram for YPartitionSplitter:



Public Member Functions

- virtual [~YPartitionSplitter](#) ()
- virtual const char * [widgetClass](#) () const
- virtual int [value](#) ()=0
- virtual void [setValue](#) (int newValue)=0

- `int usedSize () const`
- `int totalFreeSize () const`
- `int minFreeSize () const`
- `int maxFreeSize () const`
- `int freeSize ()`
- `int newPartSize ()`
- `int minNewPartSize () const`
- `int maxNewPartSize () const`
- `std::string usedLabel () const`
- `std::string freeLabel () const`
- `std::string newPartLabel () const`
- `std::string freeFieldLabel () const`
- `std::string newPartFieldLabel () const`
- `virtual bool setProperty (const std::string &propertyName, const YPropertyValue &val)`
- `virtual YPropertyValue getProperty (const std::string &propertyName)`
- `virtual const YPropertySet & propertySet ()`
- `const char * userInputProperty ()`

Protected Member Functions

- `YPartitionSplitter (YWidget *parent, int usedSize, int totalFreeSize, int newPartSize, int minNewPartSize, int minFreeSize, const std::string &usedLabel, const std::string &freeLabel, const std::string &newPartLabel, const std::string &freeFieldLabel, const std::string &newPartFieldLabel)`

3.93.1 Detailed Description

PartitionSplitter: A (very custom) widget for easily splitting one existing partition into two.

Layout:

```
+-----+-----+-----+ | Old Partition | Old Partition | New
Partition | | used | free | | +-----+-----+-----+
Old Partition free New Partition [ 123 ] =====O=====
[ 123 ]
```

At the top, there is a BarGraph that dynamically displays the sizes in graphical form. Below are an IntField to the left and an IntField to the right, each with its respective label. Between the two IntFields there is a Slider.

The user can enter a value in either IntField or drag the slider. The other sub-widgets (including the BarGraph) will automatically be adjusted. Visually (in the BarGraph), the border between "old partition free" and "new partition" will move left and right. The border between "old partition used" and "old partition free" is static.

There are built-in (configurable) limits for the minimum sizes of "old partition free" and "new partition".

Definition at line 63 of file [YPartitionSplitter.h](#).

3.93.2 Constructor & Destructor Documentation

3.93.2.1 YPartitionSplitter::YPartitionSplitter (YWidget * *parent*, int *usedSize*, int *totalFreeSize*, int *newPartSize*, int *minNewPartSize*, int *minFreeSize*, const std::string & *usedLabel*, const std::string & *freeLabel*, const std::string & *newPartLabel*, const std::string & *freeFieldLabel*, const std::string & *newPartFieldLabel*)
[protected]

Constructor.

usedSize: Used size of the old partition (constant)

totalFreeSize: Total free size of the old partition before the split: OldPartitionFree + NewPartition

newPartSize': Initial size of the new partition

minNewPartSize: Miminum size of the new partition

minFreeSize: Minimum free size of the old partition

usedLabel: BarGraph label for the used part of the old partition

freeLabel: BarGraph label for the free part of the old partition


newPartLabel: BarGraph label for the new partition

freeFieldLabel: IntField label for the free part of the old partition

newPartFieldLabel: IntField label for the size of the new partition

Definition at line 69 of file [YPartitionSplitter.cc](#).

Here is the call graph for this function:



3.93.2.2 YPartitionSplitter::~~YPartitionSplitter () [virtual]

Destructor.

Definition at line 99 of file [YPartitionSplitter.cc](#).

3.93.3 Member Function Documentation

3.93.3.1 YPropertyValue YPartitionSplitter::getProperty (const std::string & *propertyName*) [virtual]


Get a property. Reimplemented from [YWidget](#).

This method may throw YUIPropertyExceptions.

Reimplemented from [YWidget](#).

Definition at line 193 of file [YPartitionSplitter.cc](#).

Here is the call graph for this function:



3.93.3.2 const YPropertySet & YPartitionSplitter::propertySet () [virtual]


Return this class's property set. This also initializes the property upon the first call.

Reimplemented from [YWidget](#).

Reimplemented from [YWidget](#).

Definition at line 160 of file [YPartitionSplitter.cc](#).

Here is the call graph for this function:



3.93.3.3 `bool YPartitionSplitter::setProperty (const std::string & propertyName, const YPropertyValue & val) [virtual]`

Set a property. Reimplemented from [YWidget](#).


This function may throw `YUIPropertyExceptions`.

This function returns 'true' if the value was successfully set and 'false' if that value requires special handling (not in error cases: those are covered by exceptions).

Reimplemented from [YWidget](#).

Definition at line 178 of file [YPartitionSplitter.cc](#).

Here is the call graph for this function:



3.93.3.4 `virtual void YPartitionSplitter::setValue (int newValue) [pure virtual]`

Set the value (the size of the new partition).

Derived classes are required to implement this.

3.93.3.5 `const char* YPartitionSplitter::userInputProperty () [inline, virtual]`

The name of the widget property that will return user input. Inherited from [YWidget](#).

Reimplemented from [YWidget](#).

Definition at line 181 of file [YPartitionSplitter.h](#).

3.93.3.6 `virtual int YPartitionSplitter::value () [pure virtual]`

The value of this PartitionSplitter: The size of the new partition.

Derived classes are required to implement this.

3.93.3.7 `virtual const char* YPartitionSplitter::widgetClass () const [inline, virtual]`

Returns a descriptive name of this widget class for logging, debugging etc.

Reimplemented from [YWidget](#).

Definition at line 113 of file [YPartitionSplitter.h](#).

The documentation for this class was generated from the following files:

- [/usr/src/RPM/BUILD/libyui-3.0.10/src/YPartitionSplitter.h](#)
- [/usr/src/RPM/BUILD/libyui-3.0.10/src/YPartitionSplitter.cc](#)

3.94 YPartitionSplitterPrivate Struct Reference

Public Member Functions

- **YPartitionSplitterPrivate** (int usedSize, int totalFreeSize, int minNewPartSize, int minFreeSize, const std::string &usedLabel, const std::string &freeLabel, const std::string &newPartLabel, const std::string &freeFieldLabel, const std::string &newPartFieldLabel)

Public Attributes

- int **usedSize**
- int **totalFreeSize**

- int **minNewPartSize**
- int **minFreeSize**
- std::string **usedLabel**
- std::string **freeLabel**
- std::string **newPartLabel**
- std::string **freeFieldLabel**
- std::string **newPartFieldLabel**

3.94.1 Detailed Description

Definition at line 33 of file [YPartitionSplitter.cc](#).

The documentation for this struct was generated from the following file:

- /usr/src/RPM/BUILD/libyui-3.0.10/src/YPartitionSplitter.cc

3.95 YPath Class Reference

```
#include <YPath.h>
```

Public Member Functions

- [YPath](#) (const std::string &directory, const std::string &filename)
- [~YPath](#) ()
- std::string [path](#) ()
- std::string [dir](#) ()

3.95.1 Detailed Description

Finds files (e.g. plugins or theme pixmaps) recursively inside a directory.

Definition at line 43 of file [YPath.h](#).

3.95.2 Constructor & Destructor Documentation

3.95.2.1 YPath::YPath (const std::string & *directory*, const std::string & *filename*)


Constructor

to be called with the directory where to look inside and filename which to lookup.

YSettings::progSubDir will be preferred by the lookup.

Definition at line 47 of file [YPath.cc](#).

Here is the call graph for this function:



3.95.2.2 `YPath::~~YPath ()`

Destructor

Definition at line 126 of file [YPath.cc](#).

3.95.3 Member Function Documentation

3.95.3.1 `std::string YPath::dir ()`

Returns the directory where the file is found; if not found just the subdir part (if there's any) of the filename given in constructor.

Definition at line 176 of file [YPath.cc](#).

3.95.3.2 `std::string YPath::path ()`

Returns the full path of the file if found; if not found just the filename given in constructor.


Definition at line 171 of file [YPath.cc](#).

The documentation for this class was generated from the following files:

- `/usr/src/RPM/BUILD/libyui-3.0.10/src/YPath.h`
- `/usr/src/RPM/BUILD/libyui-3.0.10/src/YPath.cc`

3.96 YPerThreadLogInfo Struct Reference

Collaboration diagram for YPerThreadLogInfo:



Public Member Functions

- [YPerThreadLogInfo](#) ()
- [~YPerThreadLogInfo](#) ()
- bool [isThread](#) (pthread_t otherThreadHandle)

Public Attributes

- pthread_t **threadHandle**
- [YUILogBuffer](#) **logBuffer**
- std::ostream **logStream**

3.96.1 Detailed Description

Helper class: Per-thread logging information.

Multiple threads can easily clobber each others' half-done logging. A naive approach to prevent this would be to lock a mutex when a thread starts logging and unlock it when it's done logging. But that "when it's done" condition might never come true. `std::endl` or a newline in the output stream would be one indication, but there is no way to make sure there always is such a delimiter. If it is forgotten and that thread (that still has the mutex locked) runs into a waiting condition itself (e.g., UI thread synchronization with pipes), there would be a deadlock.

So this much safer approach was chosen: Give each thread its own logging infrastructure, i.e., its own log stream and its own log buffer.

Sure, in bad cases the logger function might still be executed in parallel and thus clobber a line or two of log output. But that's merely bad output formatting, not writing another thread's data structures without control - which can easily happen if multiple threads are working on the same output buffer, i.e. manipulate the same string.

Definition at line 208 of file [YUILog.cc](#).

3.96.2 Constructor & Destructor Documentation

3.96.2.1 YPerThreadLogInfo::YPerThreadLogInfo () [inline]

Constructor


Definition at line 213 of file [YUILog.cc](#).

3.96.2.2 YPerThreadLogInfo::~YPerThreadLogInfo () [inline]

Destructor

Definition at line 224 of file [YUILog.cc](#).

Here is the call graph for this function:



3.96.3 Member Function Documentation

3.96.3.1 bool YPerThreadLogInfo::isThread (pthread_t otherThreadHandle) [inline]

Check if this per-thread logging information belongs to the specified thread.


Definition at line 232 of file [YUILog.cc](#).

The documentation for this struct was generated from the following file:


- `/usr/src/RPM/BUILD/libyui-3.0.10/src/YUILog.cc`

3.97 YProgressBar Class Reference

Inheritance diagram for YProgressBar:



Collaboration diagram for YProgressBar:



Public Member Functions

- virtual [~YProgressBar](#) ()
- virtual const char * [widgetClass](#) () const
- std::string [label](#) ()
- virtual void [setLabel](#) (const std::string &[label](#))
- int [maxValue](#) () const
- int [value](#) () const

- virtual void [setValue](#) (int newValue)
- virtual bool [setProperty](#) (const std::string &propertyName, const [YPropertyValue](#) &val)
- virtual [YPropertyValue](#) [getProperty](#) (const std::string &propertyName)
- virtual const [YPropertySet](#) & [propertySet](#) ()

Protected Member Functions

- [YProgressBar](#) ([YWidget](#) *parent, const std::string &label, int [maxValue](#)=100)

3.97.1 Detailed Description

Definition at line 33 of file [YProgressBar.h](#).


3.97.2 Constructor & Destructor Documentation

3.97.2.1 [YProgressBar::YProgressBar](#) ([YWidget](#) * *parent*, const std::string & *label*, int *maxValue* = 100) [protected]

Constructor.

Definition at line 52 of file [YProgressBar.cc](#).

Here is the call graph for this function:



3.97.2.2 [YProgressBar::~~YProgressBar](#) () [virtual]

Destructor.

Definition at line 65 of file [YProgressBar.cc](#).

3.97.3 Member Function Documentation

3.97.3.1 YPropertyValue YProgressBar::getProperty (const std::string & *propertyName*) [virtual]


Get a property. Reimplemented from [YWidget](#).

This method may throw YUIPropertyExceptions.

Reimplemented from [YWidget](#).

Definition at line 144 of file [YProgressBar.cc](#).

Here is the call graph for this function:



3.97.3.2 std::string YProgressBar::label ()

Get the label (the caption above the progress bar).

Definition at line 71 of file [YProgressBar.cc](#).

3.97.3.3 int YProgressBar::maxValue () const

Return the maximum progress value. Notice that this value can only be set in the constructor.

Definition at line 83 of file [YProgressBar.cc](#).

3.97.3.4 const YPropertySet & YProgressBar::propertySet () [virtual]

Return this class's property set. This also initializes the property upon the first call.

Reimplemented from [YWidget](#).

Reimplemented from [YWidget](#).

Definition at line 108 of file [YProgressBar.cc](#).

Here is the call graph for this function:



3.97.3.5 void YProgressBar::setLabel (const std::string & label) [virtual]

Set the label (the caption above the progress bar).

Derived classes are free to reimplement this, but they should call this base class method at the end of the overloaded function.

Definition at line 77 of file [YProgressBar.cc](#).

Here is the call graph for this function:



3.97.3.6 bool YProgressBar::setProperty (const std::string & propertyName, const YPropertyValue & val) [virtual]

Set a property. Reimplemented from [YWidget](#).


This function may throw `YUIPropertyExceptions`.

This function returns 'true' if the value was successfully set and 'false' if that value requires special handling (not in error cases: those are covered by exceptions).

Reimplemented from [YWidget](#).

Definition at line 128 of file [YProgressBar.cc](#).

Here is the call graph for this function:



3.97.3.7 void YProgressBar::setValue (int *newValue*) [virtual]

Set the current progress value (\leq `maxValue()`).

Derived classes should reimplement this, but they should call this base class method at the end of the overloaded function.

Definition at line 95 of file [YProgressBar.cc](#).

3.97.3.8 int YProgressBar::value () const

Return the current progress value.

Definition at line 89 of file [YProgressBar.cc](#).

3.97.3.9 virtual const char* YProgressBar::widgetClass () const [inline, virtual]

Returns a descriptive name of this widget class for logging, debugging etc.

Reimplemented from [YWidget](#).

Definition at line 53 of file [YProgressBar.h](#).

The documentation for this class was generated from the following files:

- /usr/src/RPM/BUILD/libyui-3.0.10/src/YProgressBar.h
- /usr/src/RPM/BUILD/libyui-3.0.10/src/YProgressBar.cc

3.98 YProgressBarPrivate Struct Reference

Public Member Functions

- **YProgressBarPrivate** (const std::string &label, int maxValue)

Public Attributes

- std::string **label**
- int **maxValue**
- int **value**

3.98.1 Detailed Description

Definition at line 32 of file [YProgressBar.cc](#).

The documentation for this struct was generated from the following file:

- /usr/src/RPM/BUILD/libyui-3.0.10/src/YProgressBar.cc

3.99 YProperty Class Reference

```
#include <YProperty.h>
```

Public Member Functions

- [YProperty](#) (const std::string &name, YPropertyType type, bool isReadOnly=false)
- std::string [name](#) () const
- YPropertyType [type](#) () const
- bool [isReadOnly](#) () const
- std::string [typeAsStr](#) () const

Static Public Member Functions

- static std::string [typeAsStr](#) (YPropertyType [type](#))

3.99.1 Detailed Description

Class for widget properties.

Definition at line 51 of file [YProperty.h](#).

3.99.2 Constructor & Destructor Documentation

3.99.2.1 `YProperty::YProperty (const std::string & name, YPropertyType type, bool isReadOnly = false) [inline]`

Constructor: Create a property with the specified name and type. 'isReadOnly' is for properties that cannot be set, only retrieved.

Definition at line 58 of file [YProperty.h](#).

3.99.3 Member Function Documentation

3.99.3.1 `bool YProperty::isReadOnly () const [inline]`

Returns 'true' if this property cannot be changed, only retrieved.

Definition at line 77 of file [YProperty.h](#).

3.99.3.2 `std::string YProperty::name () const [inline]`

Returns the name of this property.

Definition at line 67 of file [YProperty.h](#).

3.99.3.3 `YPropertyType YProperty::type () const [inline]`

Returns the type of this property.

Definition at line 72 of file [YProperty.h](#).

3.99.3.4 `std::string YProperty::typeAsStr () const [inline]`

Returns the type of this property as string.

Definition at line 82 of file [YProperty.h](#).

3.99.3.5 `std::string YProperty::typeAsStr (YPropertyType type) [static]`

Returns a string description of a property type.

Definition at line 31 of file [YProperty.cc](#).

The documentation for this class was generated from the following files:

- /usr/src/RPM/BUILD/libyui-3.0.10/src/YProperty.h
- /usr/src/RPM/BUILD/libyui-3.0.10/src/YProperty.cc

3.100 YPropertySet Class Reference

```
#include <YProperty.h>
```

Public Types

- `typedef std::vector< YProperty > ::const_iterator const_iterator`

Public Member Functions

- [YPropertySet](#) ()
- void [check](#) (const std::string &propertyName) const
- void [check](#) (const std::string &propertyName, YPropertyType type) const
- void [check](#) (const [YProperty](#) &prop) const
- bool [contains](#) (const std::string &propertyName) const throw ()
- bool [contains](#) (const std::string &propertyName, YPropertyType type) const
- bool [contains](#) (const [YProperty](#) &prop) const
- bool [isEmpty](#) () const
- int [size](#) () const
- void [add](#) (const [YProperty](#) &prop)
- void [add](#) (const [YPropertySet](#) &otherSet)
- const_iterator [propertiesBegin](#) () const
- const_iterator [propertiesEnd](#) () const

3.100.1 Detailed Description

A set of properties to check names and types against.

Definition at line 184 of file [YProperty.h](#).

3.100.2 Constructor & Destructor Documentation

3.100.2.1 YPropertySet::YPropertySet ()

Constructor.

Definition at line 55 of file [YProperty.cc](#).

3.100.3 Member Function Documentation

3.100.3.1 void YPropertySet::add (const YProperty & *prop*)

Add a property to this property set.

Definition at line 120 of file [YProperty.cc](#).


3.100.3.2 void YPropertySet::add (const YPropertySet & *otherSet*)

Adds all properties of another property set.

If that other set contains duplicates (properties that are already in this set), those others will never be found with lookup().

Definition at line 127 of file [YProperty.cc](#).

Here is the call graph for this function:



3.100.3.3 void YPropertySet::check (const std::string & *propertyName*) const

Check if a property 'propertyName' exists in this property set. Throw a [YUIUnknownPropertyException](#) if it does not exist. Use [YPropertySet::contains\(\)](#) for a check that simply returns 'false' if it does not exist.

Definition at line 62 of file [YProperty.cc](#).

Here is the call graph for this function:



3.100.3.4 void YPropertySet::check (const std::string & *propertyName*, YPropertyType *type*) const

Check if a property 'propertyName' exists in this property set. Throw a [YUIUnknownPropertyException](#) if it does not exist.

If there is a property with that name, check also the expected type against 'type'. If the types don't match, throw a [YUIPropertyTypeMismatchException](#). If the property is read-only, throw a [YUISetReadOnlyPropertyException](#).

Definition at line 70 of file [YProperty.cc](#).

Here is the call graph for this function:




3.100.3.5 void YPropertySet::check (const YProperty & *prop*) const [inline]

Same as above, overloaded for convenience.

Definition at line 214 of file [YProperty.h](#).

Here is the call graph for this function:



3.100.3.6 bool YPropertySet::contains (const std::string & *propertyName*) const throw ()

Check if a property '*propertyName*' exists in this property set. Returns 'true' if it exists, 'false' if not.

Use [YPropertySet::check\(\)](#) for a check that throws exceptions if there is no such property.

Definition at line 81 of file [YProperty.cc](#).

3.100.3.7 bool YPropertySet::contains (const std::string & *propertyName*, YPropertyType *type*) const

Check if a property '*propertyName*' exists in this property set. Returns 'true' if it exists, 'false' if not.

If there is a property with that name, check also the expected type against '*type*'. If the types don't match, throw a [YUIPropertyTypeMismatchException](#).

If the property is read-only, throw a [YUISetReadOnlyPropertyException](#).

Use [YPropertySet::check\(\)](#) for a check that throws exceptions if there is no such property.


Definition at line 96 of file [YProperty.cc](#).

3.100.3.8 `bool YPropertySet::contains (const YProperty & prop) const` `[inline]`

Same as above, overloaded for convenience.

Definition at line 244 of file [YProperty.h](#).

Here is the call graph for this function:



3.100.3.9 `bool YPropertySet::isEmpty () const` `[inline]`

Returns 'true' if this property set does not contain anything.

Definition at line 250 of file [YProperty.h](#).

3.100.3.10 `YPropertySet::const_iterator YPropertySet::propertiesBegin () const`

Returns an iterator that points to the first property in this set.

Definition at line 139 of file [YProperty.cc](#).

3.100.3.11 `YPropertySet::const_iterator YPropertySet::propertiesEnd () const`

Returns an iterator that points after the last property in this set.

Definition at line 145 of file [YProperty.cc](#).

3.100.3.12 `int YPropertySet::size () const` `[inline]`

Returns the number of properties in this set.

Definition at line 255 of file [YProperty.h](#).

The documentation for this class was generated from the following files:

- /usr/src/RPM/BUILD/libyui-3.0.10/src/YProperty.h
- /usr/src/RPM/BUILD/libyui-3.0.10/src/YProperty.cc

3.101 YPropertyValue Class Reference

```
#include <YProperty.h>
```

Public Member Functions

- [YPropertyValue](#) (const std::string &str)
- [YPropertyValue](#) (const char *str)
- [YPropertyValue](#) (bool b)
- [YPropertyValue](#) (YInteger num)
- [YPropertyValue](#) (int num)
- **YPropertyValue** (YPropertyType [type](#))
- [YPropertyValue](#) ()
- [~YPropertyValue](#) ()
- YPropertyType [type](#) () const
- std::string [typeAsStr](#) () const
- std::string [stringVal](#) () const
- bool **boolVal** () const
- YInteger **integerVal** () const

3.101.1 Detailed Description

Transport class for the value of simple properties.

More complex properties (lists of items, tree descriptions, ...) have to be handled specifically someplace else, but most properties are of simple types and can be treated in similar ways.

Definition at line [104](#) of file [YProperty.h](#).

3.101.2 Constructor & Destructor Documentation

3.101.2.1 YPropertyValue::YPropertyValue (const std::string & *str*) [inline]

Constructor for string properties.

Definition at line [111](#) of file [YProperty.h](#).

3.101.2.2 YPropertyValue::YPropertyValue (const char * *str*) [inline]

Constructor for const char * (string) properties.

Definition at line 117 of file [YProperty.h](#).

3.101.2.3 YPropertyValue::YPropertyValue (bool *b*) [inline, explicit]

Constructor for bool properties.

Definition at line 123 of file [YProperty.h](#).

3.101.2.4 YPropertyValue::YPropertyValue (YInteger *num*) [inline, explicit]

Constructor for numerical (YCP integer) properties.

Definition at line 129 of file [YProperty.h](#).

3.101.2.5 YPropertyValue::YPropertyValue (int *num*) [inline, explicit]

Constructor for numerical (YCP integer) properties.

Definition at line 135 of file [YProperty.h](#).

3.101.2.6 YPropertyValue::YPropertyValue () [inline]

Default constructor

Definition at line 144 of file [YProperty.h](#).

3.101.2.7 YPropertyValue::~YPropertyValue ()

Destructor.

Definition at line 49 of file [YProperty.cc](#).

3.101.3 Member Function Documentation

3.101.3.1 std::string YPropertyValue::stringVal () const [inline]

Methods to get the value of this property. Check with [type\(\)](#) which one to use.

Definition at line 167 of file [YProperty.h](#).

3.101.3.2 YPropertyType YPropertyValue::type () const [inline]

Returns the type of this property value. Use this to determine which xyVal() method to use.

Definition at line 156 of file [YProperty.h](#).

3.101.3.3 std::string YPropertyValue::typeAsStr () const [inline]

Returns the type of this property value as string.


Definition at line 161 of file [YProperty.h](#).

The documentation for this class was generated from the following files:


- /usr/src/RPM/BUILD/libyui-3.0.10/src/YProperty.h
- /usr/src/RPM/BUILD/libyui-3.0.10/src/YProperty.cc

3.102 YPushButton Class Reference

Inheritance diagram for YPushButton:



Collaboration diagram for YPushButton:



Public Member Functions

- virtual [~YPushButton](#) ()
- virtual const char * [widgetClass](#) () const
- std::string [label](#) () const
- virtual void [setLabel](#) (const std::string &[label](#))
- virtual void [setIcon](#) (const std::string &iconName)
- bool [isDefaultButton](#) () const
- virtual void [setDefaultButton](#) (bool def=true)
- virtual void [setRole](#) (YButtonRole [role](#))
- YButtonRole [role](#) () const
- virtual void [setFunctionKey](#) (int fkey_no)
- bool [isHelpButton](#) () const
- virtual void [setHelpButton](#) (bool helpButton=true)
- virtual bool [setProperty](#) (const std::string &propertyName, const [YPropertyValue](#) &val)
- virtual [YPropertyValue](#) [getProperty](#) (const std::string &propertyName)
- virtual const [YPropertySet](#) & [propertySet](#) ()
- virtual std::string [shortcutString](#) () const
- virtual void [setShortcutString](#) (const std::string &str)

Protected Member Functions

- [YPushButton](#) ([YWidget](#) *parent, const std::string &[label](#))

3.102.1 Detailed Description

Definition at line 34 of file [YPushButton.h](#).


3.102.2 Constructor & Destructor Documentation

3.102.2.1 YPushButton::YPushButton (YWidget * parent, const std::string & label) [protected]

Constructor.

Definition at line 56 of file [YPushButton.cc](#).

Here is the call graph for this function:




3.102.2.2 YPushButton::~~YPushButton () [virtual]

Destructor.

Definition at line 67 of file [YPushButton.cc](#).

Here is the call graph for this function:



3.102.3 Member Function Documentation

3.102.3.1 YPropertyValue YPushButton::getProperty (const std::string & *propertyName*) [virtual]


Get a property. Reimplemented from [YWidget](#).

This method may throw YUIPropertyExceptions.

Reimplemented from [YWidget](#).

Definition at line 231 of file [YPushButton.cc](#).

Here is the call graph for this function:



3.102.3.2 bool YPushButton::isDefaultButton () const

Returns 'true' if this is the dialog's default button, i.e. the one button that gets activated if the user hits the [Return] key anywhere in the dialog.

Definition at line 90 of file [YPushButton.cc](#).

3.102.3.3 bool YPushButton::isHelpButton () const

Returns 'true' if this is a "Help" button.

When activated, a help button will traverse up its widget hierarchy and search for the topmost widget with a [helpText\(\)](#) set and display that help text in a pop-up dialog (with a local event loop).

NOTE that this is only done during [YDialog::waitForEvent\(\)](#) (i.e. in `YCP UI::WaitForEvent()`, `UI::UserInput()`, `UI::TimeoutUserInput()`) and not during [YDialog::pollEvent\(\)](#) (i.e. `YCP UI::PollInput()`) since displaying the help text will block the application until the user closes the help text.

Definition at line 125 of file [YPushButton.cc](#).

3.102.3.4 `std::string YPushButton::label () const`

Get the label (the text on the button).

Definition at line 84 of file [YPushButton.cc](#).

3.102.3.5 `const YPropertySet & YPushButton::propertySet () [virtual]`


Return this class's property set. This also initializes the property upon the first call.

Reimplemented from [YWidget](#).

Reimplemented from [YWidget](#).

Definition at line 198 of file [YPushButton.cc](#).

Here is the call graph for this function:



3.102.3.6 `YButtonRole YPushButton::role () const`

Return the role of this button.

Definition at line 164 of file [YPushButton.cc](#).


3.102.3.7 `void YPushButton::setDefaultButton (bool def = true) [virtual]`

Make this button the default button.

Derived classes should reimplement this, but call this base class function in the over-written function.

Definition at line 96 of file [YPushButton.cc](#).

Here is the call graph for this function:



3.102.3.8 void YPushButton::setFunctionKey (int fkey_no) [virtual]

Assign a function key to this widget (1 for F1, 2 for F2, etc.; 0 for none)

Reimplemented from [YWidget](#) to map function keys to button roles.

Derived classes may want to overwrite this function, but they should call this base class function in the new function.

Reimplemented from [YWidget](#).

Definition at line 172 of file [YPushButton.cc](#).

Here is the call graph for this function:



3.102.3.9 void YPushButton::setHelpButton (bool helpButton = true) [virtual]

Make this button a help button.

Derived classes are free to reimplement this, but they should call this base class method in the overloaded function.

Definition at line 131 of file [YPushButton.cc](#).

3.102.3.10 `virtual void YPushButton::setIcon (const std::string & iconName)`
[inline, virtual]

Set this button's icon from an icon file in the UI's default icon directory. Clear the icon if the name is empty.

This default implementation does nothing. UIs that can handle icons can choose to overwrite this method.

Definition at line 74 of file [YPushButton.h](#).

3.102.3.11 `void YPushButton::setLabel (const std::string & label)` [virtual]

Set the label (the text on the button).

Derived classes are free to reimplement this, but they should call this base class method at the end of the overloaded function.

Definition at line 78 of file [YPushButton.cc](#).

Here is the call graph for this function:



3.102.3.12 `bool YPushButton::setProperty (const std::string & propertyName, const YPropertyValue & val)` [virtual]

Set a property. Reimplemented from [YWidget](#).


This function may throw YUIPropertyExceptions.

This function returns 'true' if the value was successfully set and 'false' if that value requires special handling (not in error cases: those are covered by exceptions).

Reimplemented from [YWidget](#).

Definition at line 216 of file [YPushButton.cc](#).

Here is the call graph for this function:



3.102.3.13 void YPushButton::setRole (YButtonRole *role*) [virtual]

Set a predefined role for this button.

This is important when the button is a child of a [YButtonBox](#) so the layout can be arranged according to the conventions of the current UI or desktop environment.

See [YButtonBox.h](#) for more details. `YButtonRole` is defined in [YTypes.h](#)


The default is `YCustomButton`, i.e., no predefined role. [setFunctionKey\(\)](#) uses some heuristics to map function keys to buttons:

F10 -> `YOkButton` F9 -> `YCancelButton` F1 -> `YHelpButton`

Derived classes are free to reimplement this, but they should call this base class function in the overwritten function.

Definition at line 140 of file [YPushButton.cc](#).

Here is the call graph for this function:



3.102.3.14 `virtual void YPushButton::setShortcutString (const std::string & str)` [inline, virtual]


Set the string of this widget that holds the keyboard shortcut.

Reimplemented from [YWidget](#).

Reimplemented from [YWidget](#).

Definition at line 193 of file [YPushButton.h](#).

Here is the call graph for this function:



3.102.3.15 `virtual std::string YPushButton::shortcutString () const` [inline, virtual]


Get the string of this widget that holds the keyboard shortcut.

Reimplemented from [YWidget](#).

Reimplemented from [YWidget](#).

Definition at line 186 of file [YPushButton.h](#).

Here is the call graph for this function:



3.102.3.16 `virtual const char* YPushButton::widgetClass () const [inline, virtual]`

Return a descriptive name of this widget class for logging, debugging etc.

Reimplemented from [YWidget](#).

Definition at line 52 of file [YPushButton.h](#).

The documentation for this class was generated from the following files:

- `/usr/src/RPM/BUILD/libyui-3.0.10/src/YPushButton.h`
- `/usr/src/RPM/BUILD/libyui-3.0.10/src/YPushButton.cc`

3.103 YPushButtonPrivate Struct Reference

Public Member Functions

- **YPushButtonPrivate** (const std::string &label)

Public Attributes

- std::string **label**
- bool **isDefaultButton**
- bool **setDefaultButtonRecursive**
- bool **isHelpButton**
- YButtonRole **role**

3.103.1 Detailed Description

Definition at line 38 of file [YPushButton.cc](#).


The documentation for this struct was generated from the following file:

- /usr/src/RPM/BUILD/libyui-3.0.10/src/YPushButton.cc


3.104 YRadioButton Class Reference

```
#include <YRadioButton.h>
```

Inheritance diagram for YRadioButton:



Collaboration diagram for YRadioButton:



Public Member Functions

- virtual [~YRadioButton](#) ()
- virtual const char * [widgetClass](#) () const
- virtual bool [value](#) ()=0
- virtual void [setValue](#) (bool checked)=0
- std::string [label](#) () const
- virtual void [setLabel](#) (const std::string &[label](#))
- bool [useBoldFont](#) () const
- virtual void [setUseBoldFont](#) (bool bold=true)
- [YRadioButtonGroup](#) * [buttonGroup](#) ()
- virtual bool [setProperty](#) (const std::string &propertyName, const [YPropertyValue](#) &val)
- virtual [YPropertyValue](#) [getProperty](#) (const std::string &propertyName)
- virtual const [YPropertySet](#) & [propertySet](#) ()
- virtual std::string [shortcutString](#) () const
- virtual void [setShortcutString](#) (const std::string &str)
- const char * [userInputProperty](#) ()

Protected Member Functions

- [YRadioButton](#) ([YWidget](#) *parent, const std::string &[label](#))
- [YRadioButtonGroup](#) * [findRadioButtonGroup](#) () const
- virtual void [saveUserInput](#) ([YMacroRecorder](#) *macroRecorder)

3.104.1 Detailed Description

RadioButton: Widget for one-out-of-many selection.

Only one RadioButton in a RadioBox (in a RadioButtonGroup) can be set to "on" at the same time. Setting any RadioButton of a RadioButtonGroup to "on" automatically sets all others in the same RadioButtonGroup to "off".

RadioButtons customarily have a distinct visual appearance from CheckBoxes:

() RadioButton 1 (*) RadioButton 2 () RadioButton 3

[] CheckBox 1 [*] CheckBox 2 [*] CheckBox 3

Definition at line 51 of file [YRadioButton.h](#).

3.104.2 Constructor & Destructor Documentation

3.104.2.1 YRadioButton::YRadioButton (YWidget * *parent*, const std::string & *label*) [protected]

Constructor.

Creates a new RadioButton with user-visible text 'label'. 'label' can and should contain a keyboard shortcut (designated with '&').

The caller has to take care to add this RadioButton to its RadioButtonGroup:

```
if ( radioButton->buttonGroup() ) radioButton->buttonGroup()->addRadioButton(
radioButton );
```

This can't be done in the constructor because it would involve calling a virtual function, which doesn't work yet within the constructor.


Definition at line 60 of file [YRadioButton.cc](#).

3.104.2.2 YRadioButton::~YRadioButton () [virtual]

Destructor: Removes the button from the radio button group.

Definition at line 77 of file [YRadioButton.cc](#).

Here is the call graph for this function:




3.104.3 Member Function Documentation

3.104.3.1 YRadioButtonGroup * YRadioButton::buttonGroup ()

Get a pointer to the radio button group this button belongs to.

Definition at line 163 of file [YRadioButton.cc](#).

Here is the call graph for this function:



3.104.3.2 `YRadioButtonGroup * YRadioButton::findRadioButtonGroup () const` [protected]

Traverse the widget hierarchy upwards to find the corresponding [YRadioButtonGroup](#), i.e. the class that controls the radio box behaviour (i.e. that makes sure that no more than one `RadioButton` is set to "on" at the same time).

Definition at line 175 of file [YRadioButton.cc](#).

Here is the call graph for this function:



3.104.3.3 `YPropertyValue YRadioButton::getProperty (const std::string & propertyName)` [virtual]

Get a property. Reimplemented from [YWidget](#).


This method may throw exceptions, for example

- if there is no property with that name

Reimplemented from [YWidget](#).

Definition at line 149 of file [YRadioButton.cc](#).

Here is the call graph for this function:



3.104.3.4 `std::string YRadioButton::label () const`

Get the label (the text on the RadioButton).

Definition at line 93 of file [YRadioButton.cc](#).

3.104.3.5 `const YPropertySet & YRadioButton::propertySet () [virtual]`


Return this class's property set. This also initializes the property set upon the first call.

Reimplemented from [YWidget](#).

Reimplemented from [YWidget](#).

Definition at line 112 of file [YRadioButton.cc](#).

Here is the call graph for this function:



3.104.3.6 void YRadioButton::saveUserInput (YMacroRecorder * *macroRecorder*) [protected, virtual]


Save the widget's user input to a macro recorder.

Reimplemented from [YWidget](#) because only radio buttons that are on (no more than one per radio box) are recorded.

Reimplemented from [YWidget](#).

Definition at line 194 of file [YRadioButton.cc](#).

Here is the call graph for this function:



3.104.3.7 void YRadioButton::setLabel (const std::string & *label*) [virtual]

Set the label (the text on the RadioButton).

Derived classes are free to reimplement this, but they should call this base class method at the end of the overloaded function.

Definition at line 87 of file [YRadioButton.cc](#).

3.104.3.8 bool YRadioButton::setProperty (const std::string & *propertyName*, const YPropertyValue & *val*) [virtual]

Set a property. Reimplemented from [YWidget](#).

This method may throw exceptions, for example


- if there is no property with that name
- if the expected type and the type mismatch
- if the value is out of range

This function returns 'true' if the value was successfully set and 'false' if that value requires special handling (not in error cases: those are covered by exceptions).

Reimplemented from [YWidget](#).

Definition at line 133 of file [YRadioButton.cc](#).

Here is the call graph for this function:



3.104.3.9 virtual void YRadioButton::setShortcutString (const std::string & str) [inline, virtual]


Set the string of this widget that holds the keyboard shortcut.

Reimplemented from [YWidget](#).

Reimplemented from [YWidget](#).

Definition at line 177 of file [YRadioButton.h](#).

Here is the call graph for this function:



3.104.3.10 void YRadioButton::setUseBoldFont (bool *bold* = true) [virtual]

Indicate whether or not a bold font should be used.

Derived classes are free to reimplement this, but they should call this base class method at the end of the overloaded function.

Definition at line 105 of file [YRadioButton.cc](#).

3.104.3.11 virtual void YRadioButton::setValue (bool *checked*) [pure virtual]

Set the radio button value (on/off).

Derived classes are required to implement this.

3.104.3.12 virtual std::string YRadioButton::shortcutString () const [inline, virtual]


Get the string of this widget that holds the keyboard shortcut.

Reimplemented from [YWidget](#).

Reimplemented from [YWidget](#).

Definition at line 170 of file [YRadioButton.h](#).

Here is the call graph for this function:

**3.104.3.13 bool YRadioButton::useBoldFont () const**

Returns 'true' if a bold font should be used.

Definition at line 99 of file [YRadioButton.cc](#).

3.104.3.14 `const char* YRadioButton::userInputProperty () [inline, virtual]`

The name of the widget property that will return user input. Inherited from [YWidget](#).

Reimplemented from [YWidget](#).

Definition at line 184 of file [YRadioButton.h](#).

3.104.3.15 `virtual bool YRadioButton::value () [pure virtual]`

Get the current on/off value: 'true' if checked, 'false' if unchecked.

Derived classes are required to implement this.

3.104.3.16 `virtual const char* YRadioButton::widgetClass () const [inline, virtual]`

Returns a descriptive name of this widget class for logging, debugging etc.

Reimplemented from [YWidget](#).

Reimplemented from [YWidget](#).


Definition at line 84 of file [YRadioButton.h](#).

The documentation for this class was generated from the following files:


- `/usr/src/RPM/BUILD/libyui-3.0.10/src/YRadioButton.h`
- `/usr/src/RPM/BUILD/libyui-3.0.10/src/YRadioButton.cc`

3.105 YRadioButtonGroup Class Reference

Inheritance diagram for YRadioButtonGroup:



Collaboration diagram for YRadioButtonGroup:



Public Member Functions

- virtual [~YRadioButtonGroup](#) ()
- virtual const char * [widgetClass](#) () const
- [YRadioButton](#) * [currentButton](#) () const
- [YRadioButton](#) * [value](#) () const
- virtual void [addRadioButton](#) ([YRadioButton](#) *radioButton)
- virtual void [removeRadioButton](#) ([YRadioButton](#) *radioButton)
- void [uncheckOtherButtons](#) ([YRadioButton](#) *radioButton)
- virtual bool [setProperty](#) (const std::string &propertyName, const [YPropertyValue](#) &val)
- virtual [YPropertyValue](#) [getProperty](#) (const std::string &propertyName)
- virtual const [YPropertySet](#) & [propertySet](#) ()

Protected Member Functions

- [YRadioButtonGroup](#) ([YWidget](#) *parent)
- [YRadioButtonListConstIterator](#) [radioButtonsBegin](#) () const
- [YRadioButtonListConstIterator](#) [radioButtonsEnd](#) () const
- int [radioButtonsCount](#) () const

3.105.1 Detailed Description

Definition at line 38 of file [YRadioButtonGroup.h](#).

3.105.2 Constructor & Destructor Documentation

3.105.2.1 [YRadioButtonGroup::YRadioButtonGroup](#) ([YWidget](#) * *parent*) [protected]

Constructor.

Definition at line 46 of file [YRadioButtonGroup.cc](#).

3.105.2.2 [YRadioButtonGroup::~YRadioButtonGroup](#) () [virtual]

Destructor.

Definition at line 54 of file [YRadioButtonGroup.cc](#).

3.105.3 Member Function Documentation

3.105.3.1 `void YRadioButtonGroup::addRadioButton (YRadioButton * radioButton)` [virtual]

Add a RadioButton to this button group. RadioButtons are required to call this in their constructor.

Derived classes are free to overload this, but they should call this base class function in the overloaded function.


Definition at line 81 of file [YRadioButtonGroup.cc](#).

3.105.3.2 `YRadioButton * YRadioButtonGroup::currentButton () const`

Find the currently selected button.

Definition at line 108 of file [YRadioButtonGroup.cc](#).

Here is the call graph for this function:



3.105.3.3 `YPropertyValue YRadioButtonGroup::getProperty (const std::string & propertyName)` [virtual]

Get a property. Reimplemented from [YWidget](#).


This method may throw exceptions, for example

- if there is no property with that name

Reimplemented from [YWidget](#).

Definition at line 159 of file [YRadioButtonGroup.cc](#).

Here is the call graph for this function:



3.105.3.4 `const YPropertySet & YRadioButtonGroup::propertySet ()` [virtual]


Return this class's property set. This also initializes the property set upon the first call.

Reimplemented from [YWidget](#).

Reimplemented from [YWidget](#).

Definition at line 123 of file [YRadioButtonGroup.cc](#).

Here is the call graph for this function:



3.105.3.5 `YRadioButtonListConstIterator YRadioButtonGroup::radioButtonsBegin ()` `const` [protected]

Return an iterator that points to the first `RadioButton` of this button group.

Note that `RadioButtons` in this group may be direct or indirect children of the group, so don't confuse this with `YWidget::widgetsBegin()`.

Definition at line 60 of file [YRadioButtonGroup.cc](#).

3.105.3.6 `int YRadioButtonGroup::radioButtonsCount () const` [protected]

Return the number of RadioButtons in this button group.

Definition at line 74 of file [YRadioButtonGroup.cc](#).

3.105.3.7 `YRadioButtonListConstIterator YRadioButtonGroup::radioButtonsEnd () const` [protected]

Return an iterator that points behind the last RadioButton of this button group.

Definition at line 67 of file [YRadioButtonGroup.cc](#).

3.105.3.8 `void YRadioButtonGroup::removeRadioButton (YRadioButton * radioButton)` [virtual]

Remove a RadioButton from this button group. RadioButtons are required to call this in their destructor, but only if the button group is not also in the process of being destroyed (otherwise there may be race conditions with child widgets already destroyed):

if (! buttonGroup()->beingDestroyed) buttonGroup()->removeRadioButton(this);

Definition at line 88 of file [YRadioButtonGroup.cc](#).

3.105.3.9 `bool YRadioButtonGroup::setProperty (const std::string & propertyName, const YPropertyValue & val)` [virtual]

Set a property. Reimplemented from [YWidget](#).

This method may throw exceptions, for example


- if there is no property with that name
- if the expected type and the type mismatch
- if the value is out of range

This function returns 'true' if the value was successfully set and 'false' if that value requires special handling (not in error cases: those are covered by exceptions).

Reimplemented from [YWidget](#).

Definition at line 143 of file [YRadioButtonGroup.cc](#).

Here is the call graph for this function:




3.105.3.10 void YRadioButtonGroup::uncheckOtherButtons (YRadioButton * *radioButton*)

Unchecks all radio buttons except one. This method can be used by a concrete UI (the Qt UI or the NCurses UI) in the implementation of `YRadioButton::setValue()`.

Definition at line 95 of file `YRadioButtonGroup.cc`.

Here is the call graph for this function:



3.105.3.11 YRadioButton* YRadioButtonGroup::value () const [inline]

The same as `currentButton()` above for convenience.

Definition at line 66 of file `YRadioButtonGroup.h`.

Here is the call graph for this function:



3.105.3.12 `virtual const char* YRadioButtonGroup::widgetClass () const`
`[inline, virtual]`

Returns a descriptive name of this widget class for logging, debugging etc.

Reimplemented from [YWidget](#).

Definition at line [56](#) of file [YRadioButtonGroup.h](#).

The documentation for this class was generated from the following files:

- `/usr/src/RPM/BUILD/libyui-3.0.10/src/YRadioButtonGroup.h`
- `/usr/src/RPM/BUILD/libyui-3.0.10/src/YRadioButtonGroup.cc`

3.106 YRadioButtonGroupPrivate Struct Reference

Public Attributes

- YRadioButtonList **buttonList**

3.106.1 Detailed Description


Definition at line [34](#) of file [YRadioButtonGroup.cc](#).

The documentation for this struct was generated from the following file:

- `/usr/src/RPM/BUILD/libyui-3.0.10/src/YRadioButtonGroup.cc`

3.107 YRadioButtonPrivate Struct Reference

Collaboration diagram for YRadioButtonPrivate:



Public Member Functions

- [YRadioButtonPrivate](#) (const std::string &label)

Public Attributes

- std::string **label**
- [YRadioButtonGroup](#) * **radioButtonGroup**
- bool **useBoldFont**

3.107.1 Detailed Description

Definition at line 39 of file [YRadioButton.cc](#).

3.107.2 Constructor & Destructor Documentation

3.107.2.1 `YRadioButtonPrivate::YRadioButtonPrivate (const std::string & label)` [inline]

Constructor


Definition at line 44 of file [YRadioButton.cc](#).

The documentation for this struct was generated from the following file:


- `/usr/src/RPM/BUILD/libyui-3.0.10/src/YRadioButton.cc`

3.108 YReplacePoint Class Reference

Inheritance diagram for YReplacePoint:



Collaboration diagram for YReplacePoint:



Public Member Functions

- virtual void [showChild](#) ()
- virtual const char * [widgetClass](#) () const

Protected Member Functions

- [YReplacePoint](#) (YWidget *parent)

3.108.1 Detailed Description

Definition at line 30 of file [YReplacePoint.h](#).

3.108.2 Constructor & Destructor Documentation

3.108.2.1 YReplacePoint::YReplacePoint (YWidget * parent) [protected]

Constructor

Definition at line 28 of file [YReplacePoint.cc](#).

3.108.3 Member Function Documentation

3.108.3.1 void YReplacePoint::showChild () [virtual]

Show a newly added child. The application using the ReplacePoint is required to call this after the new child is created.

This cannot be done in the child widget's constructor (e.g., by overwriting [YWidget::addChild\(\)](#) since at that point [YWidget::widgetRep\(\)](#) may or may not be initialized yet.

This default implementation does nothing. Derived classes should reimplement this to make new child widgets visible.

Definition at line 35 of file [YReplacePoint.cc](#).

3.108.3.2 virtual const char* YReplacePoint::widgetClass () const [inline, virtual]

Returns a descriptive name of this widget class for logging, debugging etc.

Reimplemented from [YWidget](#).


Definition at line 56 of file [YReplacePoint.h](#).

The documentation for this class was generated from the following files:


- [/usr/src/RPM/BUILD/libyui-3.0.10/src/YReplacePoint.h](#)
- [/usr/src/RPM/BUILD/libyui-3.0.10/src/YReplacePoint.cc](#)

3.109 YRichText Class Reference

Inheritance diagram for YRichText:



Collaboration diagram for YRichText:



Public Member Functions

- [YRichText](#) ([YWidget](#) *[parent](#), const std::string &[text](#), bool [plainTextMode](#)=false)
- virtual [~YRichText](#) ()
- virtual const char * [widgetClass](#) () const
- virtual void [setValue](#) (const std::string &[newValue](#))
- std::string [value](#) () const
- void [setText](#) (const std::string &[newText](#))
- std::string [text](#) () const
- bool [plainTextMode](#) () const
- virtual void [setPlainTextMode](#) (bool [on](#)=true)
- bool [autoScrollDown](#) () const
- virtual void [setAutoScrollDown](#) (bool [on](#)=true)
- bool [shrinkable](#) () const
- void [setShrinkable](#) (bool [shrinkable](#)=true)
- virtual bool [setProperty](#) (const std::string &[propertyName](#), const [YPropertyValue](#) &[val](#))
- virtual [YPropertyValue](#) [getProperty](#) (const std::string &[propertyName](#))
- virtual const [YPropertySet](#) & [propertySet](#) ()

Protected Attributes

- [ImplPtr](#)< [YRichTextPrivate](#) > [priv](#)

3.109.1 Detailed Description

Definition at line 36 of file [YRichText.h](#).

3.109.2 Constructor & Destructor Documentation

3.109.2.1 [YRichText::YRichText](#) ([YWidget](#) * *parent*, const std::string & *text*, bool *plainTextMode* = false)

Constructor.

'plainTextMode' indicates that the text should be treated as plain text, i.e. any HTML-like tags in the text should not be interpreted in any way.

Definition at line 54 of file [YRichText.cc](#).

Here is the call graph for this function:



3.109.2.2 YRichText::~~YRichText() [virtual]

Destructor.

Definition at line 65 of file [YRichText.cc](#).

3.109.3 Member Function Documentation

3.109.3.1 bool YRichText::autoScrollDown() const

Return 'true' if this RichText widget should automatically scroll down when the text content is changed. This is useful for progress displays and log files.

Definition at line 95 of file [YRichText.cc](#).

3.109.3.2 YPropertyValue YRichText::getProperty(const std::string & *propertyName*) [virtual]


Get a property. Reimplemented from [YWidget](#).

This method may throw YUIPropertyExceptions.

Reimplemented from [YWidget](#).

Definition at line 156 of file [YRichText.cc](#).

Here is the call graph for this function:



3.109.3.3 `bool YRichText::plainTextMode () const`

Return 'true' if this RichText widget is in "plain text" mode, i.e. does not try to interpret RichText/HTML tags.

Definition at line 83 of file [YRichText.cc](#).

3.109.3.4 `const YPropertySet & YRichText::propertySet () [virtual]`

Return this class's property set. This also initializes the property upon the first call.

Reimplemented from [YWidget](#).

Reimplemented from [YWidget](#).

Definition at line 120 of file [YRichText.cc](#).

Here is the call graph for this function:



3.109.3.5 void YRichText::setAutoScrollDown (bool *on* =true) [virtual]

Set this RichText widget's "auto scroll down" mode on or off.

Derived classes may want to reimplement this, but they should call this base class function in the new function.

Definition at line 101 of file [YRichText.cc](#).

Here is the call graph for this function:

**3.109.3.6** void YRichText::setPlainTextMode (bool *on* =true) [virtual]

Set this RichText widget's "plain text" mode on or off.

Derived classes may want to reimplement this, but they should call this base class function in the new function.

Definition at line 89 of file [YRichText.cc](#).

Here is the call graph for this function:

**3.109.3.7** bool YRichText::setProperty (const std::string & *propertyName*, const YPropertyValue & *val*) [virtual]

Set a property. Reimplemented from [YWidget](#).


This function may throw `YUIPropertyExceptions`.

This function returns 'true' if the value was successfully set and 'false' if that value requires special handling (not in error cases: those are covered by exceptions).

Reimplemented from [YWidget](#).

Definition at line 140 of file [YRichText.cc](#).

Here is the call graph for this function:



3.109.3.8 void YRichText::setShrinkable (bool *shrinkable* = true)

Make this widget shrinkable, i.e. very small in layouts.

This method is intentionally not virtual because it doesn't have any immediate effect; it is only needed in [preferredWidth\(\)](#) / [preferredHeight\(\)](#).

Definition at line 113 of file [YRichText.cc](#).

Here is the call graph for this function:



3.109.3.9 void YRichText::setText (const std::string & *newText*) [inline]

Alias for [setValue\(\)](#).

Definition at line 78 of file [YRichText.h](#).

Here is the call graph for this function:

**3.109.3.10** void YRichText::setValue (const std::string & *newValue*) [virtual]

Change the text content of the RichText widget.

Derived classes should overwrite this function, but call this base class function in the new function.

Definition at line 71 of file [YRichText.cc](#).

3.109.3.11 bool YRichText::shrinkable () const

Returns 'true' if this widget is "shrinkable", i.e. it should be very small by default.

Definition at line 107 of file [YRichText.cc](#).

3.109.3.12 std::string YRichText::text () const [inline]

Alias for [value\(\)](#).

Definition at line 83 of file [YRichText.h](#).

Here is the call graph for this function:



3.109.3.13 `std::string YRichText::value () const`

Return the text content of the RichText widget.

Definition at line 77 of file [YRichText.cc](#).

3.109.3.14 `virtual const char* YRichText::widgetClass () const` [inline, virtual]

Returns a descriptive name of this widget class for logging, debugging etc.

Reimplemented from [YWidget](#).

Definition at line 60 of file [YRichText.h](#).

The documentation for this class was generated from the following files:

- `/usr/src/RPM/BUILD/libyui-3.0.10/src/YRichText.h`
- `/usr/src/RPM/BUILD/libyui-3.0.10/src/YRichText.cc`

3.110 YRichTextPrivate Struct Reference

Public Member Functions

- [YRichTextPrivate](#) (const std::string &text, bool plainTextMode)

Public Attributes

- std::string **text**
- bool **plainTextMode**

- bool **autoScrollDown**
- bool **shrinkable**

3.110.1 Detailed Description

Definition at line 33 of file [YRichText.cc](#).

3.110.2 Constructor & Destructor Documentation

3.110.2.1 **YRichTextPrivate::YRichTextPrivate** (const std::string & *text*, bool *plainTextMode*) [inline]

Constructor.

Definition at line 38 of file [YRichText.cc](#).


The documentation for this struct was generated from the following file:

- /usr/src/RPM/BUILD/libyui-3.0.10/src/YRichText.cc


3.111 YRpmGroupsTree Class Reference

```
#include <YRpmGroupsTree.h>
```

Inheritance diagram for YRpmGroupsTree:



Collaboration diagram for YRpmGroupsTree:



Public Member Functions

- [YRpmGroupsTree](#) ()
- [virtual ~YRpmGroupsTree](#) ()
- [YStringTreelItem](#) * [addRpmGroup](#) (const std::string &[rpmGroup](#))
- std::string [rpmGroup](#) (const [YStringTreelItem](#) *node)
- std::string [translatedRpmGroup](#) (const [YStringTreelItem](#) *node)
- void [addFallbackRpmGroups](#) ()

3.111.1 Detailed Description

Efficient storage for RPM group tags

Definition at line 35 of file [YRpmGroupsTree.h](#).

3.111.2 Constructor & Destructor Documentation

3.111.2.1 YRpmGroupsTree::YRpmGroupsTree ()

Constructor.

Definition at line 33 of file [YRpmGroupsTree.cc](#).

3.111.2.2 YRpmGroupsTree::~YRpmGroupsTree () [virtual]

Destructor.

Definition at line 41 of file [YRpmGroupsTree.cc](#).


3.111.3 Member Function Documentation

3.111.3.1 void YRpmGroupsTree::addFallbackRpmGroups ()

Add a predefined set of RPM groups

Definition at line 273 of file [YRpmGroupsTree.cc](#).

Here is the call graph for this function:




3.111.3.2 YStringTreeltem* YRpmGroupsTree::addRpmGroup (const std::string & rpmGroup) [inline]

Insert an RPM group into this tree if not already present. Splits the RPM group string ("abc/def/ghi") and creates tree items for each level as required. Returns the tree entry for this RPM group.

Definition at line 56 of file [YRpmGroupsTree.h](#).

Here is the call graph for this function:




3.111.3.3 `std::string YRpmGroupsTree::rpmGroup (const YStringTreeItem * node)` [inline]

Returns the complete (untranslated) RPM group tag string for 'node'.

Definition at line 62 of file [YRpmGroupsTree.h](#).

Here is the call graph for this function:




3.111.3.4 `std::string YRpmGroupsTree::translatedRpmGroup (const YStringTreeItem * node)` [inline]

Returns the complete translated RPM group tag string for 'node'.

Definition at line 68 of file [YRpmGroupsTree.h](#).

Here is the call graph for this function:




The documentation for this class was generated from the following files:

- /usr/src/RPM/BUILD/libyui-3.0.10/src/YRpmGroupsTree.h
- /usr/src/RPM/BUILD/libyui-3.0.10/src/YRpmGroupsTree.cc


3.112 YSelectionBox Class Reference

```
#include <YSelectionBox.h>
```

Inheritance diagram for YSelectionBox:



Collaboration diagram for YSelectionBox:



Public Member Functions

- virtual [~YSelectionBox](#) ()
- virtual const char * [widgetClass](#) () const
- bool [shrinkable](#) () const
- virtual void [setShrinkable](#) (bool [shrinkable](#)=true)
- bool [immediateMode](#) () const
- void [setImmediateMode](#) (bool on=true)
- virtual bool [setProperty](#) (const std::string &propertyName, const [YPropertyValue](#) &val)
- virtual [YPropertyValue](#) [getProperty](#) (const std::string &propertyName)
- virtual const [YPropertySet](#) & [propertySet](#) ()
- const char * [userInputProperty](#) ()

Protected Member Functions

- [YSelectionBox](#) ([YWidget](#) *[parent](#), const std::string &[label](#))

3.112.1 Detailed Description

Selection box: List box that displays a (scrollable) list of items from which the user can select exactly one. Each item has a label text and an optional icon (*).

This widget displays a number of items at once (as screen space permits). If there is little screen space, you might consider using a ComboBox instead which (in non-editable mode which is the default) displays just one item (the selected item) right away and the others in a pop-up dialog upon mouse click or keypress.

The selection box also has a caption label that is displayed above the list. The hotkey displayed in that caption label will move the keyboard focus into the list.

If multiple columns are needed, use the table widget instead. For tree-like structures, use the tree widget.

(*) Not all UIs (in particular not text-based UIs) support displaying icons, so an icon should never be an exclusive means to display any kind of information.

Definition at line 56 of file [YSelectionBox.h](#).

3.112.2 Constructor & Destructor Documentation

3.112.2.1 YSelectionBox::YSelectionBox (YWidget * *parent*, const std::string & *label*) [protected]

Constructor.

Definition at line 48 of file [YSelectionBox.cc](#).

Here is the call graph for this function:



3.112.2.2 YSelectionBox::~YSelectionBox () [virtual]

Destructor.

Definition at line 61 of file [YSelectionBox.cc](#).

3.112.3 Member Function Documentation

3.112.3.1 YPropertyValue YSelectionBox::getProperty (const std::string & *propertyName*) [virtual]


Get a property. Reimplemented from [YWidget](#).

This method may throw YUIPropertyExceptions.

Reimplemented from [YWidget](#).

Definition at line 140 of file [YSelectionBox.cc](#).

Here is the call graph for this function:



3.112.3.2 bool YSelectionBox::immediateMode () const

Deliver even more events than with [notify\(\)](#) set.

For [YSelectionBox](#), this is relevant mostly for the NCurses UI:

In graphical UIs like the Qt UI, the user can use the mouse to select an item in a selection box. With [notify\(\)](#) set, this will send an event right away (i.e., it will make `UserInput` and related return, while normally it would only return when the user clicks a `PushButton`).

In the NCurses UI, there is no mouse, so the user has to use the cursor keys to move to the item he wants to select. In [immediateMode\(\)](#), every cursor key press will make the selection box send an event. Without [immediateMode\(\)](#), the `NCSelectionBox` will wait until the user hits the [Return] key until an event is sent. Depending on what the application does upon each selection box event, [immediateMode\(\)](#) might make the application less responsive.

Definition at line 79 of file [YSelectionBox.cc](#).

3.112.3.3 `const YPropertySet & YSelectionBox::propertySet ()` [virtual]


Return this class's property set. This also initializes the property upon the first call.

Reimplemented from [YWidget](#).

Reimplemented from [YWidget](#).

Definition at line 95 of file [YSelectionBox.cc](#).

Here is the call graph for this function:




3.112.3.4 `void YSelectionBox::setImmediateMode (bool on = true)`

Set [immediateMode\(\)](#) on or off.

Definition at line 85 of file [YSelectionBox.cc](#).

Here is the call graph for this function:



3.112.3.5 `bool YSelectionBox::setProperty (const std::string & propertyName, const YPropertyValue & val)` [virtual]

Set a property. Reimplemented from [YWidget](#).


This function may throw `YUIPropertyExceptions`.

This function returns 'true' if the value was successfully set and 'false' if that value requires special handling (not in error cases: those are covered by exceptions).

Reimplemented from [YWidget](#).

Definition at line 121 of file [YSelectionBox.cc](#).

Here is the call graph for this function:



3.112.3.6 void YSelectionBox::setShrinkable (bool *shrinkable* = true) [virtual]

Make this SelectionBox very small. This will take effect only upon the next geometry management run.

Derived classes can overwrite this, but should call this base class function in the new function.

Definition at line 73 of file [YSelectionBox.cc](#).

Here is the call graph for this function:



3.112.3.7 `bool YSelectionBox::shrinkable () const`

Return 'true' if this SelectionBox should be very small.

Definition at line 67 of file [YSelectionBox.cc](#).

3.112.3.8 `const char* YSelectionBox::userInputProperty () [inline, virtual]`

The name of the widget property that will return user input. Inherited from [YWidget](#).

Reimplemented from [YWidget](#).

Definition at line 149 of file [YSelectionBox.h](#).

3.112.3.9 `virtual const char* YSelectionBox::widgetClass () const [inline, virtual]`

Returns a descriptive name of this widget class for logging, debugging etc.

Reimplemented from [YSelectionWidget](#).

Definition at line 75 of file [YSelectionBox.h](#).

The documentation for this class was generated from the following files:

- [/usr/src/RPM/BUILD/libyui-3.0.10/src/YSelectionBox.h](#)
- [/usr/src/RPM/BUILD/libyui-3.0.10/src/YSelectionBox.cc](#)

3.113 YSelectionBoxPrivate Struct Reference

Public Attributes

- `bool shrinkable`
- `bool immediateMode`

3.113.1 Detailed Description

Definition at line 34 of file [YSelectionBox.cc](#).


The documentation for this struct was generated from the following file:

- [/usr/src/RPM/BUILD/libyui-3.0.10/src/YSelectionBox.cc](#)


3.114 YSelectionWidget Class Reference

```
#include <YSelectionWidget.h>
```

Inheritance diagram for YSelectionWidget:



Collaboration diagram for YSelectionWidget:



Public Member Functions

- virtual `~YSelectionWidget` ()
- virtual const char * `widgetClass` () const
- std::string `label` () const
- virtual void `setLabel` (const std::string &newLabel)
- virtual void `addItem` (YItem *item_disown)
- void `addItem` (const std::string &itemLabel, bool selected=false)
- void `addItem` (const std::string &itemLabel, const std::string &iconName, bool selected=false)
- virtual void `addItems` (const YItemCollection &itemCollection)
- virtual void `deleteAllItems` ()
- void `setItems` (const YItemCollection &itemCollection)
- YItemIterator `itemsBegin` ()
- YItemConstIterator `itemsBegin` () const
- YItemIterator `itemsEnd` ()
- YItemConstIterator `itemsEnd` () const
- bool `hasItems` () const
- int `itemsCount` () const
- YItem * `firstItem` () const
- virtual YItem * `selectedItem` ()
- virtual YItemCollection `selectedItems` ()
- bool `hasSelectedItem` ()
- virtual void `selectItem` (YItem *item, bool selected=true)
- virtual void `deselectAllItems` ()
- void `setIconBasePath` (const std::string &basePath)

- `std::string iconBasePath ()` const
- `std::string iconFullPath (const std::string &iconName)` const
- `std::string iconFullPath (YItem *item)` const
- `bool itemsContain (YItem *item)` const
- `YItem * findItem (const std::string &itemLabel)` const
- `virtual std::string shortcutString ()` const
- `virtual void setShortcutString (const std::string &str)`

Protected Member Functions

- `YSelectionWidget (YWidget *parent, const std::string &label, bool enforceSingleSelection, bool recursiveSelection=false)`
- `void setEnforceSingleSelection (bool on)`
- `bool enforceSingleSelection ()` const
- `bool recursiveSelection ()` const
- `YItem * findSelectedItem (YItemConstIterator begin, YItemConstIterator end)`
- `void findSelectedItems (YItemCollection &selectedItems, YItemConstIterator begin, YItemConstIterator end)`
- `void deselectAllItems (YItemIterator begin, YItemIterator end)`
- `YItem * findItem (const std::string &wantedItemLabel, YItemConstIterator begin, YItemConstIterator end)` const
- `bool itemsContain (YItem *wantedItem, YItemConstIterator begin, YItemConstIterator end)` const
- `YItem * itemAt (int index)` const

3.114.1 Detailed Description

Base class for selection widgets:

- [YSelectionBox](#)
- [MultiselectionBox](#)
- [YCombobox](#)
- [YTree](#)
- [YDumbTab](#)

Definition at line 42 of file [YSelectionWidget.h](#).

3.114.2 Constructor & Destructor Documentation

3.114.2.1 **YSelectionWidget::YSelectionWidget** (*YWidget * parent*, *const std::string & label*, *bool enforceSingleSelection*, *bool recursiveSelection = false*)
[protected]

Constructor.

'singleSelectionMode' indicates if this base class should enforce single selection when items are added or when items are selected from the application. Note that single selection can also mean that no item is selected.

Definition at line 55 of file [YSelectionWidget.cc](#).

3.114.2.2 **YSelectionWidget::~~YSelectionWidget** () [virtual]

Destructor.

Definition at line 70 of file [YSelectionWidget.cc](#).

Here is the call graph for this function:



3.114.3 Member Function Documentation

3.114.3.1 **void YSelectionWidget::addItem** (*YItem * item_disown*) [virtual]

Add one item. This widget assumes ownership of the item object and will delete it in its destructor.


NOTE: For tree items, call this only for the toplevel items; all non-toplevel items are already owned by their respective parent items. Adding them to the parent widget will clash with this ownership.

Derived classes can overwrite this function, but they should call this base class function in the new implementation.

Reimplemented in [YContextMenu](#), [YMenuButton](#), and [YDumbTab](#).

Definition at line 168 of file [YSelectionWidget.cc](#).

Here is the call graph for this function:




3.114.3.2 void YSelectionWidget::addItem (const std::string & *itemLabel*, bool *selected* = false)

Overloaded for convenience: Add an item by string.

Definition at line 235 of file [YSelectionWidget.cc](#).

Here is the call graph for this function:




3.114.3.3 void YSelectionWidget::addItem (const std::string & *itemLabel*, const std::string & *iconName*, bool *selected* = false)

Overloaded for convenience: Add an item with a text and an icon. Note that not all UIs can display icons.

Definition at line 225 of file [YSelectionWidget.cc](#).

Here is the call graph for this function:




3.114.3.4 void YSelectionWidget::addItems (const YItemCollection & itemCollection) [virtual]

Add multiple items. For some UIs, this can be more efficient than calling [addItem\(\)](#) multiple times.

Reimplemented in [YTree](#), [YContextMenu](#), and [YMenuButton](#).

Definition at line 241 of file [YSelectionWidget.cc](#).

Here is the call graph for this function:



3.114.3.5 void YSelectionWidget::deleteAllItems () [virtual]


Delete all items.

Derived classes can overwrite this function, but they should call this base class function in the new implementation.

Reimplemented in [YContextMenu](#), and [YMenuButton](#).

Definition at line 76 of file [YSelectionWidget.cc](#).

Here is the call graph for this function:




3.114.3.6 `void YSelectionWidget::deselectAllItems ()` [virtual]

Deselect all items.

Derived classes can overwrite this function, but they should call this base class function in the new implementation.

Definition at line 454 of file [YSelectionWidget.cc](#).

Here is the call graph for this function:




3.114.3.7 `void YSelectionWidget::deselectAllItems (YItemIterator begin, YItemIterator end)` [protected]

Recursively deselect all items between iterators 'begin' and 'end'.

Definition at line 460 of file [YSelectionWidget.cc](#).

Here is the call graph for this function:



3.114.3.8 `bool YSelectionWidget::enforceSingleSelection () const` [protected]

Return 'true' if this base class should enforce single selection.


Definition at line 107 of file [YSelectionWidget.cc](#).

3.114.3.9 `YItem * YSelectionWidget::findItem (const std::string & itemLabel) const`

Find the (first) item with the specified label. Return 0 if there is no item with that label.

Definition at line 476 of file [YSelectionWidget.cc](#).

Here is the call graph for this function:




3.114.3.10 `YItem * YSelectionWidget::findItem (const std::string & wantedItemLabel, YItemConstIterator begin, YItemConstIterator end) const` [protected]

Recursively try to find an item with label 'wantedItemLabel' between iterators 'begin' and 'end'. Return that item or 0 if there is none.

Definition at line 483 of file [YSelectionWidget.cc](#).

Here is the call graph for this function:




3.114.3.11 `YItem * YSelectionWidget::findSelectedItem (YItemConstIterator begin, YItemConstIterator end)` [protected]

Recursively try to find the first selected item between iterators 'begin' and 'end'. Return that item or 0 if there is none.

Definition at line 326 of file [YSelectionWidget.cc](#).

Here is the call graph for this function:




3.114.3.12 `void YSelectionWidget::findSelectedItems (YItemCollection & selectedItems, YItemConstIterator begin, YItemConstIterator end)` [protected]

Recursively find all selected items between iterators 'begin' and 'end' and add each of them to the 'selectedItems' YItemCollection.

Definition at line 363 of file [YSelectionWidget.cc](#).

Here is the call graph for this function:



3.114.3.13 YItem * YSelectionWidget::firstItem () const

Return the first item or 0 if there is none.

Definition at line 299 of file [YSelectionWidget.cc](#).

3.114.3.14 bool YSelectionWidget::hasItems () const

Return 'true' if this widget has any items.


Definition at line 286 of file [YSelectionWidget.cc](#).

3.114.3.15 bool YSelectionWidget::hasSelectedItem ()

Return 'true' if any item is selected.

Definition at line 384 of file [YSelectionWidget.cc](#).

Here is the call graph for this function:



3.114.3.16 std::string YSelectionWidget::iconBasePath () const

Return this widget's base path where to look up icons as set with [setIconBasePath\(\)](#).

Definition at line 131 of file [YSelectionWidget.cc](#).

3.114.3.17 std::string YSelectionWidget::iconFullPath (const std::string & iconName) const

Return the full path + file name for the specified icon name. If `iconBasePath` is non-empty, it is prepended to the icon name. Otherwise, `YUI::yApp()->iconLoader()` and its icon search paths is used find the icon in one of them

If 'iconName' is empty, this will return an empty string.

Definition at line 137 of file [YSelectionWidget.cc](#).


3.114.3.18 `std::string YSelectionWidget::iconFullPath (YItem * item) const`

Return the full path + file name for the icon of the specified item. If `iconBasePath` is non-empty, it is prepended to the item's `iconName`. Otherwise, `YUI::yApp()->iconLoader()` and its icon search paths is used find the icon in one of them

If 'item' does not have an `iconName` specified, this will return an empty string.

Definition at line 159 of file [YSelectionWidget.cc](#).

Here is the call graph for this function:



3.114.3.19 `YItem * YSelectionWidget::itemAt (int index) const` [protected]

Return the item at index 'index' (from 0) or 0 if there is no such item.

Definition at line 309 of file [YSelectionWidget.cc](#).

3.114.3.20 `YItemIterator YSelectionWidget::itemsBegin ()`

Return an iterator that points to the first item.

For `YSelectionWidgets` that can have tree structures, this iterator will iterate over the toplevel items.

Important: Don't use this iterator to iterate over all items and check their "selected" state; that information might not always be up to date. Use the dedicated functions for that.


Definition at line 260 of file [YSelectionWidget.cc](#).

3.114.3.21 `bool YSelectionWidget::itemsContain (YItem * item) const`

Return 'true' if this widget's items contain the specified item.

Definition at line 420 of file [YSelectionWidget.cc](#).

Here is the call graph for this function:




3.114.3.22 `bool YSelectionWidget::itemsContain (YItem * wantedItem, YItemConstIterator begin, YItemConstIterator end) const` [protected]

Recursively check if 'wantedItem' is between iterators 'begin' and 'end'.

Definition at line 428 of file [YSelectionWidget.cc](#).

Here is the call graph for this function:



3.114.3.23 `int YSelectionWidget::itemsCount () const`

Return the number of items.

For YSelectionWidgets that can have tree structures, this returns the number of toplevel items.

Definition at line 292 of file [YSelectionWidget.cc](#).

3.114.3.24 YItemIterator YSelectionWidget::itemsEnd ()

Return an iterator that points behind the last item.

Definition at line 273 of file [YSelectionWidget.cc](#).

3.114.3.25 std::string YSelectionWidget::label () const

Return this widget's label (the caption above the item list).

Definition at line 95 of file [YSelectionWidget.cc](#).

3.114.3.26 bool YSelectionWidget::recursiveSelection () const [protected]

Return 'true' if this base class should select children recursively.

Definition at line 112 of file [YSelectionWidget.cc](#).


3.114.3.27 YItem * YSelectionWidget::selectedItem () [virtual]

Return the (first) selected item or 0 if none is selected.

Reimplemented in [YComboBox](#).

Definition at line 319 of file [YSelectionWidget.cc](#).

Here is the call graph for this function:



3.114.3.28 YItemCollection YSelectionWidget::selectedItems () [virtual]


Return all selected items. This is mostly useful for derived classes that allow selecting multiple items.

This function does not transfer ownership of those items to the caller, so don't try to delete them!

Reimplemented in [YComboBox](#).

Definition at line 353 of file [YSelectionWidget.cc](#).

Here is the call graph for this function:



3.114.3.29 void YSelectionWidget::selectItem (YItem * item, bool selected = true) [virtual]

Select or deselect an item.

Notice that this is different from [YItem::setSelected\(\)](#) because unlike the latter function, this function informs the parent widget of the selection change.


If only one item can be selected at any time (single selection), the derived class will make sure to deselect any previous selection, if applicable.

Derived classes should overwrite this function, but they should call this base class function at the new function's start (this will also check if the item really belongs to this widget and throw an exception if not).

Reimplemented in [YComboBox](#).

Definition at line 390 of file [YSelectionWidget.cc](#).

Here is the call graph for this function:



3.114.3.30 void YSelectionWidget::setEnforceSingleSelection (bool on) [protected]

Set single selection mode on or off. In single selection mode, only one item can be selected at any time.

If set, this base class enforces this when items are added or when items are selected from the application. Note that single selection can also mean that no item is selected.

Definition at line 119 of file [YSelectionWidget.cc](#).

Here is the call graph for this function:



3.114.3.31 void YSelectionWidget::setIconBasePath (const std::string & basePath)

Set this widget's base path where to look up icons. If this is a relative path, `YUI::qApp()->iconBasePath()` is prepended.


Definition at line 125 of file [YSelectionWidget.cc](#).

3.114.3.32 void YSelectionWidget::setItems (const YItemCollection & *itemCollection*) [inline]

Delete all items and add new items.

Definition at line 127 of file [YSelectionWidget.h](#).

Here is the call graph for this function:



3.114.3.33 void YSelectionWidget::setLabel (const std::string & *newLabel*) [virtual]

Change this widget's label (the caption above the item list).

Derived classes should overwrite this function, but they should call this base class function in the new implementation.

Definition at line 101 of file [YSelectionWidget.cc](#).

3.114.3.34 virtual void YSelectionWidget::setShortcutString (const std::string & *str*) [inline, virtual]

Set the string of this widget that holds the keyboard shortcut.


Reimplemented from [YWidget](#).

Reimplemented from [YWidget](#).

Reimplemented in [YDumbTab](#).

Definition at line 268 of file [YSelectionWidget.h](#).

Here is the call graph for this function:



3.114.3.35 `virtual std::string YSelectionWidget::shortcutString () const` `[inline, virtual]`

Get the string of this widget that holds the keyboard shortcut.


Reimplemented from [YWidget](#).

Reimplemented from [YWidget](#).

Reimplemented in [YDumbTab](#).

Definition at line 261 of file [YSelectionWidget.h](#).

Here is the call graph for this function:



3.114.3.36 `virtual const char* YSelectionWidget::widgetClass () const` `[inline, virtual]`

Returns a descriptive name of this widget class for logging, debugging etc.

Reimplemented from [YWidget](#).

Reimplemented in [YTable](#), [YSelectionBox](#), [YComboBox](#), [YTree](#), [YContextMenu](#), [Y-MenuButton](#), [YDumbTab](#), and [YMultiSelectionBox](#).

Definition at line 69 of file [YSelectionWidget.h](#).

The documentation for this class was generated from the following files:

- /usr/src/RPM/BUILD/libyui-3.0.10/src/YSelectionWidget.h
- /usr/src/RPM/BUILD/libyui-3.0.10/src/YSelectionWidget.cc

3.115 YSelectionWidgetPrivate Struct Reference

Public Member Functions

- **YSelectionWidgetPrivate** (const std::string &label, bool enforceSingleSelection, bool recursiveSelection)

Public Attributes

- std::string **label**
- bool **enforceSingleSelection**
- bool **recursiveSelection**
- std::string **iconBasePath**
- YItemCollection **itemCollection**

3.115.1 Detailed Description

Definition at line 35 of file [YSelectionWidget.cc](#).

The documentation for this struct was generated from the following file:

- /usr/src/RPM/BUILD/libyui-3.0.10/src/YSelectionWidget.cc

3.116 YSettings Class Reference

```
#include <YSettings.h>
```

Static Public Member Functions

- static void [setProgDir](#) (std::string directory)
- static std::string [progDir](#) ()
- static void [setIconDir](#) (std::string directory)
- static std::string [iconDir](#) ()
- static void [setThemeDir](#) (std::string directory)

- static std::string [themeDir](#) ()
- static void [setLocaleDir](#) (std::string directory)
- static std::string [localeDir](#) ()

3.116.1 Detailed Description

Settings for libyui

This singleton-object hold some presets for libyui.

Definition at line [43](#) of file [YSettings.h](#).

3.116.2 Member Function Documentation

3.116.2.1 std::string YSettings::iconDir () [static]

Returns the value of your program's icons subdir.

Definition at line [95](#) of file [YSettings.cc](#).

3.116.2.2 std::string YSettings::localeDir () [static]

Returns the value of your program's locale subdir.

Definition at line [157](#) of file [YSettings.cc](#).

3.116.2.3 std::string YSettings::progDir () [static]

Returns the value of your program's subdir.

Definition at line [71](#) of file [YSettings.cc](#).

3.116.2.4 void YSettings::setIconDir (std::string *directory*) [static]

This can be used to set a subdir ICONDIR, where your program stores a custom icons.

Once this is set, it can't be altered. If you do so although an exception will be thrown.

Definition at line [79](#) of file [YSettings.cc](#).

3.116.2.5 void YSettings::setLocaleDir (std::string *directory*) [static]

This can be used to set a subdir LOCALEDIR, where your program stores translations

Once this is set, it can't be altered. If you do so although an exception will be thrown.

Definition at line [141](#) of file [YSettings.cc](#).

3.116.2.6 void YSettings::setProgDir (std::string *directory*) [static]

This can be used to set a subdir beneath PLUGINDIR or THEMEDIR, where your program stores a custom plugin or theme.

Once this is set, it can't be altered. If you do so although an exception will be thrown.

Definition at line [55](#) of file [YSettings.cc](#).

3.116.2.7 void YSettings::setThemeDir (std::string *directory*) [static]

This can be used to set a subdir THEMEDIR, where your program stores a custom icons.

Once this is set, it can't be altered. If you do so although an exception will be thrown.

Definition at line [108](#) of file [YSettings.cc](#).

3.116.2.8 std::string YSettings::themeDir () [static]

Returns the value of your program's theme subdir.

Definition at line [124](#) of file [YSettings.cc](#).


The documentation for this class was generated from the following files:

- `/usr/src/RPM/BUILD/libyui-3.0.10/src/YSettings.h`
- `/usr/src/RPM/BUILD/libyui-3.0.10/src/YSettings.cc`


3.117 YShortcut Class Reference

```
#include <YShortcut.h>
```

Inheritance diagram for YShortcut:



Collaboration diagram for YShortcut:



Public Types

- enum { **None** = 0 }

Public Member Functions

- [YShortcut](#) ([YWidget](#) *shortcut_widget)
- virtual [~YShortcut](#) ()

- [YWidget](#) * [widget](#) () const
- const char * [widgetClass](#) () const
- bool [isButton](#) () const
- bool [isWizardButton](#) () const
- std::string [shortcutString](#) ()
- std::string [cleanShortcutString](#) ()
- char [preferred](#) ()
- char [shortcut](#) ()
- virtual void [setShortcut](#) (char newShortcut)
- void [clearShortcut](#) ()
- bool [conflict](#) ()
- void [setConflict](#) (bool newConflictState=true)
- int [distinctShortcutChars](#) ()
- bool [hasValidShortcutChar](#) ()

Static Public Member Functions

- static std::string [cleanShortcutString](#) (std::string [shortcutString](#))
- static char [shortcutMarker](#) ()
- static std::string::size_type [findShortcutPos](#) (const std::string &str, std::string::size_type start_pos=0)
- static char [findShortcut](#) (const std::string &str, std::string::size_type start_pos=0)
- static bool [isValid](#) (char c)
- static char [normalized](#) (char c)
- static std::string [getShortcutString](#) (const [YWidget](#) *widget)

Protected Member Functions

- virtual std::string [getShortcutString](#) ()

Protected Attributes

- [YWidget](#) * **[_widget](#)**
- std::string **[_shortcutString](#)**
- bool **[_shortcutStringCached](#)**
- std::string **[_cleanShortcutString](#)**
- bool **[_cleanShortcutStringCached](#)**
- int **[_preferred](#)**
- int **[_shortcut](#)**
- bool **[_conflict](#)**
- bool **[_isButton](#)**
- bool **[_isWizardButton](#)**
- int **[_distinctShortcutChars](#)**

3.117.1 Detailed Description

Helper class for shortcut management: This class holds data about the shortcut for one single widget.

Definition at line 40 of file [YShortcut.h](#).

3.117.2 Member Enumeration Documentation

3.117.2.1 anonymous enum

Marker for "no shortcut"

Definition at line 56 of file [YShortcut.h](#).

3.117.3 Constructor & Destructor Documentation

3.117.3.1 YShortcut::YShortcut (YWidget * *shortcut_widget*)

Constructor

Definition at line 41 of file [YShortcut.cc](#).

Here is the call graph for this function:



3.117.3.2 YShortcut::~YShortcut () [virtual]

Destructor

Definition at line 69 of file [YShortcut.cc](#).


3.117.4 Member Function Documentation

3.117.4.1 `std::string YShortcut::cleanShortcutString ()`

Returns the shortcut string (from the widget's shortcut property) without any "&" markers.

Definition at line 91 of file [YShortcut.cc](#).

Here is the call graph for this function:




3.117.4.2 `std::string YShortcut::cleanShortcutString (std::string shortcutString)` [static]

Static version of the above for general use: Returns the specified string without any "&" markers.

Definition at line 103 of file [YShortcut.cc](#).

Here is the call graph for this function:




3.117.4.3 `void YShortcut::clearShortcut ()`

Clear the shortcut: Override the shortcut character with nothing. This may happen if a conflict cannot be resolved.

Definition at line 173 of file [YShortcut.cc](#).

Here is the call graph for this function:



3.117.4.4 bool YShortcut::conflict () [inline]

Query the internal 'conflict' marker. This class doesn't care about that flag, it just stores it for the convenience of higher-level classes.

Definition at line 131 of file [YShortcut.h](#).

3.117.4.5 int YShortcut::distinctShortcutChars ()

Obtain the number of distinct valid shortcut characters in the shortcut string, i.e. how many different shortcuts that widget could get.

Definition at line 180 of file [YShortcut.cc](#).

Here is the call graph for this function:




3.117.4.6 char YShortcut::findShortcut (const std::string & str, std::string::size_type start_pos = 0) [static]

Static function: Find the next shortcut marker in a string, beginning at starting position start_pos.

Returns the shortcut character or 0 if none found.

Definition at line 280 of file [YShortcut.cc](#).

Here is the call graph for this function:



3.117.4.7 `std::string::size_type YShortcut::findShortcutPos (const std::string & str,
std::string::size_type start_pos = 0) [static]`

Static function: Find the next occurrence of the shortcut marker ('&') in a string, beginning at starting position `start_pos`.

Returns `string::npos` if not found or the position of the shortcut marker (not the shortcut character!) if found.

Definition at line 254 of file [YShortcut.cc](#).

Here is the call graph for this function:



3.117.4.8 `std::string YShortcut::getShortcutString (const YWidget * widget)
[static]`

Obtain a widget's shortcut property - the string that contains "&" to designate a shortcut.

Definition at line 244 of file [YShortcut.cc](#).

Here is the call graph for this function:




3.117.4.9 `std::string YShortcut::getShortcutString ()` [protected, virtual]

Obtain the the shortcut property of this shortcut's widget - the string that contains "&" to designate a shortcut.

Reimplemented in [YItemShortcut](#).

Definition at line [237](#) of file [YShortcut.cc](#).

Here is the call graph for this function:




3.117.4.10 `bool YShortcut::hasValidShortcutChar ()`

Return true if this shortcut contains any character that would be valid as a shortcut character.

Definition at line [222](#) of file [YShortcut.cc](#).

Here is the call graph for this function:



3.117.4.11 `bool YShortcut::isButton () const [inline]`

Returns 'true' if the widget that is associated with this shortcut is a button (derived from [YPushButton](#)).

Definition at line 73 of file [YShortcut.h](#).

3.117.4.12 `bool YShortcut::isValid (char c) [static]`

Returns 'true' if 'c' is a valid shortcut character, i.e. [a-zA-Z0-9], 'false' otherwise.

Definition at line 289 of file [YShortcut.cc](#).

3.117.4.13 `bool YShortcut::isWizardButton () const [inline]`

Returns 'true' if the widget that is associated with this shortcut is a wizard button (one of the navigation buttons of a wizard).

Definition at line 79 of file [YShortcut.h](#).

3.117.4.14 `char YShortcut::normalized (char c) [static]`

Return the normalized version of shortcut character 'c', i.e. a lowercase letter or a digit [a-z0-9]. Returns 0 if 'c' is invalid.


Definition at line 299 of file [YShortcut.cc](#).

3.117.4.15 `char YShortcut::preferred ()`

The preferred shortcut character, i.e. the character that had been preceded by "&" before checking / resolving conflicts began.

Definition at line 117 of file [YShortcut.cc](#).

Here is the call graph for this function:



3.117.4.16 void YShortcut::setConflict (bool *newConflictState* =true) [inline]

Set or unset the internal 'conflict' marker.

Definition at line 136 of file [YShortcut.h](#).


3.117.4.17 void YShortcut::setShortcut (char *newShortcut*) [virtual]

Set (override) the shortcut character.

Reimplemented in [YItemShortcut](#).

Definition at line 141 of file [YShortcut.cc](#).

Here is the call graph for this function:




3.117.4.18 char YShortcut::shortcut ()

The actual shortcut character.

This may be different from [preferred\(\)](#) if it is overridden.

Definition at line 129 of file [YShortcut.cc](#).

Here is the call graph for this function:



3.117.4.19 static char **YShortcut::shortcutMarker** () [inline, static]

Static function: Returns the character used for marking keyboard shortcuts.

Definition at line 154 of file [YShortcut.h](#).


3.117.4.20 std::string **YShortcut::shortcutString** ()

Returns the complete shortcut string (which may or may not contain "&"), i.e. the value of the widget's shortcut property. For PushButtons, this is the label on the button (e.g., "&Details..."), for other widgets usually the caption above it.

This value is chached, i.e. this isn't a too expensive operation.

Definition at line 75 of file [YShortcut.cc](#).

Here is the call graph for this function:



3.117.4.21 **YWidget*** **YShortcut::widget** () const [inline]

Returns the [YWidget](#) this shortcut data belong to.


Definition at line 61 of file [YShortcut.h](#).

3.117.4.22 `const char* YShortcut::widgetClass () const` `[inline]`

Returns the textual representation of the widget class of the widget this shortcut data belongs to.

Definition at line 67 of file [YShortcut.h](#).

Here is the call graph for this function:




The documentation for this class was generated from the following files:

- `/usr/src/RPM/BUILD/libyui-3.0.10/src/YShortcut.h`
- `/usr/src/RPM/BUILD/libyui-3.0.10/src/YShortcut.cc`

3.118 YShortcutManager Class Reference

```
#include <YShortcutManager.h>
```

Collaboration diagram for YShortcutManager:



Public Member Functions

- [YShortcutManager](#) ([YDialog](#) *[dialog](#))
- virtual [~YShortcutManager](#) ()
- void [checkShortcuts](#) (bool [autoResolve](#)=true)
- int [conflictCount](#) ()
- void [resolveAllConflicts](#) ()
- [YDialog](#) * [dialog](#) ()

Protected Member Functions

- void [clearShortcutList](#) ()
- void [findShortcutWidgets](#) ([YWidgetListConstIterator](#) [begin](#), [YWidgetListConstIterator](#) [end](#))
- void [resolveConflict](#) ([YShortcut](#) *[shortcut](#))
- int [findShortestWizardButton](#) (const [YShortcutList](#) &[conflictList](#))

- unsigned [findShortestWidget](#) (const YShortcutList &conflictList)

Protected Attributes

- YDialog * [_dialog](#)
- YShortcutList [_shortcutList](#)
- int [_wanted](#) [sizeof(char)<< 8]
- bool [_used](#) [sizeof(char)<< 8]
- int [_conflictCount](#)

3.118.1 Detailed Description

Helper class to manage keyboard shortcuts within one dialog and resolve keyboard shortcut conflicts.

Definition at line [38](#) of file [YShortcutManager.h](#).

3.118.2 Constructor & Destructor Documentation

3.118.2.1 YShortcutManager::YShortcutManager (YDialog * *dialog*)

Constructor.

Definition at line [44](#) of file [YShortcutManager.cc](#).

3.118.2.2 YShortcutManager::~YShortcutManager () [virtual]

Destructor

Definition at line [53](#) of file [YShortcutManager.cc](#).


Here is the call graph for this function:



3.118.3.1 void YShortcutManager::checkShortcuts (bool *autoResolve* = true)

Call `resolveAllConflicts()` if 'autoResolve' is 'true'.

Here is the call graph for this function:



Delete all members of the internal shortcut list, then empty the list.

3.118.3.3 int YShortcutManager::conflictCount () [inline]

Definition at line 63 of file YShortcutManager.h.

Returns the dialog this shortcut manager works on.


Generated on Thu Aug 8 2013 10:26:33 for libyui by Doxygen

3.118.3.5 void YShortcutManager::findShortcutWidgets (YWidgetListConstIterator *begin*, YWidgetListConstIterator *end*) [protected]

Recursively search all widgets between iterators 'begin' and 'end' (not those of any sub-dialogs!) for child widgets that could accept a keyboard shortcut and add these to `_shortcutList`.

Definition at line 379 of file [YShortcutManager.cc](#).

Here is the call graph for this function:



3.118.3.6 unsigned YShortcutManager::findShortestWidget (const YShortcutList & *conflictList*) [protected]

Find the shortest widget in 'conflictList'. Buttons get priority if they have the same number of eligible shortcut characters as another widget.

Returns the index of the shortest widget.

Definition at line 332 of file [YShortcutManager.cc](#).

3.118.3.7 int YShortcutManager::findShortestWizardButton (const YShortcutList & *conflictList*) [protected]


Find the shortest wizard button in 'conflictList', if there is any. Returns the index of that shortest wizard button or -1 if there is none.

Definition at line 307 of file [YShortcutManager.cc](#).

3.118.3.8 void YShortcutManager::resolveAllConflicts ()


Resolve shortcut conflicts. Requires [checkShortcuts\(\)](#) to be called first.

Here is the call graph for this function:



Definition at line 229 of file YShortcutManager.cc.

Here is the call graph for this function:



3.118.4 Member Data Documentation

3.118.4.1 `int YShortcutManager::_conflictCount` [protected]

Counter for shortcut conflicts

Definition at line 166 of file [YShortcutManager.h](#).

3.118.4.2 `YDialog* YShortcutManager::_dialog` [protected]

The dialog this shortcut manager works on.

Definition at line 144 of file [YShortcutManager.h](#).

3.118.4.3 `YShortcutList YShortcutManager::_shortcutList` [protected]

List of all the shortcuts in this dialog.

Definition at line 149 of file [YShortcutManager.h](#).

3.118.4.4 `bool YShortcutManager::_used[sizeof(char)<< 8]` [protected]

Flags for used shortcut characters.

Definition at line 160 of file [YShortcutManager.h](#).

3.118.4.5 `int YShortcutManager::_wanted[sizeof(char)<< 8]` [protected]

Counters for wanted shortcut characters.

Definition at line 154 of file [YShortcutManager.h](#).


The documentation for this class was generated from the following files:

- [/usr/src/RPM/BUILD/libyui-3.0.10/src/YShortcutManager.h](#)
- [/usr/src/RPM/BUILD/libyui-3.0.10/src/YShortcutManager.cc](#)

3.119 YSimpleEventHandler Class Reference

```
#include <YSimpleEventHandler.h>
```

Collaboration diagram for YSimpleEventHandler:



Public Member Functions

- [YSimpleEventHandler](#) ()
- virtual [~YSimpleEventHandler](#) ()
- void [sendEvent](#) ([YEvent](#) *event_disown)
- bool [eventPendingFor](#) ([YWidget](#) *widget) const
- [YEvent](#) * [pendingEvent](#) () const
- [YEvent](#) * [consumePendingEvent](#) ()
- void [deletePendingEventsFor](#) ([YWidget](#) *widget)
- void [clear](#) ()
- void [blockEvents](#) (bool block=true)
- void [unblockEvents](#) ()
- bool [eventsBlocked](#) () const
- void [deleteEvent](#) ([YEvent](#) *event)

Protected Attributes

- [YEvent](#) * `_pendingEvent`
- `bool _eventsBlocked`

3.119.1 Detailed Description

Simple event handler suitable for most UIs.

This event handler keeps track of one single event that gets overwritten when a new one arrives.

Definition at line 39 of file [YSimpleEventHandler.h](#).

3.119.2 Constructor & Destructor Documentation

3.119.2.1 YSimpleEventHandler::YSimpleEventHandler ()

Constructor.

Definition at line 38 of file [YSimpleEventHandler.cc](#).


3.119.2.2 YSimpleEventHandler::~YSimpleEventHandler () [virtual]

Destructor.

If there is a pending event, it is deleted here.

Definition at line 45 of file [YSimpleEventHandler.cc](#).

Here is the call graph for this function:



3.119.3 Member Function Documentation

3.119.3.1 void YSimpleEventHandler::blockEvents (bool *block* = true)

Block (or unblock) events. If events are blocked, any event sent with [sendEvent\(\)](#) from now on is ignored (and will get lost) until events are unblocked again.


Definition at line 146 of file [YSimpleEventHandler.cc](#).

3.119.3.2 void YSimpleEventHandler::clear ()

Clears any pending event (deletes the corresponding object).

Definition at line 51 of file [YSimpleEventHandler.cc](#).

Here is the call graph for this function:



3.119.3.3 YEvent * YSimpleEventHandler::consumePendingEvent ()

Consumes the pending event. Sets the internal pending event to 0. Does NOT delete the internal consuming event.

The caller assumes ownership of the object this pending event points to. In particular, he has to take care to delete that object when he is done processing it.

Returns the pending event or 0 if there is none.


Definition at line 63 of file [YSimpleEventHandler.cc](#).

3.119.3.4 void YSimpleEventHandler::deleteEvent (YEvent * event)

Delete an event. Don't call this from the outside; this is public only because of limitations of C++ .

Definition at line 157 of file [YSimpleEventHandler.cc](#).

Here is the call graph for this function:




3.119.3.5 void YSimpleEventHandler::deletePendingEventsFor (YWidget * *widget*)

Delete any pending events for the specified widget. This is useful mostly if the widget is about to be destroyed.

Definition at line 131 of file [YSimpleEventHandler.cc](#).

Here is the call graph for this function:




3.119.3.6 bool YSimpleEventHandler::eventPendingFor (YWidget * *widget*) const

Returns 'true' if there is any event pending for the specified widget.

Definition at line 120 of file [YSimpleEventHandler.cc](#).

Here is the call graph for this function:



3.119.3.7 bool YSimpleEventHandler::eventsBlocked () const [inline]

Returns 'true' if events are currently blocked.

Definition at line 121 of file [YSimpleEventHandler.h](#).

3.119.3.8 YEvent* YSimpleEventHandler::pendingEvent () const [inline]

Returns the last event that isn't processed yet or 0 if there is none.

This event handler keeps track of only one single (the last one) event.

Definition at line 80 of file [YSimpleEventHandler.h](#).

3.119.3.9 void YSimpleEventHandler::sendEvent (YEvent * event_disown)

Widget event handlers call this when an event occurred that should be the answer to a UserInput() / PollInput() (etc.) call.

The UI assumes ownership of the event object that 'event' points to, so the event MUST be created with new(). The UI is to take care to delete the event after it has been processed.


If events are blocked (see [blockEvents\(\)](#)), the event sent with this function will be ignored (but safely deleted - no memory leak).

It is an error to pass 0 for 'event'. This simple event handler keeps track of only the latest user event. If there is more than one, older events are automatically discarded. Since Events are created on the heap with the "new" operator, discarded events need to be deleted.

Events that are not discarded are deleted later (after they are processed) by the generic UI.

Definition at line 76 of file [YSimpleEventHandler.cc](#).

Here is the call graph for this function:



3.119.3.10 void YSimpleEventHandler::unblockEvents () [inline]

Unblock events previously blocked. This is just an alias for `blockEvents(false)` for better readability.

Definition at line 116 of file [YSimpleEventHandler.h](#).

Here is the call graph for this function:




The documentation for this class was generated from the following files:

- `/usr/src/RPM/BUILD/libyui-3.0.10/src/YSimpleEventHandler.h`
- `/usr/src/RPM/BUILD/libyui-3.0.10/src/YSimpleEventHandler.cc`


3.120 YSimpleInputField Class Reference

```
#include <YSimpleInputField.h>
```

Inheritance diagram for YSimpleInputField:



Collaboration diagram for YSimpleInputField:



Public Member Functions

- virtual [~YSimpleInputField](#) ()
- virtual std::string [value](#) ()=0
- virtual void [setValue](#) (const std::string &text)=0
- std::string [label](#) () const
- virtual void [setLabel](#) (const std::string &label)
- virtual bool [setProperty](#) (const std::string &propertyName, const [YPropertyValue](#) &val)
- virtual [YPropertyValue](#) [getProperty](#) (const std::string &propertyName)
- virtual const [YPropertySet](#) & [propertySet](#) ()
- virtual std::string [shortcutString](#) () const
- virtual void [setShortcutString](#) (const std::string &str)
- const char * [userInputProperty](#) ()

Protected Member Functions

- [YSimpleInputField](#) ([YWidget](#) *parent, const std::string &label)

3.120.1 Detailed Description

Abstract base class for simple input fields with a label above the field and a text value.

Definition at line 37 of file [YSimpleInputField.h](#).

3.120.2 Constructor & Destructor Documentation

3.120.2.1 YSimpleInputField::YSimpleInputField (YWidget * *parent*, const std::string & *label*) [protected]

Constructor.

Definition at line 45 of file [YSimpleInputField.cc](#).

Here is the call graph for this function:



3.120.2.2 YSimpleInputField::~~YSimpleInputField () [virtual]

Destructor.

Definition at line 56 of file [YSimpleInputField.cc](#).

3.120.3 Member Function Documentation

3.120.3.1 YPropertyValue YSimpleInputField::getProperty (const std::string & *propertyName*) [virtual]


Get a property. Reimplemented from [YWidget](#).

This method may throw YUIPropertyExceptions.

Reimplemented from [YWidget](#).

Definition at line 112 of file [YSimpleInputField.cc](#).

Here is the call graph for this function:



3.120.3.2 `std::string YSimpleInputField::label () const`

Get the label (the caption above the input field).

Definition at line 62 of file [YSimpleInputField.cc](#).

3.120.3.3 `const YPropertySet & YSimpleInputField::propertySet () [virtual]`


Return this class's property set. This also initializes the property upon the first call.

Reimplemented from [YWidget](#).

Reimplemented from [YWidget](#).

Definition at line 76 of file [YSimpleInputField.cc](#).

Here is the call graph for this function:



3.120.3.4 void YSimpleInputField::setLabel (const std::string & *label*) [virtual]

Set the label (the caption above the input field).

Derived classes are free to reimplement this, but they should call this base class method at the end of the overloaded function.

Definition at line 68 of file [YSimpleInputField.cc](#).

Here is the call graph for this function:



3.120.3.5 bool YSimpleInputField::setProperty (const std::string & *propertyName*, const YPropertyValue & *val*) [virtual]

Set a property. Reimplemented from [YWidget](#).


This function may throw YUIPropertyExceptions.

This function returns 'true' if the value was successfully set and 'false' if that value requires special handling (not in error cases: those are covered by exceptions).

Reimplemented from [YWidget](#).

Definition at line 96 of file [YSimpleInputField.cc](#).

Here is the call graph for this function:



3.120.3.6 `virtual void YSimpleInputField::setShortcutString (const std::string & str)` [inline, virtual]


Set the string of this widget that holds the keyboard shortcut.

Reimplemented from [YWidget](#).

Reimplemented from [YWidget](#).

Definition at line 121 of file [YSimpleInputField.h](#).

Here is the call graph for this function:



3.120.3.7 `virtual void YSimpleInputField::setValue (const std::string & text)` [pure virtual]

Set the current value (the text entered by the user or set from the outside) of this input field.

Derived classes are required to implement this.

3.120.3.8 `virtual std::string YSimpleInputField::shortcutString () const [inline, virtual]`


Get the string of this widget that holds the keyboard shortcut.

Reimplemented from [YWidget](#).

Reimplemented from [YWidget](#).

Definition at line 114 of file [YSimpleInputField.h](#).

Here is the call graph for this function:



3.120.3.9 `const char* YSimpleInputField::userInputProperty () [inline, virtual]`

The name of the widget property that will return user input. Inherited from [YWidget](#).

Reimplemented from [YWidget](#).

Definition at line 128 of file [YSimpleInputField.h](#).

3.120.3.10 `virtual std::string YSimpleInputField::value () [pure virtual]`

Get the current value (the text entered by the user or set from the outside) of this input field.

Derived classes are required to implement this.

The documentation for this class was generated from the following files:

- `/usr/src/RPM/BUILD/libyui-3.0.10/src/YSimpleInputField.h`
- `/usr/src/RPM/BUILD/libyui-3.0.10/src/YSimpleInputField.cc`

3.121 YSimpleInputFieldPrivate Struct Reference

Public Member Functions

- **YSimpleInputFieldPrivate** (const std::string &label)

Public Attributes

- std::string **label**

3.121.1 Detailed Description

Definition at line 33 of file [YSimpleInputField.cc](#).


The documentation for this struct was generated from the following file:

- /usr/src/RPM/BUILD/libyui-3.0.10/src/YSimpleInputField.cc


3.122 YSingleChildContainerWidget Class Reference

```
#include <YSingleChildContainerWidget.h>
```

Inheritance diagram for YSingleChildContainerWidget:



Collaboration diagram for YSingleChildContainerWidget:



Public Member Functions

- virtual `~YSingleChildContainerWidget` ()
- virtual int `preferredWidth` ()
- virtual int `preferredHeight` ()
- virtual void `setSize` (int newWidth, int newHeight)
- virtual bool `stretchable` (YUIDimension dim) const

Protected Member Functions

- `YSingleChildContainerWidget` (YWidget *parent)

3.122.1 Detailed Description

Container widget class that manages one child.

Definition at line 34 of file `YSingleChildContainerWidget.h`.


3.122.2 Constructor & Destructor Documentation

3.122.2.1 YSingleChildContainerWidget::YSingleChildContainerWidget (YWidget * parent) [protected]

Constructor.

Definition at line 29 of file `YSingleChildContainerWidget.cc`.

Here is the call graph for this function:



3.122.2.2 YSingleChildContainerWidget::~~YSingleChildContainerWidget () [virtual]

Destructor.

Definition at line 36 of file [YSingleChildContainerWidget.cc](#).

3.122.3 Member Function Documentation

3.122.3.1 int YSingleChildContainerWidget::preferredHeight () [virtual]

Preferred height of the widget.


Reimplemented from [YWidget](#).

Implements [YWidget](#).

Reimplemented in [YAlignment](#).

Definition at line 51 of file [YSingleChildContainerWidget.cc](#).

Here is the call graph for this function:



3.122.3.2 int YSingleChildContainerWidget::preferredWidth () [virtual]

Preferred width of the widget.


Reimplemented from [YWidget](#).

Implements [YWidget](#).

Reimplemented in [YAlignment](#).

Definition at line 42 of file [YSingleChildContainerWidget.cc](#).

Here is the call graph for this function:



3.122.3.3 void YSingleChildContainerWidget::setSize (int *newWidth*, int *newHeight*) [virtual]

Set the new size of the widget. In this case, the size of the single child is set.


Reimplemented from [YWidget](#).

Implements [YWidget](#).

Reimplemented in [YAlignment](#).

Definition at line 60 of file [YSingleChildContainerWidget.cc](#).

Here is the call graph for this function:



3.122.3.4 `bool YSingleChildContainerWidget::stretchable (YUIDimension dim) const`
`[virtual]`

Returns 'true' if this widget is stretchable in the specified dimension. In this case, the stretchability of the single child is returned.


Reimplemented from [YWidget](#).

Reimplemented from [YWidget](#).

Reimplemented in [YAlignment](#), and [YSquash](#).

Definition at line 68 of file [YSingleChildContainerWidget.cc](#).

Here is the call graph for this function:




The documentation for this class was generated from the following files:

- `/usr/src/RPM/BUILD/libyui-3.0.10/src/YSingleChildContainerWidget.h`
- `/usr/src/RPM/BUILD/libyui-3.0.10/src/YSingleChildContainerWidget.cc`


3.123 YSingleChildManager< T > Class Template Reference

```
#include <YChildrenManager.h>
```


Inheritance diagram for YSingleChildManager< T >:



Collaboration diagram for YSingleChildManager< T >:



Public Member Functions

- **YSingleChildManager** (T *containerParent)
- virtual void **add** (T *child)
- void **replace** (T *newChild)

3.123.1 Detailed Description

```
template<class T>class YSingleChildManager< T >
```

Children manager that can handle one single child (rejecting any more). Useful for [YAlignment](#), [YFrame](#) etc.

Definition at line 161 of file [YChildrenManager.h](#).

3.123.2 Member Function Documentation

3.123.2.1 `template<class T > virtual void YSingleChildManager< T >::add (T * child)`
`[inline, virtual]`

Add a new child.


Reimplemented from [YChildrenManager](#).

This will throw a [YUITooManyChildrenException](#) if there already is a child.

Reimplemented from [YChildrenManager< T >](#).

Definition at line 177 of file [YChildrenManager.h](#).

Here is the call graph for this function:



3.123.2.2 `template<class T > void YSingleChildManager< T >::replace (T * newChild)`
`[inline]`

Replace the previous child (if any) with a new one.

Definition at line 188 of file [YChildrenManager.h](#).


The documentation for this class was generated from the following file:

- `/usr/src/RPM/BUILD/libyui-3.0.10/src/YChildrenManager.h`


3.124 YSlider Class Reference

```
#include <YSlider.h>
```

Inheritance diagram for YSlider:



Collaboration diagram for YSlider:



Public Member Functions

- virtual [~YSlider](#) ()
- virtual const char * [widgetClass](#) () const

Protected Member Functions

- [YSlider](#) ([YWidget](#) *[parent](#), const std::string &[label](#), int [minValue](#), int [maxValue](#))

3.124.1 Detailed Description

Slider: Input widget for an integer value between a minimum and a maximum value. Very similar to IntField in semantics, but with a graphical slider that can be dragged to the desired value. It also contains an IntField to allow entering the value directly.

Don't confuse this widget with ProgressBar: ProgressBar is output-only.

This is an optional widget, i.e. not all UIs support it.

Definition at line 44 of file [YSlider.h](#).

3.124.2 Constructor & Destructor Documentation

3.124.2.1 YSlider::YSlider (YWidget * parent, const std::string & label, int minValue, int maxValue) [protected]


Constructor.

Create a Slider with 'label' as the caption, and the specified minimum and maximum values.

Note that YWidgetFactory::createSlider() also has an 'initialValue' parameter that is not used here (because the current value is not stored in this base class, but in the derived class).

Definition at line 43 of file [YSlider.cc](#).

Here is the call graph for this function:



3.124.2.2 YSlider::~~YSlider () [virtual]

Destructor.

Definition at line 57 of file [YSlider.cc](#).

3.124.3 Member Function Documentation

3.124.3.1 virtual const char* YSlider::widgetClass () const [inline, virtual]

Returns a descriptive name of this widget class for logging, debugging etc.

Reimplemented from [YIntField](#).

Definition at line 72 of file [YSlider.h](#).

The documentation for this class was generated from the following files:

- `/usr/src/RPM/BUILD/libyui-3.0.10/src/YSlider.h`
- `/usr/src/RPM/BUILD/libyui-3.0.10/src/YSlider.cc`

3.125 YSliderPrivate Struct Reference

Public Attributes

- `bool dummy`

3.125.1 Detailed Description

Definition at line [32](#) of file [YSlider.cc](#).


The documentation for this struct was generated from the following file:

- `/usr/src/RPM/BUILD/libyui-3.0.10/src/YSlider.cc`


3.126 YSpacing Class Reference

```
#include <YSpacing.h>
```

Inheritance diagram for YSpacing:



Collaboration diagram for YSpacing:



Public Member Functions

- [YSpacing](#) ([YWidget](#) **parent*, YUIDimension *dim*, bool *stretchable*=false, YLayoutSize_t *layoutUnits*=0.0)
- virtual [~YSpacing](#) ()
- virtual const char * [widgetClass](#) () const
- YUIDimension [dimension](#) () const
- int [size](#) () const
- int [size](#) (YUIDimension *dim*) const
- virtual int [preferredWidth](#) ()
- virtual int [preferredHeight](#) ()

3.126.1 Detailed Description

HSpacing, VSpacing, HStretch, VStretch

Definition at line 37 of file [YSpacing.h](#).

3.126.2 Constructor & Destructor Documentation

3.126.2.1 **YSpacing::YSpacing** ([YWidget](#) * *parent*, YUIDimension *dim*, bool *stretchable* = false, YLayoutSize_t *layoutUnits* = 0.0)

Constructor.

A Spacing/Stretch widget works only in one dimension ('dim') at the same time. But it can be stretchable and have a size at the same time, in which case the specified

size acts very much like a minimal size - but not exactly, since [YLayoutBox](#) will reduce Spacings first before other widgets have to be resized below their preferred size.

'layoutUnits' is specified in abstract UI units where a main window (800x600 pixels in the Qt UI) corresponds to a 80x25 window.

Definition at line [45](#) of file [YSpacing.cc](#).

Here is the call graph for this function:



3.126.2.2 YSpacing::~YSpacing () [virtual]

Destructor.

Definition at line [55](#) of file [YSpacing.cc](#).

3.126.3 Member Function Documentation

3.126.3.1 YUIDimension YSpacing::dimension () const

Return the primary dimension of this Spacing/Stretch, i.e. the dimension in which it uses space or stretches.

Definition at line [62](#) of file [YSpacing.cc](#).

3.126.3.2 int YSpacing::preferredHeight () [virtual]

Preferred height of the widget.

Reimplemented from [YWidget](#).

Implements [YWidget](#).

Definition at line [90](#) of file [YSpacing.cc](#).

3.126.3.3 int YSpacing::preferredWidth () [virtual]

Preferred width of the widget.

Reimplemented from [YWidget](#).

Implements [YWidget](#).

Definition at line 81 of file [YSpacing.cc](#).

3.126.3.4 int YSpacing::size () const

Return the size in the primary dimension.

This is the device dependent size (pixels or character cells), not the abstract UI layout unit from the constructor.

Definition at line 68 of file [YSpacing.cc](#).

3.126.3.5 int YSpacing::size (YUIDimension *dim*) const

Return the size in the specified dimension.

This is the device dependent size (pixels or character cells), not the abstract UI layout unit from the constructor.

Definition at line 74 of file [YSpacing.cc](#).

3.126.3.6 const char * YSpacing::widgetClass () const [virtual]

Return a descriptive name of this widget class for logging, debugging etc.

Reimplemented from [YWidget](#).

Definition at line 100 of file [YSpacing.cc](#).

Here is the call graph for this function:



The documentation for this class was generated from the following files:

- /usr/src/RPM/BUILD/libyui-3.0.10/src/YSpacing.h
- /usr/src/RPM/BUILD/libyui-3.0.10/src/YSpacing.cc

3.127 YSpacingPrivate Struct Reference

Public Member Functions

- **YSpacingPrivate** (YUIDimension dim, int size)

Public Attributes

- YUIDimension **dim**
- int **size**

3.127.1 Detailed Description

Definition at line 31 of file [YSpacing.cc](#).


The documentation for this struct was generated from the following file:

- /usr/src/RPM/BUILD/libyui-3.0.10/src/YSpacing.cc


3.128 YSquash Class Reference

```
#include <YSquash.h>
```

Inheritance diagram for YSquash:



Collaboration diagram for YSquash:



Public Member Functions

- virtual [~YSquash](#) ()
- virtual const char * [widgetClass](#) () const
- bool [horSquash](#) () const
- bool [vertSquash](#) () const
- bool [stretchable](#) (YUIDimension dim) const

Protected Member Functions

- [YSquash](#) (YWidget *parent, bool [horSquash](#), bool [vertSquash](#))

3.128.1 Detailed Description

HSquash, VSquash HVSquash:

Squash is a widget that "squashes" its one child during layout, i.e., it reduces it in size down to its preferred size. It may squash vertically, horizontally or in both dimensions.

Definition at line 41 of file [YSquash.h](#).

3.128.2 Constructor & Destructor Documentation

3.128.2.1 [YSquash::YSquash](#) (YWidget * parent, bool *horSquash*, bool *vertSquash*) [protected]

Constructor.

Squashes horizontally if 'horSquash' is 'true', vertically if 'vertSquash' is 'true'.

Definition at line 44 of file [YSquash.cc](#).

3.128.2.2 [YSquash::~~YSquash](#) () [virtual]

Destructor.

Definition at line 52 of file [YSquash.cc](#).

3.128.3 Member Function Documentation

3.128.3.1 bool [YSquash::horSquash](#) () const

Returns 'true' if this widget squashes horizontally.

Definition at line 58 of file [YSquash.cc](#).


3.128.3.2 `bool YSquash::stretchable (YUIDimension dim) const` [virtual]

In a squashed dimension the widget NOT stretchable. In an unsquashed dimension the widget is stretchable if the child is stretchable.

Reimplemented from [YSingleChildContainerWidget](#).

Definition at line 70 of file [YSquash.cc](#).

Here is the call graph for this function:



3.128.3.3 `bool YSquash::vertSquash () const`

Returns 'true' if this widget squashes vertically.

Definition at line 64 of file [YSquash.cc](#).

3.128.3.4 `const char * YSquash::widgetClass () const` [virtual]

Returns a descriptive name of this widget class for logging, debugging etc.

Reimplemented from [YWidget](#).


Definition at line 80 of file [YSquash.cc](#).

The documentation for this class was generated from the following files:

- `/usr/src/RPM/BUILD/libyui-3.0.10/src/YSquash.h`
- `/usr/src/RPM/BUILD/libyui-3.0.10/src/YSquash.cc`

3.129 YSquashPrivate Struct Reference

Collaboration diagram for YSquashPrivate:



Public Member Functions

- [YSquashPrivate](#) (bool horSquash, bool vertSquash)

Public Attributes

- [YBothDim](#)< bool > **squash**

3.129.1 Detailed Description

Definition at line 29 of file [YSquash.cc](#).

3.129.2 Constructor & Destructor Documentation

3.129.2.1 **YSquashPrivate::YSquashPrivate** (bool *horSquash*, bool *vertSquash*)
[inline]

Constructor.

Definition at line 34 of file [YSquash.cc](#).


The documentation for this struct was generated from the following file:

- /usr/src/RPM/BUILD/libyui-3.0.10/src/YSquash.cc


3.130 YStringTree Class Reference

```
#include <YStringTree.h>
```

Inheritance diagram for YStringTree:



Collaboration diagram for YStringTree:



Public Member Functions

- `YStringTree` (const char *[textdomain](#))
- virtual `~YStringTree` ()
- `YStringTreelItem` * [addBranch](#) (const std::string &content, char delimiter=0, `YStringTreelItem` *parent=0)
- std::string [origPath](#) (const `YStringTreelItem` *item, char delimiter, bool startWithDelimiter=true)
- std::string [translatedPath](#) (const `YStringTreelItem` *item, char delimiter, bool startWithDelimiter=true)
- `YTransText` [path](#) (const `YStringTreelItem` *item, char delimiter, bool startWithDelimiter=true)
- void [logTree](#) ()
- `YStringTreelItem` * [root](#) () const
- const char * [textdomain](#) () const
- void [setTextdomain](#) (const char *domain)
- std::string [translate](#) (const std::string &orig)

Protected Member Functions

- `std::string completePath` (const [YStringTreeItem](#) *item, bool translated, char delimiter, bool startWithDelimiter)
- `void logBranch` ([YStringTreeItem](#) *branch, std::string indentation)

Protected Attributes

- [YStringTreeItem](#) * `_root`
- `std::string _textdomain`

3.130.1 Detailed Description

Abstract base class for filter views with hierarchical filter criteria - e.g., RPM group tags, MIME types.

Definition at line 41 of file [YStringTree.h](#).

3.130.2 Constructor & Destructor Documentation

3.130.2.1 `YStringTree::YStringTree (const char * textdomain)`

Constructor.

'textdomain' specifies the gettext textdomain to use to translate pathname components as new branches are added.

NOTE: This will NOT change the gettext environment in any way - the tree uses `dgettext()` internally. The caller is responsible to bind that textdomain to a message catalog (`bindtextdomain()` etc.).

Definition at line 32 of file [YStringTree.cc](#).

Here is the call graph for this function:



3.130.2.2 YStringTree::~~YStringTree () [virtual]

Destructor.

Definition at line 40 of file [YStringTree.cc](#).

3.130.3 Member Function Documentation

3.130.3.1 YStringTreeItem * YStringTree::addBranch (const std::string & *content*, char *delimiter* = 0, YStringTreeItem * *parent* = 0)

Add a unique new branch with text content '*content*' to the tree, beginning at '*parent*' (root if *parent* == 0). This content can be a path specification delimited with character '*delimiter*' (if not 0), i.e. this method will split '*content*' up into path components and insert tree items for each level as appropriate. Leading delimiters will be ignored. If '*delimiter*' is 0, '*content*' is not split but used 'as is'. Items are automatically sorted alphabetically. Pathname components are automatically translated using the textdomain specified in the constructor.

Returns the tree node for this branch - either newly created or the existing one.

Example: `addBranch("/usr/local/bin", '/') addBranch("/usr/lib", '/')`

`"usr" "lib" "local" "bin"`

Definition at line 48 of file [YStringTree.cc](#).

Here is the call graph for this function:




3.130.3.2 std::string YStringTree::completePath (const YStringTreeItem * *item*, bool *translated*, char *delimiter*, bool *startWithDelimiter*) [protected]

Construct a complete original or translated path for the specified tree item. '*startWithDelimiter*' specifies whether or not the complete path should start with the delimiter character.

Definition at line 127 of file [YStringTree.cc](#).

Here is the call graph for this function:




3.130.3.3 void YStringTree::logBranch (YStringTreeltem * *branch*, std::string *indentation*) [protected]

Debugging - dump one branch of the tree into the log file.

Definition at line 195 of file [YStringTree.cc](#).

Here is the call graph for this function:




3.130.3.4 void YStringTree::logTree ()

Debugging - dump the tree into the log file.

Definition at line 186 of file [YStringTree.cc](#).

Here is the call graph for this function:




3.130.3.5 std::string YStringTree::origPath (const YStringTreeltem * item, char delimiter, bool startWithDelimiter = true) [inline]

Construct a complete original path for the specified tree item. 'startWithDelimiter' specifies whether or not the complete path should start with the delimiter character.

Definition at line 97 of file [YStringTree.h](#).

Here is the call graph for this function:




3.130.3.6 **YTransText YStringTree::path** (*const YStringTreeItem * item*, *char delimiter*,
bool startWithDelimiter = true)

Construct a complete path (both original and translated) for the specified tree item. 'startWithDelimiter' specifies whether or not the complete path should start with the delimiter character.

Note: [origPath\(\)](#) or [translatedPath\(\)](#) are much cheaper if only one version (original or translated) is required.

Definition at line 158 of file [YStringTree.cc](#).

Here is the call graph for this function:



3.130.3.7 YStringTreeItem* YStringTree::root () const [inline]

Returns the root of the filter view tree. Note: In most cases, the root item itself will not contain any useful information. Consider it the handle for the entire tree, not an actual data element.

Definition at line 139 of file [YStringTree.h](#).

3.130.3.8 void YStringTree::setTextdomain (const char * *domain*) [inline]

Set the textdomain used internally for translation of pathname components.

NOTE: This will NOT change the gettext environment in any way - the tree uses dgettext() internally. The caller is responsible to bind that textdomain to a message catalog (bindtextdomain() etc.).

Definition at line 157 of file [YStringTree.h](#).

3.130.3.9 const char* YStringTree::textdomain () const [inline]

Returns the textdomain used internally for translation of pathname components.

Definition at line 146 of file [YStringTree.h](#).

3.130.3.10 std::string YStringTree::translate (const std::string & *orig*)

Translate message '*orig*' using the internal textdomain. Returns the translated text or the original if there is no translation.


Definition at line 118 of file [YStringTree.cc](#).

3.130.3.11 std::string YStringTree::translatedPath (const YStringTreeItem * *item*, char *delimiter*, bool *startWithDelimiter* = true) [inline]

Construct a complete original path for the specified tree item. '*startWithDelimiter*' specifies whether or not the complete path should start with the delimiter character.

Definition at line 108 of file [YStringTree.h](#).

Here is the call graph for this function:




The documentation for this class was generated from the following files:

- /usr/src/RPM/BUILD/libyui-3.0.10/src/YStringTree.h
- /usr/src/RPM/BUILD/libyui-3.0.10/src/YStringTree.cc


3.131 YStringWidgetID Class Reference

```
#include <YWidgetID.h>
```

Inheritance diagram for YStringWidgetID:



Collaboration diagram for YStringWidgetID:



Public Member Functions

- [YStringWidgetID](#) (const std::string &[value](#))
- virtual [~YStringWidgetID](#) ()
- virtual bool [isEqual](#) (YWidgetID *otherID) const
- virtual std::string [toString](#) () const
- std::string [value](#) () const
- const std::string & [valueConstRef](#) () const

3.131.1 Detailed Description

Simple widget ID class based on strings.

Definition at line [72](#) of file [YWidgetID.h](#).

3.131.2 Constructor & Destructor Documentation

3.131.2.1 YStringWidgetID::YStringWidgetID (const std::string & [value](#))

Constructor.

Definition at line [31](#) of file [YWidgetID.cc](#).

3.131.2.2 YStringWidgetID::~YStringWidgetID () [[virtual](#)]

Destructor.

Definition at line 38 of file [YWidgetID.cc](#).

3.131.3 Member Function Documentation

3.131.3.1 `bool YStringWidgetID::isEqual (YWidgetID * otherID) const` [virtual]

Check if this ID is equal to another.

Reimplemented from [YWidgetID](#).

Implements [YWidgetID](#).

Definition at line 45 of file [YWidgetID.cc](#).

Here is the call graph for this function:



3.131.3.2 `std::string YStringWidgetID::toString () const` [virtual]

Convert the ID value to string. Used for logging and debugging.

Reimplemented from [YWidgetID](#).

Implements [YWidgetID](#).

Definition at line 58 of file [YWidgetID.cc](#).

3.131.3.3 `std::string YStringWidgetID::value () const`

Return the ID value.

Definition at line 65 of file [YWidgetID.cc](#).

3.131.3.4 `const std::string & YStringWidgetID::valueConstRef () const`

Return the ID value as a const ref.

Definition at line 72 of file [YWidgetID.cc](#).


The documentation for this class was generated from the following files:

- /usr/src/RPM/BUILD/libyui-3.0.10/src/YWidgetID.h
- /usr/src/RPM/BUILD/libyui-3.0.10/src/YWidgetID.cc


3.132 YTable Class Reference

```
#include <YTable.h>
```

Inheritance diagram for YTable:



Collaboration diagram for YTable:



Public Member Functions

- virtual [~YTable](#) ()
- virtual const char * [widgetClass](#) () const
- int [columns](#) () const
- bool [hasColumn](#) (int column) const
- std::string [header](#) (int column) const
- YAlignmentType [alignment](#) (int column) const
- bool [immediateMode](#) () const
- void [setImmediateMode](#) (bool [immediateMode](#)=true)
- bool [keepSorting](#) () const
- virtual void [setKeepSorting](#) (bool [keepSorting](#))
- bool [hasMultiSelection](#) () const
- virtual void [cellChanged](#) (const [YTableCell](#) *cell)=0
- virtual bool [setProperty](#) (const std::string &propertyName, const [YPropertyValue](#) &val)
- virtual [YPropertyValue](#) [getProperty](#) (const std::string &propertyName)
- virtual const [YPropertySet](#) & [propertySet](#) ()
- const char * [userInputProperty](#) ()

Protected Member Functions

- [YTable](#) ([YWidget](#) *parent, [YTableHeader](#) *header, bool multiSelection)
- void [setTableHeader](#) ([YTableHeader](#) *newHeader)

3.132.1 Detailed Description

Table: Selection list with multiple columns. The user can select exactly one row (with all its columns) from that list. Each cell (each column within each row) has a label text and an optional icon (*).

This widget is similar to [SelectionBox](#), but it has several columns for each item (each row). If just one column is desired, consider using [SelectionBox](#) instead.

Note: This is not something like a spread sheet, and it doesn't pretend or want to be. Actions are performed on rows, not on individual cells (columns within one row).

(*) Not all UIs (in particular not text-based UIs) support displaying icons, so an icon should never be an exclusive means to display any kind of information.

Definition at line 55 of file [YTable.h](#).

3.132.2 Constructor & Destructor Documentation

3.132.2.1 [YTable::YTable](#) ([YWidget](#) * parent, [YTableHeader](#) * header, bool multiSelection) [protected]


Constructor.

'header' describes the table's headers: Number of columns, column headings, and column alignment. The widget assumes ownership of this object and will delete it when appropriate. The header cannot be changed after creating the widget.

'multiSelection' indicates whether or not the user can select multiple items at the same time (e.g., with shift-click or ctrl-click). This can only be set in the constructor.

Definition at line 50 of file [YTable.cc](#).

Here is the call graph for this function:



3.132.2.2 YTable::~YTable() [virtual]

Destructor.

Definition at line 64 of file [YTable.cc](#).

3.132.3 Member Function Documentation

3.132.3.1 YAlignmentType YTable::alignment (int *column*) const

Return the alignment for the specified column.

Definition at line 106 of file [YTable.cc](#).

Here is the call graph for this function:



3.132.3.2 `virtual void YTable::cellChanged (const YTableCell * cell)` [pure virtual]

Notification that a cell (its text and/or its icon) was changed from the outside. - Applications are required to call this whenever a table cell is changed after adding the corresponding table item (the row) to the table widget.

Derived classes are required to implement this and update the display accordingly.

Note that the position of this cell can be retrieved with `cell->column()` and `cell->item-Index()`.

3.132.3.3 `int YTable::columns () const`

Return the number of columns of this table.

Definition at line 85 of file [YTable.cc](#).

Here is the call graph for this function:



3.132.3.4 `YPropertyValue YTable::getProperty (const std::string & propertyName)` [virtual]


Get a property. Reimplemented from [YWidget](#).

This method may throw `YUIPropertyExceptions`.

Reimplemented from [YWidget](#).

Definition at line 207 of file [YTable.cc](#).

Here is the call graph for this function:



3.132.3.5 `bool YTable::hasColumn (int column) const`

Return 'true' if this table has a column no. 'column' (counting from 0 on).

Definition at line 92 of file [YTable.cc](#).

Here is the call graph for this function:




3.132.3.6 `bool YTable::hasMultiSelection () const`

Return 'true' if the user can select multiple items at the same time (e.g., with shift-click or ctrl-click).

Definition at line 144 of file [YTable.cc](#).

Here is the call graph for this function:



3.132.3.7 `std::string YTable::header (int column) const`

Return the header text for the specified column.

Definition at line 99 of file [YTable.cc](#).

Here is the call graph for this function:



3.132.3.8 `bool YTable::immediateMode () const`

Deliver even more events than with [notify\(\)](#) set.

With "notify" alone, a table widget sends an `ActivatedEvent` when the user double-clicks an item or presses the "space" key on it. It does not send an event when the user just sends another item.

With "immediate", it also sends a `SelectionChangedEvent` when the user selects another item. "immediate" implicitly includes "notify".

Definition at line 113 of file [YTable.cc](#).

3.132.3.9 bool YTable::keepSorting () const

Return 'true' if the sort order is to be kept in item insertion order, i.e. if sorting the table by clicking on a column header should be disabled.

Definition at line 130 of file [YTable.cc](#).

3.132.3.10 const YPropertySet & YTable::propertySet () [virtual]

Return this class's property set. This also initializes the property upon the first call.

Reimplemented from [YWidget](#).

Reimplemented from [YWidget](#).

Definition at line 151 of file [YTable.cc](#).

Here is the call graph for this function:




3.132.3.11 void YTable::setImmediateMode (bool *immediateMode* = true)

Set `immediateMode()` on or off.

Definition at line 120 of file [YTable.cc](#).

Here is the call graph for this function:



3.132.3.12 void YTable::setKeepSorting (bool *keepSorting*) [virtual]

Switch between sorting by item insertion order (`keepSorting: true`) or allowing the user to sort by an arbitrary column (by clicking on the column header).

Derived classes can overwrite this function, but they should call this base class function in the new implementation.

Definition at line 137 of file [YTable.cc](#).

Here is the call graph for this function:



3.132.3.13 bool YTable::setProperty (const std::string & *propertyName*, const YPropertyValue & *val*) [virtual]

Set a property. Reimplemented from [YWidget](#).


This function may throw `YUIPropertyExceptions`.

This function returns 'true' if the value was successfully set and 'false' if that value requires special handling (not in error cases: those are covered by exceptions).

Reimplemented from [YWidget](#).

Definition at line 186 of file [YTable.cc](#).

Here is the call graph for this function:




3.132.3.14 void YTable::setTableHeader (YTableHeader * newHeader) [protected]

Exchange the previous table header with a new one. This will delete the old [YTableHeader](#) object.

If the new header has a different number of columns than the old one, all items will implicitly be deleted.

Definition at line 72 of file [YTable.cc](#).

Here is the call graph for this function:



3.132.3.15 const char* YTable::userInputProperty() [inline, virtual]

The name of the widget property that will return user input. Inherited from [YWidget](#).

Reimplemented from [YWidget](#).

Definition at line 194 of file [YTable.h](#).

```
3.132.3.16 virtual const char* YTable::widgetClass ( ) const [inline,
virtual]
```

Return a descriptive name of this widget class for logging, debugging etc.

Reimplemented from [YSelectionWidget](#).

Definition at line 83 of file [YTable.h](#).

The documentation for this class was generated from the following files:

- /usr/src/RPM/BUILD/libyui-3.0.10/src/YTable.h
- /usr/src/RPM/BUILD/libyui-3.0.10/src/YTable.cc

3.133 YTableCell Class Reference

```
#include <YTableItem.h>
```

Public Member Functions

- [YTableCell](#) (const std::string &label, const std::string &iconName="")
- [YTableCell](#) ([YTableItem](#) *parent, int column, const std::string &label, const std::string &iconName="")
- virtual ~[YTableCell](#) ()
- std::string label () const
- void setLabel (const std::string &newLabel)
- std::string iconName () const
- bool hasIconName () const
- void setIconName (const std::string &newIconName)
- [YTableItem](#) * parent () const
- int column () const
- int itemIndex () const
- void reparent ([YTableItem](#) *parent, int column)

3.133.1 Detailed Description

One cell (one column in one row) of a [YTableItem](#). Each cell has a label (a user visible text) and optionally an icon (*).

Note that cells don't have individual IDs; they have just an index. The first cell in an item is cell(0). In an ideal world, each [YTableItem](#) would have exactly as many cells as there

are columns in the [YTable](#), but these classes make no such assumptions. A [YTableItem](#) might have any number of cells, including none.

The [YTable](#) widget is free to ignore any excess cells if there are more than the [YTable](#) widget has columns. If there are less cells than the table has columns, the nonexistent cells will be treated as empty.

(*) Not all UIs can handle icons. UIs that can't handle them will simply ignore any icons specified for YTableCells. Thus, applications should either check the UI capabilities if it can handle icons or use icons only as an additional visual cue that still has a text counterpart (so the user can still make sense of the table content when no icons are visible).

Definition at line 212 of file [YTableItem.h](#).

3.133.2 Constructor & Destructor Documentation

3.133.2.1 `YTableCell::YTableCell(const std::string & label, const std::string & iconName = "") [inline]`

Constructor with label and optional icon name for cells that don't have a parent item yet (that will be added to a parent later with `setParent()`).

Definition at line 220 of file [YTableItem.h](#).

3.133.2.2 `YTableCell::YTableCell(YTableItem * parent, int column, const std::string & label, const std::string & iconName = "") [inline]`

Constructor with parent, column no., label and optional icon name for cells that are created with a parent.

Definition at line 231 of file [YTableItem.h](#).

3.133.2.3 `virtual YTableCell::~YTableCell() [inline, virtual]`

Destructor. Not strictly needed inside this class, but useful for derived classes. Since this is the only virtual method of this class, the cost of this is a vtable for this class and a pointer to the vtable in each instance.

Definition at line 247 of file [YTableItem.h](#).

3.133.3 Member Function Documentation

3.133.3.1 `int YTableCell::column () const` `[inline]`

Return this cell's column no. (counting from 0on) or -1 if it doesn't have a parent yet.

Definition at line 292 of file [YTableItem.h](#).

3.133.3.2 `bool YTableCell::hasIconName () const` `[inline]`

Return 'true' if this cell has an icon name.

Definition at line 272 of file [YTableItem.h](#).

3.133.3.3 `std::string YTableCell::iconName () const` `[inline]`

Return this cell's icon name.


Definition at line 267 of file [YTableItem.h](#).

3.133.3.4 `int YTableCell::itemIndex () const` `[inline]`

Convenience function: Return this cell's parent item's index within its table widget or -1 if there is no parent item or no parent table.

Definition at line 298 of file [YTableItem.h](#).

Here is the call graph for this function:

**3.133.3.5** `std::string YTableCell::label () const` `[inline]`

Return this cells's label. This is what the user sees in a dialog, so this will usually be a translated text.

Definition at line 253 of file [YTableItem.h](#).

3.133.3.6 YTableItem* YTableCell::parent () const [inline]

Return this cell's parent item or 0 if it doesn't have one yet.

Definition at line 286 of file YTableItem.h.


3.133.3.7 void YTableCell::reparent (YTableItem * parent, int column)

Set this cell's parent item and column no. if it doesn't have a parent yet.

This method will throw an exception if the cell already has a parent.

Definition at line 171 of file YTableItem.cc.

Here is the call graph for this function:

**3.133.3.8** void YTableCell::setIconName (const std::string & newIconName) [inline]

Set this cell's icon name.

If this is called after the corresponding table item (table row) is added to the table widget, call YTable::cellChanged() to notify the table widget about the fact. Only then will the display be updated.

Definition at line 281 of file YTableItem.h.

3.133.3.9 void YTableCell::setLabel (const std::string & newLabel) [inline]

Set this cell's label.

If this is called after the corresponding table item (table row) is added to the table widget, call [YTable::cellChanged\(\)](#) to notify the table widget about the fact. Only then will the display be updated.

Definition at line [262](#) of file [YTableItem.h](#).

The documentation for this class was generated from the following files:

- [/usr/src/RPM/BUILD/libyui-3.0.10/src/YTableItem.h](#)
- [/usr/src/RPM/BUILD/libyui-3.0.10/src/YTableItem.cc](#)

3.134 YTableHeader Class Reference

```
#include <YTableHeader.h>
```

Public Member Functions

- [YTableHeader](#) ()
- virtual [~YTableHeader](#) ()
- void [addColumn](#) (const std::string &[header](#), YAlignmentType [alignment](#)=YAlign-Begin)
- int [columns](#) () const
- bool [hasColumn](#) (int column) const
- std::string [header](#) (int column) const
- YAlignmentType [alignment](#) (int column) const

3.134.1 Detailed Description

Helper class for [YTable](#) for table column properties:

- number of columns
- header for each column
- alignment for each column

Definition at line [43](#) of file [YTableHeader.h](#).

3.134.2 Constructor & Destructor Documentation

3.134.2.1 YTableHeader::YTableHeader ()

Constructor.

Definition at line 48 of file [YTableHeader.cc](#).

3.134.2.2 YTableHeader::~YTableHeader () [virtual]

Destructor.

Definition at line 55 of file [YTableHeader.cc](#).

3.134.3 Member Function Documentation

3.134.3.1 void YTableHeader::addColumn (const std::string & *header*, YAlignmentType *alignment* = YAlignBegin)

Add a column with the specified column header text and alignment.

Definition at line 62 of file [YTableHeader.cc](#).

3.134.3.2 YAlignmentType YTableHeader::alignment (int *column*) const

Return the alignment for the specified column.

Definition at line 94 of file [YTableHeader.cc](#).

3.134.3.3 int YTableHeader::columns () const

Return the number of columns.

Definition at line 70 of file [YTableHeader.cc](#).

3.134.3.4 bool YTableHeader::hasColumn (int *column*) const

Return 'true' if this table header has a column no. 'column' (counting from 0 on).

Definition at line 77 of file [YTableHeader.cc](#).

3.134.3.5 std::string YTableHeader::header (int *column*) const

Return the header text for the specified column.

Definition at line 84 of file [YTableHeader.cc](#).

The documentation for this class was generated from the following files:

- [/usr/src/RPM/BUILD/libyui-3.0.10/src/YTableHeader.h](#)
- [/usr/src/RPM/BUILD/libyui-3.0.10/src/YTableHeader.cc](#)

3.135 YTableHeaderPrivate Struct Reference

Public Attributes

- `std::vector< std::string > headers`
- `std::vector< YAlignmentType > alignments`

3.135.1 Detailed Description

Definition at line 36 of file [YTableHeader.cc](#).


The documentation for this struct was generated from the following file:

- [/usr/src/RPM/BUILD/libyui-3.0.10/src/YTableHeader.cc](#)


3.136 YTableItem Class Reference

```
#include <YTableItem.h>
```

Inheritance diagram for YTableItem:



Collaboration diagram for YTableItem:



Public Member Functions

- [YTableItem](#) ()
- [YTableItem](#) (const std::string &label_0, const std::string &label_1=std::string(), const std::string &label_2=std::string(), const std::string &label_3=std::string(), const std::string &label_4=std::string(), const std::string &label_5=std::string(), const std::string &label_6=std::string(), const std::string &label_7=std::string(), const std::string &label_8=std::string(), const std::string &label_9=std::string())
- virtual [~YTableItem](#) ()
- void [addCell](#) ([YTableCell](#) *cell_disown)
- void [addCell](#) (const std::string &label, const std::string &iconName=std::string())
- void [deleteCells](#) ()
- [YTableCellIterator](#) [cellsBegin](#) ()
- [YTableCellConstIterator](#) [cellsBegin](#) () const
- [YTableCellIterator](#) [cellsEnd](#) ()
- [YTableCellConstIterator](#) [cellsEnd](#) () const
- const [YTableCell](#) * [cell](#) (int [index](#)) const
- [YTableCell](#) * [cell](#) (int [index](#))
- int [cellCount](#) () const
- bool [hasCell](#) (int [index](#)) const
- std::string [label](#) (int [index](#)) const
- std::string [iconName](#) (int [index](#)) const
- bool [hasIconName](#) (int [index](#)) const
- std::string [label](#) () const

3.136.1 Detailed Description

Item class for [YTable](#) items. Each [YTableItem](#) corresponds to one row in a [YTable](#).

A [YTableItem](#) might have any number of cells (columns within this row), including none. The [YTable](#) widget is free to ignore any excess cells if there are more than the [YTable](#) widget has columns. The [YTable](#) widget is to treat nonexistent cells like empty ones.

Note that while [YTable](#) items and their cells can be manipulated through pointers, their visual representation on screen might be updated only upon calling certain methods of the [YTable](#) widget. See the [YTable](#) reference for details.

Definition at line 52 of file [YTableItem.h](#).

3.136.2 Constructor & Destructor Documentation

3.136.2.1 [YTableItem::YTableItem](#) ()

Default constructor. Use [addCell\(\)](#) to give it any content.

Definition at line 29 of file [YTableItem.cc](#).

3.136.2.2 [YTableItem::YTableItem](#) (const std::string & *label_0*, const std::string & *label_1* = std::string(), const std::string & *label_2* = std::string(), const std::string & *label_3* = std::string(), const std::string & *label_4* = std::string(), const std::string & *label_5* = std::string(), const std::string & *label_6* = std::string(), const std::string & *label_7* = std::string(), const std::string & *label_8* = std::string(), const std::string & *label_9* = std::string())

Convenience constructor for table items without any icons.

This will create up to 10 (0..9) cells. Empty cells for empty labels at the end of the labels are not created, but empty cells in between are.


```
new YTableItem( "one", "two", "", "", "five" );
```

will create an item with 5 cells:

```
cell[0] ==> "one" cell[1] ==> "two" cell[2] ==> "" cell[3] ==> "" cell[4] ==> "five"
```

Definition at line 36 of file [YTableItem.cc](#).

Here is the call graph for this function:




3.136.2.3 YTableItem::~~YTableItem () [virtual]

Destructor.

This will delete all cells.

Definition at line 82 of file [YTableItem.cc](#).

Here is the call graph for this function:



3.136.3 Member Function Documentation


3.136.3.1 void YTableItem::addCell (YTableCell * cell_disown)

Add a cell. This item will assume ownership over the cell and delete it when appropriate (when the table is destroyed or when table items are replaced), at which time the pointer will become invalid.

Cells can still be changed after they (and the item they belong to) are added, but in that case, [YTable::cellChanged\(\)](#) needs to be called to update the table display accordingly.

Definition at line 105 of file [YTableItem.cc](#).

Here is the call graph for this function:




3.136.3.2 `void YTableItem::addCell(const std::string & label, const std::string & iconName
= std::string())`

Create a new cell and add it (even if both 'label' and 'iconName' are empty).

Definition at line 115 of file [YTableItem.cc](#).

Here is the call graph for this function:




3.136.3.3 `const YTableCell * YTableItem::cell(int index) const`

Return the cell at the specified index (counting from 0 on) or 0 if there is none.

Definition at line 132 of file [YTableItem.cc](#).

Here is the call graph for this function:



3.136.3.4 `int YTableItem::cellCount () const` [inline]

Return the number of cells this item has.

Definition at line 139 of file [YTableItem.h](#).

3.136.3.5 `YTableCellIterator YTableItem::cellsBegin ()` [inline]

Return an iterator that points to the first cell of this item.

Definition at line 120 of file [YTableItem.h](#).

3.136.3.6 `YTableCellIterator YTableItem::cellsEnd ()` [inline]

Return an iterator that points after the last cell of this item.


Definition at line 126 of file [YTableItem.h](#).

3.136.3.7 `void YTableItem::deleteCells ()`

Delete all cells.

Definition at line 89 of file [YTableItem.cc](#).

Here is the call graph for this function:



3.136.3.8 `bool YTableItem::hasCell (int index) const`

Return 'true' if this item has a cell with the specified index (counting from 0 on), 'false' otherwise.


Definition at line 125 of file [YTableItem.cc](#).

3.136.3.9 `bool YTableItem::hasIconName (int index) const`

Return 'true' if there is a cell with the specified index that has an icon name.

Definition at line 162 of file [YTableItem.cc](#).

Here is the call graph for this function:




3.136.3.10 `std::string YTableItem::iconName (int index) const`

Return the icon name of cell no. 'index' (counting from 0 on) or an empty string if there is no cell with that index.

Definition at line 155 of file [YTableItem.cc](#).


Here is the call graph for this function:

**3.136.3.11** `std::string YTableItem::label (int index) const`

Return the label of cell no. 'index' (counting from 0 on) or an empty string if there is no cell with that index.

Definition at line 148 of file [YTableItem.cc](#).

Here is the call graph for this function:



3.136.3.12 `std::string YTableItem::label () const` `[inline]`

Just for debugging.

Reimplemented from [YItem](#).

Definition at line 168 of file [YTableItem.h](#).

Here is the call graph for this function:




The documentation for this class was generated from the following files:

- `/usr/src/RPM/BUILD/libyui-3.0.10/src/YTableItem.h`
- `/usr/src/RPM/BUILD/libyui-3.0.10/src/YTableItem.cc`

3.137 YTablePrivate Struct Reference

Collaboration diagram for YTablePrivate:



Public Member Functions

- **YTablePrivate** ([YTableHeader](#) *header)

Public Attributes

- [YTableHeader](#) * **header**
- bool **keepSorting**
- bool **immediateMode**

3.137.1 Detailed Description

Definition at line 33 of file [YTable.cc](#).


The documentation for this struct was generated from the following file:

- /usr/src/RPM/BUILD/libyui-3.0.10/src/YTable.cc


3.138 YTimeField Class Reference

```
#include <YTimeField.h>
```

Inheritance diagram for YTimeField:



Collaboration diagram for YTimeField:



Public Member Functions

- virtual [~YTimeField](#) ()
- virtual const char * [widgetClass](#) () const

Protected Member Functions

- [YTimeField](#) ([YWidget](#) *[parent](#), const std::string &[label](#))

3.138.1 Detailed Description

Input field for entering a time in "hh:mm:ss" format.

Derived classes are required to implement: [value\(\)](#) [setValue\(\)](#) See [YSimpleInputField.h](#) for details.

Definition at line [41](#) of file [YTimeField.h](#).

3.138.2 Constructor & Destructor Documentation

3.138.2.1 `YTimeField::YTimeField (YWidget * parent, const std::string & label)`
[protected]

Constructor.

Definition at line 43 of file [YTimeField.cc](#).

3.138.2.2 `YTimeField::~~YTimeField ()` [virtual]

Destructor.

Definition at line 51 of file [YTimeField.cc](#).

3.138.3 Member Function Documentation

3.138.3.1 `virtual const char* YTimeField::widgetClass () const` [inline, virtual]

Returns a descriptive name of this widget class for logging, debugging etc.

Reimplemented from [YWidget](#).

Definition at line 59 of file [YTimeField.h](#).

The documentation for this class was generated from the following files:

- [/usr/src/RPM/BUILD/libyui-3.0.10/src/YTimeField.h](#)
- [/usr/src/RPM/BUILD/libyui-3.0.10/src/YTimeField.cc](#)

3.139 YTimeFieldPrivate Struct Reference

Public Attributes

- bool **dummy**

3.139.1 Detailed Description

Definition at line 32 of file [YTimeField.cc](#).


The documentation for this struct was generated from the following file:

- [/usr/src/RPM/BUILD/libyui-3.0.10/src/YTimeField.cc](#)


3.140 YTimeoutEvent Class Reference

```
#include <YEvent.h>
```

Inheritance diagram for YTimeoutEvent:



Collaboration diagram for YTimeoutEvent:



Protected Member Functions

- virtual [~YTimeoutEvent](#) ()

3.140.1 Detailed Description

Event to be returned upon timeout (i.e. no event available in the specified timeout)

Definition at line 346 of file [YEvent.h](#).

3.140.2 Constructor & Destructor Documentation

3.140.2.1 `virtual YTimeoutEvent::~YTimeoutEvent () [inline, protected, virtual]`

Protected destructor - events can only be deleted via [YDialog::deleteEvent\(\)](#). The associated dialog will take care of this event and delete it when appropriate.


Definition at line 358 of file [YEvent.h](#).

The documentation for this class was generated from the following file:


- [/usr/src/RPM/BUILD/libyui-3.0.10/src/YEvent.h](#)

3.141 YTimezoneSelector Class Reference

Inheritance diagram for YTimezoneSelector:



Collaboration diagram for YTimezoneSelector:



Public Member Functions

- virtual [~YTimezoneSelector](#) ()
- virtual const char * [widgetClass](#) () const
- virtual bool [setProperty](#) (const std::string &propertyName, const [YPropertyValue](#) &val)
- virtual [YPropertyValue](#) [getProperty](#) (const std::string &propertyName)
- virtual const [YPropertySet](#) & [propertySet](#) ()
- virtual std::string [currentZone](#) () const =0
- virtual void [setCurrentZone](#) (const std::string &zone, bool zoom)=0

Protected Member Functions

- [YTimezoneSelector](#) ([YWidget](#) *parent, const std::string &pixmap, const std::map< std::string, std::string > &timezones)

3.141.1 Detailed Description

Definition at line [35](#) of file [YTimezoneSelector.h](#).

3.141.2 Constructor & Destructor Documentation

3.141.2.1 YTimezoneSelector::YTimezoneSelector (YWidget * *parent*, const std::string & *pixmap*, const std::map< std::string, std::string > & *timezones*)
[protected]

Constructor. This widget isn't doing much on it's own, but the UI may have some fancy use.

- pixmap should be a png or jpg of a world map with centered 0°0° and the timezones are a map between zone.tab entry and user visible string.

The widget is only displaying timezones/cities in that map

Definition at line 41 of file [YTimezoneSelector.cc](#).

3.141.2.2 YTimezoneSelector::~YTimezoneSelector () [virtual]

Destructor.

Definition at line 49 of file [YTimezoneSelector.cc](#).

3.141.3 Member Function Documentation

3.141.3.1 virtual std::string YTimezoneSelector::currentZone () const [pure virtual]

subclasses have to implement this to return value

3.141.3.2 YPropertyValue YTimezoneSelector::getProperty (const std::string & *propertyName*) [virtual]


Get a property. Reimplemented from [YWidget](#).

This method may throw YUIPropertyExceptions.

Reimplemented from [YWidget](#).

Definition at line 91 of file [YTimezoneSelector.cc](#).

Here is the call graph for this function:



3.141.3.3 `const YPropertySet & YTimezoneSelector::propertySet ()` [virtual]


Return this class's property set. This also initializes the property upon the first call.

Reimplemented from [YWidget](#).

Reimplemented from [YWidget](#).

Definition at line 56 of file [YTimezoneSelector.cc](#).

Here is the call graph for this function:



3.141.3.4 `virtual void YTimezoneSelector::setCurrentZone (const std::string & zone, bool zoom)` [pure virtual]

subclasses have to implement this to set value

3.141.3.5 `bool YTimezoneSelector::setProperty (const std::string & propertyName, const YPropertyValue & val)` [virtual]

Set a property. Reimplemented from [YWidget](#).


This function may throw YUIPropertyExceptions.

This function returns 'true' if the value was successfully set and 'false' if that value requires special handling (not in error cases: those are covered by exceptions).

Reimplemented from [YWidget](#).

Definition at line 72 of file [YTimezoneSelector.cc](#).

Here is the call graph for this function:



3.141.3.6 `virtual const char* YTimezoneSelector::widgetClass () const` `[inline, virtual]`

Return a descriptive name of this widget class for logging, debugging etc.

Reimplemented from [YWidget](#).

Definition at line 60 of file [YTimezoneSelector.h](#).

The documentation for this class was generated from the following files:

- `/usr/src/RPM/BUILD/libyui-3.0.10/src/YTimezoneSelector.h`
- `/usr/src/RPM/BUILD/libyui-3.0.10/src/YTimezoneSelector.cc`

3.142 YTimezoneSelectorPrivate Class Reference

3.142.1 Detailed Description

Definition at line 33 of file [YTimezoneSelector.cc](#).

The documentation for this class was generated from the following file:

- /usr/src/RPM/BUILD/libyui-3.0.10/src/YTimezoneSelector.cc

3.143 YTransText Class Reference

```
#include <YTransText.h>
```

Public Member Functions

- [YTransText](#) (const std::string &[orig](#), const std::string &[translation](#))
- [YTransText](#) (const std::string &[orig](#))
- [YTransText](#) (const [YTransText](#) &src)
- [YTransText](#) & [operator=](#) (const [YTransText](#) &src)
- const std::string & [orig](#) () const
- const std::string & [translation](#) () const
- const std::string & [trans](#) () const
- void [setOrig](#) (const std::string &newOrig)
- void [setTranslation](#) (const std::string &newTrans)
- bool [operator<](#) (const [YTransText](#) &other) const
- bool [operator>](#) (const [YTransText](#) &other) const
- bool [operator==](#) (const [YTransText](#) &other) const

3.143.1 Detailed Description

Helper class for translated strings: Stores a message in the original (untranslated) version along with the translation into the current locale.

Definition at line 36 of file [YTransText.h](#).

3.143.2 Constructor & Destructor Documentation

3.143.2.1 [YTransText::YTransText](#) (const std::string & *orig*, const std::string & *translation*) [\[inline\]](#)

Constructor with both original and translated message.

Definition at line 43 of file [YTransText.h](#).

3.143.2.2 [YTransText::YTransText](#) (const std::string & *orig*) [\[inline\]](#)

Constructor that automatically translates the original message.


Definition at line 50 of file [YTransText.h](#).

3.143.2.3 YTransText::YTransText (const YTransText & *src*) [inline]

Copy constructor.

Definition at line 58 of file [YTransText.h](#).

Here is the call graph for this function:



3.143.3 Member Function Documentation

3.143.3.1 bool YTransText::operator< (const YTransText & *other*) const [inline]

operator< : Compares translations.

Definition at line 105 of file [YTransText.h](#).

Here is the call graph for this function:




3.143.3.2 YTransText& YTransText::operator= (const YTransText & *src*) [inline]

Assignment operator.

Definition at line 67 of file [YTransText.h](#).

Here is the call graph for this function:



3.143.3.3 `bool YTransText::operator==(const YTransText & other) const` `[inline]`

`operator==` : Compares translations.

Definition at line 117 of file [YTransText.h](#).

Here is the call graph for this function:



3.143.3.4 `bool YTransText::operator> (const YTransText & other) const` `[inline]`

`operator>` : Compares translations.

Definition at line 111 of file [YTransText.h](#).

Here is the call graph for this function:



3.143.3.5 `const std::string& YTransText::orig () const` [inline]

Return the original message.

Definition at line 78 of file [YTransText.h](#).

3.143.3.6 `void YTransText::setOrig (const std::string & newOrig)` [inline]

Set the original message. Does not touch the translation, so make sure you change both if you want to keep them synchronized!

Definition at line 95 of file [YTransText.h](#).

3.143.3.7 `void YTransText::setTranslation (const std::string & newTrans)` [inline]

Set the translation.

Definition at line 100 of file [YTransText.h](#).

3.143.3.8 `const std::string& YTransText::trans () const` [inline]

Return the translation. (alias, just as a shortcut)

Definition at line 89 of file [YTransText.h](#).

3.143.3.9 `const std::string& YTransText::translation () const` [inline]

Return the translation.

Definition at line 83 of file [YTransText.h](#).


The documentation for this class was generated from the following file:

- /usr/src/RPM/BUILD/libyui-3.0.10/src/YTransText.h


3.144 YTree Class Reference

```
#include <YTree.h>
```

Inheritance diagram for YTree:



Collaboration diagram for YTree:



Public Member Functions

- virtual [~YTree](#) ()
- virtual const char * [widgetClass](#) () const
- virtual void [rebuildTree](#) ()=0
- virtual void [addItem](#) (const YItemCollection &itemCollection)
- bool [immediateMode](#) () const
- void [setImmediateMode](#) (bool on=true)
- virtual bool [setProperty](#) (const std::string &propertyName, const [YPropertyValue](#) &val)
- virtual [YPropertyValue](#) [getProperty](#) (const std::string &propertyName)
- virtual const [YPropertySet](#) & [propertySet](#) ()
- const char * [userInputProperty](#) ()
- bool [hasMultiSelection](#) () const
- virtual [YTreeItem](#) * [currentItem](#) ()=0

Protected Member Functions

- [YTree](#) ([YWidget](#) *parent, const std::string &label, bool multiSelection, bool recursiveSelection)

3.144.1 Detailed Description

Tree: List box that displays a (scrollable) list of hierarchical items from which the user can select exactly one. Each item has a label text and an optional icon (*).

This is very similar to `SelectionBox`, but each item can have subitems that can be open (expanded) or closed (collapsed).

The tree widget also has a caption label that is displayed above the tree. The hotkey displayed in that caption label will move the keyboard focus into the tree item list.

(*) Not all UIs (in particular not text-based UIs) support displaying icons, so an icon should never be an exclusive means to display any kind of information.

'multiSelection' indicates whether or not the user can select multiple items at the same time. This can only be set in the constructor.

Definition at line 56 of file [YTree.h](#).


3.144.2 Constructor & Destructor Documentation

3.144.2.1 `YTree::YTree (YWidget * parent, const std::string & label, bool multiSelection, bool recursiveSelection)` [protected]

Constructor.

Definition at line 44 of file [YTree.cc](#).

Here is the call graph for this function:



3.144.2.2 `YTree::~YTree ()` [virtual]

Destructor.

Definition at line 57 of file [YTree.cc](#).

3.144.3 Member Function Documentation

3.144.3.1 void YTree::addItems (const YItemCollection & *itemCollection*) [virtual]

Add multiple items. For some UIs, this can be more efficient than calling [addItem\(\)](#) multiple times. This function also automatically calls [rebuildTree\(\)](#) at the end.

Derived classes can overwrite this function, but they should call this base class function at the end of the new implementation.

Reimplemented from [YSelectionWidget](#).

Reimplemented from [YSelectionWidget](#).

Definition at line 81 of file [YTree.cc](#).

Here is the call graph for this function:



3.144.3.2 virtual YTreeItem* YTree::currentItem () [pure virtual]

Return the the item that currently has the keyboard focus or 0 if no item currently has the keyboard focus.

Notice that for a MultiSelectionBox the current item is not necessarily selected, i.e., its check box may or may not be checked.

Derived classes are required to implement this function.

3.144.3.3 YPropertyValue YTree::getProperty (const std::string & *propertyName*) [virtual]


Get a property. Reimplemented from [YWidget](#).

This method may throw YUIPropertyExceptions.

Reimplemented from [YWidget](#).

Definition at line 146 of file [YTree.cc](#).

Here is the call graph for this function:




3.144.3.4 `bool YTree::hasMultiSelection () const`

Return 'true' if the user can select multiple items at the same time

Definition at line 165 of file [YTree.cc](#).

Here is the call graph for this function:



3.144.3.5 `bool YTree::immediateMode () const`

Deliver even more events than with [notify\(\)](#) set.

For [YTree](#), this is relevant mostly for the NCurses UI:

In graphical UIs like the Qt UI, the user can use the mouse to select an item in a tree. With [notify\(\)](#) set, this will send an event right away (i.e., it will make `UserInput` and related return, while normally it would only return when the user clicks a `PushButton`).

In the NCurses UI, there is no mouse, so the user has to use the cursor keys to move to the item he wants to select. In [immediateMode\(\)](#), every cursor key press will make the

tree send an event. Without [immediateMode\(\)](#), the NCTree will wait until the user hits the [Return] key until an event is sent. Depending on what the application does upon each selection box event, [immediateMode\(\)](#) might make the application less responsive.

Definition at line 64 of file [YTree.cc](#).

3.144.3.6 `const YPropertySet & YTree::propertySet () [virtual]`

Return this class's property set. This also initializes the property upon the first call.

Reimplemented from [YWidget](#).

Reimplemented from [YWidget](#).

Definition at line 89 of file [YTree.cc](#).

Here is the call graph for this function:



3.144.3.7 `virtual void YTree::rebuildTree () [pure virtual]`

Rebuild the displayed tree from the internally stored YTreeItems.

The application should call this (once) after all items have been added with [addItem\(\)](#). [YTree::addItem\(\)](#) calls this automatically.

Derived classes are required to implement this.

3.144.3.8 `void YTree::setImmediateMode (bool on = true)`

Set [immediateMode\(\)](#) on or off.

Definition at line 71 of file [YTree.cc](#).

Here is the call graph for this function:



3.144.3.9 `bool YTree::setProperty (const std::string & propertyName, const YPropertyValue & val)` [virtual]

Set a property. Reimplemented from [YWidget](#).


This function may throw YUIPropertyExceptions.

This function returns 'true' if the value was successfully set and 'false' if that value requires special handling (not in error cases: those are covered by exceptions).

Reimplemented from [YWidget](#).

Definition at line 123 of file [YTree.cc](#).

Here is the call graph for this function:



3.144.3.10 `const char* YTree::userInputProperty () [inline, virtual]`

The name of the widget property that will return user input. Inherited from [YWidget](#).

Reimplemented from [YWidget](#).

Definition at line 156 of file [YTree.h](#).

3.144.3.11 `virtual const char* YTree::widgetClass () const [inline, virtual]`

Returns a descriptive name of this widget class for logging, debugging etc.

Reimplemented from [YSelectionWidget](#).

Definition at line 74 of file [YTree.h](#).


The documentation for this class was generated from the following files:

- `/usr/src/RPM/BUILD/libyui-3.0.10/src/YTree.h`
- `/usr/src/RPM/BUILD/libyui-3.0.10/src/YTree.cc`


3.145 YTreeItem Class Reference

```
#include <YTreeItem.h>
```

Inheritance diagram for YTreeItem:



Collaboration diagram for YTreelItem:



Public Member Functions

- [YTreelItem](#) (const std::string &label, bool isOpen=false)
- **YTreelItem** (const std::string &label, const std::string &iconName, bool isOpen=false)
- [YTreelItem](#) ([YTreelItem](#) *parent, const std::string &label, bool isOpen=false)
- **YTreelItem** ([YTreelItem](#) *parent, const std::string &label, const std::string &iconName, bool isOpen=false)
- virtual [~YTreelItem](#) ()
- virtual bool [hasChildren](#) () const
- virtual YItemIterator [childrenBegin](#) ()
- virtual YItemConstIterator **childrenBegin** () const
- virtual YItemIterator [childrenEnd](#) ()
- virtual YItemConstIterator **childrenEnd** () const
- virtual void [addChild](#) ([YItem](#) *item_disown)
- virtual void [deleteChildren](#) ()
- bool [isOpen](#) () const
- void [setOpen](#) (bool open)
- virtual [YTreelItem](#) * [parent](#) () const

3.145.1 Detailed Description

Item class for tree items.

This class implements children management.

Definition at line 37 of file [YTreelItem.h](#).

3.145.2 Constructor & Destructor Documentation

3.145.2.1 YTreeItem::YTreeItem (const std::string & *label*, bool *isOpen* = *false*)

Constructors for toplevel items.

Definition at line 28 of file [YTreeItem.cc](#).

3.145.2.2 YTreeItem::YTreeItem (YTreeItem * *parent*, const std::string & *label*, bool *isOpen* = *false*)

Constructors for items that have a parent item.

They will automatically register this item with the parent item. The parent assumes ownership of this item and will delete it in its (the parent's) destructor.

Definition at line 47 of file [YTreeItem.cc](#).

Here is the call graph for this function:



3.145.2.3 YTreeItem::~YTreeItem () [virtual]

Destructor.

This will delete all children.

Definition at line 72 of file [YTreeItem.cc](#).

Here is the call graph for this function:



3.145.3 Member Function Documentation

3.145.3.1 `void YTreeItem::addChild (YItem * item_disown)` [virtual]

Add a child item to this item.

Note that the constructors that accept a parent pointer will automatically add themselves to their parent, so applications will normally not have to call this function.

Definition at line 78 of file [YTreeItem.cc](#).

3.145.3.2 `virtual YItemIterator YTreeItem::childrenBegin ()` [inline, virtual]

Return an iterator that points to the first child item of this item.

Reimplemented from [YItem](#).

Reimplemented from [YItem](#).

Definition at line 85 of file [YTreeItem.h](#).

3.145.3.3 `virtual YItemIterator YTreeItem::childrenEnd ()` [inline, virtual]

Return an iterator that points after the last child item of this item.

Reimplemented from [YItem](#).

Reimplemented from [YItem](#).


Definition at line 93 of file [YTreeItem.h](#).

3.145.3.4 `void YTreeItem::deleteChildren ()` [virtual]

Delete all child items.

Definition at line 84 of file [YTreeItem.cc](#).

Here is the call graph for this function:



3.145.3.5 `virtual bool YTreeItem::hasChildren () const` `[inline, virtual]`

Return 'true' if this item has any child items.

Reimplemented from [YItem](#).

Reimplemented from [YItem](#).

Definition at line 78 of file [YTreeItem.h](#).

3.145.3.6 `bool YTreeItem::isOpen () const`

Return 'true' if this tree item should be displayed open (with its children visible) by default.

Notice that this will always return 'false' for tree items without children.

Definition at line 99 of file [YTreeItem.cc](#).

Here is the call graph for this function:



3.145.3.7 `virtual YTreeWidgetItem* YTreeWidgetItem::parent () const` `[inline, virtual]`

Returns this item's parent item or 0 if it is a toplevel item.

Reimplemented from [YItem](#).

Reimplemented from [YItem](#).

Reimplemented in [YMenuItem](#).

Definition at line 129 of file [YTreeWidgetItem.h](#).

3.145.3.8 `void YTreeWidgetItem::setOpen (bool open)`

Change the 'isOpen' flag.

Definition at line 105 of file [YTreeWidgetItem.cc](#).

The documentation for this class was generated from the following files:

- `/usr/src/RPM/BUILD/libyui-3.0.10/src/YTreeWidgetItem.h`
- `/usr/src/RPM/BUILD/libyui-3.0.10/src/YTreeWidgetItem.cc`

3.146 YTreePrivate Struct Reference

Public Attributes

- `bool immediateMode`

3.146.1 Detailed Description

Definition at line 34 of file [YTree.cc](#).


The documentation for this struct was generated from the following file:

- `/usr/src/RPM/BUILD/libyui-3.0.10/src/YTree.cc`

3.147 YUI Class Reference

```
#include <YUI.h>
```

Collaboration diagram for YUI:



Public Member Functions

- virtual `~YUI` ()
- void `shutdownThreads` ()
- virtual void `blockEvents` (bool block=true)
- void `unblockEvents` ()
- virtual bool `eventsBlocked` () const
- virtual void `deleteNotify` (YWidget *widget)
- void `topmostConstructorHasFinished` ()
- bool `runningWithThreads` () const
- void `uiThreadMainLoop` ()
- YBuiltinCaller * `builtinCaller` () const
- void `setBuiltinCaller` (YBuiltinCaller *caller)
- virtual YEvent * `runPkgSelection` (YWidget *packageSelector)=0

Static Public Member Functions

- static YUI * `ui` ()
- static YWidgetFactory * `widgetFactory` ()
- static YOptionalWidgetFactory * `optionalWidgetFactory` ()
- static YApplication * `app` ()
- static YApplication * `application` ()
- static YApplication * `yApp` ()
- static void `ensureUICreated` ()

Protected Member Functions

- [YUI](#) (bool withThreads)
- virtual [YWidgetFactory](#) * [createWidgetFactory](#) ()=0
- virtual [YOptionalWidgetFactory](#) * [createOptionalWidgetFactory](#) ()=0
- virtual [YApplication](#) * [createApplication](#) ()=0
- virtual void [idleLoop](#) (int fd_ycp)=0
- void [terminateUIThread](#) ()
- void [createUIThread](#) ()
- virtual void [uiThreadDestructor](#) ()
- void [signalUIThread](#) ()
- bool [waitForUIThread](#) ()
- void [signalYCPThread](#) ()
- bool [waitForYCPThread](#) ()
- void [setButtonOrderFromEnvironment](#) ()

Protected Attributes

- bool [_withThreads](#)
- pthread_t [_uiThread](#)
- [YBuiltinCaller](#) * [_builtinCaller](#)
- int [pipe_to_ui](#) [2]
- int [pipe_from_ui](#) [2]
- bool [_terminate_ui_thread](#)
- bool [_eventsBlocked](#)

Friends

- class **YUIFunction**
- class **YUITerminator**
- void * **start_ui_thread** (void *ui_int)

3.147.1 Detailed Description

Abstract base class of a libYUI user interface.

Definition at line 48 of file [YUI.h](#).

3.147.2 Constructor & Destructor Documentation

3.147.2.1 YUI::YUI(bool *withThreads*) [protected]

Constructor.


Definition at line 69 of file [YUI.cc](#).

3.147.2.2 YUI::~YUI() [virtual]

Destructor.

Definition at line 82 of file [YUI.cc](#).

Here is the call graph for this function:



3.147.3 Member Function Documentation


3.147.3.1 YApplication * YUI::app() [static]

Return the global YApplication object.

This will create the YApplication upon the first call and return a pointer to the one and only (singleton) YApplication upon each subsequent call. This may throw exceptions if the YApplication cannot be created.

Definition at line 156 of file [YUI.cc](#).

Here is the call graph for this function:




3.147.3.2 static YApplication* YUI::application () [inline, static]

Aliases for [YUI::app\(\)](#)

Definition at line 112 of file [YUI.h](#).

Here is the call graph for this function:



3.147.3.3 virtual void YUI::blockEvents (bool *block* = true) [inline, virtual]

Block (or unblock) events. If events are blocked, any event sent should be ignored until events are unblocked again.

This default implementation keeps track of a simple internal flag that can be queried with [eventsBlocked\(\)](#), so if you reimplement [blockEvents\(\)](#), be sure to reimplement [eventsBlocked\(\)](#) as well.

Definition at line 161 of file [YUI.h](#).

3.147.3.4 YBuiltinCaller* YUI::builtinCaller () const [inline]

Return the transparent inter-thread communication. This will return 0 until set from the outside.

Definition at line 212 of file [YUI.h](#).

3.147.3.5 `virtual YApplication* YUI::createApplication () [protected, pure virtual]`

Create the YApplication object that provides global methods.

Derived classes are required to implement this.

3.147.3.6 `virtual YOptionalWidgetFactory* YUI::createOptionalWidgetFactory () [protected, pure virtual]`

Create the widget factory that provides all the createXY() methods for optional ("special") widgets and the corresponding hasXYWidget() methods.

Derived classes are required to implement this.

3.147.3.7 `void YUI::createUIThread () [protected]`

Creates and launches the ui thread.

Definition at line 235 of file [YUI.cc](#).

3.147.3.8 `virtual YWidgetFactory* YUI::createWidgetFactory () [protected, pure virtual]`

Create the widget factory that provides all the createXY() methods for standard (mandatory, i.e. non-optional) widgets.

Derived classes are required to implement this.

3.147.3.9 `virtual void YUI::deleteNotify (YWidget * widget) [inline, virtual]`

Notification that a widget is being deleted. This is called from the [YWidget](#) destructor.

Derived classes can implement this for any clean-up actions such as deleting any events that might be pending for that widget.

Definition at line 185 of file [YUI.h](#).


3.147.3.10 `void YUI::ensureUICreated () [static]`

Make sure there is a UI (with a UI plug-in) created.

If there is none yet, this will use all-default parameters to load a UI plug-in and create a UI (without threads).

Definition at line 170 of file [YUI.cc](#).

Here is the call graph for this function:



3.147.3.11 `virtual bool YUI::eventsBlocked () const` `[inline, virtual]`

Returns 'true' if events are currently blocked.

Reimplement this if you reimplement [blockEvents\(\)](#).

Definition at line 176 of file [YUI.h](#).

3.147.3.12 `virtual void YUI::idleLoop (int fd_ycp)` `[protected, pure virtual]`

This virtual method is called when threads are activated in case the execution control is currently on the side of the module. This means that no `UserInput()` or `PollInput()` is pending. The module just does some work. The UI <-> module protocol is in the "UI waits for the next command" state. The UI can override this method when it wants to react to user input or other external events such as repaint requests from the X server.

'fd_ycp' file descriptor that should be used to determine when to leave the idle loop. As soon as it is readable, the loop must be left. In order to avoid polling you can combine it with other ui-specific fds and do a common `select()` call.

3.147.3.13 `YOptionalWidgetFactory * YUI::optionalWidgetFactory ()` `[static]`

Return the widget factory that provides all the `createXY()` methods for optional ("special") widgets and the corresponding `hasXYWidget()` methods.

This will create the factory upon the first call and return a pointer to the one and only (singleton) factory upon each subsequent call. This may throw exceptions if the factory cannot be created.

Definition at line 141 of file [YUI.cc](#).

Here is the call graph for this function:



3.147.3.14 `bool YUI::runningWithThreads () const [inline]`

Running with threads?

Definition at line 196 of file [YUI.h](#).

3.147.3.15 `virtual YEvent* YUI::runPkgSelection (YWidget * packageSelector) [pure virtual]`

UI-specific runPkgSelection method.

Derived classes are required to implement this.

The packageSelector's dialog will take care of the event and delete it when appropriate. The returned pointer is valid until the next call to `YDialog::userInput()`, `YDialog::pollInput()`, or [YUI::runPkgSelection\(\)](#) or until the dialog with the packageSelector is destroyed.

3.147.3.16 `void YUI::setBuiltinCaller (YBuiltinCaller * caller) [inline]`

Set the transparent inter-thread communication. Built-ins are only really called if there is a valid [YBuiltinCaller](#) set.

Definition at line 218 of file [YUI.h](#).

3.147.3.17 `void YUI::setButtonOrderFromEnvironment () [protected]`


Set the button order (in [YButtonBox](#) widgets) from environment variables:

`$Y2_BUTTON_ORDER="KDE" $Y2_BUTTON_ORDER="Gnome"`

(all case insensitive)

Definition at line 386 of file [YUI.cc](#).

Here is the call graph for this function:




3.147.3.18 void YUI::shutdownThreads ()

Shut down multithreading. This needs to be called before the destructor if the UI was created with threads. If the UI was created without threads, this does nothing.

Definition at line 259 of file [YUI.cc](#).

Here is the call graph for this function:



3.147.3.19 void YUI::signalUIThread () [protected]

Signals the ui thread by sending one byte through the pipe to it.

Definition at line 273 of file [YUI.cc](#).

3.147.3.20 void YUI::signalYCPThread () [protected]

Signals the ycp thread by sending one byte through the pipe to it.


Definition at line 313 of file YUI.cc.

3.147.3.21 void YUI::terminateUIThread () [protected]

Tells the ui thread that it should terminate and waits until it does so.

Definition at line 246 of file YUI.cc.


Here is the call graph for this function:

**3.147.3.22 void YUI::topmostConstructorHasFinished ()**

Must be called after the constructor of the Qt/NCurses ui is ready. Starts the ui thread.

Definition at line 182 of file YUI.cc.

Here is the call graph for this function:




3.147.3.23 `YUI * YUI::ui ()` [static]

Access the global UI.

Definition at line 118 of file [YUI.cc](#).

Here is the call graph for this function:



3.147.3.24 `void YUI::uiThreadDestructor ()` [protected, virtual]

Destructor for the UI thread. This will be called as the last thing the UI thread does.

Derived classes can overwrite this. In most cases it makes sense to call this base class method in the new implementation.

Definition at line 111 of file [YUI.cc](#).

Here is the call graph for this function:




3.147.3.25 `void YUI::uiThreadMainLoop ()`

This method implements the UI thread in case it is existing. The loop consists of calling `idleLoop`, getting the next command from the `YCPUComponent`, evaluating it, which possibly involves calling `userInput()` or `pollInput()` and writes the answer back to the other thread where the request came from.

Definition at line 353 of file [YUI.cc](#).

Here is the call graph for this function:



3.147.3.26 void YUI::unblockEvents () [inline]

Unblock events previously blocked. This is just an alias for `blockEvents(false)` for better readability.

Note: This method is intentionally not virtual.

Definition at line 169 of file [YUI.h](#).

Here is the call graph for this function:



3.147.3.27 bool YUI::waitForUIThread () [protected]

Waits for the ui thread to send one byte through the pipe to the ycp thread and reads this byte from the pipe.

Definition at line 285 of file [YUI.cc](#).

3.147.3.28 bool YUI::waitForYCPThread () [protected]

Waits for the ycp thread to send one byte through the pipe to the ycp thread and reads this byte from the pipe.

Definition at line 325 of file [YUI.cc](#).


3.147.3.29 YWidgetFactory * YUI::widgetFactory () [static]

Return the widget factory that provides all the createXY() methods for standard (mandatory, i.e. non-optional) widgets.

This will create the factory upon the first call and return a pointer to the one and only (singleton) factory upon each subsequent call. This may throw exceptions if the factory cannot be created.

Definition at line 126 of file [YUI.cc](#).

Here is the call graph for this function:



3.147.4 Member Data Documentation

3.147.4.1 YBuiltinCaller* YUI::_builtinCaller [protected]

Inter-thread communication between the YCP thread and the UI thread: The YCP thread supplies data here and signals the UI thread, the UI thread picks up the data, executes the function, puts the result here and signals the YCP thread that waits until the result is available.

Definition at line 330 of file [YUI.h](#).

3.147.4.2 bool YUI::_eventsBlocked [protected]

Flag that keeps track of blocked events. Never query this directly, use [eventsBlocked\(\)](#) instead.

Definition at line 358 of file [YUI.h](#).

3.147.4.3 `bool YUI::_terminate_ui_thread` `[protected]`

This is a flag that signals the ui thread that it should terminate. This is done by setting the flag to true. The ui thread replies by setting the flag back to false directly after terminating itself.

Definition at line 352 of file [YUI.h](#).

3.147.4.4 `pthread_t YUI::_uiThread` `[protected]`

Handle to the ui thread.

Definition at line 321 of file [YUI.h](#).

3.147.4.5 `bool YUI::_withThreads` `[protected]`

true if a separate UI thread is created

Definition at line 316 of file [YUI.h](#).

3.147.4.6 `int YUI::pipe_from_ui[2]` `[protected]`

Used to synchronize data transfer with the ui thread. It stores a pair of file descriptors of a pipe. For each YCP value we get from the ui thread, we read one arbitrary byte from here.

Definition at line 344 of file [YUI.h](#).

3.147.4.7 `int YUI::pipe_to_ui[2]` `[protected]`

Used to synchronize data transfer with the ui thread. It stores a pair of file descriptors of a pipe. For each YCP value we send to the ui thread, we write one arbitrary byte here.


Definition at line 337 of file [YUI.h](#).

The documentation for this class was generated from the following files:


- `/usr/src/RPM/BUILD/libyui-3.0.10/src/YUI.h`
- `/usr/src/RPM/BUILD/libyui-3.0.10/src/YUI.cc`

3.148 YUIBadPropertyArgException Class Reference

Inheritance diagram for YUIBadPropertyArgException:



Collaboration diagram for YUIBadPropertyArgException:



Public Member Functions

- **YUIBadPropertyArgException** (const [YProperty](#) &property, [YWidget](#) *widget, const std::string &message="")

Protected Member Functions

- virtual std::ostream & [dumpOn](#) (std::ostream &str) const

3.148.1 Detailed Description

Definition at line 619 of file [YUIException.h](#).

3.148.2 Member Function Documentation


3.148.2.1 `std::ostream & YUIBadPropertyArgException::dumpOn (std::ostream & str)`
`const [protected, virtual]`

Write proper error message with all relevant data. Reimplemented from [YUIException](#).

Implements [YUIPropertyException](#).

Definition at line 196 of file [YUIException.cc](#).

Here is the call graph for this function:



The documentation for this class was generated from the following files:


- `/usr/src/RPM/BUILD/libyui-3.0.10/src/YUIException.h`

- /usr/src/RPM/BUILD/libyui-3.0.10/src/YUIException.cc


3.149 YUIButtonRoleMismatchException Class Reference

```
#include <YUIException.h>
```

Inheritance diagram for YUIButtonRoleMismatchException:



Collaboration diagram for YUIButtonRoleMismatchException:



Public Member Functions

- **YUIButtonRoleMismatchException** (const std::string &msg)

3.149.1 Detailed Description

Exception class for "wrong button roles in YButtonBox"

Definition at line 889 of file [YUIException.h](#).


The documentation for this class was generated from the following file:

- /usr/src/RPM/BUILD/libyui-3.0.10/src/YUIException.h


3.150 YUICantLoadAnyUIException Class Reference

```
#include <YUIException.h>
```

Inheritance diagram for YUICantLoadAnyUIException:



Collaboration diagram for YUICantLoadAnyUIException:



3.150.1 Detailed Description

Exception class for UI plugin load failure


Definition at line 874 of file [YUIException.h](#).

The documentation for this class was generated from the following file:


- `/usr/src/RPM/BUILD/libyui-3.0.10/src/YUIException.h`

3.151 YUIDialogStackingOrderException Class Reference

Inheritance diagram for YUIDialogStackingOrderException:



Collaboration diagram for YUIDialogStackingOrderException:



3.151.1 Detailed Description

Definition at line 463 of file [YUIException.h](#).


The documentation for this class was generated from the following file:

- `/usr/src/RPM/BUILD/libyui-3.0.10/src/YUIException.h`

3.152 YUIException Class Reference

```
#include <YUIException.h>
```

Inheritance diagram for YUIException:



Public Member Functions

- [YUIException](#) ()
- [YUIException](#) (const std::string &msg_r)
- virtual [~YUIException](#) () throw ()

- const [YCodeLocation](#) & [where](#) () const
- void [relocate](#) (const [YCodeLocation](#) &newLocation) const
- const std::string & [msg](#) () const
- void [setMsg](#) (const std::string &[msg](#))
- std::string [asString](#) () const
- virtual const char * [what](#) () const throw ()

Static Public Member Functions

- static std::string [strErrno](#) (int [errno_r](#))
- static std::string [strErrno](#) (int [errno_r](#), const std::string &[msg](#))
- static void [log](#) (const [YUIException](#) &exception, const [YCodeLocation](#) &location, const char *const prefix)

Protected Member Functions

- virtual std::ostream & [dumpOn](#) (std::ostream &str) const

Friends

- std::ostream & [operator<<](#) (std::ostream &str, const [YUIException](#) &obj)

3.152.1 Detailed Description

Base class for UI Exceptions.

Exception offers to store a message string passed to the constructor. Derived classes may provide additional information. Overload [dumpOn](#) to provide a proper error text.

Definition at line [281](#) of file [YUIException.h](#).

3.152.2 Constructor & Destructor Documentation

3.152.2.1 [YUIException::YUIException \(\)](#)

Default constructor. Use [YUI_THROW](#) to throw exceptions.

Definition at line [62](#) of file [YUIException.cc](#).

3.152.2.2 YUIException::YUIException (const std::string & msg_r)

Constructor taking a message. Use YUI_THROW to throw exceptions.

Definition at line 67 of file [YUIException.cc](#).

3.152.2.3 YUIException::~YUIException () throw () [virtual]

Destructor.

Definition at line 74 of file [YUIException.cc](#).

3.152.3 Member Function Documentation

3.152.3.1 std::string YUIException::asString () const

Error message provided by dumpOn as string.

Definition at line 81 of file [YUIException.cc](#).

Here is the call graph for this function:



3.152.3.2 std::ostream & YUIException::dumpOn (std::ostream & str) const [protected, virtual]

Overload this to print a proper error message.

Reimplemented in [YUIIndexOutOfRangeException](#), [YUIInvalidChildException](#)< [YWidget](#) >, [YUITooManyChildrenException](#)< [YWidget](#) >, [YUIBadPropertyArgException](#), [YUISetReadOnlyPropertyException](#), [YUIPropertyTypeMismatchException](#), [YUIUnknownPropertyException](#), and [YUIPropertyException](#).


Definition at line 90 of file [YUIException.cc](#).

3.152.3.3 `void YUIException::log (const YUIException & exception, const YCodeLocation & location, const char *const prefix) [static]`

Drop a log line on throw, catch or rethrow. Used by YUI_THROW macros.

Definition at line 127 of file [YUIException.cc](#).

Here is the call graph for this function:



3.152.3.4 `const std::string& YUIException::msg () const [inline]`

Return the message string provided to the constructor. Note: This is not necessarily the complete error message. The whole error message is provided by `asString` or `dumpOn`.

Definition at line 318 of file [YUIException.h](#).

3.152.3.5 `void YUIException::relocate (const YCodeLocation & newLocation) const [inline]`

Exchange location on rethrow.

Definition at line 310 of file [YUIException.h](#).

3.152.3.6 `void YUIException::setMsg (const std::string & msg) [inline]`

Set a new message string.

Definition at line 324 of file [YUIException.h](#).

Here is the call graph for this function:



3.152.3.7 `std::string YUIException::strErrno (int errno_r) [static]`

Make a string from `errno_r`.

Definition at line 111 of file [YUIException.cc](#).

3.152.3.8 `std::string YUIException::strErrno (int errno_r, const std::string & msg) [static]`

Make a string from `errno_r` and `msg_r`.

Definition at line 118 of file [YUIException.cc](#).

Here is the call graph for this function:



3.152.3.9 `virtual const char* YUIException::what () const throw () [inline, virtual]`

Return message string.

Reimplemented from `std::exception`.

Definition at line 354 of file [YUIException.h](#).

3.152.3.10 `const YCodeLocation& YUIException::where () const` `[inline]`

Return [YCodeLocation](#).

Definition at line 304 of file [YUIException.h](#).

3.152.4 Friends And Related Function Documentation

3.152.4.1 `std::ostream& operator<< (std::ostream & str, const YUIException & obj)`
`[friend]`

[YUIException](#) stream output

Definition at line 104 of file [YUIException.cc](#).


The documentation for this class was generated from the following files:

- `/usr/src/RPM/BUILD/libyui-3.0.10/src/YUIException.h`
- `/usr/src/RPM/BUILD/libyui-3.0.10/src/YUIException.cc`


3.153 YUIIndexOutOfRangeException Class Reference

```
#include <YUIException.h>
```

Inheritance diagram for YUIIndexOutOfRangeException:



Collaboration diagram for YUIIndexOutOfRangeException:



Public Member Functions

- [YUIIndexOutOfRangeException](#) (int [invalidIndex](#), int [validMin](#), int [validMax](#), const std::string &[msg](#)="")
- int [invalidIndex](#) () const
- int [validMin](#) () const
- int [validMax](#) () const

Protected Member Functions

- virtual std::ostream & [dumpOn](#) (std::ostream &str) const

3.153.1 Detailed Description

Exception class for "index out of range"

Definition at line [791](#) of file [YUIException.h](#).

3.153.2 Constructor & Destructor Documentation

3.153.2.1 [YUIIndexOutOfRangeException::YUIIndexOutOfRangeException](#)
(int *invalidIndex*, int *validMin*, int *validMax*, const std::string & *msg* = " ")
[inline]

Constructor.

'invalidIndex' is the offending index value. It should be between 'validMin' and 'validMax':

`validMin <= index <= validMax`

Definition at line 802 of file [YUIException.h](#).

3.153.3 Member Function Documentation


3.153.3.1 `virtual std::ostream& YUIIndexOutOfRangeException::dumpOn (std::ostream & str) const` `[inline, protected, virtual]`

Write proper error message with all relevant data. Reimplemented from [YUIException](#).

Reimplemented from [YUIException](#).

Definition at line 836 of file [YUIException.h](#).

Here is the call graph for this function:



3.153.3.2 `int YUIIndexOutOfRangeException::invalidIndex () const` `[inline]`

Return the offending index value.

Definition at line 818 of file [YUIException.h](#).

3.153.3.3 `int YUIIndexOutOfRangeException::validMax () const` `[inline]`

Return the valid maximum index.

Definition at line 828 of file [YUIException.h](#).

3.153.3.4 `int YUIIndexOutOfRangeException::validMin () const` `[inline]`

Return the valid minimum index.

Definition at line 823 of file [YUIException.h](#).


The documentation for this class was generated from the following file:

- /usr/src/RPM/BUILD/libyui-3.0.10/src/YUIException.h


3.154 YUIInvalidChildException< YWidget > Class Template - Reference

```
#include <YUIException.h>
```

Inheritance diagram for YUIInvalidChildException< YWidget >:



Collaboration diagram for YUIInvalidChildException< YWidget >:



Public Member Functions

- **YUIInvalidChildException** ([YWidget](#) *[container](#), [YWidget](#) *[child](#)=0)
- [YWidget](#) * [container](#) () const
- [YWidget](#) * [child](#) () const

Protected Member Functions

- virtual std::ostream & [dumpOn](#) (std::ostream &str) const

3.154.1 Detailed Description

template<class YWidget>class YUIInvalidChildException< YWidget >

Exception class for "invalid child". One of:

- Attempt to remove a child from a children manager that is not in that manager's children list.
- Child widget of wrong type added to a container widget, e.g., anything other than a [YPushButton](#) added to a [YButtonBox](#).

Definition at line [696](#) of file [YUIException.h](#).

3.154.2 Member Function Documentation

3.154.2.1 template<class YWidget > YWidget* YUIInvalidChildException< YWidget >::child () const [\[inline\]](#)

Returns the child widget.

Definition at line [718](#) of file [YUIException.h](#).

3.154.2.2 template<class YWidget > YWidget* YUIInvalidChildException< YWidget >::container () const [\[inline\]](#)

Returns the container widget whose child should be removed etc.

Definition at line [713](#) of file [YUIException.h](#).


```
3.154.2.3 template<class YWidget > virtual std::ostream& YUIInvalidChildException<
    YWidget >::dumpOn ( std::ostream & str ) const [inline,
    protected, virtual]
```

Write proper error message with all relevant data. Reimplemented from [YUIException](#).

Reimplemented from [YUIException](#).

Definition at line 726 of file [YUIException.h](#).

Here is the call graph for this function:




The documentation for this class was generated from the following file:

- `/usr/src/RPM/BUILD/libyui-3.0.10/src/YUIException.h`


3.155 YUIInvalidDimensionException Class Reference

```
#include <YUIException.h>
```

Inheritance diagram for YUIInvalidDimensionException:



Collaboration diagram for YUIInvalidDimensionException:



3.155.1 Detailed Description

Exception class for "value other than YD_HORIZ or YD_VERT used for dimension".

Definition at line 776 of file [YUIException.h](#).


The documentation for this class was generated from the following file:

- `/usr/src/RPM/BUILD/libyui-3.0.10/src/YUIException.h`


3.156 YUIInvalidWidgetException Class Reference

```
#include <YUIException.h>
```

Inheritance diagram for YUIInvalidWidgetException:



Collaboration diagram for YUIInvalidWidgetException:



3.156.1 Detailed Description

Exception class for invalid widgets. This is typically caused by widget pointers that continue living after the corresponding widget has already been deleted.

Definition at line 424 of file [YUIException.h](#).

The documentation for this class was generated from the following file:

- `/usr/src/RPM/BUILD/libyui-3.0.10/src/YUIException.h`

3.157 YUILoader Class Reference

```
#include <YUILoader.h>
```

Static Public Member Functions

- static void `loadUI` (bool *withThreads*=false)
- static void `loadPlugin` (const std::string &*name*, bool *withThreads*=false)
- static bool `pluginExists` (const std::string &*pluginBaseName*)

3.157.1 Detailed Description

Class to load one of the concrete UI plug-ins: Qt, NCurses, Gtk.

Definition at line 44 of file [YUILoader.h](#).

3.157.2 Member Function Documentation

3.157.2.1 void `YUILoader::loadPlugin` (const std::string & *name*, bool *withThreads* = false) [static]

Load a UI plug-in. 'name' is one of the YUIPlugin_ -defines above.

This might throw exceptions.

Definition at line 99 of file [YUILoader.cc](#).


3.157.2.2 void `YUILoader::loadUI` (bool *withThreads* = false) [static]

Load any of the available UI plug-ins in this order:

- Qt if \$DISPLAY is set
- NCurses if stdout is a tty

Definition at line 39 of file [YUILoader.cc](#).

Here is the call graph for this function:



The documentation for this class was generated from the following files:

- `/usr/src/RPM/BUILD/libyui-3.0.10/src/YUILoader.h`
- `/usr/src/RPM/BUILD/libyui-3.0.10/src/YUILoader.cc`

3.158 YUILogBuffer Class Reference

Public Member Functions

- [YUILogBuffer](#) ()
- virtual [~YUILogBuffer](#) ()
- virtual `std::streamsize` [xspn](#) (const char *sequence, `std::streamsize` maxLength)
- virtual `int` [overflow](#) (int ch=EOF)
- `std::streamsize` [writeBuffer](#) (const char *sequence, `std::streamsize` seqLen)
- void [flush](#) ()

Friends

- class **YUILog**

3.158.1 Detailed Description

Stream buffer class that will use the YUILog's logger function.

See also <http://blogs.awesomeplay.com/elanthis/archives/2007/12/10/>

Definition at line 54 of file [YUILog.cc](#).

3.158.2 Constructor & Destructor Documentation

3.158.2.1 YUILogBuffer::YUILogBuffer () [inline]

Constructor.


Definition at line 63 of file [YUILog.cc](#).

3.158.2.2 virtual YUILogBuffer::~YUILogBuffer () [inline, virtual]

Destructor.

Definition at line 73 of file [YUILog.cc](#).

Here is the call graph for this function:



3.158.3 Member Function Documentation

3.158.3.1 void YUILogBuffer::flush ()

Flush the output buffer: Write any data unwritten so far.

Definition at line 178 of file [YUILog.cc](#).

Here is the call graph for this function:



3.158.3.2 `int YUILogBuffer::overflow (int ch = EOF)` `[virtual]`

Write one character in case of buffer overflow.

Reimplemented from `std::streambuf`.

Definition at line 166 of file [YUILog.cc](#).

Here is the call graph for this function:



3.158.3.3 `std::streamsize YUILogBuffer::writeBuffer (const char * sequence, std::streamsize seqLen)`

Write (no more than `maxLength` characters of) a sequence of characters and return the number of characters written.

This is the actual worker function that uses the `YUILog::loggerFunction` to actually write characters.

Definition at line 121 of file [YUILog.cc](#).

3.158.3.4 `std::streamsize YUILogBuffer::xsputn (const char * sequence, std::streamsize maxLength)` `[virtual]`

Write (no more than `maxLength` characters of) a sequence of characters and return the number of characters written.

Reimplemented from `std::streambuf`. This is called for all output operations on the associated ostream.

Definition at line 159 of file [YUILog.cc](#).

Here is the call graph for this function:



The documentation for this class was generated from the following file:

- /usr/src/RPM/BUILD/libyui-3.0.10/src/YUILog.cc

3.159 YUILogPrivate Struct Reference

Public Member Functions

- [YUILogPrivate](#) ()
- [~YUILogPrivate](#) ()
- [YPerThreadLogInfo](#) * [findCurrentThread](#) ()

Public Attributes

- std::string **logFileName**
- std::ofstream **stdLogStream**
- YUILoggerFunction **loggerFunction**
- YUIEnableDebugLoggingFunction **enableDebugLoggingHook**
- YUIDebugLoggingEnabledFunction **debugLoggingEnabledHook**
- bool **enableDebugLogging**
- std::vector< [YPerThreadLogInfo](#) * > **threadLogInfo**

3.159.1 Detailed Description

Definition at line 250 of file [YUILog.cc](#).

3.159.2 Constructor & Destructor Documentation

3.159.2.1 YUILogPrivate::YUILogPrivate () `[inline]`

Constructor

Definition at line [255](#) of file [YUILog.cc](#).

3.159.2.2 YUILogPrivate::~YUILogPrivate () `[inline]`

Destructor

Definition at line [265](#) of file [YUILog.cc](#).

3.159.3 Member Function Documentation

3.159.3.1 YPerThreadLogInfo* YUILogPrivate::findCurrentThread () `[inline]`

Find the per-thread logging information for the current thread. Create a new one if it doesn't exist yet.


Definition at line [275](#) of file [YUILog.cc](#).

The documentation for this struct was generated from the following file:


- [/usr/src/RPM/BUILD/libyui-3.0.10/src/YUILog.cc](#)

3.160 YUINoDialogException Class Reference

Inheritance diagram for YUINoDialogException:



Collaboration diagram for YUINoDialogException:



3.160.1 Detailed Description

Definition at line [451](#) of file [YUIException.h](#).


The documentation for this class was generated from the following file:

- `/usr/src/RPM/BUILD/libyui-3.0.10/src/YUIException.h`


3.161 YUINullPointerException Class Reference

```
#include <YUIException.h>
```

Inheritance diagram for YUINullPointerException:



Collaboration diagram for YUINullPointerException:



3.161.1 Detailed Description

Exception class for generic null pointer exceptions. When available, a more specialized exception class should be used.

Definition at line 391 of file [YUIException.h](#).


The documentation for this class was generated from the following file:

- /usr/src/RPM/BUILD/libyui-3.0.10/src/YUIException.h


3.162 YUIOutOfMemoryException Class Reference

```
#include <YUIException.h>
```

Inheritance diagram for YUIOutOfMemoryException:



Collaboration diagram for YUIOutOfMemoryException:



3.162.1 Detailed Description

Exception class for "out of memory". Typically used if operator new returned 0.

Definition at line 407 of file [YUIException.h](#).


The documentation for this class was generated from the following file:

- /usr/src/RPM/BUILD/libyui-3.0.10/src/YUIException.h

3.163 YUIPlugin Class Reference

```
#include <YUIPlugin.h>
```

Inheritance diagram for YUIPlugin:



Public Member Functions

- [YUIPlugin](#) (const char *pluginLibBaseName)
- virtual [~YUIPlugin](#) ()
- void [unload](#) ()
- void * [locateSymbol](#) (const char *symbol)
- bool [error](#) () const
- bool [success](#) () const
- std::string [errorMsg](#) () const

Protected Member Functions

- void * [pluginLibHandle](#) ()
- std::string [pluginLibBaseName](#) () const
- std::string [pluginLibFullPath](#) () const

3.163.1 Detailed Description

Wrapper class for dlopen() and related.

Definition at line 35 of file [YUIPlugin.h](#).


3.163.2 Constructor & Destructor Documentation

3.163.2.1 YUIPlugin::YUIPlugin (const char * *pluginLibBaseName*)

Constructor: Load the specified plugin library from the standard UI plugin directory (/usr/lib/yui/).

Definition at line 37 of file [YUIPlugin.cc](#).

Here is the call graph for this function:



3.163.2.2 YUIPlugin::~~YUIPlugin () [virtual]

Destructor.

Please note that this will NOT attempt to unload the plugin library since this is usually counterproductive. If unloading the plugin is desired, call [unload\(\)](#) manually.

Definition at line 57 of file [YUIPlugin.cc](#).

3.163.3 Member Function Documentation

3.163.3.1 bool YUIPlugin::error () const

Returns 'true' if there was an error loading the plugin.

Definition at line 104 of file [YUIPlugin.cc](#).

3.163.3.2 `std::string YUIPlugin::errorMsg () const`

Returns a human readable (but in most cases untranslated) error message if there was an error.

Definition at line 116 of file [YUIPlugin.cc](#).


3.163.3.3 `void * YUIPlugin::locateSymbol (const char * symbol)`

Try to locate the specified symbol (function or global variable) in the plugin library.

Returns the in-memory address of that symbol or 0 if it could not be found or if loading the plugin library had failed in the constructor.

Definition at line 86 of file [YUIPlugin.cc](#).

Here is the call graph for this function:



3.163.3.4 `std::string YUIPlugin::pluginLibBaseName () const` `[inline, protected]`

Returns the base name of the plugin library.

Definition at line 96 of file [YUIPlugin.h](#).

3.163.3.5 `std::string YUIPlugin::pluginLibFullPath () const` `[protected]`

Returns the full path of the plugin library.

Definition at line 73 of file [YUIPlugin.cc](#).

Here is the call graph for this function:



3.163.3.6 void* YUIPlugin::pluginLibHandle () [inline, protected]

Returns the dlopen() handle of the plugin library.

Definition at line 91 of file [YUIPlugin.h](#).

3.163.3.7 bool YUIPlugin::success () const

Returns 'true' if there was no error loading the plugin.

Definition at line 110 of file [YUIPlugin.cc](#).

3.163.3.8 void YUIPlugin::unload ()

Unload this plugin. This calls dlclose() which will unload the plugin library if it is no longer used, i.e. if the reference count dlopen() uses reaches 0.

Definition at line 65 of file [YUIPlugin.cc](#).


The documentation for this class was generated from the following files:

- /usr/src/RPM/BUILD/libyui-3.0.10/src/YUIPlugin.h
- /usr/src/RPM/BUILD/libyui-3.0.10/src/YUIPlugin.cc


3.164 YUIPluginException Class Reference

```
#include <YUIException.h>
```

Inheritance diagram for YUIPluginException:



Collaboration diagram for YUIPluginException:



Public Member Functions

- **YUIPluginException** (const std::string &pluginName)

3.164.1 Detailed Description

Exception class for plugin load failure

Definition at line 859 of file [YUIException.h](#).


The documentation for this class was generated from the following file:

- /usr/src/RPM/BUILD/libyui-3.0.10/src/YUIException.h


3.165 YUIPropertyException Class Reference

```
#include <YUIException.h>
```

Inheritance diagram for YUIPropertyException:



Collaboration diagram for YUIPropertyException:



Public Member Functions

- [YProperty property](#) () const
- [YWidget * widget](#) () const

- void [setWidget](#) ([YWidget](#) *w)

Protected Member Functions

- **YUIPropertyException** (const [YProperty](#) &prop, [YWidget](#) *widget=0)
- virtual std::ostream & [dumpOn](#) (std::ostream &str) const =0

3.165.1 Detailed Description

Abstract base class for widget property exceptions.

Definition at line 490 of file [YUIException.h](#).

3.165.2 Member Function Documentation

3.165.2.1 virtual std::ostream& **YUIPropertyException::dumpOn** (std::ostream & *str*)
const [protected, pure virtual]

Write proper error message with all relevant data. Reimplemented from [YUIException](#).

Reimplemented from [YUIException](#).

Implemented in [YUIBadPropertyArgException](#), [YUISetReadOnlyPropertyException](#), [YUIPropertyTypeMismatchException](#), and [YUIUnknownPropertyException](#).

3.165.2.2 **YProperty** **YUIPropertyException::property** () const [inline]

Returns the property that caused this exception.

Definition at line 507 of file [YUIException.h](#).

3.165.2.3 void **YUIPropertyException::setWidget** (**YWidget** * *w*) [inline]

Set the corresponding widget.

Definition at line 517 of file [YUIException.h](#).

3.165.2.4 **YWidget*** **YUIPropertyException::widget** () const [inline]

Returns the corresponding widget or 0 if there was none.

Definition at line 512 of file [YUIException.h](#).


The documentation for this class was generated from the following file:

- /usr/src/RPM/BUILD/libyui-3.0.10/src/YUIException.h


3.166 YUIPropertyTypeMismatchException Class Reference

```
#include <YUIException.h>
```

Inheritance diagram for YUIPropertyTypeMismatchException:



Collaboration diagram for YUIPropertyTypeMismatchException:



Public Member Functions

- **YUIPropertyTypeMismatchException** (const [YProperty](#) &[property](#), YPropertyType [type](#), [YWidget](#) *[widget](#)=0)
- YPropertyType [type](#) () const

Protected Member Functions

- virtual std::ostream & [dumpOn](#) (std::ostream &[str](#)) const

3.166.1 Detailed Description

Exception class for "property type mismatch": The application tried to set a property with a wrong type.

Definition at line [562](#) of file [YUIException.h](#).

3.166.2 Member Function Documentation


3.166.2.1 `std::ostream & YUIPropertyTypeMismatchException::dumpOn (std::ostream & str) const` `[protected, virtual]`

Write proper error message with all relevant data. Reimplemented from [YUIException](#).

Implements [YUIPropertyException](#).

Definition at line 161 of file [YUIException.cc](#).

Here is the call graph for this function:



3.166.2.2 `YPropertyType YUIPropertyTypeMismatchException::type () const` `[inline]`

Return the property type the application tried to set.

Definition at line 579 of file [YUIException.h](#).


The documentation for this class was generated from the following files:

- `/usr/src/RPM/BUILD/libyui-3.0.10/src/YUIException.h`
- `/usr/src/RPM/BUILD/libyui-3.0.10/src/YUIException.cc`


3.167 YUISetReadOnlyPropertyException Class Reference

```
#include <YUIException.h>
```

Inheritance diagram for YUISetReadOnlyPropertyException:



Collaboration diagram for YUISetReadOnlyPropertyException:



Public Member Functions

- **YUISetReadOnlyPropertyException** (const [YProperty](#) &property, [YWidget](#) *widget=0)

Protected Member Functions

- virtual std::ostream & [dumpOn](#) (std::ostream &str) const

3.167.1 Detailed Description

Exception class for attempt to set a read-only property.

Definition at line 597 of file [YUIException.h](#).

3.167.2 Member Function Documentation


3.167.2.1 std::ostream & **YUISetReadOnlyPropertyException::dumpOn** (std::ostream & str) const [protected, virtual]

Write proper error message with all relevant data. Reimplemented from [YUIException](#).

Implements [YUIPropertyException](#).

Definition at line 180 of file [YUIException.cc](#).

Here is the call graph for this function:




The documentation for this class was generated from the following files:


- /usr/src/RPM/BUILD/libyui-3.0.10/src/YUIException.h
- /usr/src/RPM/BUILD/libyui-3.0.10/src/YUIException.cc

3.168 YUISyntaxErrorException Class Reference

Inheritance diagram for YUISyntaxErrorException:



Collaboration diagram for YUISyntaxErrorException:



Public Member Functions

- **YUISyntaxErrorException** (const std::string &[msg](#))

3.168.1 Detailed Description

Definition at line [475](#) of file [YUIException.h](#).

The documentation for this class was generated from the following file:

- [/usr/src/RPM/BUILD/libyui-3.0.10/src/YUIException.h](#)

3.169 YUITerminator Class Reference

Public Member Functions

- [~YUITerminator](#) ()

3.169.1 Detailed Description

Helper class to make sure the UI is properly shut down.

Definition at line [506](#) of file [YUI.cc](#).

3.169.2 Constructor & Destructor Documentation

3.169.2.1 YUITerminator::~YUITerminator ()

Destructor.

If there still is a UI, it will be deleted. If there is none, this will do nothing.

Definition at line [521](#) of file [YUI.cc](#).


The documentation for this class was generated from the following file:

- [/usr/src/RPM/BUILD/libyui-3.0.10/src/YUI.cc](#)


3.170 YUITooManyChildrenException< YWidget > Class - Template Reference

```
#include <YUIException.h>
```

Inheritance diagram for YUITooManyChildrenException< YWidget >:



Collaboration diagram for YUITooManyChildrenException< YWidget >:



Public Member Functions

- **YUITooManyChildrenException** ([YWidget](#) *[container](#))
- [YWidget](#) * [container](#) () const

Protected Member Functions

- virtual std::ostream & [dumpOn](#) (std::ostream &str) const

3.170 YUITooManyChildrenException< YWidget > Class Template Reference 587

3.170.1 Detailed Description

```
template<class YWidget>class YUITooManyChildrenException< YWidget >
```

Exception class for "too many children": Attempt to add a child to a widget class that can't handle children ([YPushButton](#) etc.) or just one child ([YFrame](#), [YDialog](#)).

Definition at line [647](#) of file [YUIException.h](#).

3.170.2 Member Function Documentation

3.170.2.1 `template<class YWidget > YWidget* YUITooManyChildrenException< YWidget >::container () const` `[inline]`

Returns the container widget that can't handle that many children.

Definition at line [662](#) of file [YUIException.h](#).


3.170.2.2 `template<class YWidget > virtual std::ostream& YUITooManyChildrenException< YWidget >::dumpOn (std::ostream & str) const` `[inline, protected, virtual]`

Write proper error message with all relevant data. Reimplemented from [YUIException](#).

Reimplemented from [YUIException](#).

Definition at line [670](#) of file [YUIException.h](#).

Here is the call graph for this function:




The documentation for this class was generated from the following file:

- `/usr/src/RPM/BUILD/libyui-3.0.10/src/YUIException.h`


3.171 YUIUnknownPropertyException Class Reference

```
#include <YUIException.h>
```

Inheritance diagram for YUIUnknownPropertyException:



Collaboration diagram for YUIUnknownPropertyException:



Public Member Functions

- **YUIUnknownPropertyException** (const std::string &propertyName, [YWidget](#) *widget=0)

Protected Member Functions

- virtual std::ostream & [dumpOn](#) (std::ostream &str) const

3.171.1 Detailed Description

Exception class for "unknown property name": The application tried to set (or query) a property that doesn't exist.

Definition at line [537](#) of file [YUIException.h](#).

3.171.2 Member Function Documentation


3.171.2.1 `std::ostream & YUIUnknownPropertyException::dumpOn (std::ostream & str) const` [protected, virtual]

Write proper error message with all relevant data. Reimplemented from [YUIException](#).

Implements [YUIPropertyException](#).

Definition at line 140 of file [YUIException.cc](#).

Here is the call graph for this function:




The documentation for this class was generated from the following files:

- `/usr/src/RPM/BUILD/libyui-3.0.10/src/YUIException.h`
- `/usr/src/RPM/BUILD/libyui-3.0.10/src/YUIException.cc`


3.172 YUIUnsupportedWidgetException Class Reference

```
#include <YUIException.h>
```


Inheritance diagram for YUIUnsupportedWidgetException:



Collaboration diagram for YUIUnsupportedWidgetException:



Public Member Functions

- **YUIUnsupportedWidgetException** (const std::string &widgetType)

3.172.1 Detailed Description

Exception class for "optional widget not supported".

Note that applications are supposed to check with [YUI::optionalWidgetFactory\(\)](#)->has-XYWidget() before trying to create such a widget. This exception is thrown if that check

wasn't done, the application tried to create that kind of widget anyway, but the UI doesn't support that widget.

Definition at line 759 of file [YUIException.h](#).


The documentation for this class was generated from the following file:

- `/usr/src/RPM/BUILD/libyui-3.0.10/src/YUIException.h`


3.173 YUIWidgetNotFoundException Class Reference

```
#include <YUIException.h>
```

Inheritance diagram for YUIWidgetNotFoundException:



Collaboration diagram for YUIWidgetNotFoundException:



Public Member Functions

- **YUIWidgetNotFoundException** (const std::string &idString)

3.173.1 Detailed Description

Exception class for "No widget found with that ID".

Definition at line 439 of file [YUIException.h](#).


The documentation for this class was generated from the following file:

- /usr/src/RPM/BUILD/libyui-3.0.10/src/YUIException.h

3.174 YWidget Class Reference

```
#include <YWidget.h>
```

Inheritance diagram for YWidget:



Classes

- class [OptimizeChanges](#)

Public Member Functions

- virtual [~YWidget](#) ()
- virtual const char * [widgetClass](#) () const
- virtual std::string [debugLabel](#) () const
- std::string [helpText](#) () const
- void [setHelpText](#) (const std::string &[helpText](#))
- virtual const [YPropertySet](#) & [propertySet](#) ()
- virtual bool [setProperty](#) (const std::string &propertyName, const [YPropertyValue](#) &val)
- virtual [YPropertyValue](#) [getProperty](#) (const std::string &propertyName)
- bool [hasChildren](#) () const
- [YWidget](#) * [firstChild](#) () const
- [YWidget](#) * [lastChild](#) () const
- [YWidgetListConstIterator](#) [childrenBegin](#) () const
- [YWidgetListConstIterator](#) [childrenEnd](#) () const
- int [childrenCount](#) () const
- bool [contains](#) ([YWidget](#) *child) const
- virtual void [addChild](#) ([YWidget](#) *child)
- virtual void [removeChild](#) ([YWidget](#) *child)
- void [deleteChildren](#) ()
- [YWidget](#) * [parent](#) () const
- bool [hasParent](#) () const
- void [setParent](#) ([YWidget](#) *newParent)
- [YDialog](#) * [findDialog](#) ()
- [YWidget](#) * [findWidget](#) ([YWidgetID](#) *id, bool doThrow=true) const
- virtual int [preferredWidth](#) ()=0
- virtual int [preferredHeight](#) ()=0
- virtual int [preferredSize](#) (YUIDimension dim)
- virtual void [setSize](#) (int newWidth, int newHeight)=0
- bool [isValid](#) () const
- bool [beingDestroyed](#) () const
- void * [widgetRep](#) () const
- void [setWidgetRep](#) (void *toolkitWidgetRep)
- bool [hasId](#) () const
- [YWidgetID](#) * [id](#) () const
- void [setId](#) ([YWidgetID](#) *newId_disown)
- virtual void [setEnabled](#) (bool enabled=true)

- void [setDisabled](#) ()
- virtual bool [isEnabled](#) () const
- virtual bool [stretchable](#) (YUIDimension dim) const
- void [setStretchable](#) (YUIDimension dim, bool newStretch)
- void [setDefaultStretchable](#) (YUIDimension dim, bool newStretch)
- virtual int [weight](#) (YUIDimension dim)
- bool [hasWeight](#) (YUIDimension dim)
- void [setWeight](#) (YUIDimension dim, int [weight](#))
- void [setNotify](#) (bool [notify](#)=true)
- bool [notify](#) () const
- void [setNotifyContextMenu](#) (bool [notifyContextMenu](#)=true)
- bool [notifyContextMenu](#) () const
- bool [sendKeyEvents](#) () const
- void [setSendKeyEvents](#) (bool doSend)
- bool [autoShortcut](#) () const
- void [setAutoShortcut](#) (bool _newAutoShortcut)
- int [functionKey](#) () const
- bool [hasFunctionKey](#) () const
- virtual void [setFunctionKey](#) (int fkey_no)
- virtual bool [setKeyboardFocus](#) ()
- virtual std::string [shortcutString](#) () const
- virtual void [setShortcutString](#) (const std::string &str)
- virtual const char * [userInputProperty](#) ()
- void [dumpWidgetTree](#) (int indentationLevel=0)
- void [dumpDialogWidgetTree](#) ()
- void [setChildrenEnabled](#) (bool enabled)
- virtual void [saveUserInput](#) (YMacroRecorder *macroRecorder)
- void * [operator new](#) (size_t size)
- virtual void [startMultipleChanges](#) ()
- virtual void [doneMultipleChanges](#) ()

Protected Member Functions

- [YWidget](#) (YWidget *parent)
- [YWidgetChildrenManager](#) * [childrenManager](#) () const
- void [setChildrenManager](#) (YWidgetChildrenManager *manager)
- void [setBeingDestroyed](#) ()
- void [dumpWidget](#) (YWidget *w, int indentationLevel)

3.174.1 Detailed Description

Abstract base class of all UI widgets

Definition at line 54 of file [YWidget.h](#).


3.174.2 Constructor & Destructor Documentation

3.174.2.1 YWidget::YWidget (YWidget * *parent*) [protected]

Constructor.

Definition at line 104 of file [YWidget.cc](#).

Here is the call graph for this function:




3.174.2.2 YWidget::~~YWidget () [virtual]

Destructor.

Definition at line 135 of file [YWidget.cc](#).

Here is the call graph for this function:



3.174.3 Member Function Documentation

3.174.3.1 void YWidget::addChild (YWidget * *child*) [virtual]


Add a new child.

This may throw exceptions if more children are added than this widget can handle.

Reimplemented in [YAlignment](#).

Definition at line 174 of file [YWidget.cc](#).

Here is the call graph for this function:



3.174.3.2 bool YWidget::autoShortcut () const

Returns 'true' if a keyboard shortcut should automatically be assigned to this widget - without complaints in the log file.

Definition at line 310 of file [YWidget.cc](#).

3.174.3.3 bool YWidget::beingDestroyed () const

Check if this widget is in the process of being destroyed.


Definition at line 256 of file [YWidget.cc](#).

3.174.3.4 YWidgetListConstIterator YWidget::childrenBegin () const [inline]

Return an iterator that points to the first child or to `childrenEnd()` if there are no children.

Definition at line 212 of file [YWidget.h](#).

Here is the call graph for this function:




3.174.3.5 `int YWidget::childrenCount () const [inline]`

Returns the current number of children.

Definition at line 224 of file [YWidget.h](#).

Here is the call graph for this function:




3.174.3.6 `YWidgetListConstIterator YWidget::childrenEnd () const [inline]`

Return an iterator that points after the last child.

Definition at line 218 of file [YWidget.h](#).

Here is the call graph for this function:



3.174.3.7 `YWidgetChildrenManager * YWidget::childrenManager () const`
[protected]

Returns this widget's children manager.


Definition at line 157 of file [YWidget.cc](#).

3.174.3.8 `bool YWidget::contains (YWidget * child) const` [inline]

Checks if 'child' is a (direct!) child of this widget.

Definition at line 229 of file [YWidget.h](#).

Here is the call graph for this function:



3.174.3.9 std::string YWidget::debugLabel () const [virtual]

Returns a descriptive label of this widget instance.

This default implementation returns this widget's "shortcut property" (possibly truncated to avoid over-long texts) - the property that contains the keyboard shortcut used to activate this widget or to move the keyboard focus to it. In most cases this is this widget's label.

Note: This is usually translated to the user's target language. This makes this useful for debugging only.

Reimplemented in [YLabel](#), and [YDumbTab](#).

Definition at line 221 of file [YWidget.cc](#).

Here is the call graph for this function:




3.174.3.10 void YWidget::deleteChildren ()

Delete all children and remove them from the children manager's list.

Definition at line 200 of file [YWidget.cc](#).

Here is the call graph for this function:




3.174.3.11 void YWidget::dumpDialogWidgetTree ()

Debugging function: Dump the widget tree from this widget's dialog parent. If there is no such dialog parent, dump the widget tree from here on.

Definition at line 658 of file [YWidget.cc](#).

Here is the call graph for this function:



3.174.3.12 void YWidget::dumpWidget (YWidget * w, int indentationLevel) [protected]

Helper function for [dumpWidgetTree\(\)](#): Dump one widget to the log file.

Definition at line 687 of file [YWidget.cc](#).

Here is the call graph for this function:




3.174.3.13 void YWidget::dumpWidgetTree (int indentationLevel = 0)

Debugging function: Dump the widget tree from here on to the log file.

Definition at line 669 of file [YWidget.cc](#).

Here is the call graph for this function:



3.174.3.14 YDialog * YWidget::findDialog ()

Traverse up the widget hierarchy and find the dialog this widget belongs to. Returns 0 if there is none.

Definition at line 374 of file [YWidget.cc](#).

Here is the call graph for this function:




3.174.3.15 YWidget * YWidget::findWidget (YWidgetID * id, bool doThrow = true) const

Recursively find a widget by its ID. If there is no widget with that ID, this function throws a [YUIWidgetNotFoundException](#) if 'doThrow' is 'true'. It returns 0 if 'doThrow' is 'false'.

Definition at line 602 of file [YWidget.cc](#).

Here is the call graph for this function:




3.174.3.16 YWidget* YWidget::firstChild () const [inline]

Returns the first child or 0 if there is none. Useful mostly for children managers that handle only one child.

Definition at line 199 of file [YWidget.h](#).

Here is the call graph for this function:



3.174.3.17 int YWidget::functionKey () const

Return a function key number that is assigned to this widget. (1 for F1, 2 for F2, etc.; 0 for none)

Definition at line 322 of file [YWidget.cc](#).

3.174.3.18 YPropertyValue YWidget::getProperty (const std::string & *propertyName*) [virtual]

Get a property. Derived classes need to implement this.


This method may throw exceptions, for example

- if there is no property with that name

Reimplemented in [YWizard](#), [YComboBox](#), [YTable](#), [YInputField](#), [YPushButton](#), [YCheckBoxFrame](#), [YPartitionSplitter](#), [YCheckBox](#), [YLogView](#), [YIntField](#), [YRadioButton](#), [YMultiProgressMeter](#), [YLabel](#), [YRichText](#), [YBarGraph](#), [YMultiLineEdit](#), [YDownloadProgress](#), [YTree](#), [YContextMenu](#), [YMenuButton](#), [YSelectionBox](#), [YBusyIndicator](#), [YRadioButtonGroup](#), [YProgressBar](#), [YDumbTab](#), [YSimpleInputField](#), [YGraph](#), [YFrame](#), [YMultiSelectionBox](#), and [YTimezoneSelector](#).

Definition at line 453 of file [YWidget.cc](#).

Here is the call graph for this function:




3.174.3.19 bool YWidget::hasChildren () const [inline]

Returns 'true' if this widget has any children.

Definition at line 192 of file [YWidget.h](#).

Here is the call graph for this function:



3.174.3.20 `bool YWidget::hasFunctionKey () const`

Check if a function key is assigned to this widget.

Definition at line [328](#) of file [YWidget.cc](#).

3.174.3.21 `bool YWidget::hasId () const`

Returns 'true' if this widget has an ID.

Definition at line [368](#) of file [YWidget.cc](#).

3.174.3.22 `bool YWidget::hasParent () const`

Return 'true' if this widget has a parent, 'false' if not.

Definition at line [276](#) of file [YWidget.cc](#).

3.174.3.23 `bool YWidget::hasWeight (YUIDimension dim)`

Return whether or not the widget has a weight in the specified dimension.

Definition at line [585](#) of file [YWidget.cc](#).

Here is the call graph for this function:



3.174.3.24 `std::string YWidget::helpText () const`

Return the help text for this widget.

Definition at line 340 of file [YWidget.cc](#).

3.174.3.25 `YWidgetID * YWidget::id () const`

Returns this widget's ID.

Definition at line 353 of file [YWidget.cc](#).

3.174.3.26 `bool YWidget::isEnabled () const` `[virtual]`

Returns 'true' if this widget is enabled.

Definition at line 502 of file [YWidget.cc](#).

3.174.3.27 `bool YWidget::isValid () const`

Checks whether or not this object is valid. This is to enable dangling pointer error checking (i.e. this object is already deallocated, but a pointer to it is still in use).

See also the `YUI_CHECK_WIDGET()` macro in [YUIException.h](#)


Definition at line 242 of file [YWidget.cc](#).

3.174.3.28 `YWidget* YWidget::lastChild () const` `[inline]`

Returns the last child or 0 if there is none.

Definition at line 205 of file [YWidget.h](#).

Here is the call graph for this function:



3.174.3.29 `bool YWidget::notify () const`

Returns whether the widget will notify, i.e. will case `UserInput` to return.

Definition at line 529 of file [YWidget.cc](#).

3.174.3.30 `bool YWidget::notifyContextMenu () const`

Returns whether the widget will send an event when the user clicks selects the context menu e.g. via right click.

Definition at line 535 of file [YWidget.cc](#).

3.174.3.31 `void * YWidget::operator new (size_t size)`

Overloaded operator `new` to ensure widgets are always created on the heap, never on the stack.

Simpler implementations of this have a tendency to be fooled by poorly implemented derived classes.

Definition at line 128 of file [YWidget.cc](#).

3.174.3.32 `YWidget * YWidget::parent () const`

Return this widget's parent or 0 if it doesn't have a parent.

Definition at line 269 of file [YWidget.cc](#).

3.174.3.33 `virtual int YWidget::preferredHeight () [pure virtual]`

Preferred height of the widget.

Derived classes are required to implement this.

Implemented in [YButtonBox](#), [YAlignment](#), [YSpacing](#), [YLayoutBox](#), [YEmpty](#), and [YSingleChildContainerWidget](#).

3.174.3.34 `int YWidget::preferredSize (YUIDimension dim) [virtual]`

Preferred size of the widget in the specified dimension. This default implementation calls [preferredWidth\(\)](#) or [preferredHeight\(\)](#) which makes sense for most cases.


Derived classes can reimplement this, but this is discouraged.

Note: Even in that case, [preferredWidth\(\)](#) and [preferredHeight\(\)](#) need to be implemented, but they might then call [preferredSize\(\)](#).

Reimplemented in [YLayoutBox](#).

Definition at line 541 of file [YWidget.cc](#).

Here is the call graph for this function:

**3.174.3.35** `virtual int YWidget::preferredWidth () [pure virtual]`

Preferred width of the widget.

Derived classes are required to implement this.

Implemented in [YButtonBox](#), [YAlignment](#), [YSpacing](#), [YLayoutBox](#), [YEmpty](#), and [YSingleChildContainerWidget](#).

3.174.3.36 `const YPropertySet & YWidget::propertySet ()` [virtual]

Return this class's property set. This also initializes the property upon the first call.

Derived classes should reimplement this.

Remember to add the base class's property set to your own in reimplemented versions, e.g.:


```
const YPropertySet & MyWidgetClass::propertySet() { static YPropertySet propSet;
if ( propSet.isEmpty() ) { // Add properties for the derived class propSet.add( YProperty(
YUIProperty_Value, YStringProperty ) ); propSet.add( YProperty( YUIProperty_Label,
YStringProperty ) );
// Add base class properties propSet.add( YWidget::propertySet() ); }
return propSet; }
```

Otherwise the base class's properties will not be available in the derived class. It is also important that the base class's properties are added after those of the derived class so the derived class's properties have priority over those of the base class.

Reimplemented in [YWizard](#), [YComboBox](#), [YTable](#), [YInputField](#), [YPushButton](#), [YCheckBoxFrame](#), [YPartitionSplitter](#), [YCheckBox](#), [YLogView](#), [YIntField](#), [YRadioButton](#), [YMultiProgressMeter](#), [YLabel](#), [YRichText](#), [YBarGraph](#), [YMultiLineEdit](#), [YDownloadProgress](#), [YTree](#), [YContextMenu](#), [YMenuButton](#), [YSelectionBox](#), [YBusyIndicator](#), [YRadioButtonGroup](#), [YProgressBar](#), [YDumbTab](#), [YSimpleInputField](#), [YGraph](#), [YFrame](#), [YMultiSelectionBox](#), and [YTimezoneSelector](#).

Definition at line 393 of file [YWidget.cc](#).

Here is the call graph for this function:




3.174.3.37 void YWidget::removeChild (YWidget * *child*) [virtual]

Remove a child. This only removes the child from the children manager's list; it does not delete it.

Definition at line 189 of file [YWidget.cc](#).

Here is the call graph for this function:

**3.174.3.38** void YWidget::saveUserInput (YMacroRecorder * *macroRecorder*) [virtual]

Recursively save the user input of all child widgets to a macro recorder:

All child widgets that could contain data entered by the user are requested to send their contents to the macro recorder, e.g. input fields, check boxes etc.


This default implementation records this widget's user input property (the property returned by `userInputProperty`) and then recursively calls [saveUserInput\(\)](#) for all child widgets. This is suitable for most cases, for container widgets as well as for leaf widgets that have no or exactly one property that needs to be recorded.

Widgets that need another number of properties recorded should reimplement this method (and NOT call this default method in the new implementation).

Reimplemented in [YInputField](#), [YRadioButton](#), and [YMultiSelectionBox](#).

Definition at line 714 of file [YWidget.cc](#).

Here is the call graph for this function:



3.174.3.39 `bool YWidget::sendKeyEvents () const`

Returns 'true' if this widget should send key events, i.e. if it has 'opt('keyEvent) set.

Definition at line 298 of file [YWidget.cc](#).

3.174.3.40 `void YWidget::setAutoShortcut (bool newAutoShortcut)`

Sets the 'autoShortcut' flag.

Definition at line 316 of file [YWidget.cc](#).

3.174.3.41 `void YWidget::setBeingDestroyed () [protected]`

Set the "being destroyed" flag, i.e. indicate that this widget is in the process of being destroyed. The base class method already sets this, but sometimes it might be useful to call this in a derived class's destructor so certain optimizations work better.

This status intentionally cannot be reverted to "not being destroyed".


Definition at line 262 of file [YWidget.cc](#).

3.174.3.42 `void YWidget::setChildrenEnabled (bool enabled)`

Enable or disable all widgets in this widget tree.

Definition at line 638 of file [YWidget.cc](#).

Here is the call graph for this function:



3.174.3.43 void YWidget::setChildrenManager (YWidgetChildrenManager * manager) [protected]

Sets a new children manager for this widget. The widget assumes ownership of this children manager and will delete it when appropriate.

The default children manager (a YWidgetChildrenRejector) rejects all children. This is useful for leaf widgets such as PushButton, ComboBox etc.

Derived classes that can handle children might want to set the children manager to a YWidgetChildrenManager (the base class that does not reject children) or to a YSingleWidgetChildManager (the class that handles exactly one child widget).

Definition at line 164 of file [YWidget.cc](#).

3.174.3.44 void YWidget::setDefaultStretchable (YUIDimension dim, bool newStretch)

Set the stretchable state to "newStretch". 'hstretch or 'vstretch options may override this.

Definition at line 561 of file [YWidget.cc](#).

3.174.3.45 void YWidget::setDisabled () [inline]

Disable this widget (overloaded for better readability).

Definition at line 399 of file [YWidget.h](#).

Here is the call graph for this function:



3.174.3.46 `void YWidget::setEnabled (bool enabled =true) [virtual]`

Enable or disable this widget, i.e. make it accept or reject user input.

Derived classes should call the base class method to update the internal "enabled" flag.

Definition at line [495](#) of file [YWidget.cc](#).

3.174.3.47 `void YWidget::setFunctionKey (int fkey.no) [virtual]`

Assign a function key to this widget (1 for F1, 2 for F2, etc.; 0 for none)

Derived classes may want to overwrite this function, but they should call this base class function in the new function.

Reimplemented in [YPushButton](#).

Definition at line [334](#) of file [YWidget.cc](#).

3.174.3.48 `void YWidget::setHelpText (const std::string & helpText)`

Set a help text for this widget.

Currently, the UI does not do anything with this text but store it. Displaying the text at a convenient time is currently the application's responsibility. This may change in future versions.

Reimplemented in [YWizard](#).

Definition at line [346](#) of file [YWidget.cc](#).

Here is the call graph for this function:



3.174.3.49 void YWidget::setId (YWidgetID * *newId* *disown*)

Set this widget's ID.

The widget assumes ownership of this ID and will delete it when needed. (In the widget's destructor or when a new ID is set)

Widget IDs are purely for application use. C++ applications don't need to use them; they are much better off using widget pointers. For other languages, though, that can't use C++ pointers (e.g., YCP) it makes sense to have widget IDs to identify widgets.

Definition at line 359 of file [YWidget.cc](#).

3.174.3.50 bool YWidget::setKeyboardFocus () [virtual]

Set the keyboard focus to this widget. The default implementation just emits a warning message. Overwrite this function for all widgets that can accept the keyboard focus.

This function returns true if the widget did accept the keyboard focus, and false if not.

Definition at line 594 of file [YWidget.cc](#).

3.174.3.51 void YWidget::setNotify (bool *notify* = true)

Sets the Notify property

Definition at line 517 of file [YWidget.cc](#).

Here is the call graph for this function:



3.174.3.52 `void YWidget::setNotifyContextMenu (bool notifyContextMenu = true)`

Sets the `notifyContextMenu` property

Definition at line 523 of file [YWidget.cc](#).

Here is the call graph for this function:




3.174.3.53 `void YWidget::setParent (YWidget * newParent)`

Set this widget's parent.

Definition at line 283 of file [YWidget.cc](#).

Here is the call graph for this function:



3.174.3.54 `bool YWidget::setProperty (const std::string & propertyName, const YPropertyValue & val) [virtual]`

Set a property. Derived classes need to implement this.

This method may throw exceptions, for example


- if there is no property with that name
- if the expected type and the type mismatch
- if the value is out of range

This function returns 'true' if the value was successfully set and 'false' if that value requires special handling (not in error cases: those are covered by exceptions).

Reimplemented in [YComboBox](#), [YTable](#), [YInputField](#), [YPushButton](#), [YCheckBoxFrame](#), [YPartitionSplitter](#), [YCheckBox](#), [YLogView](#), [YIntField](#), [YRadioButton](#), [YMultiProgressMeter](#), [YRichText](#), [YLabel](#), [YBarGraph](#), [YMultiLineEdit](#), [YDownloadProgress](#), [YTree](#), [YContextMenu](#), [YMenuButton](#), [YSelectionBox](#), [YBusyIndicator](#), [YRadioButtonGroup](#), [YProgressBar](#), [YDumbTab](#), [YSimpleInputField](#), [YGraph](#), [YFrame](#), [YMultiSelectionBox](#), and [YTimezoneSelector](#).

Definition at line 428 of file [YWidget.cc](#).

Here is the call graph for this function:



3.174.3.55 void YWidget::setSendKeyEvents (bool doSend)

Specify whether or not this widget should send key events.

Definition at line 304 of file [YWidget.cc](#).

3.174.3.56 void YWidget::setShortcutString (const std::string & str) [virtual]

Set the string of this widget that holds the keyboard shortcut, if any. Most widgets will call `setLabel()`.


Overwrite this for widgets that can have keyboard shortcuts.

Reimplemented in [YSelectionWidget](#), [YInputField](#), [YPushButton](#), [YCheckBox](#), [YLogView](#), [YIntField](#), [YRadioButton](#), [YMultiLineEdit](#), [YCheckBoxFrame](#), [YDumbTab](#), and [Y-](#)

[SimpleInputField](#).

Definition at line 508 of file [YWidget.cc](#).

Here is the call graph for this function:



3.174.3.57 `virtual void YWidget::setSize (int newWidth, int newHeight)` [pure virtual]

Set the new size of the widget.

Layout manager widgets (like [YLayoutBox](#)) call this during geometry management after all widgets are queried about their preferred widths and heights. Depending on layout constraints, widgets might be resized beyond or below their preferred size.

The sizes passed here are not meant to affect any future [preferredWidth\(\)](#) or [preferredHeight\(\)](#) calls; they are just the outcome of all kinds of compromises (too little screen space or too much) for the current geometry management calculation.

Derived classes are required to implement this function.

Implemented in [YButtonBox](#), [YAlignment](#), [YLayoutBox](#), and [YSingleChildContainerWidget](#).

3.174.3.58 `void YWidget::setStretchable (YUIDimension dim, bool newStretch)`

Set the stretchable state to "newStretch" regardless of any 'hstretch' or 'vstretch' options.

Definition at line 555 of file [YWidget.cc](#).

3.174.3.59 `void YWidget::setWeight (YUIDimension dim, int weight)`

Set a weight in the specified dimension.

Definition at line 579 of file [YWidget.cc](#).

Here is the call graph for this function:



3.174.3.60 `void YWidget::setWidgetRep (void * toolkitWidgetRep)`

Set the pointer to the underlying toolkit's (Qt, ...) widget representing this abstract UI widget.

This pointer might be useful for derived UIs to store a counterpart of the toolkit widget in each [YWidget](#). The abstract UI does not need that, though; this is purely for the convenience of derived UIs. All the abstract UI ever does with that pointer is store it.

Definition at line 488 of file [YWidget.cc](#).

3.174.3.61 `virtual std::string YWidget::shortcutString () const` [inline, virtual]

Get the string of this widget that holds the keyboard shortcut, if any. Most widgets will return `label()`.

Overwrite this for widgets that can have keyboard shortcuts.

Reimplemented in [YSelectionWidget](#), [YInputField](#), [YPushButton](#), [YCheckBox](#), [YLog-View](#), [YIntField](#), [YRadioButton](#), [YMultiLineEdit](#), [YCheckBoxFrame](#), [YDumbTab](#), and [Y-SimpleInputField](#).

Definition at line 533 of file [YWidget.h](#).

3.174.3.62 `virtual void YWidget::startMultipleChanges ()` [inline, virtual]

In some UIs updating the screen content is an expensive operation. Use [startMultipleChanges\(\)](#) to tell the ui that you're going to perform multiple changes to the widget. The UI may delay any screen updates until `doneMultipleChanges()` is called.

Definition at line 613 of file [YWidget.h](#).

3.174.3.63 `bool YWidget::stretchable (YUIDimension dim) const` [virtual]

This is a boolean value that determines whether the widget is resizable beyond its preferred size in the specified dimension. A selection box is stretchable in both dimensions, a push button is not stretchable by default, a frame is stretchable if its contents are stretchable. Most widgets accept a 'hstretch' or 'vstretch' option to become stretchable even when by default they are not.

Reimplemented in [YButtonBox](#), [YAlignment](#), [YDumbTab](#), [YLayoutBox](#), [YSquash](#), and [YSingleChildContainerWidget](#).

Definition at line 567 of file [YWidget.cc](#).

3.174.3.64 `virtual const char* YWidget::userInputProperty ()` [inline, virtual]

The name of the widget property that will return user input, if there is any. Widgets that do have user input (such as [InputField](#), [ComboBox](#), [SelBox](#)) should overwrite this methods. Widgets that are purely passive (such as [Label](#), [RichText](#)) should not.

Reimplemented in [YComboBox](#), [YInputField](#), [YCheckBox](#), [YTable](#), [YIntField](#), [YRadioButton](#), [YPartitionSplitter](#), [YMultiLineEdit](#), [YTree](#), [YSelectionBox](#), [YCheckBoxFrame](#), [YSimpleInputField](#), and [YMultiSelectionBox](#).

Definition at line 549 of file [YWidget.h](#).

3.174.3.65 `int YWidget::weight (YUIDimension dim)` [virtual]

The weight is used in situations where all widgets can get their preferred size and yet space is available. The remaining space will be divided between all stretchable widgets according to their weights. A widget with greater weight will get more space. The default weight for all widgets is 0.

Derived classes can overwrite this function, but they should call this base class function in the new function.

Definition at line 573 of file [YWidget.cc](#).

3.174.3.66 `virtual const char* YWidget::widgetClass () const` [inline, virtual]

Returns a descriptive name of this widget class for logging, debugging etc.

Reimplemented in [YButtonBox](#), [YWizard](#), [YPartitionSplitter](#), [YMultiProgressMeter](#), [YRadioButton](#), [YTable](#), [YGraph](#), [YSelectionBox](#), [YComboBox](#), [YTree](#), [YSlider](#), [YContextMenu](#), [YInputField](#), [YLabel](#), [YMenuButton](#), [YSelectionWidget](#), [YDialog](#), [YSpacing](#), [YIntField](#), [YLogView](#), [YDownloadProgress](#), [YSquash](#), [YAlignment](#), [YCheckBox](#), [YDate-](#)

[Field](#), [YRichText](#), [YTimezoneSelector](#), [YLayoutBox](#), [YTimeField](#), [YDumbTab](#), [YImage](#), [YBarGraph](#), [YPackageSelector](#), [YRadioButtonGroup](#), [YReplacePoint](#), [YBusyIndicator](#), [YCheckBoxFrame](#), [YEmpty](#), [YFrame](#), [YProgressBar](#), [YPushButton](#), [YMultiLineEdit](#), and [YMultiSelectionBox](#).

Definition at line 72 of file [YWidget.h](#).

3.174.3.67 void * YWidget::widgetRep () const

Return a pointer to the underlying toolkit's (Qt, ...) widget representing this abstract UI widget.


Definition at line 481 of file [YWidget.cc](#).

The documentation for this class was generated from the following files:


- [/usr/src/RPM/BUILD/libyui-3.0.10/src/YWidget.h](#)
- [/usr/src/RPM/BUILD/libyui-3.0.10/src/YWidget.cc](#)

3.175 YWidgetEvent Class Reference

Inheritance diagram for YWidgetEvent:



Collaboration diagram for YWidgetEvent:



Public Member Functions

- `YWidgetEvent (YWidget *widget=0, EventReason reason=Activated, EventType eventType=WidgetEvent)`
- `virtual YWidget * widget () const`
- `EventReason reason () const`

Protected Member Functions

- `virtual ~YWidgetEvent ()`

Protected Attributes

- `YWidget * _widget`
- `EventReason _reason`

3.175.1 Detailed Description

Definition at line [165](#) of file [YEvent.h](#).


3.175.2 Constructor & Destructor Documentation

3.175.2.1 YWidgetEvent::YWidgetEvent (YWidget * widget = 0, EventReason reason = Activated, EventType eventType = WidgetEvent)

Constructor.

Definition at line 110 of file [YEvent.cc](#).

Here is the call graph for this function:



3.175.2.2 virtual YWidgetEvent::~~YWidgetEvent () [inline, protected, virtual]

Protected destructor - events can only be deleted via [YDialog::deleteEvent\(\)](#). The associated dialog will take care of this event and delete it when appropriate.

Definition at line 194 of file [YEvent.h](#).

3.175.3 Member Function Documentation

3.175.3.1 EventReason YWidgetEvent::reason () const [inline]

Returns the reason for this event. This very much like an event sub-type.

Definition at line 185 of file [YEvent.h](#).

3.175.3.2 virtual YWidget* YWidgetEvent::widget () const [inline, virtual]

Returns the widget that caused this event. Reimplemented from [YEvent](#).

Reimplemented from [YEvent](#).

Definition at line 180 of file [YEvent.h](#).

The documentation for this class was generated from the following files:

- /usr/src/RPM/BUILD/libyui-3.0.10/src/YEvent.h
- /usr/src/RPM/BUILD/libyui-3.0.10/src/YEvent.cc

3.176 YWidgetFactory Class Reference

```
#include <YWidgetFactory.h>
```

Public Member Functions

- [YDialog](#) * **createMainDialog** (YDialogColorMode colorMode=YDialogNormal-Color)
- [YDialog](#) * **createPopupDialog** (YDialogColorMode colorMode=YDialogNormal-Color)
- virtual [YDialog](#) * **createDialog** (YDialogType dialogType, YDialogColorMode colorMode=YDialogNormalColor)=0
- [YLayoutBox](#) * **createVBox** ([YWidget](#) *parent)
- [YLayoutBox](#) * **createHBox** ([YWidget](#) *parent)
- virtual [YLayoutBox](#) * **createLayoutBox** ([YWidget](#) *parent, YUIDimension dimension)=0
- virtual [YButtonBox](#) * **createButtonBox** ([YWidget](#) *parent)=0
- virtual [YPushButton](#) * **createPushButton** ([YWidget](#) *parent, const std::string &label)=0
- virtual [YLabel](#) * **createLabel** ([YWidget](#) *parent, const std::string &text, bool isHeading=false, bool isOutputField=false)=0
- [YLabel](#) * **createHeading** ([YWidget](#) *parent, const std::string &label)
- virtual [YInputField](#) * **createInputField** ([YWidget](#) *parent, const std::string &label, bool passwordMode=false)=0
- virtual [YCheckBox](#) * **createCheckBox** ([YWidget](#) *parent, const std::string &label, bool isChecked=false)=0
- virtual [YRadioButton](#) * **createRadioButton** ([YWidget](#) *parent, const std::string &label, bool isChecked=false)=0
- virtual [YComboBox](#) * **createComboBox** ([YWidget](#) *parent, const std::string &label, bool editable=false)=0
- virtual [YSelectionBox](#) * **createSelectionBox** ([YWidget](#) *parent, const std::string &label)=0
- virtual [YTree](#) * **createTree** ([YWidget](#) *parent, const std::string &label, bool multi-selection=false, bool recursiveSelection=false)=0
- virtual [YTable](#) * **createTable** ([YWidget](#) *parent, [YTableHeader](#) *header_disown, bool multiSelection=false)=0
- virtual [YProgressBar](#) * **createProgressBar** ([YWidget](#) *parent, const std::string &label, int maxValue=100)=0

- virtual [YRichText](#) * **createRichText** ([YWidget](#) *parent, const std::string &text=std::string(), bool plainTextMode=false)=0
- virtual [YBusyIndicator](#) * **createBusyIndicator** ([YWidget](#) *parent, const std::string &label, int timeout=1000)=0
- [YPushButton](#) * **createIconButton** ([YWidget](#) *parent, const std::string &iconName, const std::string &fallbackTextLabel)
- [YLabel](#) * **createOutputField** ([YWidget](#) *parent, const std::string &label)
- virtual [YIntField](#) * **createIntField** ([YWidget](#) *parent, const std::string &label, int minVal, int maxVal, int initialVal)=0
- [YInputField](#) * **createPasswordField** ([YWidget](#) *parent, const std::string &label)
- virtual [YMenuButton](#) * **createMenuButton** ([YWidget](#) *parent, const std::string &label)=0
- virtual [YMultiLineEdit](#) * **createMultiLineEdit** ([YWidget](#) *parent, const std::string &label)=0
- virtual [YImage](#) * **createImage** ([YWidget](#) *parent, const std::string &imageName, bool animated=false)=0
- virtual [YLogView](#) * **createLogView** ([YWidget](#) *parent, const std::string &label, int visibleLines, int storedLines=0)=0
- virtual [YMultiSelectionBox](#) * **createMultiSelectionBox** ([YWidget](#) *parent, const std::string &label)=0
- virtual [YPackageSelector](#) * **createPackageSelector** ([YWidget](#) *parent, long - ModeFlags=0)=0
- virtual [YWidget](#) * **createPkgSpecial** ([YWidget](#) *parent, const std::string &subwidgetName)=0
- [YSpacing](#) * **createHStretch** ([YWidget](#) *parent)
- [YSpacing](#) * **createVStretch** ([YWidget](#) *parent)
- [YSpacing](#) * **createHSpacing** ([YWidget](#) *parent, YLayoutSize_t size=1.0)
- [YSpacing](#) * **createVSpacing** ([YWidget](#) *parent, YLayoutSize_t size=1.0)
- virtual [YSpacing](#) * **createSpacing** ([YWidget](#) *parent, YUIDimension dim, bool stretchable=false, YLayoutSize_t size=0.0)=0
- virtual [YEmpty](#) * **createEmpty** ([YWidget](#) *parent)=0
- [YAlignment](#) * **createLeft** ([YWidget](#) *parent)
- [YAlignment](#) * **createRight** ([YWidget](#) *parent)
- [YAlignment](#) * **createTop** ([YWidget](#) *parent)
- [YAlignment](#) * **createBottom** ([YWidget](#) *parent)
- [YAlignment](#) * **createHCenter** ([YWidget](#) *parent)
- [YAlignment](#) * **createVCenter** ([YWidget](#) *parent)
- [YAlignment](#) * **createHVCenter** ([YWidget](#) *parent)
- [YAlignment](#) * **createMarginBox** ([YWidget](#) *parent, YLayoutSize_t horMargin, YLayoutSize_t vertMargin)
- [YAlignment](#) * **createMarginBox** ([YWidget](#) *parent, YLayoutSize_t leftMargin, - YLayoutSize_t rightMargin, YLayoutSize_t topMargin, YLayoutSize_t bottomMargin)
- [YAlignment](#) * **createMinWidth** ([YWidget](#) *parent, YLayoutSize_t minWidth)

- [YAlignment](#) * **createMinHeight** ([YWidget](#) *parent, YLayoutSize_t minHeight)
- [YAlignment](#) * **createMinSize** ([YWidget](#) *parent, YLayoutSize_t minWidth, YLayoutSize_t minHeight)
- virtual [YAlignment](#) * **createAlignment** ([YWidget](#) *parent, YAlignmentType horAlignment, YAlignmentType verAlignment)=0
- [YSquash](#) * **createHSquash** ([YWidget](#) *parent)
- [YSquash](#) * **createVSquash** ([YWidget](#) *parent)
- [YSquash](#) * **createHVSquash** ([YWidget](#) *parent)
- virtual [YSquash](#) * **createSquash** ([YWidget](#) *parent, bool horSquash, bool verSquash)=0
- virtual [YFrame](#) * **createFrame** ([YWidget](#) *parent, const std::string &label)=0
- virtual [YCheckBoxFrame](#) * **createCheckBoxFrame** ([YWidget](#) *parent, const std::string &label, bool checked)=0
- virtual [YRadioButtonGroup](#) * **createRadioButtonGroup** ([YWidget](#) *parent)=0
- virtual [YReplacePoint](#) * **createReplacePoint** ([YWidget](#) *parent)=0

Protected Member Functions

- [YWidgetFactory](#) ()
- virtual [~YWidgetFactory](#) ()

Friends

- class **YUI**

3.176.1 Detailed Description

Abstract widget factory for mandatory widgets. Use [YOptionalWidgetFactory](#) for optional ("special") widgets.

Refer to the respective widget's documentation (in the header file) for documentation about the function parameters.

Definition at line 76 of file [YWidgetFactory.h](#).

3.176.2 Constructor & Destructor Documentation

3.176.2.1 [YWidgetFactory::YWidgetFactory](#) () [protected]

Constructor.

Use [YUI::widgetFactory\(\)](#) to get the singleton for this class.

Definition at line 32 of file [YWidgetFactory.cc](#).

3.176.2.2 YWidgetFactory::~YWidgetFactory () [protected, virtual]

Destructor.

Definition at line 37 of file [YWidgetFactory.cc](#).


The documentation for this class was generated from the following files:

- /usr/src/RPM/BUILD/libyui-3.0.10/src/YWidgetFactory.h
- /usr/src/RPM/BUILD/libyui-3.0.10/src/YWidgetFactory.cc

3.177 YWidgetID Class Reference

```
#include <YWidgetID.h>
```

Inheritance diagram for YWidgetID:



Public Member Functions

- virtual [~YWidgetID](#) ()
- virtual bool [isEqual](#) (YWidgetID *otherID) const =0
- virtual std::string [toString](#) () const =0

Protected Member Functions

- [YWidgetID](#) ()

3.177.1 Detailed Description

Abstract base class for widget IDs.

Definition at line 36 of file [YWidgetID.h](#).

3.177.2 Constructor & Destructor Documentation

3.177.2.1 YWidgetID::YWidgetID () [inline, protected]

Constructor. Protected since this is an abstract base class.

Definition at line 42 of file [YWidgetID.h](#).

3.177.2.2 virtual YWidgetID::~YWidgetID () [inline, virtual]

Destructor.

Definition at line 48 of file [YWidgetID.h](#).

3.177.3 Member Function Documentation

3.177.3.1 virtual bool YWidgetID::isEqual (YWidgetID * otherID) const [pure virtual]

Check if this ID is equal to another.

Implemented in [YStringWidgetID](#).

3.177.3.2 virtual std::string YWidgetID::toString () const [pure virtual]

Convert the ID value to string. Used for logging and debugging.


Implemented in [YStringWidgetID](#).

The documentation for this class was generated from the following file:

- [/usr/src/RPM/BUILD/libyui-3.0.10/src/YWidgetID.h](#)

3.178 YWidgetPrivate Struct Reference

Collaboration diagram for YWidgetPrivate:



Public Member Functions

- `YWidgetPrivate` (`YWidgetChildrenManager` *manager, `YWidget` *parent-Widget=0)

Public Attributes

- `YWidgetChildrenManager` * **childrenManager**
- `YWidget` * **parent**
- bool **beingDestroyed**
- bool **enabled**
- bool **notify**
- bool **notifyContextMenu**
- bool **sendKeyEvents**
- bool **autoShortcut**
- void * **toolkitWidgetRep**
- `YWidgetID` * **id**
- `YBothDim< bool >` **stretch**
- `YBothDim< int >` **weight**
- int **functionKey**
- std::string **helpText**

3.178.1 Detailed Description

Definition at line 54 of file `YWidget.cc`.

3.178.2 Constructor & Destructor Documentation

3.178.2.1 `YWidgetPrivate::YWidgetPrivate (YWidgetChildrenManager * manager,
YWidget * parentWidget = 0) [inline]`

Constructor


Definition at line 59 of file [YWidget.cc](#).

The documentation for this struct was generated from the following file:


- `/usr/src/RPM/BUILD/libyui-3.0.10/src/YWidget.cc`

3.179 YWidgetTreeItem Class Reference

Inheritance diagram for YWidgetTreeItem:



Collaboration diagram for YWidgetTreeItem:



Public Member Functions

- **YWidgetTreeItem** ([YWidget](#) *widget, bool [isOpen](#))
- **YWidgetTreeItem** ([YWidgetTreeItem](#) *parent, [YWidget](#) *widget, bool [isOpen](#))
- [YWidget](#) * **widget** () const

Protected Member Functions

- void **setWidgetLabel** ()

3.179.1 Detailed Description

Custom tree item class to map tree items to widgets

Definition at line 59 of file [YDialogSpy.cc](#).


The documentation for this class was generated from the following file:

- [/usr/src/RPM/BUILD/libyui-3.0.10/src/YDialogSpy.cc](#)


3.180 YWizard Class Reference

```
#include <YWizard.h>
```

Inheritance diagram for YWizard:



Collaboration diagram for YWizard:



Public Member Functions


- virtual `~YWizard()`
- virtual const char * `widgetClass()` const
- YWizardMode `wizardMode()` const
- virtual `YPushButton * backButton()` const =0

- virtual [YPushButton](#) * **abortButton** () const =0
- virtual [YPushButton](#) * **nextButton** () const =0
- virtual [YReplacePoint](#) * **contentsReplacePoint** () const =0
- void [protectNextButton](#) (bool protect)
- bool [nextButtonIsProtected](#) () const
- virtual void [setButtonLabel](#) ([YPushButton](#) *button, const std::string &newLabel)
- virtual void [setHelpText](#) (const std::string &helpText)=0
- virtual void [setDialogIcon](#) (const std::string &iconName)=0
- virtual void [setDialogTitle](#) (const std::string &titleText)=0
- virtual void [setDialogHeading](#) (const std::string &headingText)=0
- virtual void [addStep](#) (const std::string &text, const std::string &id)=0
- virtual void [addStepHeading](#) (const std::string &text)=0
- virtual void [deleteSteps](#) ()=0
- virtual void [setCurrentStep](#) (const std::string &id)=0
- virtual void [updateSteps](#) ()=0
- virtual void [addTreeItem](#) (const std::string &parentID, const std::string &text, const std::string &id)=0
- virtual void [selectTreeItem](#) (const std::string &id)=0
- virtual std::string [currentTreeSelection](#) ()=0
- virtual void [deleteTreeItems](#) ()=0
- virtual void [addMenu](#) (const std::string &text, const std::string &id)=0
- virtual void [addSubMenu](#) (const std::string &parentMenuID, const std::string &text, const std::string &id)=0
- virtual void [addMenuEntry](#) (const std::string &parentMenuID, const std::string &text, const std::string &id)=0
- virtual void [addMenuSeparator](#) (const std::string &parentMenuID)=0
- virtual void [deleteMenus](#) ()=0
- virtual void [showReleaseNotesButton](#) (const std::string &label, const std::string &id)=0
- virtual void [hideReleaseNotesButton](#) ()=0
- virtual void [retranslateInternalButtons](#) ()=0
- void [ping](#) ()
- virtual [YPropertyValue](#) [getProperty](#) (const std::string &propertyName)
- virtual const [YPropertySet](#) & [propertySet](#) ()

Protected Member Functions

- [YWizard](#) ([YWidget](#) *parent, const std::string &backButtonLabel, const std::string &abortButtonLabel, const std::string &nextButtonLabel, [YWizardMode](#) [wizard-Mode](#)=[YWizardMode_Standard](#))

Here is the call graph for this function:



3.180.2.2 YWizard::~~YWizard () [virtual]

Destructor.

Definition at line 67 of file [YWizard.cc](#).

3.180.3 Member Function Documentation

3.180.3.1 virtual void YWizard::addMenu (const std::string & *text*, const std::string & *id*) [pure virtual]

Add a menu to the menu bar. If the menu bar is not visible yet, it will be made visible. 'text' is the user-visible text for the menu bar (including keyboard shortcuts marked with '&'), 'id' is the menu ID for later [addMenuEntry\(\)](#) etc. calls.

3.180.3.2 virtual void YWizard::addMenuEntry (const std::string & *parentMenuID*, const std::string & *text*, const std::string & *id*) [pure virtual]

Add a menu entry to the menu with ID 'parentMenuID'. 'id' is what will be returned by `UI::UserInput()` etc. when a user activates this menu entry.

3.180.3.3 virtual void YWizard::addMenuSeparator (const std::string & *parentMenuID*) [pure virtual]

Add a menu separator to a menu.

3.180.3.4 `virtual void YWizard::addStep (const std::string & text, const std::string & id)`
[pure virtual]

Add a step for the steps panel on the side bar. This only adds the step to the internal list of steps. The display is only updated upon calling [updateSteps\(\)](#).

3.180.3.5 `virtual void YWizard::addStepHeading (const std::string & text)` [pure virtual]

Add a step heading for the steps panel on the side bar. This only adds the heading to the internal list of steps. The display is only updated upon calling [updateSteps\(\)](#).

3.180.3.6 `virtual void YWizard::addSubMenu (const std::string & parentMenuID, const std::string & text, const std::string & id)` [pure virtual]

Add a submenu to the menu with ID 'parentMenuID'.

3.180.3.7 `virtual void YWizard::addTreeltem (const std::string & parentID, const std::string & text, const std::string & id)` [pure virtual]

Add a tree item. If "parentID" is an empty string, it will be a root item. 'text' is the text that will be displayed in the tree, 'id' the ID with which this newly created item can be referenced - and that will be returned when the user clicks on a tree item.

3.180.3.8 `virtual YPushButton* YWizard::backButton () const` [pure virtual]

Return the wizard buttons or 0 if there is no such button.

Derived classes are required to implement this.

3.180.3.9 `virtual YReplacePoint* YWizard::contentsReplacePoint () const` [pure virtual]

Return the internal contents ReplacePoint.

Derived classes are required to implement this.

3.180.3.10 `virtual std::string YWizard::currentTreeSelection ()` [pure virtual]

Returns the current tree selection or an empty string if nothing is selected or there is no tree.

3.180.3.11 `virtual void YWizard::deleteMenus ()` [pure virtual]

Delete all menus and hide the menu bar.

3.180.3.12 `virtual void YWizard::deleteSteps ()` [pure virtual]

Delete all steps and step headings from the internal lists. The display is only updated upon calling [updateSteps\(\)](#).

3.180.3.13 `virtual void YWizard::deleteTreeItems ()` [pure virtual]

Delete all tree items.

3.180.3.14 `YPropertyValue YWizard::getProperty (const std::string & propertyName)` [virtual]


Get a property. Reimplemented from [YWidget](#).

This method may throw `YUIPropertyExceptions`.

Reimplemented from [YWidget](#).

Definition at line 131 of file [YWizard.cc](#).

Here is the call graph for this function:



3.180.3.15 `virtual void YWizard::hideReleaseNotesButton ()` [pure virtual]

Hide an existing "Release Notes" button.

3.180.3.16 `bool YWizard::nextButtonIsProtected () const`

Check if the wizard's "Next" button is currently protected against disabling.

Definition at line 80 of file [YWizard.cc](#).

3.180.3.17 `void YWizard::ping ()`

NOP command to check if a [YWizard](#) is running.

Definition at line 106 of file [YWizard.cc](#).

3.180.3.18 `const YPropertySet & YWizard::propertySet () [virtual]`


Return this class's property set. This also initializes the property upon the first call.

Reimplemented from [YWidget](#).

Reimplemented from [YWidget](#).

Definition at line 113 of file [YWizard.cc](#).

Here is the call graph for this function:

**3.180.3.19** `void YWizard::protectNextButton (bool protect)`

Protect the wizard's "Next" button against disabling.

Definition at line 87 of file [YWizard.cc](#).

3.180.3.20 `virtual void YWizard::retranslateInternalButtons () [pure virtual]`

Retranslate internal buttons that are not accessible from the outside:

- [Help]
- [Steps]
- [Tree]

3.180.3.21 `virtual void YWizard::selectTreeltem (const std::string & id)` [pure virtual]

Select the tree item with the specified ID, if such an item exists.


3.180.3.22 `void YWizard::setButtonLabel (YPushButton * button, const std::string & newLabel)` [virtual]

Set the label of one of the wizard buttons ([backButton\(\)](#), [abortButton\(\)](#), [nextButton\(\)](#)) if that button is non-null.

The default implementation simply calls `button->setLabel(newLabel)`.

Definition at line [94](#) of file [YWizard.cc](#).

Here is the call graph for this function:



3.180.3.23 `virtual void YWizard::setCurrentStep (const std::string & id)` [pure virtual]

Set the current step. This also triggers [updateSteps\(\)](#) if necessary.

3.180.3.24 `virtual void YWizard::setDialogHeading (const std::string & headingText)` [pure virtual]

Set the dialog heading.

3.180.3.25 `virtual void YWizard::setDialogIcon (const std::string & iconName)` [pure virtual]

Set the dialog icon. An empty icon name clears the current icon.

3.180.3.26 `virtual void YWizard::setDialogTitle (const std::string & titleText)` [pure virtual]

Set the dialog title shown in the window manager's title bar. An empty string clears the current title.

3.180.3.27 `virtual void YWizard::setHelpText (const std::string & helpText)` [pure virtual]

Set the help text.

Reimplemented from [YWidget](#).

3.180.3.28 `virtual void YWizard::showReleaseNotesButton (const std::string & label,
const std::string & id)` [pure virtual]

Show a "Release Notes" button above the "Help" button in the steps panel with the specified label that will return the specified id to `UI::UserInput()` when clicked.

3.180.3.29 `virtual void YWizard::updateSteps ()` [pure virtual]

Update the steps display: Reflect the internal steps and heading lists in the layout.

3.180.3.30 `virtual const char* YWizard::widgetClass () const` [inline, virtual]

Returns a descriptive name of this widget class for logging, debugging etc.

Reimplemented from [YWidget](#).

Definition at line 117 of file [YWizard.h](#).

3.180.3.31 `YWizardMode YWizard::wizardMode () const`

Return the wizard mode (what kind of wizard this is): `YWizardMode_Standard`, `YWizardMode_Steps`, `YWizardMode_Tree`

Definition at line 74 of file [YWizard.cc](#).

The documentation for this class was generated from the following files:

- /usr/src/RPM/BUILD/libyui-3.0.10/src/YWizard.h
- /usr/src/RPM/BUILD/libyui-3.0.10/src/YWizard.cc

3.181 YWizardPrivate Struct Reference

Public Member Functions

- **YWizardPrivate** (YWizardMode wizardMode)

Public Attributes

- YWizardMode **wizardMode**
- bool **nextButtonsProtected**

3.181.1 Detailed Description

Definition at line 33 of file [YWizard.cc](#).

The documentation for this struct was generated from the following file:

- /usr/src/RPM/BUILD/libyui-3.0.10/src/YWizard.cc